

HAZARD MAPPING OF THE PHILIPPINES USING LIDAR (PHIL-LIDAR I)

LiDAR Surveys and Flood Mapping of Sawaga River



University of the Philippines Training Center
for Applied Geodesy and Photogrammetry
Central Mindanao University



APRIL 2017



© University of the Philippines Diliman and Central Mindanao University 2017

Published by the UP Training Center for Applied Geodesy and Photogrammetry (TCAGP)
College of Engineering
University of the Philippines – Diliman
Quezon City
1101 PHILIPPINES

This research project is supported by the Department of Science and Technology (DOST) as part of its Grants-in-Aid Program and is to be cited as:

E.C. Paringit, and G.R. Puno, (Eds.). (2017), LiDAR Surveys and Flood Mapping of Sawaga River. Quezon City: University of the Philippines Training Center for Applied Geodesy and Photogrammetry — 275pp

The text of this information may be copied and distributed for research and educational purposes with proper acknowledgement. While every care is taken to ensure the accuracy of this publication, the UP TCAGP disclaims all responsibility and all liability (including without limitation, liability in negligence) and costs which might incur as a result of the materials in this publication being inaccurate or incomplete in any way and for any reason.

For questions/queries regarding this report, contact:

Dr. George R. Puno

Project Leader, PHIL-LIDAR 1 Program
Central Mindanao University
Maramag, Bukidnon 8714
E-mail: geopuno@yahoo.com

Enrico C. Paringit, Dr. Eng.

Program Leader, PHIL-LiDAR 1 Program
University of the Philippines Diliman
Quezon City, Philippines 1101
E-mail: ecparingit@up.edu.ph

National Library of the Philippines
ISBN: 978-621-430-018-1

TABLE OF CONTENTS

TABLE OF CONTENTS	ii
LIST OF TABLES	iv
LIST OF FIGURES	vi
LIST OF ACRONYMS AND ABBREVIATIONS	ix
CHAPTER 1: OVERVIEW OF THE PROGRAM AND SAWAGA RIVER	1
1.1 Background of the Phil-LIDAR 1 Program	1
1.2 Overview of the Sawaga River Basin.....	2
CHAPTER 2: LIDAR DATA ACQUISITION OF THE SAWAGA FLOODPLAIN	4
2.1 Flight Plans.....	4
2.2 Ground Base Stations.....	6
2.3 Flight Missions	15
2.4 Survey Coverage	17
CHAPTER 3: LIDAR DATA PROCESSING FOR SAWAGA FLOODPLAIN	19
3.1 LiDAR Data Processing for Sawaga Floodplain	19
3.1.1 Overview of the LiDAR Data Pre-Processing	19
3.2 Transmittal of Acquired LiDAR Data	21
3.3 Trajectory Computation	22
3.4 LiDAR Point Cloud Computation	25
3.5 LiDAR Data Quality Checking	26
3.6 LiDAR Point Cloud Classification and Rasterization.....	32
3.7 LiDAR Image Processing and Orthophotograph Rectification.....	34
3.8 DEM Editing and Hydro-Correction.....	35
3.9 Mosaicking of Blocks.....	37
3.10 Calibration and Validation of Mosaicked LiDAR DEM	39
3.11 Integration of Bathymetric Data into the LiDAR Digital Terrain Model	43
3.12 Feature Extraction.....	44
3.12.1 Quality Checking of Digitized Features’ Boundary	44
3.12.2 Height Extraction.....	44
3.12.3 Feature Attribution.....	44
3.12.4 Final Quality Checking of Extracted Features.....	46
CHAPTER 4: LIDAR VALIDATION SURVEY AND MEASUREMENTS OF THE SAWAGA RIVER BASIN	47
4.1 Summary of Activities	47
4.2 Control Survey	48
4.3 Baseline Processing.....	52
4.4 Network Adjustment	53
4.5 Cross-section and Bridge As-Built survey and Water Level Marking.....	55
4.6 Validation Points Acquisition Survey.....	60
4.7 River Bathymetric Survey.....	62
CHAPTER 5: FLOOD MODELING AND MAPPING	67
5.1 Data Used for Hydrologic Modeling.....	67
5.1.1 Hydrometry and Rating Curves	67
5.1.2 Precipitation	67
5.1.3 Rating Curves and River Outflow.....	69
5.2 RIDF Station	71
5.3 HMS Model	73
5.4 Cross-section Data	77
5.5 Flo 2D Model	78
5.6 Results of HMS Calibration	79
5.7 Calculated outflow hydrographs and discharge values for different rainfall return periods.....	81
5.7.1 Hydrograph using the Rainfall Runoff Model	81
5.8 River Analysis (RAS) Model Simulation	82
5.9 Flow Depth and Flood Hazard.....	83
5.10 Inventory of Areas Exposed to Flooding	90
5.11 Flood Validation	114

REFERENCES	116
ANNEX	117
ANNEX 1. Technical Specifications of the LIDAR Sensors used in the Sawaga Floodplain Survey...	117
ANNEX 2. NAMRIA Certification of Reference Points Used in the LIDAR Survey	118
ANNEX 3. The LIDAR Survey Team Composition	125
ANNEX 4. Data Transfer Sheet for Sawaga Floodplain	126
ANNEX 5. Flight logs for the flight missions	133
ANNEX 6. Flight Status Reports.....	151
ANNEX 7. Mission Summary Reports.....	171
ANNEX 8. Sawaga Model Basin Parameters	256
ANNEX 9. Sawaga Model Reach Parameters.....	258
ANNEX 10. Sawaga Field Validation Points	259
ANNEX 11. Educational Institutions Affected by flooding in Sawaga Flood Plain	269
ANNEX 12. Health Institutions affected by flooding in Sawaga Flood Plain.....	273

LIST OF TABLES

Table 1. Flight planning parameters for Pegasus LiDAR system.	4
Table 2. Details of the recovered NAMRIA horizontal control point MSE-19 used as base station for the LiDAR acquisition.....	7
Table 3. Details of the recovered NAMRIA horizontal control point MSE-20 used as base station for the LiDAR acquisition.....	8
Table 4. Details of the recovered NAMRIA horizontal control point MSE-3241 used as base station for the LiDAR acquisition.....	9
Table 5. Details of the recovered NAMRIA horizontal control point MSE-3340 used as base station for the LiDAR acquisition.	10
Table 6. Details of the recovered NAMRIA horizontal control point BKN-475 used as base station for the LiDAR acquisition.....	11
Table 7. Details of the recovered NAMRIA horizontal control point BKN-478 used as base station for the LiDAR acquisition.....	12
Table 8. Details of the recovered NAMRIA benchmark BK-56 used as base station for the LiDAR acquisition with processed coordinates.	13
Table 9. Ground control points used during LiDAR data acquisition.	14
Table 10. Flight missions under DREAM program which covers part of Sawaga river basin.	15
Table 11. Flight missions for LiDAR data acquisition in Sawaga floodplain	15
Table 12. Actual parameters used during LiDAR data acquisition.	16
Table 13. List of municipalities and cities surveyed during Sawaga floodplain LiDAR survey.....	17
Table 14. Self-Calibration Results values for Sawaga flights.....	25
Table 15. List of LiDAR blocks for Sawaga floodplain.	27
Table 16. Sawaga classification results in TerraScan.	32
Table 17. LiDAR blocks with its corresponding area.	35
Table 18. Shift Values of each LiDAR Block of Sawaga floodplain.....	37
Table 19. Calibration Statistical Measures.....	41
Table 20. Validation Statistical Measures.	42
Table 21. Quality Checking Ratings for Sawaga Building Features.	44
Table 22. Building Features Extracted for Sawaga Floodplain.....	45
Table 23. Total Length of Extracted Roads for Sawaga Floodplain.....	45
Table 24. Number of Extracted Water Bodies for Sawaga Floodplain.....	45
Table 25. List of reference and control points used during the survey in Sawaga River (Source: NAMRIA, UP-TCAGP)	48
Table 26. Baseline Processing Report for Sawaga River Static Survey.....	52
Table 27. Control Point Constraints	53
Table 28. Adjusted Grid Coordinates.....	53
Table 29. Adjusted Geodetic Coordinates	54
Table 30. Reference and control points used and its location (Source: NAMRIA, UP-TCAGP)	54
Table 31. RIDF values for Malaybalay Rain Gauge computed by PAGASA	71
Table 32. Range of calibrated values for the Sawaga River Basin.....	79
Table 33. Summary the Efficiency Test of the Sawaga HMS Model.....	80
Table 34. Peak values of the Sawaga HEC-HMS Model outflow using the Malaybalay RIDF 24-hour values.....	81
Table 35. Municipalities affected in Manupali-Sawaga-Upper Pulangi floodplain	83
Table 36. Affected Areas in Lantapan, Bukidnon during 5-Year Rainfall Return Period.....	90
Table 37. Affected Areas in Lantapan, Bukidnon during 5-Year Rainfall Return Period	91
Table 38. Affected Areas in Malaybalay City, Bukidnon during 5-Year Rainfall Return Period	92
Table 39. Affected Areas in Malaybalay City, Bukidnon during 5-Year Rainfall Return Period	93
Table 40. Affected Areas in Maramag, Bukidnon during 5-Year Rainfall Return Period	94
Table 41. Affected Areas in Quezon, Bukidnon during 5-Year Rainfall Return Period	95
Table 42. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period	96
Table 43. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period	97
Table 44. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period	98

Table 45. Affected Areas in Lantapan, Bukidnon during 25-Year Rainfall Return Period.....	99
Table 46. Affected Areas in Malaybalay City, Bukidnon during 25-Year Rainfall Return Period	100
Table 47. Affected Areas in Maramag, Bukidnon during 25-Year Rainfall Return Period	101
Table 48. Affected Areas in Quezon, Bukidnon during 25-Year Rainfall Return Period	102
Table 49. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period	103
Table 50. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period	104
Table 51. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period	105
Table 52. Affected Areas in Lantapan, Bukidnon during 100-Year Rainfall Return Period.....	106
Table 53. Affected Areas in Malaybalay City, Bukidnon during 100-Year Rainfall Return Period	107
Table 54. Affected Areas in Maramag, Bukidnon during 100-Year Rainfall Return Period	108
Table 55. Affected Areas in Quezon, Bukidnon during 100-Year Rainfall Return Period	109
Table 56. Affected Areas in Valencia City, Bukidnon during 100-Year Rainfall Return Period	110
Table 57. Affected Areas in Valencia City, Bukidnon during 100-Year Rainfall Return Period	111
Table 58. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period	112
Table 59. Areas covered by each warning level with respect to the rainfall scenarios.....	113
Table 60. Actual flood vs simulated flood depth at different levels in the Manupali-Sawaga-Upper Pulangi River Basin.	115
Table 61. The summary of the Accuracy Assessment in the Manupali-Sawaga-Upper Pulangi River Basin Survey	115

LIST OF FIGURES

Figure 1. Map of the Sawaga River Basin in brown	2
Figure 2. Flight plans and base stations for Sawaga floodplain survey.....	5
Figure 3. GPS set-up over MSE-19 at the center island located at the road intersections going to Cagayan de Oro, Butuan City and Iligan City (a) and NAMRIA reference point MSE-19 (b) as recovered by the field team.	7
Figure 4. GPS set-up over MSE-20 in front of Cagayan de Oro Gardens Memorial Park, located at Barangay Lumbia, Cagayan de Oro City (a) and NAMRIA reference point MSE-20 (b) as recovered by the field team.	8
Figure 5. GPS set-up over MSE-3241 on a center island near a gasoline station beside SM Cagayan de Oro (a) and NAMRIA reference point MSE-3241 (b) as recovered by the field team.....	9
Figure 6. GPS set-up over MSE-3340 inside Agusan Barangay Plaza (a) and NAMRIA reference point MSE-3340 (b) as recovered by the field team.	10
Figure 7. GPS set-up over NAMRIA reference point BKN-475 inside Agusan Barangay Plaza	11
Figure 8. GPS set-up over BKN-478 beside the basketball court of Purok 6, Brgy. Sinayawan, Valencia City (a) and NAMRIA reference point BKN-475 (b) as recovered by the field team.	12
Figure 9. GPS set-up over NAMRIA benchmark BK-56 inside Agusan Barangay Plaza.....	13
Figure 10. Actual LiDAR survey coverage for Sawaga floodplain.	18
Figure 11. Schematic Diagram for Data Pre-Processing Component.....	20
Figure 12. Smoothed Performance Metric Parameters of Sawaga Flight 1693P.	22
Figure 13. Solution Status Parameters of Sawaga Flight 1693P.	23
Figure 14. The best estimated trajectory of the LiDAR missions conducted over the Sawaga floodplain.	24
Figure 15. Boundary of the processed LiDAR data over Sawaga Floodplain	26
Figure 16. Image of data overlap for Sawaga floodplain.	28
Figure 17. Density map of merged LiDAR data for Sawaga floodplain.	29
Figure 18. Elevation difference map between flight lines for Sawaga floodplain.....	30
Figure 19. Quality checking for a Sawaga flight 1693P using the Profile Tool of QT Modeler.	31
Figure 20. Tiles for Sawaga floodplain (a) and classification results (b) in TerraScan.	32
Figure 21. Point cloud before (a) and after (b) classification.....	33
Figure 22. The production of the last return DSM (a) and DTM (b), first return DSM (c) and secondary DTM (d) in some portion of Sawaga floodplain.....	33
Figure 23. Available orthophotographs near Sawaga floodplain.....	34
Figure 24. Sample orthophotograph tiles near Sawaga floodplain.	34
Figure 25. Portions in the DTM of Sawaga floodplain – Portions in the DTM of Sawaga floodplain – a bridge, abrupt elevation change along the tributaries and building footprint before (a), (c), (e) and after manual editing (b), (d), (f).....	36
Figure 26. Map of Processed LiDAR Data for Sawaga Flood Plain.	38
Figure 27. Map of Sawaga Flood Plain with validation survey points in green.....	40
Figure 28. Correlation plot between calibration survey points and LiDAR data.....	41
Figure 29. Correlation plot between validation survey points and LiDAR data.	42
Figure 30. Map of Sawaga Flood Plain with bathymetric survey points shown in blue.....	43
Figure 31. Blocks (in blue) of the Sawaga building features that were subjected to QC.....	44
Figure 32. Extracted features for Sawaga floodplain.....	46
Figure 33. Extent of the bathymetric survey (blue line) in Sawaga River and the LiDAR data validation survey (red)	47
Figure 34. Sawaga River Basin Control Survey Extent	49
Figure 35. GNSS receiver set up, Trimble® SPS 882, at BK--56, located at the west post of the welcome arc of Malaybalay City in Brgy. Sumpong, Bukidnon.....	50
Figure 36. GNSS receiver setup, BKN-475, located within the DPWH Compound in Brgy. Aglayan, Valencia City, Bukidnon.	50
Figure 37. GNSS receiver set up, Trimble® SPS 882, at UP_MAN -2, located near the approach of Manupali Bridge in Brgy. Bangcud, Malaybalay City, Province of Bukidnon.....	51
Figure 38. GNSS receiver serup, UP_LUM-2, located near the Pulangui Diversion Dam in Brgy. Lumbayao, Valencia City, Province of Bukidnon.	51

Figure 39. Sawaga Bridge facing upstream.....	55
Figure 40. As-built survey of Sawaga Bridge.....	55
Figure 41. Sawaga Bridge Location Map.....	56
Figure 42. Sawaga Bridge Cross-section Diagram.....	57
Figure 43. Sawaga Bridge Data Sheet.....	58
Figure 44. Sawaga Bridge facing upstream.....	59
Figure 45. Validation points acquisition survey set-up for Sawaga River.....	60
Figure 46. Validation points acquisition covering the Sawaga River Basin Area.....	61
Figure 47. Manual Bathymetric survey of ABSD at Sawaga River using Nikon® Total Station.....	62
Figure 48. Gathering of random bathymetric points along Sawaga River.....	63
Figure 49. Manual Bathymetric survey of ABSD at Sawaga River using Nikon® Total Station.....	64
Figure 50. Quality checking points gathered along Sawaga River by DVBC.....	65
Figure 51. Sawaga Riverbed Profile.....	66
Figure 52. The location map of Sawaga HEC-HMS model used for calibration.....	68
Figure 53. The cross-section plot of the Sawaga Bridge.....	69
Figure 54. Rainfall and outflow data used for modeling.....	69
Figure 55. HQ Curve of HEC-HMS model.....	70
Figure 56. Location of Malaybalay RIDF Station relative to Sawaga River Basin.....	71
Figure 57. Synthetic storm generated for a 24-hr period rainfall for various return periods.....	72
Figure 58. The soil map of the Sawaga River Basin.....	73
Figure 59. The land cover map of the Sawaga River Basin (Source: NAMRIA).....	74
Figure 60. Slope Map of Sawaga River Basin.....	75
Figure 61. Stream delineation map of Sawaga river basin.....	75
Figure 62. HEC-HMS generated Sawaga River Basin Model.....	76
Figure 63. Sawaga River Cross-section generated using HEC GeoRAS tool.....	77
Figure 64. Screenshot of subcatchment with the computational area to be modeled in FLO-2D GDS Pro78	
Figure 65. Outflow Hydrograph of Sawaga produced by the HEC-HMS model compared with observed outflow.....	79
Figure 66. Outflow hydrograph at Sawaga Station generated using Malaybalay RIDF simulated in HEC- HMS.....	81
Figure 67. Sample output of Sawaga RAS Model.....	82
Figure 68. 100-year Flood Hazard Map for Manupali-Sawaga-Upper Pulangi Floodplain.....	84
Figure 69. 100-year Flood Depth Map for Manupali-Sawaga-Upper Pulangi Floodplain.....	85
Figure 70. 25-year Flood Hazard Map for Manupali-Sawaga-Upper Pulangi Floodplain.....	86
Figure 71. 25-year Flood Depth Map for Manupali-Sawaga-Upper Pulangi Floodplain.....	87
Figure 72. 5-year Flood Hazard Map for Manupali-Sawaga-Upper Pulangi Floodplain.....	88
Figure 73. 5-year Flood Depth Map for Manupali-Sawaga-Upper Pulangi Floodplain.....	89
Figure 74. Affected Areas in Lantapan, Bukidnon during 5-Year Rainfall Return Period.....	90
Figure 75. Affected Areas in Malaybalay City, Bukidnon during 5-Year Rainfall Return Period.....	91
Figure 76. Affected Areas in Malaybalay City, Bukidnon during 5-Year Rainfall Return Period.....	92
Figure 77. Affected Areas in Malaybalay City, Bukidnon during 5-Year Rainfall Return Period.....	93
Figure 78. Affected Areas in Lantapan, Bukidnon during 5-Year Rainfall Return Period.....	94
Figure 79. Affected Areas in Quezon, Bukidnon during 5-Year Rainfall Return Period.....	95
Figure 80. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period.....	96
Figure 81. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period.....	97
Figure 82. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period.....	98
Figure 83. Affected Areas in Lantapan, Bukidnon during 25-Year Rainfall Return Period.....	99
Figure 84. Affected Areas in Malaybalay City, Bukidnon during 25-Year Rainfall Return Period.....	100
Figure 85. Affected Areas in Lantapan, Bukidnon during 25-Year Rainfall Return Period.....	101
Figure 86. Affected Areas in Quezon, Bukidnon during 25-Year Rainfall Return Period.....	102
Figure 87. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period.....	103
Figure 88. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period.....	104
Figure 89. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period.....	105

Figure 90. Affected Areas in Lantapan, Bukidnon during 100-Year Rainfall Return Period.....	106
Figure 91. Affected Areas in Lantapan, Bukidnon during 25-Year Rainfall Return Period.....	107
Figure 92. Affected Areas in Maramag, Bukidnon during 100-Year Rainfall Return Period	108
Figure 93. Affected Areas in Quezon, Bukidnon during 100-Year Rainfall Return Period	109
Figure 94. Affected Areas in Valencia City, Bukidnon during 100-Year Rainfall Return Period	110
Figure 95. Affected Areas in Valencia City, Bukidnon during 100-Year Rainfall Return Period	111
Figure 96. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period	112
Figure 97. The Validation Points for a 5-year Flood Depth Map of the Manupali-Sawaga-Upper Pulangi Floodplain	114
Figure 98. Flood map depth vs actual flood depth.....	115

LIST OF ACRONYMS AND ABBREVIATIONS

AAC	Asian Aerospace Corporation	IMU	Inertial Measurement Unit
Ab	abutment	kts	knots
ALTM	Airborne LiDAR Terrain Mapper	LAS	LiDAR Data Exchange File format
ARG	automatic rain gauge	LC	Low Chord
ATQ	Antique	LGU	local government unit
AWLS	Automated Water Level Sensor	LiDAR	Light Detection and Ranging
BA	Bridge Approach	LMS	LiDAR Mapping Suite
BM	benchmark	m AGL	meters Above Ground Level
CAD	Computer-Aided Design	MMS	Mobile Mapping Suite
CMU	Central Mindanao University	MSL	mean sea level
CN	Curve Number	NAMRIA	National Mapping and Resource Information Authority
CSRS	Chief Science Research Specialist	NSTC	Northern Subtropical Convergence
DAC	Data Acquisition Component	PAF	Philippine Air Force
DEM	Digital Elevation Model	PAGASA	Philippine Atmospheric Geophysical and Astronomical Services Administration
DENR	Department of Environment and Natural Resources	PDOP	Positional Dilution of Precision
DOST	Department of Science and Technology	PPK	Post-Processed Kinematic [technique]
DPPC	Data Pre-Processing Component	PRF	Pulse Repetition Frequency
DREAM	Disaster Risk and Exposure Assessment for Mitigation [Program]	PTM	Philippine Transverse Mercator
DRRM	Disaster Risk Reduction and Management	QC	Quality Check
DSM	Digital Surface Model	QT	Quick Terrain [Modeler]
DTM	Digital Terrain Model	RA	Research Associate
DVBC	Data Validation and Bathymetry Component	RIDF	Rainfall-Intensity-Duration-Frequency
FMC	Flood Modeling Component	RMSE	Root Mean Square Error
FOV	Field of View	SAR	Synthetic Aperture Radar
GiA	Grants-in-Aid	SCS	Soil Conservation Service
GCP	Ground Control Point	SRTM	Shuttle Radar Topography Mission
GNSS	Global Navigation Satellite System	SRS	Science Research Specialist
GPS	Global Positioning System	SSG	Special Service Group
HEC-HMS	Hydrologic Engineering Center - Hydrologic Modeling System	TBC	Thermal Barrier Coatings
HEC-RAS	Hydrologic Engineering Center - River Analysis System	UP-TCAGP	University of the Philippines – Training Center for Applied Geodesy and Photogrammetry
HC	High Chord	UTM	Universal Transverse Mercator
IDW	Inverse Distance Weighted [interpolation method]	WGS	World Geodetic System
		ADZU	Ateneo de Zamboanga University

CHAPTER 1: OVERVIEW OF THE PROGRAM AND SAWAGA RIVER

Enrico C. Paringit, Dr. Eng., and Dr. George R. Puno

1.1 Background of the Phil-LIDAR 1 Program

The University of the Philippines Training Center for Applied Geodesy and Photogrammetry (UP-TCAGP) launched a research program entitled “Nationwide Hazard Mapping using LiDAR” or Phil-LiDAR 1, supported by the Department of Science and Technology (DOST) Grants-in-Aid (GiA) Program. The program was primarily aimed at acquiring a national elevation and resource dataset at sufficient resolution to produce information necessary to support the different phases of disaster management. Particularly, it targeted to operationalize the development of flood hazard models that would produce updated and detailed flood hazard maps for the major river systems in the country.

Also, the program was aimed at producing an up-to-date and detailed national elevation dataset suitable for 1:5,000 scale mapping, with 50 cm and 20 cm horizontal and vertical accuracies, respectively. These accuracies were achieved through the use of the state-of-the-art Light Detection and Ranging (LiDAR) airborne technology procured by the project through DOST.

The methods applied in this report are thoroughly described in a separate publication entitled “FLOOD MAPPING OF RIVERS IN THE PHILIPPINES USING AIRBORNE LIDAR: METHODS” (Paringit, et. Al. 2017).

The implementing partner university for the Phil-LiDAR 1 Program is the Central Mindanao State University (CMU). CMU is in charge of processing LiDAR data and conducting data validation reconnaissance, cross section, bathymetric survey, validation, river flow measurements, flood height and extent data gathering, flood modeling, and flood map generation for the 13 river basins in the Region. The university is located in Maramag City in the province of Bukidnon.

1.2 Overview of the Sawaga River Basin




Figure 1. Map of the Sawaga River Basin in brown

Sawaga River Basin is situated in the heart of Bukidnon, in Malaybalay City. It lies between the geographical coordinates of $7^{\circ}58'38.93''$ to $8^{\circ}13'50.16''$ north latitudes and $124^{\circ}55'7.81''$ to $125^{\circ}14'26.85''$ east longitudes. The basin has a total area of 42,692 hectares and comprises 40 barangay local government units; one (1) barangay belongs to the municipality of Cabanglasan, three (3) under Lantapan and 36 barangays within Malaybalay City. It traverses the barangays of Nabago, Mailag, and Colonia in the City of Valencia and Sto. Niño, Simaya, Managok and Violeta in the City of Malaybalay, Bukidnon. The DENR River Basin Control Office (RBCO) states that the Sawaga River Basin has a drainage area of 413.451 km² (RBCO, 2015).

The upper watershed is encompassed by Mount Kitanglad Mountain Range, a protected national park and the ancestral domain of the Talaandig Tribe of the province. It harbors natural mossy forest housing endangered Philippine Eagle and other threatened wildlife. The watershed of Sawaga provides the needs of the Talaandig community as well as take part in their cultural identity. The river feeds other ecological and economic services of downstream communities and the industries alike evident on the expanding banana, pineapple, sugarcane and corn agri-industrial plantations. Moreover, extensive irrigated rice fields are evident in the midstream section of Sawaga River.

The economy of the province of Bukidnon largely rests on agriculture particularly farming, fishing, trade, and commerce. The province is a major producer of rice, corn, sugar, coffee and cassava (Province of Bukidnon Brief Information, 2014). On January 19, 2017, the tail-end of a cold front triggered floods in parts of Mindanao, including eight (8) barangays in the City of Valencia in the Province of Bukidnon. (Lagsa, 2017).

Malaybalay City being the province's political and economic center has been experiencing problems of traffic congestion, pollution, waste management and flooding brought along by the rising urbanization. Flooding in particular mostly damaged the agricultural sector. Occurrences of flooding in the recent years were on December 2011 during Typhoon Sendong, December 2012 during Typhoon Pablo, October 2014, and December 2014 during Typhoon Seniang.

Its main stem, Sawaga River, partner HEI, Central Mindanao University. According to the 2015 national census of PSA, a total of 27,330 persons are residing in the barangays in the City of Malaybalay and Valencia which are within the immediate vicinity of the river.

Sawaga River was among is part of the twelve (12) river systems to be assigned to the Central Mindanao University (CMU) for the generation of flood hazard maps using Light Detection and Ranging (LiDAR) technology under the Phil-LiDAR Program. The activity involved flood modeling through the development of Hydrologic Engineering Center's - Hydrologic Model System (HEC-HMS) and River Analysis System (HEC-RAS) models for precipitation-runoff and flood depth simulations, respectively.

The basin model generated using Synthetic Aperture Radar (SAR) 10m Digital Elevation Model (DEM) and digitized river centerline consists of 29 sub basins, 15 reaches, and 13 junctions. The model was calibrated using the actual data during a rainfall event on May 31 to June 1, 2016 and was evaluated using statistical tests. Results revealed a satisfactory model performance fit for simulation use. Hypothetical discharge scenarios were simulated using the calibrated model and Rainfall Intensity Duration Frequency (RIDF) data of Philippines Atmospheric Geophysical and Astronomical Services Administration (PAG-ASA) taken at a 31-year historical data of Malaybalay rain gauge. Subsequent flood movement was simulated using LiDAR Digital Terrain Model (DTM) showing flood extent and depth information. Flood hazard maps generated project the flood scenarios for the 5-, 25-, and 100-year return periods.

CHAPTER 2: LIDAR DATA ACQUISITION OF THE SAWAGA FLOODPLAIN

Engr. Ma. Rosario Concepcion O. Ang, Engr. John Louie D. Fabila, Engr. Sarah Jane D. Samalbuero, Engr. Gladys Mae Apat, Alex John B. Escobido, Engr. Ma. Ailyn L. Olanda, Engr. Ma. Joanne I. Balaga, Jovy Anne S. Narisma, Engr. Wilbert Ian M. San Juan, Esmael L. Guardian

The methods applied in this Chapter were based on the DREAM methods manual (Sarmiento, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

2.1 Flight Plans

Plans were made to acquire LiDAR data within the delineated priority area for Sawaga floodplain in Misamis Oriental. These missions were planned for 12 lines that ran for at most four and a half (4.5) hours including take-off, landing and turning time. The flight planning parameters for the LiDAR system is found in Table 1. Figure 2 shows the flight plan for Sawaga floodplain.

Table 1. Flight planning parameters for Pegasus LiDAR system.

Block Name	Flying Height (m AGL)	Overlap (%)	Field of View (θ)	Pulse Repetition Frequency (PRF) (KHz)	Scan Frequency (Hz)	Average Speed (kts)	Average Turn Time (Minutes)
RX_BLKE	900	30	50	200	30	130	5
BLK 64A	900	30	50	200	30	130	5
BLK 64B	900	30	50	200	30	130	5
BLK 64C	900	30	50	200	30	130	5
BLK 64D	900	30	50	200	30	130	5
BLK 64E	900	30	50	200	30	130	5




Figure 2. Flight plans and base stations for Sawaga floodplain survey

2.2 Ground Base Stations

The project team was able to recover six (6) NAMRIA ground control points: MSE-19, MSE-20, BKN-475 and BKN-478 which are of second (2nd) order accuracy; and MSE-3241, MSE-3340 which are of third (3rd) order accuracy. The team was also able to recover one (1) NAMRIA benchmark: BK-56 which is of first (1st) order vertical accuracy. The benchmark was used as vertical reference point and was also established as ground control point. The certifications for the NAMRIA reference points are found in ANNEX 2. These were used as base stations during flight operations for the entire duration of the survey (May 27 – July 10, 2014 and October 23 – November 14, 2016). Base stations were observed using dual frequency GPS receivers, TRIMBLE SPS 882 and SPS 852. Flight plans and location of base stations used during the aerial LiDAR acquisition in Sawaga floodplain are shown in Figure 2.

Figure 3 to Figure 9 show the recovered NAMRIA reference points within the area. In addition, Table 2 to Table 8 show the details about the following NAMRIA control stations, while Table 9 shows the list of all ground control points occupied during the acquisition together with the corresponding dates of utilization.



Figure 3. GPS set-up over MSE-19 at the center island located at the road intersections going to Cagayan de Oro, Butuan City and Iligan City (a) and NAMRIA reference point MSE-19 (b) as recovered by the field team.

Table 2. Details of the recovered NAMRIA horizontal control point MSE-19 used as base station for the LiDAR acquisition.

Station Name	MSE-19	
Order of Accuracy	2 nd order	
Relative Error (horizontal positioning)	1:50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude Longitude Ellipsoidal Height	8° 30' 19.11464" North 124° 37' 6.46518" East 11.24200 meters
Grid Coordinates, Philippine Transverse Mercator Zone 5 (PTM Zone 5 PRS 92)	Easting Northing	457,992.786 meters 940,451.853 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude Longitude Ellipsoidal Height	8° 30' 15.52234" North 124° 37' 11.86795" East 78.72200 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting Northing	678,151.65 meters 940,474.22 meters




Figure 4. GPS set-up over MSE-20 in front of Cagayan de Oro Gardens Memorial Park, located at Barangay Lumbia, Cagayan de Oro City (a) and NAMRIA reference point MSE-20 (b) as recovered by the field team.

Table 3. Details of the recovered NAMRIA horizontal control point MSE-20 used as base station for the LiDAR acquisition.

Station Name	MSE-20	
Order of Accuracy	2 nd order	
Relative Error (horizontal positioning)	1:50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude Longitude Ellipsoidal Height	8° 25' 34.65372" North 124° 36' 50.02579" East 182.812 meters
Grid Coordinates, Philippine Transverse Mercator Zone 5 (PTM Zone 5 PRS 92)	Easting Northing	457481.339 meters 931713.993 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude Longitude Ellipsoidal Height	8° 25' 31.08192" North 124° 36' 55.43561" East 250.444 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting Northing	677685.12 meters 931773.67 meters



Figure 5. GPS set-up over MSE-3241 on a center island near a gasoline station beside SM Cagayan de Oro (a) and NAMRIA reference point MSE-3241 (b) as recovered by the field team.

Table 4. Details of the recovered NAMRIA horizontal control point MSE-3241 used as base station for the LiDAR acquisition.

Station Name	MSE-3241	
Order of Accuracy	3 rd order	
Relative Error (horizontal positioning)	1:20,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude Longitude Ellipsoidal Height	8° 27' 31.07607" North 124° 37' 23.18891" East 109.46700 meters
Grid Coordinates, Philippine Transverse Mercator Zone 5 (PTM Zone 5 PRS 92)	Easting Northing	458499.251 meters 935289.375 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude Longitude Ellipsoidal Height	8° 27' 27.49608" North 124° 37' 28.59587" East 177.055 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting Northing	678684.71 meters 935314.30 meters




Figure 6. GPS set-up over MSE-3340 inside Agusan Barangay Plaza (a) and NAMRIA reference point MSE-3340 (b) as recovered by the field team.

Table 5. Details of the recovered NAMRIA horizontal control point MSE-3340 used as base station for the LiDAR acquisition.

Station Name	MSE-3340	
Order of Accuracy	3 rd order	
Relative Error (horizontal positioning)	1:20,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude Longitude Ellipsoidal Height	8° 29' 23.43073" North 124° 44' 11.52934" East 5.996 meters
Grid Coordinates, Philippine Transverse Mercator Zone 5 (PTM Zone 5 PRS 92)	Easting Northing	470991.591 meters 983730.493 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude Longitude Ellipsoidal Height	8° 29' 19.85261" North 124° 44' 16.93252" East 73.801 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting Northing	691159.9 meters 938819.85 meters



Figure 7. GPS set-up over NAMRIA reference point BKN-475 inside Agusan Barangay Plaza

Table 6. Details of the recovered NAMRIA horizontal control point BKN-475 used as base station for the LiDAR acquisition.

Station Name	BKN-475	
Order of Accuracy	2 nd order	
Relative Error (horizontal positioning)	1:50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude Longitude Ellipsoidal Height	8° 3' 25.94887" North 125° 7' 58.6868" East 404.314 meters
Grid Coordinates, Philippine Transverse Mercator Zone 5 (PTM Zone 5 PRS 92)	Easting Northing	890880.244 meters 514656.29 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude Longitude Ellipsoidal Height	8° 3' 22.52096" North 125° 8' 4.12506" East 473.98 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting Northing	891179.54 meters 735073.78 meters




Figure 8. GPS set-up over BKN-478 beside the basketball court of Purok 6, Brgy. Sinayawan, Valencia City (a) and NAMRIA reference point BKN-475 (b) as recovered by the field team.

Table 7. Details of the recovered NAMRIA horizontal control point BKN-478 used as base station for the LiDAR acquisition.

Station Name	BKN-478	
Order of Accuracy	2 nd order	
Relative Error (horizontal positioning)	1:50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude Longitude Ellipsoidal Height	7° 52' 39.32095" North 125° 8' 33.26511" East 302.837 meters
Grid Coordinates, Philippine Transverse Mercator Zone 5 (PTM Zone 5 PRS 92)	Easting Northing	871017.702 meters 515721.851 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude Longitude Ellipsoidal Height	7° 52' 35.94157" North 125° 8' 38.71964" East 372.885 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting Northing	871315.75 meters 736235.86 meters




Figure 9. GPS set-up over NAMRIA benchmark BK-56 inside Agusan Barangay Plaza

Table 8. Details of the recovered NAMRIA benchmark BK-56 used as base station for the LiDAR acquisition with processed coordinates.

Station Name	BK-56	
Order of Accuracy	1 st order	
Relative Error (horizontal positioning)	1:50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude Longitude Ellipsoidal Height	8° 9' 56.15912" North 125° 6' 49.1855" East 657.991 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude Longitude Ellipsoidal Height	8° 9' 52.70089" North 125° 8' 4.12506" East 473.98 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N WGS 1984)	Easting Northing	732882.695 meters 903158.564 meters
Elevation (mean sea level)	10.9546 meters	

Table 9. Ground control points used during LiDAR data acquisition.

Date Surveyed	Flight Number	Mission Name	Ground Control Points
May 27,2014	1517P	1RXE147A	MSE-19 & MSE-3241
June 9, 2014	1569P	1BLKRXE160A	MSE-19 & MSE-3241
June 16, 2014	1597P	1BLKRXE167A	MSE-19 & MSE-3241
June 24,2014	1629P	1BLKRXES175A	MSE-20 & MSE-3340
July 10, 2014	1693P	1RXES191A	MSE-20 & MSE-3340
October 23, 2016	23486P	1BKND297A	BKN-478 & BK-56
October 24, 2016	23488P	1BKND298A	BKN-478 & BK-56
October 25, 2016	23492P	1BKND299A	BKN-475 & BK-56
November 6, 2016	23516P	1BKNF311A	BKN-475 & BK-56
November 6, 2016	23518P	1BKNF311B	BKN-475 & BK-56
November 7, 2016	23520P	1BKNF312A	BKN-475 & BK-56
November 8, 2016	23524P	1BKND313A	BKN-475 & BK-56
November 10, 2016	23534P	1BKNG315A	BKN-475 & BK-56
November 11, 2016	23536P	1BKND316A	BKN-475 & BK-56
November 12, 2016	23540P	1BKNE317A	BKN-475 & BK-56
November 13, 2016	23544P	1BKNE318A	BKN-475 & BK-56
November 13, 2016	23546P	1BKNE319A	BKN-475 & BK-56
November 14, 2016	23548P	1BLK64A320A	BKN-475 & BK-56

2.3 Flight Missions

Two (2) missions under DREAM program covered around three hundred fourteen (314) square kilometers (Table 10) within Sawaga river basin. Eighteen (18) missions were conducted to complete the LiDAR data acquisition in Sawaga floodplain, for a total of seventy four hours and seven minutes (74+07) of flying time for RP-C9022. All missions were acquired using the Pegasus LiDAR system. Table 11 shows the total area of actual coverage and the corresponding flying hours per mission, while Table 12 presents the actual parameters used during the LiDAR data acquisition.

Table 10. Flight missions under DREAM program which covers part of Sawaga river basin.

Flight Number	Mission Name	Area Surveyed within the Floodplain (km ²)
388G	2TAGWA224A	158.77
396G	2TAGWD226A	155.32
TOTAL		314.09

Table 11. Flight missions for LiDAR data acquisition in Sawaga floodplain

Date Surveyed	Flight Number	Flight Plan Area (km ²)	Surveyed Area (km ²)	Area Surveyed within the Floodplain (km ²)	Area Surveyed outside the Floodplain (km ²)	No. of Images (Frames)	Flying Hours	
							Hr	Min
May 27, 2014	1517P	522.19	164.99	0	164.99	NA	4	23
June 9, 2014	1569P	340.82	289.86	0	289.86	NA	4	18
June 16, 2014	1597P	522.19	155.21	0	155.21	NA	4	0
June 24, 2014	1629P	182.55	223.66	0	223.66	527	3	47
July 10, 2014	1693P	522.19	196.80	0	196.80	NA	3	11
October 23, 2016	23486P	182.55	86.52	0	86.52	NA	3	41
October 24, 2016	23488P	133.31	155.98	0	155.98	NA	4	29
October 25, 2016	23492P	242.43	207.05	84.49	122.56	NA	4	23
November 6, 2016	23516P	235.81	177.38	96.66	80.72	NA	5	16
November 6, 2016	23518P	235.81	94.78	50.45	44.33	NA	2	29
November 7, 2016	23520P	381.09	252.33	132.96	119.37	NA	4	11
November 8, 2016	23524P	164.60	124.87	101.04	23.83	NA	4	29
November 10, 2016	23534P	145.29	50.15	11.36	38.79	NA	4	05
November 11, 2016	23536P	164.60	105.80	35.01	70.79	NA	4	23
November 12, 2016	23540P	242.43	96.13	20.24	75.89	NA	4	11
November 13, 2016	23544P	242.43	189.41	110.73	78.68	NA	4	11
November 13, 2016	23546P	145.29	136.72	101.20	35.52	NA	4	11
November 14, 2016	23548P	235.81	197.42	99.44	97.98	NA	4	29
TOTAL		4841.39	2905.06	843.58	2061.48	527	74	07

Table 12. Actual parameters used during LiDAR data acquisition.

Flight Number	Flying Height (m AGL)	Overlap (%)	FOV (θ)	PRF (KHz)	Scan Frequency (Hz)	Average Speed (kts)	Average Turn Time (Minutes)
1517P	900	30	50	200	30	130	5
1569P	1000	30	50	200	30	130	5
1597P	800	30	50	200	30	130	5
1629P	1200	30	50	200	30	130	5
1693P	1100	30	50	200	30	130	5
23486P	800	30	50	200	30	130	5
23488P	800	30	50	200	30	130	5
23492P	1000	30	50	200	30	130	5
23516P	1000	30	50	200	30	130	5
23518P	1000	30	50	200	30	130	5
23520P	1200	30	50	200	30	130	5
23524P	1200	30	50	200	30	130	5
23534P	1200	30	50	200	30	130	5
23536P	1200	30	50	200	30	130	5
23540P	1200	30	50	200	30	130	5
23544P	1200	30	50	200	30	130	5
23546P	1200	30	50	200	30	130	5
23548P	1200	30	50	200	30	130	5

2.4 Survey Coverage

Sawaga floodplain is located in the province of Bukidnon with majority of the floodplain situated within the City of Valencia and Malaybalay. Municipality of Manolo Fortich is mostly covered by the survey. The list of municipalities and cities surveyed, with at least one (1) square kilometer coverage, is shown in Table 13. The actual coverage of the LiDAR acquisition for Sawaga floodplain is presented in Figure 10.

Table 13. List of municipalities and cities surveyed during Sawaga floodplain LiDAR survey.

Province	Municipality/City	Area of Municipality/City (km ²)	Total Area Surveyed (km ²)	Percentage of Area Surveyed
Bukidnon	Manolo Fortich	350.15	249.97	71.39%
	Libona	282.23	182.47	64.63%
	Valencia City	726.07	393.05	54.13%
	Sumilao	259.26	119.07	45.935
	Maramag	323.88	91.75	28.32%
	Lantapan	290.82	80.20	27.58%
	Malaybalay City	1,115.98	281.10	25.19%
	Malitbog	359.59	38.81	10.79%
	Quezon	641.25	38.25	5.97%
	Impasug-Ong	854.63	29.11	3.41%
	Baungon	331.88	3.97	1.20%
Misamis Oriental	Villanueva	46.05	32.51	70.60%
	Jasaan	68.33	44.11	64.56%
	Tagoloan	55.72	19.10	34.27%
	Cagayan de Oro City	440.17	147.73	33.56%
	Claveria	768.95	28.33	3.68%
	Balingasag	125.59	1.37	1.09
TOTAL		7,040.55	1,780.9	31.54%




Figure 10. Actual LiDAR survey coverage for Sawaga floodplain.

CHAPTER 3: LIDAR DATA PROCESSING FOR SAWAGA FLOODPLAIN

*Engr. Ma. Rosario Concepcion O. Ang, Engr. John Louie D. Fabila, Engr. Sarah Jane D. Samalbuero,
Engr. Gladys Mae Apat, Alex John B. Escobido, Engr. Ma. Ailyn L. Olanda, Engr. Ma. Joanne I. Balaga,
Jovy Anne S. Narisma, Engr. Wilbert Ian M. San Juan, Esmael L. Guardian*

The methods applied in this Chapter were based on the DREAM methods manual (Ang, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

3.1 LiDAR Data Processing for Sawaga Floodplain

3.1.1 Overview of the LiDAR Data Pre-Processing

The data transmitted by the Data Acquisition Component are checked for completeness based on the list of raw files required to proceed with the pre-processing of the LiDAR data. Upon acceptance of the LiDAR field data, georeferencing of the flight trajectory is done in order to obtain the exact location of the LiDAR sensor when the laser was shot. Point cloud georectification is performed to incorporate correct position and orientation for each point acquired. The georectified LiDAR point clouds are subject for quality checking to ensure that the required accuracies of the program, which are the minimum point density, vertical and horizontal accuracies, are met. The point clouds are then classified into various classes before generating Digital Elevation Models such as Digital Terrain Model and Digital Surface Model.

Using the elevation of points gathered in the field, the LiDAR-derived digital models are calibrated. Portions of the river that are barely penetrated by the LiDAR system are replaced by the actual river geometry measured from the field by the Data Validation and Bathymetry Component. LiDAR acquired temporally are then mosaicked to completely cover the target river systems in the Philippines. Orthorectification of images acquired simultaneously with the LiDAR data is done through the help of the georectified point clouds and the metadata containing the time the image was captured.

These processes are summarized in the flowchart shown in Figure 11.




Figure 11. Schematic Diagram for Data Pre-Processing Component

3.2 Transmittal of Acquired LiDAR Data

Data transfer sheets for all the LiDAR missions for Sawaga floodplain can be found in ANNEX 5. Missions flown during the first survey conducted on August 2013 used the Airborne LiDAR Terrain Mapper (ALTM™ Optech Inc.) Gemini system while missions acquired during the second survey on November 2016 were flown using the Pegasus system over Malaybalay City, Bukidnon. The Data Acquisition Component (DAC) transferred a total of 418.93 Gigabytes of Range data, 4.98 Gigabytes of POS data, 2822.86 Megabytes of GPS base station data, and 79.66 Gigabytes of raw image data to the data server on August 9, 2013 for the first survey and November 15, 2016 for the second survey. The Data Pre-processing Component (DPPC) verified the completeness of the transferred data. The whole dataset for Sawaga was fully transferred on November 24, 2016, as indicated on the Data Transfer Sheets for Sawaga floodplain.

3.3 Trajectory Computation

The *Smoothed Performance Metric* parameters of the computed trajectory for flight 1693P, one of the Sawaga flights, which is the North, East, and Down position RMSE values are shown in Figure 12. The x-axis corresponds to the time of flight, which is measured by the number of seconds from the midnight of the start of the GPS week, which on that week fell on July 10, 2014 00:00AM. The y-axis is the RMSE value for that particular position.




Figure 12. Smoothed Performance Metric Parameters of Sawaga Flight 1693P.

The time of flight was from 352000 seconds to 360500 seconds, which corresponds to morning of July 10, 2014. The initial spike that is seen on the data corresponds to the time that the aircraft was getting into position to start the acquisition, and the POS system starts computing for the position and orientation of the aircraft. Redundant measurements from the POS system quickly minimized the RMSE value of the positions. The periodic increase in RMSE values from an otherwise smoothly curving RMSE values correspond to the turn-around period of the aircraft, when the aircraft makes a turn to start a new flight line. Figure 12 shows that the North position RMSE peaks at 1.80 centimeters, the East position RMSE peaks at 1.50 centimeters, and the Down position RMSE peaks at 2.60 centimeters, which are within the prescribed accuracies described in the methodology.




Figure 13. Solution Status Parameters of Sawaga Flight 1693P.

The *Solution Status* parameters of flight 1693P, one of the Sawaga flights, which are the number of GPS satellites, Positional Dilution of Precision (PDOP), and the GPS processing mode used, are shown in Figure 13. The graphs indicate that the number of satellites during the acquisition did not go down to 6. Majority of the time, the number of satellites tracked was between 7 and 10. The PDOP value also did not go above the value of 3, which indicates optimal GPS geometry. The processing mode stayed at the value of 0 for majority of the survey with some peaks up to 2 attributed to the turns performed by the aircraft. The value of 0 corresponds to a Fixed, Narrow-Lane mode, which is the optimum carrier-cycle integer ambiguity resolution technique available for POSPAC MMS. All of the parameters adhered to the accuracy requirements for optimal trajectory solutions, as indicated in the methodology. The computed best estimated trajectory for all Sawaga flights is shown in Figure 14.




Figure 14. The best estimated trajectory of the LiDAR missions conducted over the Sawaga floodplain

3.4 LiDAR Point Cloud Computation

The produced LAS data contains 274 flight lines, with each flight line containing one channel for flights using Gemini system and two channels for flights using Pegasus system. The summary of the self-calibration results obtained from LiDAR processing in LiDAR Mapping Suite (LMS) software for all flights over Sawaga floodplain are given in Table 14.

Table 14. Self-Calibration Results values for Sawaga flights.

Parameter		Acceptable Value
Boresight Correction stdev	(<0.001degrees)	0.000586
IMU Attitude Correction Roll and Pitch Corrections stdev	(<0.001degrees)	0.000953
GPS Position Z-correction stdev	(<0.01meters)	0.0087

The optimum accuracy values were obtained for all Sawaga flights based on the computed standard deviations of the corrections of the orientation parameters. Standard deviation values for individual blocks are available in the ANNEX 8. Mission Summary Reports.

3.5 LiDAR Data Quality Checking

The boundary of the processed LiDAR data on top of a SAR Elevation Data over Sawaga Floodplain is shown in Figure 15. The map shows gaps in the LiDAR coverage that are attributed to cloud coverage.




Figure 15. Boundary of the processed LiDAR data over Sawaga Floodplain

The total area covered by the Sawaga missions is 2772.84 sq.km that is comprised of nineteen (19) flight acquisitions grouped and merged into nineteen (19) blocks as shown in Table 15.

Table 15. List of LiDAR blocks for Sawaga floodplain.

LiDAR Blocks	Flight Numbers	Area (sq. km)
Tagoloan_Bl396G	396G	142.86
Tagoloan_Bl388G	388G	150.69
NorthernMindanao_RX_BlE_additional	1569P	429.95
	1597P	
	1629P	
	1693P	
NorthernMindanao_RX_BlE	1517P	91.47
NorthernMindanao_RX_BlE_additional2	1569P	226.25
	1597P	
	1629P	
	1693P	
Bukidnon_Bl64A	23492P	227.37
Bukidnon_Bl64A_additional	23534P	21.72
Bukidnon_Bl64A_supplement	23536P	80.87
Bukidnon_Bl64B_supplement2	23540P	263.4
	23544P	
Bukidnon_Bl64B	23516P	244.68
	23518P	
	23520P	
Bukidnon_Bl64B_supplement	23548P	172.64
Bukidnon_Bl64C	23520P	159.70
	23516P	
Bukidnon_Bl64C_additional	23534P	55.92
Bukidnon_Bl64C_supplement	23546P	119.87
Bukidnon_Bl64D	23524P	80.72
Bukidnon_Bl64D_additional	23524P	75.71
Bukidnon_Bl64D_supplement	23536P	23.74
Bukidnon_Bl64E	23488P	156.01
Bukidnon_Bl64E_supplement	23486P	49.27
TOTAL		2,772.84 sq.km

The overlap data for the merged LiDAR blocks, showing the number of channels that pass through a particular location is shown in Figure 16. Since the Gemini system employs one channel, we would expect an average value of 1 (blue) for areas where there is limited overlap, and a value of 2 (yellow) or more (red) for areas with three or more overlapping flight lines. While for the Pegasus system which employs two channels, we would expect an average value of 2 (blue) for areas where there is limited overlap, and a value or 3 (yellow) or more for areas with three or more overlapping flight lines.




Figure 16. Image of data overlap for Sawaga floodplain.

The overlap statistics per block for the Sawaga floodplain can be found in ANNEX 8. One pixel corresponds to 25.0 square meters on the ground. For this area, the minimum and maximum percent overlaps are 27.70% and 72.40% respectively, which passed the 25% requirement.

The density map for the merged LiDAR data, with the red parts showing the portions of the data that satisfy the 2 points per square meter criterion is shown in Figure 17. It was determined that all LiDAR data for Sawaga floodplain satisfy the point density requirement, and the average density for the entire survey area is 4.23 points per square meter.




Figure 17. Density map of merged LiDAR data for Sawaga floodplain.

The elevation difference between overlaps of adjacent flight lines is shown in Figure 18. The default color range is from blue to red, where bright blue areas correspond to portions where elevations of a previous flight line, identified by its acquisition time, are higher by more than 0.20m relative to elevations of its adjacent flight line. Bright red areas indicate portions where elevations of a previous flight line are lower by more than 0.20m relative to elevations of its adjacent flight line. Areas with bright red or bright blue need to be investigated further using Quick Terrain Modeler software.




Figure 18. Elevation difference map between flight lines for Sawaga floodplain.

A screen capture of the processed LAS data from a Sawaga flight 1693P loaded in QT Modeler is shown in Figure 19. The upper left image shows the elevations of the points from two overlapping flight strips traversed by the profile, illustrated by a dashed red line. The x-axis corresponds to the length of the profile. It is evident that there are differences in elevation, but the differences do not exceed the 20-centimeter mark. This profiling was repeated until the quality of the LiDAR data becomes satisfactory. No reprocessing was done for this LiDAR dataset.




Figure 19. Quality checking for a Sawaga flight 1693P using the Profile Tool of QT Modeler.

3.6 LiDAR Point Cloud Classification and Rasterization

Table 16. Sawaga classification results in TerraScan.

Pertinent Class	Total Number of Points
Ground	3,857,468,123
Low Vegetation	2,850,039,233
Medium Vegetation	5,472,064,570
High Vegetation	5,504,381,780
Building	381,576,586

The tile system that TerraScan employed for the LiDAR data and the final classification image for a block in Sawaga floodplain is shown in Figure 20. A total of 3,754 1km by 1km tiles were produced. The number of points classified to the pertinent categories is illustrated in Table 16. The point cloud has a maximum and minimum height of 1,590.61 meters and 65.84 meters respectively.




Figure 20. Tiles for Sawaga floodplain (a) and classification results (b) in TerraScan.

An isometric view of an area before and after running the classification routines is shown in Figure 21. The ground points are in orange, the vegetation is in different shades of green, and the buildings are in cyan. It can be seen that residential structures adjacent or even below canopy are classified correctly, due to the density of the LiDAR data.




Figure 21. Point cloud before (a) and after (b) classification.

The production of last return (V_ASCII) and the secondary (T_ASCII) DTM, first (S_ASCII) and last (D_ASCII) return DSM of the area in top view display are shown in Figure 22. It shows that DTMs are the representation of the bare earth while on the DSMs, all features are present such as buildings and vegetation.




Figure 22. The production of the last return DSM (a) and DTM (b), first return DSM (c) and secondary DTM (d) in some portion of Sawaga floodplain

3.7 LiDAR Image Processing and Orthophotograph Rectification

The 301 km by 1km tiles of the block covering the Sawaga floodplain is shown in Figure 23. After tie point selection to fix photo misalignments, color points were added to smoothen out visual inconsistencies along the seamlines where photos overlap. The block covering the Sawaga floodplain survey attained a total of 240.922 km² in orthophotograph coverage, comprised of 642 images. However, the block does not have a complete set of orthophotographs and no orthophotographs cover the area of the Sawaga floodplain. A zoomed in version of sample orthophotographs named in reference to its tile number is shown in Figure 24.




Figure 23. Available orthophotographs near Sawaga floodplain.



Figure 24. Sample orthophotograph tiles near Sawaga floodplain.

3.8 DEM Editing and Hydro-Correction

Nineteen (19) mission blocks were processed for Sawaga flood plain. These blocks are composed of Bukidnon, Tagoloan and NorthernMindanao missions with a total area of 2,772.84 square kilometers. Table 17 shows the name and corresponding area of each block in square kilometers.

Table 17. LiDAR blocks with its corresponding area.

LiDAR Blocks	Area (sq.km)
Tagoloan_396G	142.86
Tagoloan_388G	150.69
NorthernMindanao_RX_Blke_additional	429.95
NorthernMindanao_RX_Blke	91.47
NorthernMindanao_RX_Blke_additional2	226.25
Bukidnon_Bl64A	227.37
Bukidnon_Bl64A_additional	21.72
Bukidnon_Bl64A_supplement	80.87
Bukidnon_Bl64B_supplement2	263.4
Bukidnon_Bl64B	244.68
Bukidnon_Bl64B_supplement	172.64
Bukidnon_Bl64C	159.70
Bukidnon_Bl64C_additional	55.92
Bukidnon_Bl64C_supplement	119.87
Bukidnon_Bl64D	80.72
Bukidnon_Bl64D_additional	75.71
Bukidnon_Bl64D_supplement	23.74
Bukidnon_Bl64E	156.01
Bukidnon_Bl64E_supplement	49.27
TOTAL	2,772.84 sq.km

Portions of DTM before and after manual editing are shown in Figure 25. The bridge (Figure 25a) and abrupt elevation change through presence of high portions along the tributaries (Figure 25c) is considered to be an impedance to the flow of water along the river and has to be removed (Figure 25b and Figure 25d) in order to hydrologically correct the river. This was done through interpolation process wherein a specific polygon determines the upstream and downstream elevation values to generate an interpolated portion of a river and eventually remove the bridge footprint. Another example in is the interpolation of a building footprint (Figure 25e) which has to be removed in a DTM (Figure 25f).




Figure 25. Portions in the DTM of Sawaga floodplain – Portions in the DTM of Sawaga floodplain – a bridge, abrupt elevation change along the tributaries and building footprint before (a), (c), (e) and after manual editing (b), (d), (f)

3.9 Mosaicking of Blocks

The Bukidnon_Bl64C was used as the reference block for mosaicking of Bukidnon blocks while Northern Mindanao blocks used NorthernMindanao_RX_Bl6E as reference. Table 18 shows the area of each LiDAR blocks and the shift values applied during mosaicking. Shifting values were derived from the height difference of the calibrated block and the overlapping adjacent block.

Mosaicked LiDAR DTM for Sawaga floodplain is shown in Figure 26. It can be seen that the entire Sawaga floodplain is 100% covered by LiDAR data.

Table 18. Shift Values of each LiDAR Block of Sawaga floodplain.

Mission Blocks	Shift Values (meters)		
	x	y	z
Blocks in Bukidnon			
Bukidnon_Bl64A	0.00	0.00	-0.01
Bukidnon_Bl64A-supplement	0.00	0.00	0.03
Bukidnon_Bl64A_additional	0.00	0.00	-0.08
Bukidnon_Bl64B	0.00	0.00	-0.16
Bukidnon_Bl64B_supplement	0.00	0.00	-0.16
Bukidnon_Bl64B_supplement2	0.00	0.00	-0.03
Bukidnon_Bl64C	0.00	0.00	0.00
Bukidnon_Bl64C_supplement	0.00	0.00	0.08
Bukidnon_Bl64C_additional	0.00	0.00	0.17
Bukidnon_Bl64D	0.00	0.00	0.02
Bukidnon_Bl64D_supplement	0.00	0.00	-0.11
Bukidnon_Bl64D_additional	0.00	0.00	-0.04
Blocks in Northern Mindanao			
Bukidnon_Bl64E	0.00	0.00	0.63
Bukidnon_Bl64E_supplement	0.00	0.00	-0.37
NorthernMindanao_RX_Bl6E	0.00	0.00	0.00
NorthernMindanao_RX_Bl6E_additional	0.00	0.00	-0.37
NorthernMindanao_RX_Bl6E_additional2	0.00	0.00	-0.48




Figure 26. Map of Processed LiDAR Data for Sawaga Flood Plain.

3.10 Calibration and Validation of Mosaicked LiDAR DEM

The extent of the validation survey done by the Data Validation and Bathymetry Component (DVBC) in Sawaga to collect points with which the LiDAR dataset is validated is shown in Figure 27. A total of 7,734 survey points were used for calibration and validation of Sawaga LiDAR data. Random selection of 80% of the survey points, resulting to 4,512 points, were used for calibration. A good correlation between the uncalibrated mosaicked LiDAR elevation values and the ground survey elevation values is shown in Figure 28. Statistical values were computed from extracted LiDAR values using the selected points to assess the quality of data and obtain the value for vertical adjustment. The computed height difference between the LiDAR DTM and calibration elevation values is 0.38 meters with a standard deviation of 0.08 meters. Calibration of Sawaga LiDAR data was done by subtracting the height difference value, 0.38 meters, to Sawaga mosaicked LiDAR data. Table 19 shows the statistical values of the compared elevation values between LiDAR data and calibration data.




Figure 27. Map of Sawaga Flood Plain with validation survey points in green.




Figure 28. Correlation plot between calibration survey points and LiDAR data.

Table 19. Calibration Statistical Measures.

Calibration Statistical Measures	Value (meters)
Height Difference	0.38
Standard Deviation	0.08
Average	-0.38
Minimum	-0.64
Maximum	0.56

The remaining 20% of the total survey points, resulting to 825 points, were used for the validation of calibrated Sawaga DTM. A good correlation between the calibrated mosaicked LiDAR elevation values and the ground survey elevation, which reflects the quality of the LiDAR DTM is shown in Figure 29. The computed RMSE between the calibrated LiDAR DTM and validation elevation values is 0.19 meters with a standard deviation of 0.19 meters, as shown in Table 20.




Figure 29. Correlation plot between validation survey points and LiDAR data.

Table 20. Validation Statistical Measures.

Validation Statistical Measures	Value (meters)
RMSE	0.19
Standard Deviation	0.19
Average	0.00
Minimum	-0.38
Maximum	0.40

3.11 Integration of Bathymetric Data into the LiDAR Digital Terrain Model

For bathy integration, cross section data were available for Sawaga with 2,034 bathymetric survey points. The resulting raster surface produced was done by Inverse Distance Weighted (IDW) interpolation method. After burning the bathymetric data to the calibrated DTM, assessment of the interpolated surface is represented by the computed RMSE value of 0.31 meters. The extent of the bathymetric survey done by the Data Validation and Bathymetry Component (DVBC) in Sawaga integrated with the processed LiDAR DEM is shown in Figure 30.




Figure 30. Map of Sawaga Flood Plain with bathymetric survey points shown in blue.

3.12 Feature Extraction

The features salient in flood hazard exposure analysis include buildings, road networks, bridges and water bodies within the floodplain area with 200 m buffer zone. Mosaicked LiDAR DEM with 1 m resolution was used to delineate footprints of building features, which consist of residential buildings, government offices, medical facilities, religious institutions, and commercial establishments, among others. Road networks comprise of main thoroughfares such as highways and municipal and barangay roads essential for routing of disaster response efforts. These features are represented by a network of road centerlines.

3.12.1 Quality Checking of Digitized Features’ Boundary

Sawaga floodplain, including its 200 m buffer, has a total area of 438.79 sq km. For this area, a total of 14.00 sq km, corresponding to a total of 3372 building features, are considered for QC. Figure 31 shows the QC blocks for Sawaga floodplain.




Figure 31. Blocks (in blue) of the Sawaga building features that were subjected to QC

Quality checking of Sawaga building features resulted in the ratings shown in Table 21.

Table 21. Quality Checking Ratings for Sawaga Building Features.

FLOODPLAIN	COMPLETENESS	CORRECTNESS	QUALITY	REMARKS
Sawaga	99.47	99.76	89.09	PASSED

3.12.2 Height Extraction

Height extraction was done for 14,606 building features in Sawaga floodplain. Of these building features, 150 were filtered out after height extraction, resulting to 14,456 buildings with height attributes. The lowest building height is at 2.00 m, while the highest building is at 7.16 m.

3.12.3 Feature Attribution

Field data collection for the attribution process was done through Geotagging (point to a specific feature and shoot method) using a handheld GPS with a built-in camera. The x,y,z and the viewing direction of the GPS in 0-359 degrees during the photo capture were the essential information in the process. Using Arcmap’s tool “Geotagged Photos to Points”, the symbology of the imported point shapefile was set as

“Airfield” and the viewing angle was set as “Direction”. The “Path” is automatically created in the points’ attribute table wherein the photo’s directory is linked every after the “Identify” button is clicked to a specific point.

Table 22 summarizes the number of building features per type. On the other hand, Table 23 shows the total length of each road type, while Table 24 shows the number of water features extracted per type.

Table 22. Building Features Extracted for Sawaga Floodplain.

Facility Type	No. of Features
Residential	13, 577
School	213
Market	30
Agricultural/Agro-Industrial Facilities	2
Medical Institutions	17
Barangay Hall	9
Military Institution	0
Sports Center/Gymnasium/Covered Court	11
Telecommunication Facilities	1
Transport Terminal	0
Warehouse	112
Power Plant/Substation	0
NGO/CSO Offices	3
Police Station	0
Water Supply/Sewerage	0
Religious Institutions	66
Bank	1
Factory	0
Gas Station	13
Fire Station	1
Other Government Offices	78
Other Commercial Establishments	321
City Hall	1
Total	14,456

Table 23. Total Length of Extracted Roads for Sawaga Floodplain.

Floodplain	Road Network Length (km)					Total
	Barangay Road	City/Municipal Road	Provincial Road	National Road	Others	
Sawaga	254.00		0	19.39	0	273.39

Table 24. Number of Extracted Water Bodies for Sawaga Floodplain.

Floodplain	Water Body Type					Total
	Rivers/Streams	Lakes/Ponds	Sea	Dam	Fish Pen	
Sawaga	4	0	0	0	0	4

A total of 12 bridges and culverts over small channels that are part of the river network were also extracted for the floodplain.

3.12.4 Final Quality Checking of Extracted Features

All extracted ground features were completely given the required attributes. All these output features comprise the flood hazard exposure database for the floodplain. This completes the feature extraction phase of the project.

Figure 32 shows the Digital Surface Model (DSM) of Sawaga floodplain overlaid with its ground features.




Figure 32. Extracted features for Sawaga floodplain.

CHAPTER 4: LIDAR VALIDATION SURVEY AND MEASUREMENTS OF THE SAWAGA RIVER BASIN

Engr. Ma. Rosario Concepcion O. Ang, Engr. John Louie D. Fabila, Engr. Sarah Jane D. Samalburro, Engr. Gladys Mae Apat, Alex John B. Escobido, Engr. Ma. Ailyn L. Olanda, Engr. Ma. Joanne I. Balaga, Jovy Anne S. Narisma, Engr. Wilbert Ian M. San Juan, Esmael L. Guardian

The methods applied in this Chapter were based on the DREAM methods manual (Balicanta, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

4.1 Summary of Activities

The project team conducted a field survey in Sawaga River on April 7, 11, 12, to 14, 19 to 23 and 27, 2016, May 8 to 10, 13, 14 and 16, 2016 with the following scope: reconnaissance; control survey; and cross-section and as-built survey at Sawaga Bridge in Brgy. Violeta, City of Malaybalay, Bukidnon. Random checking points for the contractor's cross-section and bathymetry data were gathered by DVBC on August 11, 2016 using a Trimble® SPS 882 GNSS PPK survey technique. In addition to this, validation points acquisition survey was conducted covering the Sawaga River Basin area. The entire survey extent is illustrated in Figure 33.




Figure 33. Extent of the bathymetric survey (blue line) in Sawaga River and the LiDAR data validation survey (red)

4.2 Control Survey

The GNSS network used for Sawaga River is composed of two (2) loops established on August 10, 2016 occupying the following reference points: BK-56, a first-order BM, in Brgy. Sumpong, Malaybalay City, Bukidnon; and BKN-475 a second-order GCP, in Brgy. Linabo, Malaybalay City, Bukidnon.

Two (2) control points established in the area by ABSD were also occupied: UP_MAN-2 located near the approach of Manupali Bridge in Brgy. Bangcud, Malaybalay City, Province of Bukidnon, and UP_LUM-2 located near the Pulangui Diversion Dam in Brgy. Lumbayao, Valencia City, Province of Bukidnon.

The summary of reference and control points and its location is summarized in Table 25 while GNSS network established is illustrated in Figure 34.

Table 25. List of reference and control points used during the survey in Sawaga River (Source: NAMRIA, UP-TCAGP)

Control Point	Order of Accuracy	Geographic Coordinates (WGS UTM Zone 52N)				
		Latitude	Longitude	Ellipsoid Height (m)	Elevation (MSL) (m)	Date of Establishment
BK-56	1 st order, BM	8° 9' 52.69903"N	125° 6' 54.60334"E	727.714	656.645	2008
BKN-475	2 nd order, GCP	8° 3' 22.52096"N	125° 8' 4.12506"E	473.980	403.169	2007
UP_MAN-2	Established	7° 59' 16.34151"N	125° 8' 3.89549"E	394.653	322.44	02-10-15
UP_LUM2	Established	7° 56' 49.14628"N	125° 9' 40.23913"E	411.207	339.432	04-19-2016




Figure 34. Sawaga River Basin Control Survey Extent

The GNSS set-ups on recovered reference points and established control points in Sawaga River are shown from Figure 35 to Figure 38.




Figure 35. GNSS receiver set up, Trimble® SPS 882, at BK--56, located at the west post of the welcome arc of Malaybalay City in Brgy. Sumpung, Bukidnon



Figure 36. GNSS receiver setup, BKN-475, located within the DPWH Compound in Brgy. Aglayan, Valencia City, Bukidnon.



Figure 37. GNSS receiver set up, Trimble® SPS 882, at UP_MAN -2, located near the approach of Manupali Bridge in Brgy. Bangcud, Malaybalay City, Province of Bukidnon




Figure 38. GNSS receiver set up, UP_LUM-2, located near the Pulangui Diversion Dam in Brgy. Lumbayao, Valencia City, Province of Bukidnon.

4.3 Baseline Processing

GNSS Baselines were processed simultaneously in TBC by observing that all baselines have fixed solutions with horizontal and vertical precisions within +/- 20 cm and +/- 10 cm requirement, respectively. In case where one or more baselines did not meet all of these criteria, masking is performed. Masking is done by removing/masking portions of these baseline data using the same processing software. It is repeatedly processed until all baseline requirements are met. If the reiteration yields out of the required accuracy, resurvey is initiated. Baseline processing result of control points in Sawaga River Basin is summarized in Table 26 generated by TBC software.

Table 26. Baseline Processing Report for Sawaga River Static Survey

Observation	Date of Observation	Solution Type	H. Prec. (Meter)	V. Prec. (Meter)	Geodetic Az.	Ellipsoid Dist. (Meter)	Height (m)
BK-56 --- BKN-475	8-10-2016	Fixed	0.007	0.024	169°55'49"	12174.173	-253.707
BK-56 --- UP_MAN-2	8-10-2016	Fixed	0.004	0.022	173°48'19"	19664.461	-334.563
BKN-475 --- UP_MAN-2	8-10-2016	Fixed	0.004	0.015	180°03'12"	7562.993	-80.875
BK-56--- UP_LUM-2	8-10-2016	Fixed	0.006	0.029	149°19'44"	27983.972	-318.479
BKN-475 --- UP_LUM-2	8-10-2016	Fixed	0.004	0.016	134°51'09"	17132.460	-253.707

As shown in Table 26, a total of five (5) baselines were processed with coordinate and ellipsoidal height values of BKN-475 held fixed. All of them passed the required accuracy.

4.4 Network Adjustment

After the baseline processing procedure, network adjustment is performed using TBC. Looking at the Adjusted Grid Coordinates table of the TBC generated Network Adjustment Report, it is observed that the square root of the squares of x and y must be less than 20 cm and z less than 10 cm in equation form:

$$\sqrt{(x_e)^2 + (y_e)^2} < 20 \text{ cm} \quad \text{and} \quad z_e < 10 \text{ cm}$$

Where:

- x_e is the Easting Error,
- y_e is the Northing Error, and
- z_e is the Elevation Error

for each control point. See the Network Adjustment Report shown from Tables 23 to 25 for the complete details. Refer to ANNEX 11 for the computation for the accuracy of ABSD.

The four (4) control points, BK-56, BKN-475, UP-MAN-2, and UP_LUM-2 were occupied and observed simultaneously to form a GNSS loop. The coordinates and ellipsoidal height of BKN-475 were held fixed during the processing of the control points as presented in Table 27. Through this reference point, the coordinates and ellipsoidal height of the unknown control points will be computed.

Table 27. Control Point Constraints

Point ID	Type	North (Meter)	East (Meter)	Height (Meter)	Elevation (Meter)
BK-56	Grid				
BKN-475	Global	Fixed	Fixed	Fixed	
Fixed = 0.000001(Meter)					

Table 28. Adjusted Grid Coordinates

Point ID	Easting (Meter)	Easting Error (Meter)	Northing (Meter)	Northing Error (Meter)	Elevation (Meter)	Elevation Error (Meter)	Constraint
BK-56	733046.484	0.009	903110.050	0.007	656.645	?	e
BKN-475	735238.147	?	891131.322	?	403.210	0.057	LLh
UP_MAN-2	735270.463	0.009	883566.236	0.007	322.440	0.061	
UP_LUM-2	747450.236	0.009	879107.389	0.007	338.965	0.067	

With the mentioned equation, $\sqrt{(x_e)^2 + (y_e)^2} < 20 \text{ cm}$ for horizontal and $z_e < 10 \text{ cm}$ for the vertical; the computation for the accuracy are as follows:

a. BK-56

horizontal accuracy = $\sqrt{(0.9)^2 + (0.7)^2}$
 = $\sqrt{0.81 + 0.49}$
 = $1.3 < 20 \text{ cm}$
 vertical accuracy = Fixed

c. UP_MAN-2

horizontal accuracy = $\sqrt{(0.9)^2 + (0.7)^2}$
 = $\sqrt{0.81 + 0.49}$
 = $1.3 < 20 \text{ cm}$
 vertical accuracy = $6.1 < 10 \text{ cm}$

b. BKN-475

horizontal accuracy = Fixed
 vertical accuracy = Fixed

d. UP_LUM-2

horizontal accuracy = $\sqrt{(0.9)^2 + (0.7)^2}$
 = $\sqrt{0.81 + 0.49}$
 = $1.3 < 20 \text{ cm}$
 vertical accuracy = $6.7 < 10 \text{ cm}$

Following the given formula, the horizontal and vertical accuracy result of the four (4) occupied control points are within the required precision.

Table 29. Adjusted Geodetic Coordinates

Point ID	Latitude	Longitude	Ellipsoid Height (Meter)	Height Error (Meter)	Constraint
BK-56	N8°09'52.69746"	E125°06'54.60518"	729.219	?	e
BKN-475	N8°03'22.52096"	E125°08'04.12506"	475.526	0.057	LLh
UP_MAN-2	N7°59'16.33836"	E125°08'03.89549"	394.653	0.061	
UP_LUM-2	N7°56'49.14664"	E125°14'40.69052"	410.740	0.067	

The corresponding geodetic coordinates of the observed points are within the required accuracy as shown in Table 29. Based on the result of the computation, the accuracy condition is satisfied; hence, the required accuracy for the program was met.

The summary of reference control points used is indicated in Table 30.

Table 30. Reference and control points used and its location (Source: NAMRIA, UP-TCAGP)

Point ID	Easting (Meter)	Easting Error (Meter)	Northing (Meter)	Northing Error (Meter)	Elevation (Meter)	Elevation Error (Meter)	Constraint
BK-56	1 st order, BM	8°9'52.69903"N	125°6'54.60334"E	727.714	903110.046	733046.488	656.645
BKN-475	2 nd order, GCP	8°3'22.52096"N	125° 8' 4.12506"E	473.980	891131.322	735238.147	403.175
UP_MAN-2	Established	7°59'16.34151"N	125° 8' 3.89549"E	394.653	883566.236	735270.463	322.44
UP_LUM-2	Established	7°56'49.14628"N	125°9'40.23913"E	411.207	879107.378	747450.247	339.432

4.5 Cross-section and Bridge As-Built survey and Water Level Marking

Cross-section and as-built surveys were conducted on April 27, 2016 at the upstream side of Sawaga Bridge in Brgy. Violeta, City of Malaybalay as shown in Figure 39. Nikon® Total Station was utilized for this survey as shown in Figure 40.



Figure 39. Sawaga Bridge facing upstream



Figure 40. As-built survey of Sawaga Bridge

The cross-sectional line of Sawaga Bridge is about 104.524 m with twenty-seven (27) cross-sectional points using the control points UP_SAW-1 and UP_SAW-2 as the GNSS base stations. The location map, cross-section diagram, and the bridge data form are shown in Figure 41 to Figure 43, respectively.




Figure 41. Sawaga Bridge Location Map





Figure 42. Sawaga Bridge Cross-section Diagram

Bridge Data Form

Bridge Name:	SAGAWA BRIDGE		
River Name:	SAGAWA RIVER		
Location (Brgy. City, Region):	Brgy. Violeta, Malaybalay City, Bukidnon		
Survey Team:	Jerby Galcosa		
Date and Time:	April 27, 2018; 10:55 A.M.		
Flow Condition:	low	✓ normal	high
Weather Condition:	✓ fair	rainy	

Cross-sectional View (not to scale)



Legend:

- BA = Bridge Approach
- P = Pier
- Ab = Abutment
- D = Deck
- WL = Water Level/Surface
- MSL = Mean Sea Level
- = Measurement Value

Line Segment	Measurement (m)	Remarks
1. BA1-BA2	3.88 m	
2. BA2-BA3	40.80 m	
3. BA3-BA4	3.81 m	
4. BA1-Ab1	12.11 m	
5. Ab2-BA4	12.11 m	
6. Deck/beam thickness	1.50 m	
7. Deck elevation	343 m	

Note: Observer should be facing downstream

Figure 43. Sawaga Bridge Data Sheet

Water surface elevation of Sawaga River was determined by a Nikon® Total Station on April 27, 2016 at 10:55 AM at Sawaga Bridge area with a value of 337.07 m in MSL as shown in Figure 42. This was translated into marking on the bridge's abutment as shown in Figure 44. The marking will serve as reference for flow data gathering and depth gauge deployment of the partner HEI responsible for Sawaga River, Central Mindanao University.



Figure 44. Sawaga Bridge facing upstream

4.6 Validation Points Acquisition Survey

Validation points acquisition survey was conducted by DVBC from August 12, 2016 using a survey grade GNSS Rover receiver, Trimble® SPS 882, mounted on a range pole which was attached at the back of the vehicle as shown in Figure 45. It was secured with cable ties and ropes to ensure that it was horizontally and vertically balanced. The antenna height was 2.235 m and measured from the ground up to the bottom of the quick release of the GNSS Rover receiver. The PPK technique utilized for the conduct of the survey was set to continuous topo mode with PLW-48 occupied as the GNSS base station in the conduct of the survey.



Figure 45. Validation points acquisition survey set-up for Sawaga River

The survey started from Brgy. Basak, Municipality of Lantapan, Bukidnon going southeast along the national highway and ended in Brgy. Dologon, City of Valencia, Bukidnon. A total of 9,668 points were gathered with an approximate length of 54 km using UP_MAN-2 as GNSS base station for the entire extent of validation points acquisition survey as illustrated in the map in Figure 46.




Figure 46. Validation points acquisition covering the Sawaga River Basin Area

4.7 River Bathymetric Survey

Manual bathymetric survey was executed on April 12-14, 2016 using a Nikon® Total Station as illustrated in Figure 47. The survey started downstream in Brgy. Colonia, City of Valencia, Bukidnon with coordinates 7° 58' 44.72870"N, 125° 8' 46.05364"E and ended upstream in Brgy. Violeta, City of Malaybalay, Bukidnon, with coordinates 8° 3' 55.15445"N, 125° 9' 38.69823"E. The control points UP_SAW-1 and UP_SAW-2 were used as GNSS base station all throughout the entire survey.

Gathering of random points for the checking of ABSD's bathymetric data was performed by DVBC on August 11, 2016 using a Trimble® SPS 882 GNSS PPK survey technique, see Figure 48. A map showing the DVBC bathymetric checking points is shown in Figure 50.

Linear square correlation (R2) and RMSE analysis were performed on the two (2) datasets. The linear square coefficient range is determined to ensure that the submitted data of the contractor is within the accuracy standard of the project which is ± 20 cm and ± 10 cm for horizontal and vertical, respectively. The R2 value must be within 0.85 to 1. An R2 approaching 1 signifies a strong correlation between the vertical (elevation values) of the two datasets. A computed R2 value of 0.998 was obtained by comparing the data of the contractor and DVBC; signifying a strong correlation between the two (2) datasets.

In addition to the Linear Square correlation, Root Mean Square (RMSE) analysis is also performed in order to assess the difference in elevation between the DVBC checking points and the contractor's. The RMSE value should only have a maximum radial distance of 5 m and the difference in elevation within the radius of 5 meters should not be beyond 0.50 m. For the bathymetric data, a computed value of 0.148 was acquired. The computed R2 and RMSE values are within the accuracy requirement of the program.



Figure 47. Manual Bathymetric survey of ABSD at Sawaga River using Nikon® Total Station



Figure 48. Gathering of random bathymetric points along Sawaga River

The manual bathymetric survey for Sawaga River gathered a total of 2,679 points covering an approximate of 20 km of the river traversing Brgy. Colonia in the City of Valencia, Bukidnon and Brgy. Sto. Niño, Simaya, Managok and Violeta in the City of Malaybalay, Bukidnon. A CAD drawing was also produced to illustrate the riverbed profile of Sawaga River. As shown in Figure 51, the highest and lowest elevation has a 35-m difference. The highest elevation observed was 342.166 m above MSL located in Brgy. Violeta, Malaybalay City, Bukidnon while the lowest was 306.500 m above MSL located in Brgy. Nabago, Valencia City, Bukidnon.




Figure 49. Manual Bathymetric survey of ABSD at Sawaga River using Nikon® Total Station




Figure 50. Quality checking points gathered along Sawaga River by DVBC




Figure 51. Sawaga Riverbed Profile

CHAPTER 5: FLOOD MODELING AND MAPPING

*Engr. Ma. Rosario Concepcion O. Ang, Engr. John Louie D. Fabila, Engr. Sarah Jane D. Samalbuero ,
Engr. Gladys Mae Apat , Alex John B. Escobido , Engr. Ma. Ailyn L. Olanda, Engr. Ma. Joanne I. Balaga,
Jovy Anne S. Narisma, Engr. Wilbert Ian M. San Juan , Esmael L. Guardian*

The methods applied in this Chapter were based on the DREAM methods manual (Lagmay, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

5.1 Data Used for Hydrologic Modeling

5.1.1 Hydrometry and Rating Curves

All data that affect the hydrologic cycle of the Sawaga River Basin were monitored, collected, and analyzed. Rainfall, water level, and flow in a certain period of time, which may affect the hydrologic cycle of the Sawaga River Basin were monitored, collected, and analyzed.

5.1.2 Precipitation

Precipitation data is one input requirement for the HMS calibration. Two precipitation data were utilized for the basin calibration. These were taken at Barangay 1, Malaybalay City using an automatic rain gauge (ARG) installed by the Department of Science and Technology – Advanced Science and Technology Institute (DOST-ASTI) and at Barangay San Jose, Malaybalay City using a manual rain gauge of Central Mindanao University. The location of the rain gauges is shown in Figure 52.

Total rain volume acquired from the two rain gauges is 44.9 mm. Peak rainfall for ARG at Barangay 1 is 9.4mm while for Barangay San Jose, peak rainfall is 4mm. It peaked on 31 May 2016 at 20:15 and 19:45, respectively. The lag time between the peak rainfall and discharge for Barangay 1 and Barangay San Jose is 4 hours and 15 minutes, and 4 hours and 45 minutes, respectively. Figure 54 shows the summary of the Sawaga river hydrometry.




Figure 52. The location map of Sawaga HEC-HMS model used for calibration

5.1.3 Rating Curves and River Outflow

The river velocity and water level change were used for the calculation of discharge, one of the required data for HMS model calibration. Velocity was measured at Cabacungan bridge of Barangay Linabo, Malaybalay City using a mechanical flow meter while water level was obtained from an Automated Water Level Sensor (AWLS) installed in the bridge. Acquired data was during a localized rainfall event on May 31 to June 1, 2016 from 1600 to 1140 hours. Peak discharge is 24.48 m³/s on June 1 at 0030hours. Figure 54 illustrates river discharge as influenced by the rate of the rainfall.




Figure 53. The cross-section plot of the Sawaga Bridge




Figure 54. Rainfall and outflow data used for modeling.

Using the gathered stage and discharge data, a rating curve was developed to illustrate its relationship. Stage was determined by the tying up the water surface elevation and water level change measured using the AWLS. Meanwhile, discharge was calculated using the cross section area, stage, and river velocity measured using a mechanical flow meter. The relationship is expressed in the form of the equation below. For Cabacungan Bridge, the rating curve is expressed as $Q = 42.706h^2 - 71.741h + 30.34$ as shown in Figure 55.




Figure 55. HQ Curve of HEC-HMS model.

5.2 RIDF Station

The Philippine Atmospheric Geophysical and Astronomical Services Administration (PAGASA) computed for Rainfall Intensity Duration Frequency (RIDF) values for the Malaybalay Rain Gauge. The RIDF rainfall amount for 24 hours was converted to a synthetic storm by interpolating and re-arranging the values in such a way a certain peak value will be attained at a certain time. This station is chosen based on its proximity to the Manupali watershed. The extreme values for this watershed were computed based on a 31-year record.

Table 31. RIDF values for Malaybalay Rain Gauge computed by PAGASA

COMPUTED EXTREME VALUES (in mm) OF PRECIPITATION									
T (yrs)	10 mins	20 mins	30 mins	1 hr	2 hrs	3 hrs	6 hrs	12 hrs	24 hrs
2	17.9	28.5	35.6	47.8	63.7	73.5	90.2	103.4	112.8
5	26.7	45.3	57.9	78.4	100.8	114.3	130.2	143.2	153.6
10	32.5	56.5	72.7	98.6	125.3	141.4	156.7	169.6	180.7
15	35.8	62.8	81	110	139.1	156.6	171.6	184.4	195.9
20	38.1	67.2	86.8	117.9	148.8	167.3	182.1	194.8	206.6
25	39.9	70.6	91.3	124.1	156.3	175.5	190.1	202.8	214.8
50	45.4	81	105.1	143	179.3	200.9	214.9	227.5	240.2
100	50.8	91.4	118.8	161.8	202.2	226	239.5	252	265.3




Figure 56. Location of Malaybalay RIDF Station relative to Sawaga River Basin




Figure 57. Synthetic storm generated for a 24-hr period rainfall for various return periods.

5.3 HMS Model

The soil shapefile (dated pre-2004) was taken from the Bureau of Soils and Water Management under the Department of Agriculture. The land cover dataset is from the National Mapping and Resource information Authority (NAMRIA). The soil and land cover of the Sawaga River Basin are shown in Figures 58 and 59, respectively.




Figure 58. The soil map of the Sawaga River Basin




Figure 59. The land cover map of the Sawaga River Basin (Source: NAMRIA)

For Sawaga, three soil classes were identified. These are clay loam, clay, and undifferentiated soil. Moreover, seven land cover classes were identified. These are built-up, cultivated area, forest plantation, grassland, open forest, shrubland, and tree plantation and perennial.




Figure 60. Slope Map of Sawaga River Basin




Figure 61. Stream delineation map of Sawaga river basin

Using ArcMap 10.1 with HEC-GeoHMS version 10.1 extension, the drainage system of Sawaga river was delineated using the river's centreline and SAR-DEM 10m resolution as primary input data. Delineated drainage system includes the basin boundary, subbasin and the stream networks. The river centreline was digitized starting from upstream towards downstream in Google Earth (2014).

Using the 10m SAR-DEM with default threshold area of 500 hectares, the delineated drainage system of Manupali Watershed generated twenty-six (26) sub-basins, thirteen (13) reaches and fourteen (14) junctions including the main outlet of the watershed (Figure 62).




Figure 62. HEC-HMS generated Sawaga River Basin Model.

5.4 Cross-section Data

Riverbed cross-sections of the watershed were necessary in the HEC-RAS model setup. The cross-section data for the HEC-RAS model was derived from the LiDAR DEM data. It was defined using the Arc GeoRAS tool and was post-processed in ArcGIS.




Figure 63. Sawaga River Cross-section generated using HEC GeoRAS tool.

5.5 Flo 2D Model

The automated modelling process allows for the creation of a model with boundaries that are almost exactly coincidental with that of the catchment area. As such, they have approximately the same land area and location. The entire area is divided into square grid elements, 10 meter by 10 meter in size. Each element is assigned a unique grid element number which serves as its identifier, then attributed with the parameters required for modelling such as x-and y-coordinate of centroid, names of adjacent grid elements, Manning coefficient of roughness, infiltration, and elevation value. The elements are arranged spatially to form the model, allowing the software to simulate the flow of water across the grid elements and in eight directions (north, south, east, west, northeast, northwest, southeast, southwest).

Based on the elevation and flow direction, it is seen that the water will generally flow from the northwest of the model to the southeast, following the main channel. As such, boundary elements in those particular regions of the model are assigned as inflow and outflow elements respectively.



Figure 64. Screenshot of subcatchment with the computational area to be modeled in FLO-2D GDS Pro

The simulation is then run through FLO-2D GDS Pro. This particular model had a computer run time of 28.32373 hours. After the simulation, FLO-2D Mapper Pro is used to transform the simulation results into spatial data that shows flood hazard levels, as well as the extent and inundation of the flood. Assigning the appropriate flood depth and velocity values for Low, Medium, and High creates the following food hazard map. Most of the default values given by FLO-2D Mapper Pro are used, except for those in the Low hazard level. For this particular level, the minimum h (Maximum depth) is set at 0.2 m while the minimum vh (Product of maximum velocity (v) times maximum depth (h)) is set at $0 \text{ m}^2/\text{s}$.

The creation of a flood hazard map from the model also automatically creates a flow depth map depicting the maximum amount of inundation for every grid element. The legend used by default in Flo-2D Mapper is not a good representation of the range of flood inundation values, so a different legend is used for the layout. In this particular model, the inundated parts cover a maximum land area of $30\,871\,500.00 \text{ m}^2$.

There is a total of $208\,903\,237.15 \text{ m}^3$ of water entering the model. Of this amount, $11\,957\,813.56 \text{ m}^3$ is due to rainfall while $196\,945\,423.58 \text{ m}^3$ is inflow from other areas outside the model. $3\,829\,085.00 \text{ m}^3$ of this water is lost to infiltration and interception, while $2\,099\,733.22 \text{ m}^3$ is stored by the flood plain. The rest, amounting up to $202\,974\,422.96 \text{ m}^3$, is outflow.

5.6 Results of HMS Calibration

After calibrating the Sawaga HEC-HMS river basin model, its accuracy was measured against the observed values (see ANNEX 9: Sawaga Model Basin Parameters). Figure 64 shows the comparison between the two discharge data.




Figure 65. Outflow Hydrograph of Sawaga produced by the HEC-HMS model compared with observed outflow.

Table 32 shows adjusted ranges of values of the parameters used in calibrating the model.

Table 32. Range of calibrated values for the Sawaga River Basin.

Hydrologic Element	Calculation Type	Method	Parameter	Range of Calibrated Values
Basin	Loss	SCS Curve number	Initial Abstraction (mm)	13 - 40
			Curve Number	65 - 76
	Transform	Clark Unit Hydrograph	Time of Concentration (hr)	0.096 - 1
			Storage Coefficient (hr)	0.35 – 3.80
	Baseflow	Recession	Recession Constant	1
Ratio to Peak			0.15	
Reach	Routing	Muskingum-Cunge	Manning's Coefficient	0.0001 - 1

Initial abstraction defines the amount of precipitation that must fall before surface runoff. The magnitude of the outflow hydrograph increases as initial abstraction decreases. The range of values from 13mm to 40mm signifies that there is minimal to average amount of infiltration or rainfall interception by vegetation.

The curve number is the estimate of the precipitation excess of soil cover, land use, and antecedent moisture. The magnitude of the outflow hydrograph increases as curve number increases. The range of 65 to 76 for curve number is less than the advisable range for Philippine watersheds (70 to 80) depending on the soil and land cover of the area (Horritt, personal communication, 2012). For Sawaga, the basin mostly consists of cultivated area and shrubland; the soil consists mostly of clay and undifferentiated soil.

The time of concentration and storage coefficient are the travel time and index of temporary storage of runoff in a watershed. The range of calibrated values from 0.096 hours to 3.80 hours determines the reaction time of the model with respect to the rainfall. The peak magnitude of the hydrograph also decreases when these parameters are increased.

Recession constant is the rate at which baseflow recedes between storm events, while ratio to peak is the ratio of the baseflow discharge to the peak discharge. Recession constant of 1 indicates that the basin is unlikely to quickly go back to its original discharge. Ratio to peak of 0.15 indicates a steeper receding limb of the outflow hydrograph.

The basin was calibrated with Manning’s roughness coefficient of 0.0001 – 1. The Manning’s value corresponding to the land cover of Sawaga watershed is 0.04 for land cultivated with mature field crops (Brunner, 2010)

Table 33. Summary the Efficiency Test of the Sawaga HMS Model

Accuracy measure	Value
RMSE	2.4
r^2	0.94
NSE	0.81
PBIAS	22.73
RSR	0.44

The Root Mean Square Error (RMSE) method aggregates the individual differences of these two measurements. It was computed as 2.4 (m³/s).

The Pearson correlation coefficient (r^2) assesses the strength of the linear relationship between the observations and the model. This value being close to 1 corresponds to an almost perfect match of the observed discharge and the resulting discharge from the HEC HMS model. Here, it measured 0.94.

The Nash-Sutcliffe (E) method was also used to assess the predictive power of the model. Here the optimal value is 1. The model attained an efficiency coefficient of 0.81.

A positive Percent Bias (PBIAS) indicates a model’s propensity towards under-prediction. Negative values indicate bias towards over-prediction. Again, the optimal value is 0. In the model, the PBIAS is 22.73.

The Observation Standard Deviation Ratio, RSR, is an error index. A perfect model attains a value of 0 when the error in the units of the valuable a quantified. The model has an RSR value of 0.44.

5.7 Calculated outflow hydrographs and discharge values for different rainfall return periods

5.7.1 Hydrograph using the Rainfall Runoff Model

The summary graph (Figure 65) shows the Sawaga River outflow using the Malaybalay Rainfall Intensity-Duration-Frequency curves (RIDF) in 5 different return periods (5-year, 10-year, 25-year, 50-year, and 100-year rainfall time series) based on the Philippine Atmospheric Geophysical and Astronomical Services Administration (PAG-ASA) data. The simulation results reveal significant increase in outflow magnitude as the rainfall intensity increases for a range of durations and return periods.




Figure 66. Outflow hydrograph at Sawaga Station generated using Malaybalay RIDF simulated in HEC-HMS

A summary of the total precipitation, peak rainfall, peak outflow and time to peak of the Sawaga discharge using the Malaybalay Rainfall Intensity-Duration-Frequency curves (RIDF) in five different return periods is shown in Figure 65.

Table 34 outlines the peak values of the Sawaga HEC-HMS Model outflow using the Malaybalay RIDF 24-hour values.

Table 34. Peak values of the Sawaga HEC-HMS Model outflow using the Malaybalay RIDF 24-hour values

RIDF Period	Total Precipitation (mm)	Peak rainfall (mm)	Peak outflow (m ³ /s)	Time to Peak	Lag Time
5-yr	153.6	26.7	959.7	2 hours, 20 mins	1 hour 10 minutes
10-yr	180.7	32.5	1422.4	2 hours, 10 mins	1 hour 10 minutes
25-yr	214.8	39.9	2001.8	2 hours	1 hour 10 minutes
50-yr	240.2	45.4	2432.4	2 hours	1 hour 10 minutes
100-yr	265.3	50.8	2869.5	1 hour, 50 mins	1 hour 10 minutes

5.8 River Analysis (RAS) Model Simulation

The HEC-RAS Flood Model produced a simulated water level at every cross-section for every time step for every flood simulation created. The resulting model will be used in determining the flooded areas within the model. The simulated model will be an integral part in determining real-time flood inundation extent of the river after it has been automated and uploaded on the DREAM website. For this publication, only a sample output map river was to be shown. The sample generated map of Sawaga River using the calibrated HMS base flow is shown in Figure 66.



Figure 67. Sample output of Sawaga RAS Model

5.9 Flow Depth and Flood Hazard

The resulting hazard and flow depth maps have a 10m resolution. Figure 67 to Figure 72 shows the 5-, 25-, and 100-year rain return scenarios of the Manupali-Sawaga-Upper Pulangi floodplain. The floodplain, with an area of 732.86 sq. km., covers the municipalities of Lantapan, Maramag, Quezon, and San Fernando and the cities of Malaybalay and Valencia. Table 36 shows the percentage of area affected by flooding per municipality.

Table 35. Municipalities affected in Manupali-Sawaga-Upper Pulangi floodplain

Municipality	Total Area	Area Flooded	% Flooded
Lantapan	355.91	81.26	22.83%
Malaybalay City	1004.67	259.22	25.80%
Maramag	320.61	10.19	3.18%
Quezon	647.63	6.02	0.93%
San Fernando	605.87	0.49	0.08%
Valencia City	668.14	375.69	56.23%




Figure 68. 100-year Flood Hazard Map for Manupali-Sawaga-Upper Pulangi Floodplain




Figure 69. 100-year Flood Depth Map for Manupali-Sawaga-Upper Pulangi Floodplain




Figure 70. 25-year Flood Hazard Map for Manupali-Sawaga-Upper Pulangi Floodplain




Figure 71. 25-year Flood Depth Map for Manupali-Sawaga-Upper Pulangi Floodplain




Figure 72. 5-year Flood Hazard Map for Manupali-Sawaga-Upper Pulangi Floodplain




Figure 73. 5-year Flood Depth Map for Manupali-Sawaga-Upper Pulangi Floodplain

5.10 Inventory of Areas Exposed to Flooding

Affected barangays in Manupali-Sawaga-Upper Pulangi Floodplain, grouped by municipality, are listed below. For the said floodplain, five municipalities consisting of 66 barangays are expected to experience flooding when subjected to 5-, 25-, and 100-yr rainfall return period.

For the 5-year return period, 22.41% of the municipality of Lantapan with an area of 290.82 sq. km. will experience flood levels of less than 0.20 meters. 2.04% of the area will experience flood levels of 0.21 to 0.50 meters while 1.03%, 0.77%, 0.60%, and 0.07% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 36. Affected Areas in Lantapan, Bukidnon during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Lantapan (in sq. km)					
	Balila	Bantuanon	Bugcaon	Capitan Juan	Kulasihan	Poblacion
0.03-0.20	0.064	24.75	12.6	6.14	13.03	8.58
0.21-0.50	0	2.3	0.9	0.33	1.84	0.56
0.51-1.00	0	1.28	0.38	0.2	0.85	0.29
1.01-2.00	0	0.78	0.49	0.056	0.8	0.12
2.01-5.00	0	0.71	0.51	0.0047	0.49	0.018
> 5.00	0	0.046	0.062	0.0041	0.1	0




Figure 74. Affected Areas in Lantapan, Bukidnon during 5-Year Rainfall Return Period

For the 5-year return period, 17.48% of the municipality of Malaybalay City with an area of 1115.98 sq. km. will experience flood levels of less than 0.20 meters. 2.17% of the area will experience flood levels of 0.21 to 0.50 meters while 1.80%, 1.26%, 0.95%, and 0.29% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 37. Affected Areas in Lantapan, Bukidnon during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Malaybalay City (in sq. km)									
	Aglayan	Apo Macote	Bangcud	Barangay 1	Barangay 2	Barangay 3	Barangay 4	Barangay 5	Barangay 6	Barangay 7
0.03-0.20	11.63	4.77	3.45	2.25	0.48	0.28	0.33	0.34	3.06	0.68
0.21-0.50	0.56	0.16	0.78	0.071	0.022	0.014	0.018	0.013	0.077	0.058
0.51-1.00	0.39	0.084	0.32	0.055	0.0068	0.012	0.011	0.0059	0.049	0.012
1.01-2.00	0.35	0.068	0.72	0.058	0.014	0.0081	0.01	0.011	0.041	0.0077
2.01-5.00	0.16	0.087	1.1	0.076	0.058	0.0049	0.028	0.032	0.041	0.02
> 5.00	0.01	0.0079	0.21	0.031	0.061	0	0.005	0.02	0.04	0.0025




Figure 75. Affected Areas in Malaybalay City, Bukidnon during 5-Year Rainfall Return Period

Table 38. Affected Areas in Malaybalay City, Bukidnon during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Malaybalay City (in sq. km)									
	Barangay 8	Barangay 9	Barangay 10	Barangay 11	Cabangahan	Canayan	Casisang	Laguaitas	Linabo	Magsaysay
0.03-0.20	0.33	4.2	6.64	0.45	4.43	1.06	27.29	25.1	5.29	2
0.21-0.50	0.016	0.2	0.43	0.012	0.72	0.024	1.26	1.15	0.45	0.11
0.51-1.00	0.01	0.18	0.18	0.0081	0.37	0.018	0.86	0.73	0.22	0.055
1.01-2.00	0.0079	0.17	0.19	0.0029	0.23	0.012	0.89	0.73	0.27	0.021
2.01-5.00	0.01	0.058	0.1	0.000021	0.18	0.01	0.69	0.62	0.31	0.0043
> 5.00	0.028	0.066	0.0081	0	0.0011	0.0012	0.63	0.31	0.083	0




Figure 76. Affected Areas in Malaybalay City, Bukidnon during 5-Year Rainfall Return Period

Table 39. Affected Areas in Malaybalay City, Bukidnon during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Malaybalay City (in sq. km)									
	Maligaya	Managok	Miglamin	San Jose	San Martin	Santo Niño	Simaya	Sinanglanan	Sumpang	Violeta
0.03-0.20	11.93	13.94	1.44	12.92	21.39	5.89	12.46	6.02	0.36	4.66
0.21-0.50	0.43	3.7	0.022	0.71	0.77	4.42	5.6	0.67	0.011	1.73
0.51-1.00	0.32	3.62	0.012	0.37	0.49	3.68	5.14	1.12	0.0051	1.72
1.01-2.00	0.36	2.9	0.01	0.24	0.38	2.19	2.08	1.11	0.0085	0.99
2.01-5.00	0.15	1.92	0.0093	0.2	0.23	2.47	0.98	0.39	0.01	0.68
> 5.00	0.0011	0.17	0.0002	0.66	0.0084	0.57	0.17	0	0.021	0.17




Figure 77. Affected Areas in Malaybalay City, Bukidnon during 5-Year Rainfall Return Period

For the 5-year return period, 3.20% of the municipality of Maramag with an area of 323.88 sq. km. will experience flood levels of less than 0.20 meters. 0.67% of the area will experience flood levels of 0.21 to 0.50 meters while 0.67%, 0.34%, 0.07%, and 0.06% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 40. Affected Areas in Maramag, Bukidnon during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Maramag (in sq. km)
	Dologon
0.03-0.20	10.38
0.21-0.50	2.18
0.51-1.00	2.18
1.01-2.00	1.09
2.01-5.00	0.23
> 5.00	0.18




Figure 78. Affected Areas in Lantapan, Bukidnon during 5-Year Rainfall Return Period

For the 5-year return period, 0.60% of the municipality of Quezon with an area of 641.25 sq. km. will experience flood levels of less than 0.20 meters. 0.06% of the area will experience flood levels of 0.21 to 0.50 meters while 0.08%, 0.12%, and 0.01% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and 2.01 to 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 41. Affected Areas in Quezon, Bukidnon during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Quezon (in sq. km)
	Paitan
0.03-0.20	3.84
0.21-0.50	0.4
0.51-1.00	0.52
1.01-2.00	0.77
2.01-5.00	0.072
> 5.00	0




Figure 79. Affected Areas in Quezon, Bukidnon during 5-Year Rainfall Return Period

For the 5-year return period, 32.07% of the municipality of Valencia City with an area of 726.07 sq. km. will experience flood levels of less than 0.20 meters. 5.30% of the area will experience flood levels of 0.21 to 0.50 meters while 4.69%, 3.81%, 3.45%, and 1.00% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 42. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Valencia City (in sq. km)									
	Bagontaas	Banlag	Barobo	Batangan	Catumbalon	Colonia	Concepcion	Dagat-Kidavao	Kahapunan	Laligan
0.03-0.20	20.71	14.12	12.48	5.92	2.96	0.85	10.22	21.25	1.28	5.34
0.21-0.50	3.59	3.09	0.46	1.94	1.55	0.67	0.28	4.94	0.2	2.82
0.51-1.00	1.92	3.09	0.37	0.94	2.36	0.59	0.18	2.47	0.34	5.9
1.01-2.00	1.28	1.5	0.33	0.43	3.22	0.5	0.15	0.93	1.03	2.38
2.01-5.00	1.21	0.34	0.21	0.24	0.5	0.31	0.19	0.2	1.72	0.71
> 5.00	0.19	0.0019	0.009	0.03	0.34	0.056	0.14	0.0003	0.023	0.018




Figure 80. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period

Table 43. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Valencia City (in sq. km)								
	Lumbayao	Lumbo	Lurogan	Maapag	Mabuhay	Mailag	Mt. Nebo	Nabago	Pinatilan
0.03-0.20	3.84	24.07	20.83	3.12	8.01	5.41	3.43	0.99	3.58
0.21-0.50	0.14	1.54	0.85	1.48	1.17	1.47	0.17	1.11	1.22
0.51-1.00	0.099	1.03	0.46	1.34	0.51	0.87	0.086	1.02	1.01
1.01-2.00	0.069	1.08	0.4	0.8	0.44	0.46	0.039	1.53	0.77
2.01-5.00	0.19	0.67	0.35	0.5	0.53	0.5	0.0064	4.42	0.12
> 5.00	0.55	0.31	0.02	0.13	0.12	0.44	0	1.58	0.18




Figure 81. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period

Table 44. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Valencia City (in sq. km)								
	Poblacion	San Carlos	San Isidro	Sinabugan	Sinayawan	Sugod	Tongantongan	Tugaya	Vintar
0.03-0.20	0.24	20.79	0.057	13.67	3.09	3.56	11.29	1.99	9.78
0.21-0.50	0.12	1.53	0.11	1.03	1.77	0.57	2.97	0.1	1.56
0.51-1.00	0.2	0.63	0.41	0.91	2.42	0.75	2.75	0.059	1.35
1.01-2.00	0.31	0.42	2.24	1.6	1.6	1.2	0.96	0.014	1.95
2.01-5.00	0.23	0.43	2.62	3.55	1.2	1.55	0.9	0.0001	1.66
> 5.00	0.15	0.091	0.37	0.93	0.12	0.7	0.11	0	0.66




Figure 82. Affected Areas in Valencia City, Bukidnon during 5-Year Rainfall Return Period

For the 25-year return period, 20.82% of the municipality of Lantapan with an area of 290.82 sq. km. will experience flood levels of less than 0.20 meters. 2.47% of the area will experience flood levels of 0.21 to 0.50 meters while 1.42%, 0.99%, 1.01%, and 0.23% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 45. Affected Areas in Lantapan, Bukidnon during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Lantapan (in sq. km)					
	Balila	Bantuanon	Bugcaon	Capitan Juan	Kulasihan	Poblacion
0.03-0.20	0.064	23.12	11.67	6	11.53	8.16
0.21-0.50	0	2.69	1.19	0.34	2.17	0.78
0.51-1.00	0	1.67	0.53	0.25	1.32	0.35
1.01-2.00	0	1.15	0.52	0.12	0.87	0.23
2.01-5.00	0	1.02	0.84	0.022	0.99	0.054
> 5.00	0	0.23	0.2	0.0041	0.24	0.00063




Figure 83. Affected Areas in Lantapan, Bukidnon during 25-Year Rainfall Return Period

For the 25-year return period, 3.37% of the municipality of Malaybalay City with an area of 1115.98 sq. km. will experience flood levels of less than 0.20 meters. 0.42% of the area will experience flood levels of 0.21 to 0.50 meters while 0.36%, 0.35%, 0.69%, and 0.21% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 46. Affected Areas in Malaybalay City, Bukidnon during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Malaybalay City (in sq. km)												
	Aglayan	Apo Macote	Bangcud	Cabangahan	Casisang	Laguitas	Linabo	Magsaysay	San Jose	San Martin	Santo Niño	Simaya	Sinanglanan
0.03-0.20	10.37	4.65	1.97	1.76	2.05	0.9	0.0028	1.96	1.75	0.8	3.59	0.1	5.69
0.21-0.50	0.64	0.21	0.73	0.38	0.13	0.079	0	0.12	0.1	0.033	1.58	0.0071	0.52
0.51-1.00	0.4	0.11	0.28	0.17	0.09	0.045	0	0.07	0.079	0.017	1.9	0.0046	0.73
1.01-2.00	0.36	0.073	0.18	0.078	0.068	0.044	0	0.033	0.056	0.014	1.5	0.0098	1.47
2.01-5.00	0.26	0.1	1.01	0.12	0.02	0.035	0.31	0.0098	0.0055	0.011	2.29	0.0058	0.87
> 5.00	0.031	0.043	0.33	0.018	0.63	0.0027	0.083	0	0.00000031	0.0084	0.7	0.17	0.0059




Figure 84. Affected Areas in Malaybalay City, Bukidnon during 25-Year Rainfall Return Period

For the 25-year return period, 2.61% of the municipality of Maramag with an area of 323.88 sq. km. will experience flood levels of less than 0.20 meters. 0.59% of the area will experience flood levels of 0.21 to 0.50 meters while 0.54%, 0.64%, 0.42%, and 0.22% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 47. Affected Areas in Maramag, Bukidnon during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Maramag (in sq. km)
	Dologon
0.03-0.20	8.45
0.21-0.50	1.92
0.51-1.00	1.75
1.01-2.00	2.06
2.01-5.00	1.35
> 5.00	0.71




Figure 85. Affected Areas in Lantapan, Bukidnon during 25-Year Rainfall Return Period

For the 25-year return period, 0.53% of the municipality of Quezon with an area of 641.25 sq. km. will experience flood levels of less than 0.20 meters. 0.06% of the area will experience flood levels of 0.21 to 0.50 meters while 0.03%, 0.05%, 0.20%, and 0.01% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 48. Affected Areas in Quezon, Bukidnon during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Quezon (in sq. km)
	Paitan
0.03-0.20	3.39
0.21-0.50	0.38
0.51-1.00	0.17
1.01-2.00	0.35
2.01-5.00	1.27
> 5.00	0.037




Figure 86. Affected Areas in Quezon, Bukidnon during 25-Year Rainfall Return Period

For the 25-year return period, 26.33% of the municipality of Valencia City with an area of 726.07 sq. km. will experience flood levels of less than 0.20 meters. 4.59% of the area will experience flood levels of 0.21 to 0.50 meters while 4.29%, 5.25%, 5.86%, and 3.85% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 49. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Valencia City (in sq. km)									
	Bagontaas	Banlag	Barobo	Batangan	Catumbalon	Colonia	Concepcion	Dagat-Kidavao	Kahapunan	Laligan
0.03-0.20	17.5	12.64	12.13	0.37	0.34	0.27	9.99	17.54	0.53	4.1
0.21-0.50	4.57	2.24	0.49	0.44	0.18	0.22	0.32	6.12	0.44	1.71
0.51-1.00	2.48	3.3	0.38	0.7	0.22	0.49	0.21	4.05	0.34	4.12
1.01-2.00	1.78	3.26	0.4	2.14	0.22	0.72	0.18	1.66	0.93	5.95
2.01-5.00	1.97	0.7	0.4	3.03	5.12	0.27	0.22	0.41	2.25	1.24
> 5.00	0.59	0.0051	0.059	2.81	4.84	0.021	0.24	0.0005	0.11	0.033




Figure 87. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period

Table 50. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Valencia City (in sq. km)								
	Lumbayao	Lumbo	Lurogan	Maapag	Mabuhay	Mailag	Mt. Nebo	Nabago	Pinatilan
0.03-0.20	3.7	22.7	19.95	0.49	6	3.93	3.19	0.011	0.0012
0.21-0.50	0.15	1.77	1.12	0.5	2.01	1.64	0.2	0.076	0.0078
0.51-1.00	0.12	1.08	0.52	1.07	1.15	1.27	0.11	0.93	0.12
1.01-2.00	0.081	0.67	0.44	2.42	0.77	1.09	0.11	2.13	0.25
2.01-5.00	0.13	0.75	0.64	1.46	0.68	0.66	0.13	5.01	0.38
> 5.00	0.72	1.73	0.23	1.45	0.18	0.58	0.0001	2.51	6.12




Figure 88. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period

Table 51. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Valencia City (in sq. km)								
	Poblacion	San Carlos	San Isidro	Sinabuagan	Sinayawan	Sugod	Tongantongan	Tugaya	Vintar
0.03-0.20	0.092	19.37	0.019	13	1.27	2.65	9.5	1.92	7.97
0.21-0.50	0.068	2.1	0.024	1.04	0.8	0.31	3.05	0.097	1.65
0.51-1.00	0.087	0.93	0.1	0.73	1.99	0.35	2.51	0.078	1.74
1.01-2.00	0.22	0.6	0.93	1.2	3.93	1.33	2.57	0.049	2.12
2.01-5.00	0.22	0.53	4.14	3.88	1.99	2.78	1.13	0.014	2.45
> 5.00	0.56	0.36	0.58	1.85	0.23	0.91	0.22	0	1.02




Figure 89. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period

For the 100-year return period, 0.02% of the municipality of Lantapan with an area of 290.82 sq. km. will experience flood levels of less than 0.20 meters. 0.00% of the area will experience flood levels of 0.21 to 0.50 meters while 0.00% of the area will experience flood depths of 0.51 to 1 meter. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 52. Affected Areas in Lantapan, Bukidnon during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Lantapan (in sq. km)
	Bantuanon
0.03-0.20	0.056
0.21-0.50	0.001
0.51-1.00	0.001
1.01-2.00	0.002
2.01-5.00	0.0053
> 5.00	0.012




Figure 90. Affected Areas in Lantapan, Bukidnon during 100-Year Rainfall Return Period

For the 100-year return period, 0.15% of the municipality of Malaybalay City with an area of 1115.98 sq. km. will experience flood levels of less than 0.20 meters. 0.10% of the area will experience flood levels of 0.21 to 0.50 meters while 0.20%, 0.15%, 0.13%, and 0.06% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 53. Affected Areas in Malaybalay City, Bukidnon during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Malaybalay City (in sq. km)	
	Apo Macote	Santo Niño
0.03-0.20	0	1.71
0.21-0.50	0	1.1
0.51-1.00	0	2.18
1.01-2.00	0	1.67
2.01-5.00	0	1.48
> 5.00	0.0011	0.69




Figure 91. Affected Areas in Lantapan, Bukidnon during 25-Year Rainfall Return Period

For the 100-year return period, 2.38% of the municipality of Maramag with an area of 323.88 sq. km. will experience flood levels of less than 0.20 meters. 0.61% of the area will experience flood levels of 0.21 to 0.50 meters while 0.53%, 0.78%, 0.43%, and 0.28% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 54. Affected Areas in Maramag, Bukidnon during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Maramag (in sq. km)
	Dologon
0.03-0.20	7.71
0.21-0.50	1.97
0.51-1.00	1.73
1.01-2.00	2.53
2.01-5.00	1.38
> 5.00	0.92




Figure 92. Affected Areas in Maramag, Bukidnon during 100-Year Rainfall Return Period

For the 100-year return period, 0.49% of the municipality of Quezon with an area of 641.25 sq. km. will experience flood levels of less than 0.20 meters. 0.08% of the area will experience flood levels of 0.21 to 0.50 meters while 0.02%, 0.05%, 0.22%, and 0.01% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 55. Affected Areas in Quezon, Bukidnon during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Quezon (in sq. km)
	Paitan
0.03-0.20	3.17
0.21-0.50	0.54
0.51-1.00	0.16
1.01-2.00	0.29
2.01-5.00	1.4
> 5.00	0.038




Figure 93. Affected Areas in Quezon, Bukidnon during 100-Year Rainfall Return Period

For the 100-year return period, 23.11% of the municipality of Valencia City with an area of 726.07 sq. km. will experience flood levels of less than 0.20 meters. 4.54% of the area will experience flood levels of 0.21 to 0.50 meters while 3.78%, 5.55%, 6.57%, and 4.22% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in the table are the affected areas in square kilometers by flood depth per barangay.

Table 56. Affected Areas in Valencia City, Bukidnon during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Valencia City (in sq. km)												
	Bagontaas	Banlag	Barobo	Batangan	Catumbalon	Colonia	Concepcion	Dagat-Kidavao	Kahapunan	Laligan	Santo Niño	Simaya	Sinanglanan
0.03-0.20	14.56	11.91	11.9	0.26	0.21	0.22	9.83	15.26	0.23	3.53	3.59	0.1	5.69
0.21-0.50	4.64	1.97	0.53	0.36	0.12	0.085	0.36	6.81	0.3	1.3	1.58	0.0071	0.52
0.51-1.00	2.19	2.85	0.4	0.24	0.25	0.15	0.22	4.7	0.59	3.06	1.9	0.0046	0.73
1.01-2.00	1.65	3.87	0.43	1.75	0.25	0.16	0.19	2.42	0.86	7.04	1.5	0.0098	1.47
2.01-5.00	2.1	1.53	0.5	4.05	4.1	0.046	0.25	0.59	2.41	2.17	2.29	0.0058	0.87
> 5.00	0.83	0.013	0.12	2.84	5.98	0.021	0.31	0.0013	0.22	0.05	0.7	0.17	0.0059




Figure 94. Affected Areas in Valencia City, Bukidnon during 100-Year Rainfall Return Period

Table 57. Affected Areas in Valencia City, Bukidnon during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Valencia City (in sq. km)								
	Lumbayao	Lumbo	Lurogan	Maapag	Mabuhay	Mailag	Mt. Nebo	Nabago	Pinatilan
0.03-0.20	0.59	21.92	16.13	0.15	4.55	3.74	2.13	0.0038	0
0.21-0.50	0.013	2	1.04	0.19	2.61	1.9	0.15	0.0089	0.00037
0.51-1.00	0.0044	1.21	0.55	0.74	1.29	1.45	0.09	0.27	0.0021
1.01-2.00	0.0016	0.82	0.4	2.62	1.27	0.85	0.082	2.68	0.28
2.01-5.00	0.0035	0.91	0.52	1.96	0.82	0.56	0.13	4.62	0.25
> 5.00	0.0009	1.85	0.3	1.72	0.22	0.61	0.0038	3.08	6.35




Figure 95. Affected Areas in Valencia City, Bukidnon during 100-Year Rainfall Return Period

Table 58. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Valencia City (in sq. km)								
	Poblacion	San Carlos	San Isidro	Sinabugan	Sinayawan	Sugod	Tongantongan	Tugaya	Vintar
0.03-0.20	0.059	17.5	0.01	11.93	0.79	2.47	8.73	1.9	7.3
0.21-0.50	0.04	2.3	0.013	1.02	0.48	0.4	2.82	0.096	1.39
0.51-1.00	0.086	1.07	0.043	0.72	0.88	0.22	2.54	0.083	1.55
1.01-2.00	0.19	0.7	0.43	0.77	4.25	1.11	3.25	0.061	1.94
2.01-5.00	0.3	0.61	4.46	3.46	3.49	3.12	1.28	0.026	3.46
> 5.00	0.57	0.44	0.77	1.33	0.31	1.01	0.37	0.0001	1.31




Figure 96. Affected Areas in Valencia City, Bukidnon during 25-Year Rainfall Return Period

Among the barangays in the municipality of Lantapan in Bukidnon, Bantuanon is projected to have the highest percentage of area that will experience flood levels at 10.27%. Meanwhile, Kulasihan posted the second highest percentage of area that may be affected by flood depths at 5.88%.

Among the barangays in the municipality of Malaybalay City in Bukidnon, Casisang is projected to have the highest percentage of area that will experience flood levels at 10.87%. Meanwhile, Laguitas posted the second highest percentage of area that may be affected by flood depths at 9.85%.

Brgy. Dologon is the only barangay affected in the municipality of Maramag in Bukidnon. The barangay is projected to experience flood in 5.58% of the municipality.

Brgy. Paitan is the only barangay affected in the municipality of Quezon in Bukidnon. The barangay is projected to experience flood in 1.93% of the municipality.

Among the barangays in the municipality of Valencia City in Bukidnon, Dagat-Kidavao is projected to have the highest percentage of area that will experience flood levels at 10.24%. Meanwhile, Bagontaas posted the second highest percentage of area that may be affected by flood depths at 9.94%.

Moreover, the generated flood hazard maps for the Manupali-Sawaga-Upper Pulangi Floodplain were used to assess the vulnerability of the educational and medical institutions in the floodplain. Using the flood depth units of PAG-ASA for hazard maps (“Low”, “Medium”, and “High”), the affected institutions were given their individual assessment for each Flood Hazard Scenario (5-year, 25-year, and 10-year).

Table 59. Areas covered by each warning level with respect to the rainfall scenarios

Warning Level	Area Covered in sq. km.		
	5 year	25 year	100 year
Low	72.25	67.13	68.35
Medium	87.85	98.40	97.07
High	68.99	126.61	152.82
TOTAL	229.09	292.14	318.24

Of the 115 identified Education Institute in Manupali-Sawaga-Upper Pulangi Flood plain, 20 schools were discovered exposed to Low-level flooding during a 5-year scenario, while 25 schools were found exposed to Medium-level flooding and 12 schools were discovered exposed to High-level flooding in the same scenario.

In the 25-year scenario, 23 schools were found exposed to Low-level flooding, while 28 schools were discovered exposed to Medium-level flooding. In the same scenario, 24 schools were found exposed to High-level flooding.

For the 100-year scenario, 19 schools were discovered exposed to Low-level flooding, while 26 schools were exposed to Medium-level flooding. In the same scenario, 33 schools were found exposed to High-level flooding. See Appendix D for a detailed enumeration of affected education institutes in the Manupali-Sawaga-Upper Pulangi floodplain.

Apart from this, 34 Medical Institutions were identified in the Manupali-Sawaga-Upper Pulangi Floodplain. Five (5) of these medical institutions were found exposed to Low-level flooding during a 5-year scenario, while 10 were discovered exposed to Medium-level flooding. In the same scenario, two (2) hospitals were found exposed to High-level flooding.

In the 25-year scenario, seven (7) medical institutions were discovered exposed to Low-level flooding, while 10 were found exposed to Medium-level flooding. In the same scenario, seven (7) hospitals were discovered exposed to High-level flooding.

For the 100-year scenario, eight (8) medical institutions were found exposed to Low-level flooding, while 10 were discovered exposed to Medium-level flooding. In the same scenario, eight (8) hospitals were found exposed to High-level flooding. See Appendix E for a detailed enumeration of the affected medical institutions in the Manupali-Sawaga-Upper Pulangi floodplain.

5.11 Flood Validation

In order to check and validate the extent of flooding in different river systems, a validation survey work was performed. Field personnel gathered secondary data regarding flood occurrence in the area within the major river system in the Philippines.

From the Flood Depth Maps produced by Phil-LiDAR 1 Program, multiple points representing the different flood depths for different scenarios were identified for validation.

The validation personnel went to the specified points identified in a river basin and gathered data regarding the actual flood level in each location. Data gathering was done through the help of a local DRRM office to obtain maps or situation reports about the past flooding events and through interviews of some residents with knowledge of or have had experienced flooding in a particular area.

The actual data from the field were compared to the simulated data to assess the accuracy of the Flood Depth Maps produced and to improve on what is needed.

The flood validation consists of 404 points randomly selected all over the Manupali-Sawaga-Upper Pulangi flood plain. It has an RMSE value of 1.69. The validation points are found in ANNEX 11.




Figure 97. The Validation Points for a 5-year Flood Depth Map of the Manupali-Sawaga-Upper Pulangi Floodplain




Figure 98. Flood map depth vs actual flood depth

Table 60. Actual flood vs simulated flood depth at different levels in the Manupali-Sawaga-Upper Pulangi River Basin.

SAWAGA BASIN		MODELED FLOOD DEPTH (m)						Total
		0-0.20	0.21-0.50	0.51-1.00	1.01-2.00	2.01-5.00	> 5.00	
Actual Flood Depth (m)	0-0.20	141	27	22	46	30	8	274
	0.21-0.50	10	5	5	15	10	2	47
	0.51-1.00	9	4	3	12	16	1	45
	1.01-2.00	9	5	3	7	9	0	33
	2.01-5.00	0	1	0	1	3	0	5
	> 5.00	0	0	0	0	0	0	0
	Total	169	42	33	81	68	11	404

On the whole, the overall accuracy generated by the flood model is estimated at 39.36% with 159 points correctly matching the actual flood depths. In addition, there were 67 points estimated one level above and below the correct flood depths while there were 67 points and 107 points estimated two levels above and below, and three or more levels above and below the correct flood. A total of 4 points were overestimated while a total of 42 points were underestimated in the modelled flood depths of Manupali-Sawaga-Upper Pulangi. Table 43 depicts the summary of the Accuracy Assessment in the Manupali-Sawaga-Upper Pulangi River Basin Survey.

Table 61. The summary of the Accuracy Assessment in the Manupali-Sawaga-Upper Pulangi River Basin Survey

	No. of Points	%
Correct	159	39.36
Overestimated	203	50.25
Underestimated	42	10.40
Total	404	100.00

REFERENCES

- Ang M.O., Paringit E.C., et al. 2014. *DREAM Data Processing Component Manual*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- Balicanta L.P., Paringit E.C., et al. 2014. *DREAM Data Validation Component Manual*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- Brunner, G.H.2010a. HEC-RAS River Anaylsis System Hydraulic Reference Manuel. Davis, CA: U.S. Corps of Engineers, Institue for Water Resources, Hydrologic Engineering Center
- Lagmay A.F., Paringit E.C., et al. 2014. *DREAM Flood Modeling Component Manual*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- Lagsa, B. (2017). *Floods hit Lanao del Sur, Bukidnon; Cagayan de Oro still on alert*. Rappler.com.
- Paringit E.C, Balicanta L.P., Ang, M.O., Sarmiento, C. 2017. *Flood Mapping of Rivers in the Philippines Using Airborne Lidar: Methods*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- Sarmiento C., Paringit E.C., et al. 2014. *DREAM Data Acquisition Component Manual*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- UP TCAGP 2016, *Acceptance and Evaluation of Synthetic Aperture Radar Digital Surface Model (SAR DSM) and Ground Control Points (GCP)*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- Province of Bukidnon Brief Information. (2014). *Bukidnon Brief Information*. Retrieved from Official Website of the Province of Bukidnon: <http://www.bukidnon.gov.ph/home/index.php/about-bukidnon/about-bukidnon>

ANNEX

ANNEX 1. Technical Specifications of the LIDAR Sensors used in the Sawaga Floodplain Survey

Table A-1.1 Parameters and Specification of LiDAR Sensors used in the Sawaga Floodplain Survey

Parameter	Specification
Operational envelope (1,2,3,4)	150-5000 m AGL, nominal
Laser wavelength	1064 nm
Horizontal accuracy (2)	1/5,500 x altitude, 1 σ
Elevation accuracy (2)	< 5-20 cm, 1 σ
Effective laser repetition rate	Programmable, 100-500 kHz
Position and orientation system	POS AV™AP50 (OEM)
Scan width (FOV)	Programmable, 0-75°
Scan frequency (5)	Programmable, 0-140 Hz (effective)
Sensor scan product	800 maximum
Beam divergence	0.25 mrad (1/e)
Roll compensation	Programmable, $\pm 37^\circ$ (FOV dependent)
Vertical target separation distance	<0.7 m
Range capture	Up to 4 range measurements, including 1 st , 2 nd , 3 rd , and last returns
Intensity capture	Up to 4 intensity returns for each pulse, including last (12 bit)
Image capture	5 MP interline camera (standard); 60 MP full frame (optional)
Full waveform capture	12-bit Optech IWD-2 Intelligent Waveform Digitizer
Data storage	Removable solid state disk SSD (SATA II)
Power requirements	28 V, 800 W, 30 A
Dimensions and weight	Sensor: 630 x 540 x 450 mm; 65 kg; Control rack: 650 x 590 x 490 mm; 46 kg
Operating Temperature	-10°C to +35°C
Relative humidity	0-95% non-condensing

1 Target reflectivity $\geq 20\%$


2 Dependent on selected operational parameters using nominal FOV of up to 40° in standard atmospheric conditions with 24-km visibility

3 Angle of incidence $\leq 20^\circ$

4 Target size \geq laser footprint 5 Dependent on system configuration

ANNEX 2. NAMRIA Certification of Reference Points Used in the LIDAR Survey

1. MSE-19



Republic of the Philippines
Department of Environment and Natural Resources
NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY

June 24, 2014

CERTIFICATION

To whom it may concern:


This is to certify that according to the records on file in this office, the requested survey information is as follows -

Province: MISAMIS ORIENTAL		
Station Name: MSE-19		
Order: 2nd		
Island: MINDANAO		Barangay: BULUA
Municipality: CAGAYAN DE ORO		
PRS92 Coordinates		
Latitude: 8° 30' 19.11464"	Longitude: 124° 37' 6.46518"	Ellipsoidal Hgt: 11.24200 m.
WGS84 Coordinates		
Latitude: 8° 30' 15.52234"	Longitude: 124° 37' 11.86796"	Ellipsoidal Hgt: 78.72200 m.
PTM Coordinates		
Northing: 940451.853 m.	Easting: 457992.786 m.	Zone: 6
UTM Coordinates		
Northing: 940,474.22	Easting: 678,151.66	Zone: 51


Location Description


MSE-19
The station is located at the intersection of roads going to Cagayan de Oro City, Butuan City and Iligan City. It is situated on the center island between two triangular islands, about 14.5 m E of Bulua marker, about 21m W of black-tiled peace marker, about 10m S of road centerline, and about 3.5m S of the N end of the arc-shaped curb of the island. Station mark is the head of a 4" copper nail set on the center of a 30cm. x 30 cm. x 60cm. concrete monument protruding by about 12cm. above the ground, with inscriptions, MSE-19, 2003 NAMRIA.

Requesting Party:	Engr. Cruz
Purpose:	Reference
OR Number:	8796376 A
T.N.:	2014-1437



RUEL M. BELEN, MNSA
Director, Mapping And Geodesy Branch






CIVIL ENGINEERING

NAMRIA OFFICES
Main - Leron Avenue, Fort Bonifacio, 858 Taguig City, Philippines. Tel. No. (02) 8104811 to 41
Branch - 427 Basilio St. San Nicolas, 1010 Manila, Philippines. Tel. No. (02) 241-3404 to 88
www.namria.gov.ph

ISO 9001:2008 CERTIFIED FOR MAPPING AND GEOSPATIAL INFORMATION MANAGEMENT

Figure A-2.1 MSE-19

2. MSE-20



Republic of the Philippines
Department of Environment and Natural Resources
NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY

July 11, 2014

CERTIFICATION

To whom it may concern:


This is to certify that according to the records on file in this office, the requested survey information is as follows -

Province: MISAMIS ORIENTAL		
Station Name: MSE-20		
Order: 2nd		
Island: MINDANAO		Barangay: LUMBIA
Municipality: CAGAYAN DE ORO		MSL Elevation:
PRS92 Coordinates		
Latitude: 8° 25' 34.65372"	Longitude: 124° 34' 40.03979"	Ellipsoidal Hgt: 182.61260 m.
WGS84 Coordinates		
Latitude: 8° 25' 31.08192"	Longitude: 124° 34' 45.43561"	Ellipsoidal Hgt: 216.44400 m.
PTM / PRS82 Coordinates		
Northing: 931713.893 m.	Easting: 457491.339 m.	Zone: 5
UTM / PRS87 Coordinates		
Northing: 931,733.87	Easting: 677,685.12	Zone: 51


Location Description


MSE-20
The station is located at barangay Lumbia, Cagayan de Oro City. It is situated about 17m S of Km Post 14-47, 10 Km. drive from Cagayan de Oro towards Talakog, and about 7 min. drive from SM mall. The station is in front of Oro Gardens Memorial Park, about 2.3m WNW of center curb, about 4m ESE of road centerline, and about 14m NW of S gate. Station mark is the head of a 4" copper nail, set on the center of a 5cm x 5cm cement pvtly, with inscriptions, MSE-20, 2003 NAMRIA.

Requesting Party:	UP TCAGP / Engr. Christopher Cruz
Purpose:	Reference
OR Number:	8796507 A
T.N.:	2014-1597



RUEL ORLA BECEN, MNSA
Director, Mapping And Geodesy Branch






MAIN OFFICE:
Main: 6000 Avenue, Fort Bonifacio, 054 Taguig City, Philippines. Tel. No. (802) 819-8000 ext. 8111
Branch: 401 Davao City, San Roque, 8000 Davao City, Philippines. Tel. No. (802) 271-2000 ext. 1100
www.namria.gov.ph

ISO 9001:2009 CERTIFIED FOR MAPPING AND GEOSPATIAL INFORMATION MANAGEMENT

Figure A-2.2 MSE-20

3. MSE-3241



Republic of the Philippines
Department of Environment and Natural Resources
NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY

April 18, 2013

CERTIFICATION

To whom it may concern:

This is to certify that according to the records on file in this office, the requested survey information is as follows -


Province: MISAMIS ORIENTAL		
Station Name: MSE-3241		
Island: MINDANAO	Order: 3rd	Barangay: BARANGAY 10 (POB.)
Municipality: CAGAYAN DE ORO CITY (CAPITAL)	PR92 Coordinates	
Latitude: 8° 27' 31.07807"	Longitude: 124° 37' 23.18881"	Ellipsoidal Hgt: 109.46700 m.
WGS84 Coordinates		
Latitude: 8° 27' 27.49608"	Longitude: 124° 37' 28.59687"	Ellipsoidal Hgt: 177.05500 m.
PTM Coordinates		
Northing: 935289.375 m.	Easting: 458499.251 m.	Zone: 6
UTM Coordinates		
Northing: 935,314.39	Easting: 678,684.71	Zone: 61


Location Description

MSE-3241
Is located at the center island along Macapagal Rd., Brgy. 10 (Pob.), Cagayan de Oro City. It is situated between Sungle Bldg. and Super Mart Mall, about 25 m. facing the mall entrance. Mark is the head of a 4 in. copper nail embedded on a 25 cm. x 25 cm. concrete block, with inscriptions "MSE-3241 2007 NAMRIA".

Requesting Party:	UP DREAMI Malchor Nery
Purpose:	Reference
OR Number:	3943548 B
T.N.:	2013-0311

RUEL OM. BELEN, MNSA
Director, Mapping and Geodesy Department






NAMRIA OFFICE:
Main - Cavite Avenue, Fort Bonifacio, Taguig City, Philippines. Tel. No. (800) 810-4001 to 41
Branch - 402 Bayabas St., San Nicolas, 1010 Manila, Philippines. Tel. No. (602) 741-3494 to 95
www.namria.gov.ph

Figure A-2.3 MSE-3241

4. MSE-3340



Republic of the Philippines
Department of Environment and Natural Resources
NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY

July 11, 2014

CERTIFICATION

To whom it may concern:


This is to certify that according to the records on file in this office, the requested survey information is as follows -

Province: MISAMIS ORIENTAL		
Station Name: MSE-3340		
Order: 3rd		
Island: MINDANAO		Barangay: AGUSAN
Municipality: CAGAYAN DE ORO CITY (CAPITAL)	PRS92 Coordinates	MSL Elevation:
Latitude: 8° 29' 23.43073"	Longitude: 124° 44' 11.52834"	Ellipsoidal Hgt: 5.89600 m.
WGS84 Coordinates		
Latitude: 8° 29' 19.85261"	Longitude: 124° 44' 18.93252"	Ellipsoidal Hgt: 73.80100 m.
PTM / PRS92 Coordinates		
Northing: 938730.493 m.	Easting: 470891.591 m.	Zone: 5
UTM / PRS92 Coordinates		
Northing: 938,819.85	Easting: 651,159.99	Zone: 51


Location Description

MSE-3340
MSE 3340 is located inside the Agusan Barangay Plaza, Agusan, Cagayan de Oro City. Mark is the rubber engraved with bronze nail at the center of a concrete monuments with inscription "MSE 3340, 2008 LMS 10" on top.


Requesting Party: UP TCAGP / Engr. Christopher Cruz
Purpose: Reference
OR Number: 8796507 A
T.N.: 2014-1598



RUBI D.M. BELEN, MNSA
Director, Mapping And Geodesy Branch



0 0 2 7 1 2 5 1 6 1 5 0 0 3 1



REGIONAL OFFICES:
Main: Linao-Avenida, Port Bantao, 904 Tagay City, Philippines. Tel. No. (032) 819-4311 to 43
Branch : 421 Bantao St. San Nicolas, 910 Marikina, Philippines, Tel. No. 8822-091-3494 to 98
www.nma.gov.ph

ISO 9001: 2008 CERTIFIED FOR MAPPING AND GEOSPATIAL INFORMATION MANAGEMENT

Figure A-2.4 MSE-3340

5. BKN-475



Republic of the Philippines
Department of Environment and Natural Resources
NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY

February 11, 2015

CERTIFICATION

To whom it may concern:

This is to certify that according to the records on file in this office, the requested survey information is as follows -

Province: BUKIDNON		
Station Name: BKN-475		
Order: 2nd		
Barangay: AGLAYAN		
MSL Elevation:		
<i>PRS92 Coordinates</i>		
Latitude: 8° 3' 25.94887"	Longitude: 125° 7' 58.68680"	Ellipsoidal Hgt: 404.31400 m.
<i>WGS84 Coordinates</i>		
Latitude: 8° 3' 22.52096"	Longitude: 125° 8' 4.12506"	Ellipsoidal Hgt: 473.98000 m.
<i>PTM / PRS92 Coordinates</i>		
Northing: 890860.244 m.	Easting: 514656.29 m.	Zone: 5
<i>UTM / PRS92 Coordinates</i>		
Northing: 891,179.54	Easting: 735,073.76	Zone: 51

Location Description

BKN-475
From Malaybalay City Proper, travel along the Nat'l. Road going to Valencia City until reaching Brgy. Aglayan. Station is located inside the DPWH compound. Mark is the head of a 4 in. copper nail embedded on a 30 cm. x 30 cm. concrete block, with inscriptions "BKN-475 2007 NAMRIA".

Requesting Party: **AB Surveying & Dev't.**
Purpose: **Reference**
OR Number: **8077642 I**
T.N.: **2015-0286**



RUEL M. BELEN, MNSA
Director / Mapping And Geodesy Branch



9 9 0 2 1 1 2 0 1 5 1 4 0 1 2 4




NAMRIA OFFICES:
Main - Lantion Avenue, Fort Bonifacio, 188 Taguig City, Philippines. Tel. No. (02) 810-8811 to 41
Branch - 421 Batawa St. San Nicolas, 1010 Manila, Philippines. Tel. No. (02) 291-3434 to 66
www.namria.gov.ph

ISO 9001:2008 CERTIFIED FOR MAPPING AND GEOSPATIAL INFORMATION MANAGEMENT

Figure A-2.5 BKN-475

6. BKN-478



Republic of the Philippines
Department of Environmental and Natural Resources
NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY

November 14, 2016

CERTIFICATION

To whom it may concern:


This is to certify that according to the records on file in this office, the requested survey information is as follows -

Province: BUKIDNON		
Station Name: BKN-478		
Order: 3rd		
Island: MINDANAO	Barangay: SINAYAWAN	MSL Elevation:
Municipality: CITY OF VALENCIA	PRSS2 Coordinates	
Latitude: 7° 52' 39.33095"	Longitude: 125° 8' 33.26511"	Ellipsoidal Hgt: 302.83700 m.
WGS84 Coordinates		
Latitude: 7° 52' 35.94157"	Longitude: 125° 8' 38.71964"	Ellipsoidal Hgt: 372.88500 m.
PTM / PRSS2 Coordinates		
Northing: 871017.702 m.	Easting: 515721.891 m.	Zone: 5
UTM / PRSS2 Coordinates		
Northing: 871,315.75	Easting: 734,235.88	Zone: 51


Location Description

BKN-478 is located beside the basketball court of Purok 6, Brgy. Sinayawan. Mark is the head of a 4 in. copper nail embedded on a 30 cm. x 30 cm. concrete block, with inscriptions "BKN-478 2007 NAMRIA".


Requesting Party:	Phil Lidar 1
Purpose:	Reference
CR Number:	FREE ISSUE
T.N.:	2016-2056



RUEL D.M. BELEN, MNRA
Director, Mapping And Geodesy Branch



0 9 1 1 4 0 0 1 1 4 0 3 2



ISO 9001:2008 CERTIFIED FOR MAPPING AND GEOSPATIAL INFORMATION MANAGEMENT

NAMRIA OFFICES:
 Main: Linao Avenue, Cor Bonifacio, McKinley Town Center, Taguig City, Philippines. Tel. No: (632) 870-8821 to 88
 Branch: 401 Bonifacio St. San Antonio, 9118 Marikina, Philippines. Tel. No: (02) 811-4384 to 85
www.namria.gov.ph

Figure A-2.6 BKN-478

7. BK-56

 Republic of the Philippines
Department of Environment and Natural Resources
NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY

February 11, 2015

CERTIFICATION

To whom it may concern:

This is to certify that according to the records on file in this office, the requested survey information is as follows -

Province: BUKIDNON Station Name: BK-56		
Island: Mindanao	Municipality: MALAYBALAY	Barangay: KALASUNGAY
Elevation: 656.6448 +/- 0.00	Order: 1st Order	Datum: Mean Sea Level
Latitude:	Longitude:	

Location Description

BK-56
Station is located at the west post of the welcome arc of Malaybalay, and about 7m. from the centerline of the highway. Mark is the head of 4" copper nail set on a drilled hole and cemented on top of a 15x15 cm. cement pty with the inscription "BMBK-56, 2008, NAMRIA".

Requesting Party: **AB Surveying & Dev't.**
Purpose: **Reference**
OR Number: **8077642 I**
T.N.: **2015-0285**


RUEL M. BELEN, MNSA
Director, Mapping And Geodesy Branch


9 9 0 2 1 1 2 0 1 3 1 3 5 9 4 1

 **NAMRIA OFFICE:**
Main: Luning Avenue, Fort Bonifado, 1656 Taguig City, Philippines. Tel. No. (832) 810-8821 to 41
Branch - 421 Baraca St. San Nicolas, 1010 Manila, Philippines. Tel. No. (532) 241-3404 to 98
www.namria.gov.ph
ISO 9001: 2008 CERTIFIED FOR MAPPING AND GEOSPATIAL INFORMATION MANAGEMENT

Figure A-2.7 BK-56

ANNEX 3. The LIDAR Survey Team Composition

Table A-3.1 The LiDAR Survey Team Composition

Data Acquisition Component Sub-Team	Designation	Name	Agency / Affiliation
PHIL-LIDAR 1	Program Leader	ENRICO C. PARINGIT, D.ENG	UP-TCAGP
Data Acquisition Component Leader	Data Component Project Leader – I	ENGR. CZAR JAKIRI SARMIENTO	
Survey Supervisor	Chief Science Research Specialist (CSRS)	ENGR. CHRISTOPHER CRUZ	
	Supervising Science Research Specialist (Supervising SRS)	LOVELY GRACIA ACUÑA	
		LOVELYN ASUNCION	
FIELD TEAM			
LiDAR Operation	Senior Science Research Specialist (SSRS)	JASMINE ALVIAR	UP-TCAGP
		PAULINE ARCEO	
	Research Associate (RA)	GRACE SINADJAN	
		ENGR. IRO NIEL ROXAS	
		REGINA FELISMINO	
		NICHOLAS ILEJAY	
Ground Survey, Data Download and Transfer	RA	LANCE KERWIN CINCO	
		BRYLLE DE CASTRO	
LiDAR Operation	Airborne Security	SSG. LEE JAY PUNZALAN	PHILIPPINE AIR FORCE (PAF)
	Pilot	CAPT. JEFFREY JEREMY ALAJAR	ASIAN AEROSPACE CORPORATION (AAC)
		CAPT. CESAR ALFONSO III	
		CAPT. ANTON DAYO	
		CAPT. ERNESTO SAYSAY JR.	

ANNEX 4. Data Transfer Sheet for Sawaga Floodplain

DATA TRANSFER SHEET
05/10/2014 @ Northern Mindanao *Outgoing*

DATE	FLIGHT NO.	MISSION NAME	SENSOR	RAW LAS		LOGS(MB)	PGS	RAM MESSAGES	MISSION LOG (LIDAR) LOGS	RANGE	DIGITIZER	BASE STATION(S)		OPERATOR LOGS (PDF) (00)	FLIGHT PLAN		SERVER LOCATION
				Output LAS	KML (points)							TYPE STATION(S)	Date info (pdf)		Altitude	KML	
5/22/2014	1407P	1BLK07B142A	PEGASUS	1.8	1042	0.01	201	21.8	771	13.1	NA	3.19	1K5	1KB	40	NA	Z:\Airborne_Raw\1407P
5/23/2014	1501P	1BLK07C143A	PEGASUS	3	1021	0.1	271	22.3	529	20.5	NA	7.01	1K0	1KB	5656	NA	Z:\Airborne_Raw\1501P
5/24/2014	1505P	1BLK57BC144A	PEGASUS	2.25	709	0	212	45.7	240	21.6	NA	7.05	1K0	1KB	37	NA	Z:\Airborne_Raw\1505P
5/25/2014	1509P	1RDXE146A	PEGASUS	2.4	360	11.3	254	30.5	34-699	26.2	NA	4.90	1K1	1KB	5543	NA	Z:\Airborne_Raw\1509P
5/27/2014	1517P	1RXE147A	PEGASUS	2.74	1407	12	265	NA	NA	27.7	NA	9.7	1K2	1KB	7577	NA	Z:\Airborne_Raw\1517P
5/28/2014	1521P	1RXC148A	PEGASUS	2.39	480	12	252	NA	NA	26	NA	5.54	1K0	1KB	52	NA	Z:\Airborne_Raw\1521P

<p>Received from</p> <p>Name: <u>C. Jaraman</u></p> <p>Position: <u>ed</u></p> <p>Signature: <u>[Signature]</u></p>	<p>Received by</p> <p>Name: <u>JORDA PRIETO</u></p> <p>Position: <u>SSRS</u></p> <p>Signature: <u>[Signature]</u> 6/10/2014</p>
---	--

Figure A-4.1 Transfer Sheet for Sawaga Floodplain - A

DATA TRANSFER SHEET
6/28/2014(Northern Mindanao - ready)

DATE	FLIGHT NO.	MISSION NAME	SENSOR	RAW LAS		LOGS (MB)	POS	RAW IMAGES/CASE	MISSION LOGS (FILES/CASE)	RANGE	DIGITIZER	BASE STATION(S)		OPERATOR LOGS (FILE/CASE)	FLIGHT PLAN		SERVER LOCATION
				Output LAS	KNL (swath)							BASE STATION(S)	Base info (file)		Actual	ICML	
6/8/2014	1565P	1BLK71B159A	Pegasus	NA	16	8.93	160	NA	NA	13.3	NA	7.75	1KB	1KB	36	NA	Z:\Airborne_Raw
6/9/2014	1569P	1BLKRKE160A	Pegasus	4.18	832	15.5	290	898	52	38.5	NA	10	1KB	1KB	85	NA	Z:\Airborne_Raw
6/16/2014	1587P	1BLKRKE167A	Pegasus	2.18	332	10.5	237	NA	NA	21.3	NA	7.52	1KB	1KB	68	NA	Z:\Airborne_Raw
6/19/2014	1603P	1RXS170A	Pegasus	3.16	526	11.2	258	453	308	22.1	NA	7.07	1KB	1KB	77/76	NA	Z:\Airborne_Raw
6/20/2014	1613P	1BLK71G171A	Pegasus	3.44	177	13.7	258	873	487	33.2	NA	5.92	1KB	1KB	46	NA	Z:\Airborne_Raw
6/23/2014	1625P	1BLK57BC174A	Pegasus	3.09	1112	11.7	212	903	415	29.4	81.6	4.97	1KB	1KB	52/56	NA	Z:\Airborne_Raw
6/24/2014	1629P	1BLKRKES175A	Pegasus	2.78	370	10.7	187	363	288	26.1	NA	4.45	1KB	1KB	73	NA	Z:\Airborne_Raw
6/27/2014	1641P	1BLK68A178A	Pegasus	2.94	1995	12.6	289	574	386	28.9	67.2	7.7	1KB	1KB	65/65/60/58	NA	Z:\Airborne_Raw
6/27/2014	1643P	1BLK67ABS178B	Pegasus	5.92	95	4.33	119	NA	NA	5.65	NA	7.7	1KB	1KB	48	NA	Z:\Airborne_Raw
6/28/2014	1645P	1BLK71C179A	Pegasus	2.84	NA	11.4	242	518	375	27.4	NA	6.25	1KB	1KB	60/68	NA	Z:\Airborne_Raw



<p>Received from</p> <p>Name <u>TIN ANDAYA</u></p> <p>Position <u>RA</u></p> <p>Signature </p>	<p>Received by</p> <p>Name <u>JONIA PRIETO</u></p> <p>Position <u>SRS</u></p> <p>Signature <u>7/28/14</u> </p>
---	---

Figure A-4.2 Transfer Sheet for Sawaga Floodplain - B

DATA TRANSFER SHEET (8/05/2014)(Northern Mindanao - ready)																		
DATE	FLIGHT NO.	MISSION NAME	SENSOR	RAW LAS		LOGS(MB)	SHP	POS	RAW IMAGE(SIZE)	MISSION LOG FILE(SIZE LOGS)	RANGE	CONTIGER	BASE STATION(S)		OPERATED LOGS (M/LOG)	FLIGHT PLAN		SERVER LOCATION
				Output L/S	KML (small)								BASE STATION(S)	Base file (Kb)		Actual	KML	
7/3/2014	1665P	1BLK715186A	Pegasus	806	93	4.69	94.5	160	NA	NA	6.77	NA	5.94	903	1KB	36	NA	Z:\Arbans_Raw
7/5/2014	1673P	1BLK715186A	Pegasus	1.06	379	7.58	335	160	20.4	167	12.5	27.8	5.00	903	1KB	6284	NA	Z:\Arbans_Raw
7/5/2014	1677P	1BLK715187A	Pegasus	806	68	5.33	188	141	11.2	96	7.76	NA	4.90	903	1KB	130	NA	Z:\Arbans_Raw
7/8/2014	1685P	1BLK715189A	Pegasus	2.31	515	11	578	242	37	269	22.4	47.4	4.99	903	1KB	184	NA	Z:\Arbans_Raw
7/8/2014	1687P	1BLK715190B	Pegasus	940	79	4.81	170	130	NA	NA	7.47	NA	4.99	903	1KB	NA	NA	Z:\Arbans_Raw
7/9/2014	1689P	1BLK715190A	Pegasus	2.66	156	12.0	740	267	NA	NA	27.1	NA	3.69	903	1KB	196207	NA	Z:\Arbans_Raw
7/10/2014	1693P	1RXES191A	Pegasus	1.70	551	8.11	448	176	NA	NA	15.9	NA	4.08	903	1KB	53	NA	Z:\Arbans_Raw

<p>Received from</p> <p>Name <u>TIN ANDRINA</u></p> <p>Position <u>ILA</u></p> <p>Signature <u>[Signature]</u></p>	<p>Received by</p> <p>Name <u>JOIDA F. PRIETO</u></p> <p>Position <u>SECS</u></p> <p>Signature <u>[Signature]</u> 8/6/14</p>
--	---

Figure A-4.3 Transfer Sheet for Sawaga Floodplain - C

DATA TRANSFER SHEET
BUKIDNON 11/14/2016

DATE	FLIGHT NO.	MISSION NAME	SENSOR	RAW LAS		LOGS	POS	RAW IMAGES/CAS	MISSION LOG FILE/CAS LOGS	RANGE	DIGITIZER	BASE STATION(S)		OPERATOR LOSS (DPLDG)	FLIGHT PLAN		SERVER LOCATION
				Output LAS	KML (swath)							BASE STATION(S)	Base Info (M)		Actual	KML	
October 23, 2016	23486P	1BKND297 A	PEGASUS	1.53	215	8.14	208	NA	NA	13.2	NA	210	1KB	1KB	1.29	NA	Z:\D\CRAW DATA
October 24, 2016	23488P	1BKND29 8A	PEGASUS	2.11	363	11.4	255	NA	NA	21	NA	272	1KB	1KB	457	NA	Z:\D\CRAW DATA

Received from

Name R. P. Santos
Position RA
Signature [Signature]

Received by

Name Ac. Bayat
Position SSPS
Signature Ac Bayat 11/16/16

Figure A-4.4 Transfer Sheet for Sawaga Floodplain - D

DATA TRANSFER SHEET
BUKENDON (11/07/2016)

DATE	FLIGHT NO.	MISSION NAME	SENSOR	RAW LAS		LOGS	POS	RAW IMAGES/CAS	MISSION LOG FILE/CAS LOGS	RANGE	DIGITIZER	BASE STATION(S)		OPERATOR LOGS (OP LOG)	FLIGHT PLAN		SERVER LOCATION
				Output LAS	KML (swath)							BASE STATION(S)	Base Info (SAC)		Actual	KML	
October 25, 2016	23492P	1BKNDL299A	PEGASUS	2.2 GB	28Kb	9.91 MB	230 MB	NA	NA	20.9 GB	NA	217 MB	9KB	NA	NA	NA	Z:\GAC\RAW\DATA

Received from

Name R. PUNTO
 Position RA
 Signature 

Received by


Name J. Bongat
 Position SSRS
 Signature 

Figure A-4.5 Transfer Sheet for Sawaga Floodplain - E

DATA TRANSFER SHEET
BUKIDNON 11/14/2016

DATE	FLIGHT NO.	MISSION NAME	SENSOR	RAW LAS		LOGS	POS	RBR IMAGE/CAS	MISSION LOG FILE/CAS LOGS	RANGE	DIGITIZER	BASE STATION(S)		OPERATOR LOGS (DPLOG)	FLIGHT PLAN		SERVER LOCATION
				Output LAS	KML (swath)							BASE STATION(S)	Base Info (HW)		Actual	KML	
November 06, 2016	23516P	1BKNF311A	PEGASUS	2.41	NA	11.9	269	NA	NA	22.5	NA	283	1KB	1KB	715	NA	Z:\DAC\RAW DATA
November 06, 2016	23518P	1BKNF311B	PEGASUS	973	NA	4.96	105	NA	NA	8.86	NA	283	1KB	1KB	857	NA	Z:\DAC\RAW DATA
November 07, 2016	23520P	1BKNF312A	PEGASUS	2.63	NA	13.1	274	NA	NA	24.5	NA	198	1KB	1KB	595	59.8	Z:\DAC\RAW DATA
November 08, 2016	23524P	1BKNF313A	PEGASUS	2.91	NA	12.1	237	NA	NA	27	NA	141	1KB	1KB	595	12.8	Z:\DAC\RAW DATA

23524P

Received from

Name: R. P. WATS
 Position: RP
 Signature: [Signature]

Received by

Name: AC Bongat
 Position: SSRS
 Signature: [Signature] 11/14/16

Figure A-4.6 Transfer Sheet for Sawaga Floodplain - F

DATA TRANSFER SHEET
BUNDNON 11/21/2016

DATE	FLIGHT NO.	MISSION NAME	SENSOR	RAW LAS		LOGS	POS	RAW IMAGES/CASI	MISSION LOG FILE/CASI LOGS	RANGE	DIGITIZER	BASE STATION(S)		OPERATOR LOGS (JOB LOG)	FLIGHT PLAN		SERVER LOCATION
				Output LAS	KML (swath)							BASE STATION(S)	Base Info (xtd)		Actual	KML	
November 10, 2016	23534P	1BKNG31 5A	PEGASUS	1.61	NA	8	255	NA	NA	16.6	NA	136	1KB	1KB	NA	NA	Z:\DAC\RAW DATA
November 11, 2016	23536P	1BKND3 16A	PEGASUS	2.45	NA	16.6	236	NA	NA	22.9	NA	146	1KB	1KB	595	5KB	Z:\DAC\RAW DATA
November 12, 2016	23540P	1BKNE317 A	PEGASUS	2.3	NA	9.76	263	NA	NA	21.4	NA	131	1KB	1KB	646	NA	Z:\DAC\RAW DATA
November 13, 2016	23544P	1BKNE318 A	PEGASUS	2.61	NA	10.8	230	NA	NA	24.3	NA	299	1KB	1KB	585	NA	Z:\DAC\RAW DATA
November 13, 2016	23546P	1BKNG31 8B	PEGASUS	1.95	NA	9.55	262	NA	NA	15.1	NA	299	1KB	1KB	554	NA	Z:\DAC\RAW DATA
November 14, 2016	23548P	1BKNEF31 9A	PEGASUS	2.85	NA	12	268	NA	NA	26.7	NA	208	1KB	1KB	554	NA	Z:\DAC\RAW DATA
November 15, 2016	23552P	1BK64A3 20A	PEGASUS	2.1	NA	10.5	261	NA	NA	29.6	NA	131	1KB	1KB	174	NA	Z:\DAC\RAW DATA

Received from
 Name R. P. WNTD
 Position RA
 Signature [Signature]

Received by
 Name A. Bongat
 Position SRS
 Signature [Signature] 11/24/2016

Figure A-4.7 Transfer Sheet for Sawaga Floodplain - G

ANNEX 5. Flight logs for the flight missions


1. Flight Log for Mission 1517P

Flight Log No.: 1517P

DREAM Data Acquisition Flight Log


1 LIDAR Operator: <u>I. Roxas</u>	2 ALTM Model: <u>Pentax</u>	3 Mission Name: <u>RXE143A</u>	4 Type: <u>VFR</u>	5 Aircraft Type: <u>Cessna T206H</u>	6 Aircraft Identification: <u>RP-C902</u>
7 Pilot: <u>J. Alajar</u>	8 Co-Pilot: <u>C. Alfonso</u>	9 Route: <u>CDO</u>			
10 Date: <u>May 27, 2014</u>	12 Airport of Departure (Airport, City/Province): <u>CDO</u>	12 Airport of Arrival (Airport, City/Province): <u>CDO</u>			
13 Engine On: <u>0702H</u>	14 Engine Off: <u>1125H</u>	15 Total Engine Time: <u>4+23</u>	16 Take off:	17 Landing:	18 Total Flight Time:
19 Weather: <u>very cloudy</u>					
20 Remarks: <p style="text-align: center;">surveyed half of RXD and half of RXE at 800m, 1000m then 700m; camera stylus malfunctioned</p>					
21 Problems and Solutions:					

Acquisition Flight Approved by




Signature over Printed Name
(End User Representative)

Acquisition Flight Certified by




Signature over Printed Name
(IAF Representative)

Pilot-in-Command




Signature over Printed Name

Lidar Operator



Signature over Printed Name



DREAM
Disaster Risk and Exposure Assessment for Mitigation

Figure A-5.1 Flight Log for Mission 1517P


2. Flight Log for Mission 1569P

Flight Log No. *1569P*

See Also Data Acquisition Flight Log


1. Pilot Operator: <i>A. Brown</i>	2. Aircraft Model/Type: <i>AS350</i>	3. Aircraft Name (if applicable): <i>AS350</i>	4. Date (YYYY):	5. Aircraft Type (General Category):	6. Aircraft Identification (if applicable):
7. Pilot: <i>A. Brown</i>	8. Co-pilot: <i>J. Smith</i>	9. Route: <i>AS350 - AS350</i>	10. Airport of Arrival (airport, City/Province):		
11. Date: <i>June 14, 2014</i>	12. Airport of Departure (airport, City/Province): <i>AS350</i>		13. Airport of Arrival (airport, City/Province): <i>AS350</i>		14. Total Flight Time:
15. Engine On: <i>08:00</i>	16. Engine Off: <i>11:00</i>	17. Fuel Engine Burn: <i>4.5</i>	18. Take off:	19. Landing:	
13. Weather: <i>cloudy</i>					
20. Remarks: <i>Mission successful; gaps due to fuel</i>					
21. Problems and Solutions: <i>some water fuel - resolved</i>					

Acquisition Flight Approved By




Signature over Printed Name
(Not Your Representative)

Acquisition Flight Certified By




Signature over Printed Name
(Not Representative)

Flight Approved




Signature over Printed Name

Laboratory



Signature over Printed Name



DREAM
Disaster Risk and Exposure Assessment for Mitigation

Figure A-5.2 Flight Log for Mission 1569P


3. Flight Log for Mission 1597P

Flight Log No: 1597P

GENERAL Data Acquisition Flight Log


1. DDAE Operator: <i>D. Francisco</i>	2. ALTM Master: <i>Francisco</i>	3. Mission Name: <i>ARC - 001</i>	4. Type: <i>VH</i>	5. Aircraft Type: <i>CS-440A</i>	6. Aircraft Registration: <i>AF-002 12</i>
7. Pilot: <i>D. Francisco</i>	8. Co-Pilot: <i>J. Lopez</i>	9. Route: <i>002 - 000</i>	10. Airport of Arrival (Airport, City/Township):		
11. Airport of Departure: <i>000</i>		12. Airport of Arrival (Airport, City/Township): <i>000</i>			
13. Engine On: <i>08:57.0</i>	14. Engine Off: <i>12:57.0</i>	15. Total Engine Hours: <i>4.0</i>	16. Fuel Used:	17. Landing:	18. Total Flight Time:
19. Remarks:					
<i>Mission successful; filled gaps in RVE</i>					
20. Problems and Solutions:					

Supervisor Flight Approved by




Signature (Supervisor Name)
(Full Name Representation)

Acquisition Flight Certified by




Signature (Pilot Name)
(Full Name Representation)

Flight Commander




Signature (Flight Commander Name)

Lidar Operator



Signature (Lidar Operator Name)



DREAM
Discover Risk and Exposure Assessment for Mitigation

Figure A-5.3 Flight Log for Mission 1597P


4. Flight Log for Mission 1629P

Flight Log Mission 1629P

DREAM Data Acquisition Flight Log


1. Operator Name: <i>G. Anderson</i>	2. Altitude (feet): <i>5000</i>	3. Mission Number: <i>1629P</i>	4. Date: <i>2010-08-20</i>
5. Pilot: <i>G. Anderson</i>	6. Co-Pilot: <i>J. Smith</i>	7. Route: <i>See map</i>	8. Aircraft Type: <i>AS350</i>
9. Date: <i>Aug 20, 2010</i>	10. Airport / Region: <i>AS350</i>	11. Airport of Arrival (Airport, City/Province): <i>AS350</i>	
12. Flight In: <i>07:00</i>	13. Flight Out: <i>10:00</i>	14. Total Flight Time: <i>3:00</i>	15. Fuel Used: <i>100L</i>
16. Weather: <i>partly cloudy</i>			
17. Remarks: <i>Mission successful at 1000 ft</i>			
18. Problems and Solutions: <i>Left engine problem before flight</i>			

Acquisition Flight Initiated By




Signature over Printed Name
(Not Representative)

Acquisition Flight Certified By




Signature over Printed Name
(Not Representative)

Pilot (Co-pilot)




Signature over Printed Name

Site Operator



Signature over Printed Name

DREAM 

Disaster Risk and Exposure Assessment for Irrigation

Figure A-5.4 Flight Log for Mission 1629P


5. Flight Log for Mission 1693P

Flight Log No. 1693P

AVIATION Data Applicable Flight Log


1. Pilot Operator: <u>J. Alvarez</u>	2. ALTIM Model: <u>Ply</u>	3. Mission Number: <u>1693P/1694</u>	4. Type: <u>VII</u>	5. Aircraft Type: <u>Cessna 441</u>	6. Aircraft Identification: <u>1693-002</u>
7. Date: <u>July 15, 2017</u>	8. Time: <u>7:00am</u>	9. Base: <u>CGO</u>	10. Airport of Arrival (Airport ID reference):		
11. Date: <u>July 15, 2017</u>	12. Airport of Departure: <u>CGO</u>	13. Airport of Arrival: <u>CGO</u>	14. Take off: <u>6:55</u>	15. Landing:	16. Total Flight Time:
17. Engine On: <u>09:15</u>	18. Engine Off: <u>12:25</u>	19. Total Engine Time: <u>3+11</u>			
20. Weather: <u>Fair</u>					
21. Remarks: filled gaps in Rxis; started at 1200m then 1400m over Rxis est.					
22. Problems and Solutions:					

Acquisition Flight Approved by




Signature over Printed Name
(MFR Representative)

Acquisition Flight Certified by




Signature over Printed Name
(MFR Representative)

Pilot in Command




Signature over Printed Name

Pilot Operator



Signature over Printed Name

DREAM 

Disaster Risk and Exposure Assessment for Mitigation

Figure A-5.5 Flight Log for Mission 1693P

6. Flight Log for Mission 23486P

PHIL-LIDAR 1 Data Acquisition Flight Log						Flight Log No.: 23486P
1 UDAR Operator: J. Alvar	2 ALTM Model: <i>Pegasus</i>	3 Mission Name: <i>100% 27A</i>	4 Type: VFR	5 Aircraft Type: Cessna T206H	6 Aircraft Identification: <i>EP-cator</i>	
7 Pilot: <i>A. Tays</i>	8 Co-Pilot: <i>K. Chi</i>	9 Route: <i>Laguindingan - Laguindingan</i>				
10 Date: <i>Oct 23, 2016</i>	12 Airport of Departure (Airport, City/Province): <i>Laguindingan</i>		11 Airport of Arrival (Airport, City/Province): <i>Laguindingan</i>			
13 Engine On: <i>1155H</i>	14 Engine Off: <i>1534H</i>	15 Total Engine Time: <i>3+41</i>	16 Take off: <i>1300A</i>	17 Landing: <i>1534H</i>	18 Total Flight Time: <i>3+31</i>	
19 Weather: <i>heavy build up w/ ppt</i>						
20 Flight Classification			21 Remarks			
20.a Billable	20.b Non Billable	20.c Others	<i>visual closing in target areas; transferred to Manila Futch (Capitan W); surveyed few at 1300m MSL</i>			
<input checked="" type="checkbox"/> Acquisition Flight <input type="checkbox"/> Ferry Flight <input type="checkbox"/> System Test Flight <input type="checkbox"/> Calibration Flight	<input type="checkbox"/> Aircraft Test Flight <input type="checkbox"/> AAC Admin Flight <input type="checkbox"/> Others: _____	<input type="checkbox"/> LIDAR System Maintenance <input type="checkbox"/> Aircraft Maintenance <input type="checkbox"/> Phil-LIDAR Admin Activities				
22 Problems and Solutions						
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____						
Acquisition Flight Approved by <i>[Signature]</i> Signature over Printed Name (EOP User Representative)	Acquisition Flight Certified by <i>[Signature]</i> Signature over Printed Name (PAF Representative)	Pilot-in-Command <i>[Signature]</i> Signature over Printed Name	UDAR Operator <i>[Signature]</i> Signature over Printed Name	Aircraft Mechanic/ LIDAR <i>[Signature]</i> Signature over Printed Name		

Figure A-5.6 Flight Log for Mission 23486P

7. Flight Log for Mission 23488P

Flight Log No: 23488P

PHIL-LIDAR 1 Data Acquisition Flight Log					
1 LIDAR Operator: <i>K. Quinsada</i>	2 ALTM Model: <i>Pegasus</i>	3 Mission Name: <i>Boys 240A</i>	4 Type: <i>VFR</i>	5 Aircraft Type: <i>Cessna T206H</i>	6 Aircraft Identification: <i>RP-C9122</i>
7 Pilot: <i>A. Pango</i>	8 Co-Pilot: <i>K. Quinsada</i>	9 Route: <i>Laguindingan - Laguidigan</i>			
10 Date: <i>Oct 24, 2014</i>	12 Airport of Departure (Airport, City/Province): <i>Laguindingan</i>		11 Airport of Arrival (Airport, City/Province): <i>Laguindingan</i>		
13 Engine On: <i>0647</i>	14 Engine Off: <i>1040H</i>	15 Total Engine Time: <i>4+29</i>	16 Take off: <i>0616 H</i>	17 Landing: <i>1035 H</i>	18 Total Flight Time: <i>4+19</i>
19 Weather: <i>partly cloudy to heavy build up</i>					
20 Flight Classification			21 Remarks		
20.a Billable <input checked="" type="checkbox"/> Acquisition Flight <input type="checkbox"/> Ferry Flight <input type="checkbox"/> System Test Flight <input type="checkbox"/> Calibration Flight			20.b Non Billable <input type="checkbox"/> Aircraft Test Flight <input type="checkbox"/> AAC Admin Flight <input type="checkbox"/> Others: _____		
			20.c Others <input type="checkbox"/> LIDAR System Maintenance <input type="checkbox"/> Aircraft Maintenance <input type="checkbox"/> Phil-LIDAR Admin Activities		
21 Remarks: <i>Cloudy/heavy build up over target area, surveyed Tagulayan watershed at 1700 MSL</i>					
22 Problems and Solutions					
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____					
Acquisition Flight Approved by [Signature] Signature over Printed Name (End User Representative)		Acquisition Flight Certified by [Signature] Signature over Printed Name (PAP Representative)		Pilot-in-Crew and [Signature] Signature over Printed Name	
		LIDAR Operator [Signature] Signature over Printed Name		Aircraft Mechanic/ LIDAR [Signature] Signature over Printed Name	

Figure A-5.7 Flight Log for Mission 23488P

8. Flight Log for Mission 23492P

PHIL-LIDAR 1 Data Acquisition Flight Log						Flight Log No: 23492P
1 LIDAR Operator: <i>K. Gaisardo</i>	2 ALTM Model: <i>Pearson</i>	3 Mission Name: <i>BANE 200A</i>	4 Type: <i>VFR</i>	5 Aircraft Type: <i>Cessna T200H</i>	6 Aircraft Identification: <i>PP-C9102</i>	
7 Pilot: <i>A. Paga</i>	8 Co-Pilot: <i>K. Chiu</i>	9 Route: <i>Laguindingan - Laguindingan</i>				
10 Date: <i>Oct 25, 2019</i>	12 Airport of Departure (Airport, City/Province): <i>Laguindingan</i>	11 Airport of Arrival (Airport, City/Province): <i>Laguindingan</i>				
13 Engine On: <i>0620H</i>	14 Engine Off: <i>1025H</i>	15 Total Engine Time: <i>4:05</i>	16 Take off: <i>0917H</i>	17 Landing: <i>1030H</i>	18 Total Flight Time: <i>4:13</i>	
19 Weather: <i>partly cloudy to cloudy</i>						
20 Flight Classification			21 Remarks			
20.a Billable	20.b Non Billable	20.c Others	<i>Surveyed BANE @ 1500m MSL</i>			
<input checked="" type="checkbox"/> Acquisition Flight <input type="checkbox"/> Ferry Flight <input type="checkbox"/> System Test Flight <input type="checkbox"/> Calibration Flight	<input type="checkbox"/> Aircraft Test Flight <input type="checkbox"/> AAC Admin Flight <input type="checkbox"/> Others: _____	<input type="checkbox"/> LIDAR System Maintenance <input type="checkbox"/> Aircraft Maintenance <input type="checkbox"/> Phil-LIDAR Admin Activities				
22 Problems and Solutions						
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____						
Acquisition Flight Approved by Technician <i>[Signature]</i> Signature over Printed Name (End User Representative)	Acquisition Flight Certified by <i>[Signature]</i> SSG WALTERS MPA Signature over Printed Name (PAF Representative)	Pilot-in-Command <i>[Signature]</i> ANTHONY DAYO Signature over Printed Name	LIDAR Operator <i>[Signature]</i> Ken Gaisardo Signature over Printed Name	Aircraft Mechanic/ LIDAR <i>[Signature]</i> Signature over Printed Name		

Figure A-5.8 Flight Log for Mission 23492P

9. Flight Log for Mission 23516P





Phil-LIDAR 1 Data Acquisition Flight Log						Flight Log No.: 23516P
1 LIDAR Operator: F. JULIAN	2 Alt Model: PC64005	3 Mission Name: MANUPAL	4 Type: VPR	5 Aircraft Type: Cessna 441	6 Aircraft Identification: RP-04132	
7 Pilot: A. DAYO	8 Co-Pilot: E. SATELA	9 Route: MANUPAL	12 Airport of Arrival (Airport, City/Province): LAGOPOBON			
10 Date: May 6, 2014	11 Airport of Departure (Airport, City/Province): LAGOPOBON		13 Total Engine Time: 4:23		16 Take off: 08:30	18 Total Flight Time: 4:13
13 Engine Oil: OE 25	14 Engine Oil: 12 NS	15 Total Engine Time: 4:23		17 Landing: 12:43		
19 Weather: Cloud						
20 Flight Classification			21 Remarks			
20a. IFR/DAE <input type="checkbox"/> Acquisition Flight <input type="checkbox"/> Ferry Flight <input type="checkbox"/> System Test Flight <input type="checkbox"/> Calibration Flight			20b. Non-IFR/DAE <input type="checkbox"/> Aircraft Test Flight <input type="checkbox"/> AAC Admin Flight <input type="checkbox"/> Others: _____			
20c. Others <input type="checkbox"/> LIDAR System Maintenance <input type="checkbox"/> Aircraft Maintenance <input type="checkbox"/> Phil-LIDAR Admin Activities			SUCCESSFUL FLIGHT ; COVERED MANUPAL - SAKAJAJA PROBLEMS ; WITH VOIDS			
22 Problems and Solutions						
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____						
Acquisition Flight Approved by  Signature over Printed Name (End User Representative)	Acquisition Flight Certified by  Signature over Printed Name (Phil-LIDAR Representative)	Pilot-in-Command  Signature over Printed Name	LIDAR Operator  Signature over Printed Name	Aircraft Mechanic/ LIDAR Technician _____ Signature over Printed Name		

Figure A-5.9 Flight Log for Mission 23516P

10. Flight Log for Mission 23518P

Flight Log No.: 23518P






PHS-LIDAR 1 Data Acquisition Flight Log					
1. LIDAR Operator: SAK PUSKINO	2. Altis Model: FAH005	3. Mission Name: WINDPIND	4. Type: VFR	5. Aircraft Type: Cessna 441	6. Aircraft Identification: PP-0113
7. Pilot: A. Dora	8. Co-Pilot: E. SAYSAJ	9. Route: VALEPWA	12. Airport of Arrival (Airport, City/Province): LAGUINDI NGAN		
10. Date: Nov. 6, 2014	11. Airport of Departure (Airport, City/Province): LAGUINDI NGAN		13. Engine On: 14 54	14. Engine Off: 17 33	15. Total Flight Time: 2 + 29
16. Weather: PAIF			17. Take off:	18. Landing:	19. Total Flight Time: 2 + 19
20. Flight Classification			21. Remarks		
20.a. Utility <input type="checkbox"/> Acquisition Flight <input type="checkbox"/> Ferry Flight <input type="checkbox"/> System Test Flight <input type="checkbox"/> Calibration Flight			20.b. Non Utility <input type="checkbox"/> Aircraft Test Flight <input type="checkbox"/> AAC Adm'n Flight <input type="checkbox"/> Others: _____		
20.c. Others <input type="checkbox"/> LIDAR System Malfunction <input type="checkbox"/> Aircraft Maintenance <input type="checkbox"/> Pil-LIDAR Adm'n Activities			SUCCESSFUL FLIGHT; COVERED MAMPWA - SAWAGA FLOODPLAIN		
22. Problems and Solutions					
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____					
Acquisition Flight Approved by	Acquisition Flight Certified by	Pilot in Command	LIDAR Operator	Aircraft Mechanic/ LIDAR Technician	
					
Signature over Printed Name (End User Representative)	Signature over Printed Name (PAF Representative)	Signature over Printed Name	Signature over Printed Name	Signature over Printed Name	

Figure A-5.10 Flight Log for Mission 23518P

11. Flight Log for Mission 23520P

Flight Log No.: 23520P





1. LIDAR Operator: F. SUCRAY		2. Air LH Model: PR6600		3. Mission Name: MANUPAL		4. Type: VFR		5. Aircraft Type: Cessna 441		6. Aircraft Identification: RP-C0121				
7. Pilot: A. DAYO		8. Co-Pilot: E. SOYCAN		9. Route: VALERGA										
10. Date: Nov. 7, 2016		11. Airport of Departure (Airport, City/Province): LAGUINDIGAN				12. Airport of Arrival (Airport, City/Province): LAGUINDIGAN								
13. Engine On: 08:30		14. Engine Off: 15:30		15. Total Engine Time: 4:00		16. Take off:		17. Landing:		18. Total Flight Time: 9:00				
19. Weather: FAIR														
20. Flight Classification						21. Remarks								
20.a. 01.a. <input checked="" type="radio"/> Acquisition Flight		20.a. 01.b. <input type="radio"/> Ferry Flight		20.a. 01.c. <input type="radio"/> System Test Flight		20.a. 01.d. <input type="radio"/> Calibration Flight		20.a. 02.a. <input type="radio"/> Aircraft Test Flight		20.a. 02.b. <input type="radio"/> AEC Admin Flight				
								20.a. 02.c. <input type="radio"/> LIDAR System Maintenance		20.a. 02.d. <input type="radio"/> Aircraft Maintenance				
								20.a. 02.e. <input type="radio"/> Pre-LIDAR Admin Activities						
						SUCCESSFUL FLIGHT, COVERED LAB / WORK OVER MANUPAL - SABANA (LADP/ALJ)								
22. Problems and Solutions														
<input checked="" type="radio"/> Weather Problem <input type="radio"/> System Problem <input type="radio"/> Aircraft Problem <input type="radio"/> Pilot Problem <input type="radio"/> Others: _____														
Acquisition Flight Approved by			Acquisition Flight Identified by			Pilot-in-Command			LIDAR Operator			Aircraft Mechanic/LIDAR Technician		
												-		
Signature over Printed Name (End User Representative)			Signature over Printed Name (PIF Representative)			Signature over Printed Name A. DAYO			Signature over Printed Name F. SUCRAY			Signature over Printed Name		

Figure A-5.11 Flight Log for Mission 23520P

12. Flight Log for Mission 23524P





PVE-LIDAR 1 Data Acquisition Flight Log						Flight Log No: 23524P	
1 LIDAR Operator: PHILIP PULSUMBO	2 AIM Model: TRIMBLE	3 Mission Name: 480000133A	4 Type: VFR	5 Aircraft Type: Cessna 441	6 Aircraft Identification: PP-1172		
7 Pilot: A. DAYO	8 Co-Pilot: E. JAYEM	9 Route: VALANGUA					
10 Date: Nov. 9, 2016	12 Airport of Departure (Airport, City/Province): LAGUNA DELA RIA		12 Airport of Arrival (Airport, City/Province): LAGUNA DELA RIA				
13 Engine On: 9:45	14 Engine Off: 13:24	15 Total Engine Time: 4:39	16 Take off:	17 Landing:	18 Total Flight Time: 4:19		
19 Weather: FMG							
20 Flight Classification			21 Remarks				
20a: <input checked="" type="checkbox"/> Acquisition Flight	20b: <input type="checkbox"/> Aircraft Test Flight	20c: <input type="checkbox"/> LIDAR System Maintenance	21 Remarks: 2000000000 - FLIGHT, COVERED UPPER PLANAL FLOOD PLAIN				
<input type="checkbox"/> Ferry Flight	<input type="checkbox"/> AAC Aerial Flight	<input type="checkbox"/> Aircraft Maintenance					
<input type="checkbox"/> System Test Flight	<input type="checkbox"/> Others:	<input type="checkbox"/> PVE-LIDAR Admin Activities					
<input type="checkbox"/> Calibration Flight							
22 Problems and Solutions							
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others:							
Acquisition Flight Approved by  Signature over Printed Name (End User Representative)	Acquisition Flight Certified by  Signature over Printed Name (Pilot Representative)	Pilot-in-Command  Signature over Printed Name	LIDAR Operator  Signature over Printed Name	Aircraft Mechanic/ LIDAR Technician Signature over Printed Name			

Figure A-5.12 Flight Log for Mission 23524P

13. Flight Log for Mission 23534P

Flight Log No.: 23534P





PHIL-LIDAR 1 Data Acquisition Flight Log					
1) LIDAR Operator: F. ILEBAT	2) A/T Model: Q400M2	3) Mission Name: 23534P	4) Type: VFR	5) Aircraft Type: Cessna 441	6) Aircraft Identification: PH-L111
7) Pilot: A. OCHO	8) Co-Pilot: B. SANSAY	9) Route: MANILA			
10) Date: Nov 10, 2010	11) Airport of Departure (Airport, City/Province): Manila	12) Airport of Arrival (Airport, City/Province): Manila			
13) Engine On: 12:34	14) Engine Off: 12:39	15) Total Engine Time: 04:05	16) Take off:	17) Landing:	18) Total Flight Time: 03:55
19) Weather: Clear					
20) Flight Classification			21) Remarks		
20a) <input checked="" type="radio"/> Able <input type="radio"/> Feary Flight <input type="radio"/> System Test Flight <input type="radio"/> Calibration Flight			20b) <input type="radio"/> Non-Operable <input type="radio"/> Aircraft Test Flight <input type="radio"/> AAC Admin Flight <input type="radio"/> Others:		
<input type="radio"/> LIDAR System Maintenance <input type="radio"/> Aircraft Maintenance <input type="radio"/> Phil-LIDAR Admin Activities			21) Remarks: Successful Flight		
22) Problems and Solutions					
<input type="radio"/> Weather Problem <input type="radio"/> System Problem <input type="radio"/> Aircraft Problem <input type="radio"/> Pilot Problem <input type="radio"/> Others:					
Acquisition Flight Approved by  Signature over Printed Name (End User Representative)	Acquisition Flight Certified by  Signature over Printed Name (PAF Representative)	Pilot in Command  Signature over Printed Name	LIDAR Operator  Signature over Printed Name	Aircraft Mechanic/LIDAR Technician Signature over Printed Name	

Figure A-5.13 Flight Log for Mission 23534P

14. Flight Log for Mission 23536P

Flight Log No: 23536P

1 LIDAR Operator: R. PERCOTO		2 Altitude: 7000ft	3 Mission Name: YANEPCAA	4 Type: VFR	5 Aircraft Type: Cessna 441	6 Aircraft Identification: RP-0123
7 Pilot: A. DAYO	8 Co-Pilot: E. DAYO	9 Route: YANEPCAA	10 Airport of Arrival (Airport, City/Province):			
11 Date: Nov. 2, 2018	12 Airport of Departure (Airport, City/Province):		13 Airport of Arrival (Airport, City/Province):			
13 Engine On: 08:49	14 Engine Off: 09:12	15 Total Engine Time: 04:23		16 Take off:	17 Landing:	18 Total Flight Time: 04:23
19 Weather						
20 Flight Classification					21 Remarks	
20a: <input checked="" type="radio"/> Enroute		20b: Not Enroute		20c: Others		
<input checked="" type="radio"/> Acquisition Flight <input type="radio"/> Proxy Flight <input type="radio"/> Systems Test Flight <input type="radio"/> Calibration Flight		<input type="radio"/> Aircraft Test Flight <input type="radio"/> AAL Admin Flight <input type="radio"/> Others: _____		<input type="radio"/> LIDAR System Maintenance <input type="radio"/> Aircraft Maintenance <input type="radio"/> Full LIDAR Admin Activities		
22 Problems and Solutions						
<input type="radio"/> Weather Problem <input type="radio"/> System Problem <input type="radio"/> Aircraft Problem <input type="radio"/> Pilot Problem <input type="radio"/> Others: _____						
Acquisition Flight Approved by		Acquisition Flight Verified by		Pilot In Command		LIDAR Operator
Signature over Printed Name (End User Representative)		Signature over Printed Name (Pilot In Command)		Signature over Printed Name		Signature over Printed Name

Figure A-5.14 Flight Log for Mission 23536P

15. Flight Log for Mission 23540P

Flight Log No: 23540P

PHIL-LIDAR 1 Data Acquisition Flight Log					
1 LIDAR Operator: F. ILICAY	2 Altitude: 7000ft	3 Mission Name: IBANEZ TA	4 Type: VFR	5 Aircraft Type: Cessna 208B	6 Aircraft Identification: PP-CA422
7 Pilot: A. DAYO	8 Co-Pilot: E. SAYSAY	9 Route: VALIGUA			
10 Date: Nov. 12, 2012	12 Airport of Departure (Airport, City/Province): Laguayan DepEd An		13 Airport of Arrival (Airport, City/Province): Laguayan DepEd An		
13 Engine On: 10:14	14 Engine Off: 11:30	15 Total Engine Time: 01:16	16 Take off:	17 Landing:	18 Total Flight Time: 01:16
19 Weather: PAZ					
20 Flight Classification			21 Remarks		
20.a. Details <input checked="" type="radio"/> Acquisition Flight <input type="radio"/> Ferry Flight <input type="radio"/> Systems Test Flight <input type="radio"/> Calibration Flight			20.b. Non-Flight <input type="radio"/> Aircraft Test Flight <input type="radio"/> AAC Admin Flight <input type="radio"/> Others: _____		
20.c. Others <input type="radio"/> LIDAR System Maintenance <input type="radio"/> Aircraft Maintenance <input type="radio"/> Phil-LIDAR Admin Activities			SUCCESSFUL FLIGHT, Surveyed gaps over BANE		
22 Problems and Solutions					
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____					
Acquisition Flight Approved by Signature over Printed Name (End User Representative)	Acquisition Flight Certified by Signature over Printed Name (Data Representative)	Pilot in Command ANTON DAYO Signature over Printed Name	LIDAR Operator F. ILICAY Signature over Printed Name	Aircraft Mechanic/LIDAR Technician Signature over Printed Name	

Figure A-5.15 Flight Log for Mission 23540P

16. Flight Log for Mission 23544P

Flight Log No: 23544P

PSI-LIDAR Data Acquisition Flight Log					
1 LIDAR Operator: E. Tulasian	2 Airframe Model: PC-602B	3 Mission Name: VALLEJO	4 Type: VFR	5 Aircraft Type: Cessna T208H	6 Aircraft Identification: EP-0922
7 Pilot: A. Pardo	8 Co-Pilot: S. SAAV	9 Route: VALLEJO			
10 Date: Nov 05, 2016	11 Airport of Departure (Airport, City/Province): LAGUIN/DAVAO		12 Airport of Arrival (Airport, City/Province): LAGUIN/DAVAO		
13 Engine On: 07:45	14 Engine Off: 11:56	15 Total Engine Time: 04:11	16 Take off:	17 Landing:	18 Total Flight Time: 04:11
19 Weather: PAVG.					
20 Flight Classification			21 Remarks		
20a: <input checked="" type="radio"/> Data	20b: <input type="radio"/> Test	20c: <input type="radio"/> Other	21 Remarks: SUCCESSFUL FLIGHT - completed BRNG over Vallejo		
<input checked="" type="radio"/> Acquisition Flight <input type="radio"/> Ferry Flight <input type="radio"/> System Test Flight <input type="radio"/> Calibration Flight	<input type="radio"/> Aircraft Test Flight <input type="radio"/> AAC Admin Flight <input type="radio"/> Other: _____	<input type="radio"/> LIDAR System Maintenance <input type="radio"/> Aircraft Maintenance <input type="radio"/> PSI-LIDAR Admin Activities			
22 Problems and Solutions					
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____					
Acquisition Flight Approved by Signature over Printed Name (End User Representative)	Acquisition Flight Certified by Signature over Printed Name (PIR Representative)	Mission Conducted by Signature over Printed Name	LIDAR Operator Signature over Printed Name	Aircraft Mechanic/LIDAR Technician Signature over Printed Name	

Figure A-5.16 Flight Log for Mission 23544P

17. Flight Log for Mission 23546P

Flight Log No: 23546P





Phil-LIDAR 1 Data Acquisition Flight Log					
1 LIDAR Operator: F. SANCHEZ	2 Airframe Model: P280AS05	3 Mission Name: 23546P	4 Type: VFR	5 Aircraft Type: Cessna 441	6 Aircraft Identification: RP-04123
7 Pilot: A. DAYO	8 Co-Pilot: E. SAYSAY	9 Route: VALERIA	12 Airport of Arrival (Airport, City/Province): LA 64 (INDIA) 6.40		
10 Date: Nov 05, 2019	11 Airport of Departure (Airport, City/Province): LA 64 (INDIA) 6.40	13 Total Engine Time: 04:11	14 Engine On: 03:53	15 Engine Off: 04:04	16 Total Flight Time: 04:09
17 Weather: Clouds 4000 2000 3000 5000					
18 Flight Classification			19 Remarks		
20a. <input checked="" type="checkbox"/> Acquisition Flight	20b. <input type="checkbox"/> Aircraft Test Flight	20c. <input type="checkbox"/> LIDAR System Maintenance	SUGGESTION TARGET, Completed 04:09 over Valencia		
<input type="checkbox"/> Ferry Flight	<input type="checkbox"/> AAL Admin Flight	<input type="checkbox"/> Aircraft Maintenance			
<input type="checkbox"/> System Test Flight	<input type="checkbox"/> Other: _____	<input type="checkbox"/> Phil-LIDAR Admin Activities			
<input type="checkbox"/> Calibration Flight					
21 Problems and Solutions					
<input type="checkbox"/> Weather Problem <input type="checkbox"/> Systems Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____					
Acquisition Flight Approved by  Signature over Printed Name (End User Representative)	Acquisition Flight Certified by  Signature over Printed Name (Phil Representative)	Pilot-in-Command  Signature over Printed Name	LIDAR Operator  Signature over Printed Name	Aircraft Mechanic/LIDAR Technician _____ Signature over Printed Name	

Figure A-5.17 Flight Log for Mission 23546P

18. Flight Log for Mission 23548P

Flight Log No: 23548P

PHI-LIDAR Data Acquisition Flight Log					
1. LIDAR Operator: F. LESDAY	2. LIDAR Model: PC680WS	3. Mission Name: SARAWAK	4. Type: VFR	5. Aircraft Type: Cessna 441	6. Aircraft Identification: EP-0482
7. Pilot: A. DAYO	8. Co-Pilot: E. S. ANWAR	9. Route: SARAWAK			
10. Date: Nov. 14, 2016	11. Airport of Departure (Airport, City/Province): Kuching	12. Airport of Arrival (Airport, City/Province): Kuching			
13. Engine On: 08:19	14. Engine Off: 12:48	15. Total Engine Time: 04:29	16. Take off:	17. Landing:	18. Total Flight Time: 04:19
19. Weather: Cloud					
20. Flight Classification			21. Remarks		
20.a. Mission	20.b. Other	20.c. Others	SARAWAK FLIGHT		
<input type="checkbox"/> Acquisition Flight <input type="checkbox"/> Ferry Flight <input type="checkbox"/> System Test Flight <input type="checkbox"/> Calibration Flight	<input type="checkbox"/> Aircraft Test Flight <input type="checkbox"/> AAC Admin Flight <input type="checkbox"/> Others: _____	<input type="checkbox"/> LIDAR System Maintenance <input type="checkbox"/> Aircraft Maintenance <input type="checkbox"/> PHI-LIDAR Admin Activities			
22. Problems and Solutions					
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____					
Acquisition Flight Approved by Signature over Printed Name (End User Representative)	Acquisition Certified by Signature over Printed Name (AS Representative)	Pilot in Command Signature over Printed Name	LIDAR Operator Signature over Printed Name	Aircraft Mechanic/ LIDAR Technician _____ Signature over Printed Name	

Figure A-5.18 Flight Log for Mission 23548P

ANNEX 6. Flight Status Reports

NORTHERN MINDANAO

(May 27 – July 10, 2014 and October 23 – November 14, 2016)

Table A-6.1 Flight Status Report

Flight No	Area	Mission	Operator	Date Flown	Remarks
1517P	RX BLK D,E	1RXE147A	I. Roxas	May 27, 2014	Surveyed half of RX D and half of RX E at 800m, 1000m then 900m; cam stylus malfunctioned
1569P	RX BLK E	1BLKRXE160A	G.Sinadjan	June 9, 2014	Mission successful; gaps due to high terrain; camera assertion failed
1597P	RX BLK D,E	1BLKRXE167A	G.Sinadjan	June 16, 2014	Mission successful; filled gaps in RX E
1629P	RX BLK E	1BLKRXES175A	G.Sinadjan	June 24, 2014	Mission successful at 1400 AGL
1693P	RX BLK ES	1RXES191A	J. Alviar	July 10, 2014	Filled in gaps in RX E
23486P	MANOLO FORTICH BKN S2	1BKND297A	J Alviar	October 23,2014	Surveyed Manolo Fortich at 1300m MSL; heavy build up and precipitation in bukidnon
23488P	MANOLO FORTICH BKN S1	1BKND298A	K. Quisado	October 24,2014	Closed visual over target areas; surveyed Tagoloan watershed in Manolo Fortich at 1700m MSL
23492P	BKN E	1BKND299A	K Quisado	October 25,2014	Surveyed BKN E at 1500m MSL
23516P	VALENCIA BNK F	1BKNF311A	FN Ilejay	November6,2016	Surveyed Manupali-Sawaga floodplain with voids due to build up and strong winds
23518P	VALENCIA BNK F	1BKNF311B	PJ Arceo RA Felismino	November6,2016	Surveyed only 4 lines over Manupali-Sawaga floodplain due to time constraint
23520P	VALENCIA BKN F	1BKNF312A	FN Ilejay	November7,2016	Surveyed gaps over Manupali-Sawaga floodplain
23524P	VALENCIA BKN D	1BKND313A	PJ Arceo RA Felismino	November8,2016	Surveyed Manupali-Sawaga-Upper Pulangi floodplain

23534P	VALENCIA BNK G	1BKNGS315A	FN Ilejay	November 10, 2016	Surveyed Manupali- Sawaga floodplain with voids due to build up and strong winds
23536P	VALENCIA BKN E	1BKNE317A	PJ Arceo, RA Felismino	November 11,2016	Surveyed gaps over Manupali-Sawaga floodplain
23540P	VALENCIA BKN E	1BKNE317A	FN Ilejay	November 12, 2016	Surveyed gaps over Manupali-Sawaga floodplain
23544P	VALENCIA BKN E	1BKNE318A	RA Felismino	November 13, 2016	Completed BKN E over Valencia
23546P	VALENCIA BKN G	1BKNG318B	FN Ilejay	November 13, 2016	COMPLETED BKN G OVER VALENCIA
23548P	VALENCIA BKN E,F	1BKNEF319A	FN Ilejay	November 14, 2016	Fill up gaps and voids over Malaybalay and Valencia

LAS BOUNDARIES PER FLIGHT

Flight No. : 1517P

Area: RX D, RX E

Mission Name: 1RXE147A

Parameters:

Altitude: 900m;

Scan Frequency: 30Hz;

Scan Angle: 25deg;

Overlap: 30%




Figure A-6.1 Swath for Flight No. 1517P

Flight No. : 1569P
Area: RX D
Mission Name: 1BLKRXE160A
Parameters:
Altitude: 1000 m;
Scan Frequency: 30Hz;
Scan Angle: 25deg;
Overlap: 30%




Figure A-6.2 Swath for Flight No. 1569P

Flight No. : 1597P
Area: RX D, RX E
Mission Name: 1BLKRXE167A
Parameters:
Altitude: 800m;
Scan Frequency: 30Hz;
Scan Angle: 25 deg;
Overlap: 30%




Figure A-6.3 Swath for Flight No. 1597P

Flight No. : 1629P

Area: RX E

Mission Name: 1BLKRXE175A

Parameters:

Altitude: 1400m;

Scan Frequency: 30Hz;

Scan Angle: 25 deg;

Overlap: 30%




Figure A-6.4 Swath for Flight No. 1629P

Flight No. : 1693P
Area: RX ES
Mission Name: 1RXES191A
Parameters:
Altitude: 1200m;
Scan Frequency: 30Hz;
Scan Angle: 25 deg;
Overlap: 30%




Figure A-6.5 Swath for Flight No. 1693P

Flight No. : 23486P
Area: BKN S2
Mission Name: 1BKND297A
Parameters:
Altitude: 1300m;
Scan Frequency: 30Hz;
Scan Angle: 25 deg;
Overlap: 30%




Figure A-6.6 Swath for Flight No. 23486P

Flight No. : 23488P
Area: BKN S1
Mission Name: 1BKNDE298A
Parameters:
Altitude: 1700m;
Scan Frequency: 30Hz;
Scan Angle: 25 deg;
Overlap: 30%




Figure A-6.7 Swath for Flight No. 23488P

Flight No. : 23492P

Area: BKN E

Mission Name: 1BKNDE299A

Parameters:

Altitude: 1500m;

Scan Frequency: 30Hz;

Scan Angle: 25 deg;

Overlap: 30%




Figure A-6.8 Swath for Flight No. 23492P

Flight No. : 23516P
Area: VALENCIA BKN F
Mission Name: 1BKNF311A
Parameters:
Altitude: 1000m;
Scan Frequency: 30Hz;
Scan Angle: 25 deg;
Overlap: 30%




Figure A-6.9 Swath for Flight No. 23516P

Flight No. : 23518P

Area: BKN F

Mission Name: 1BKNF311B

Parameters:

Altitude: 1000m;

Scan Frequency: 30Hz;

Scan Angle: 25 deg;

Overlap: 30%




Figure A-6.10 Swath for Flight No. 23518P

Flight No. : 23520P
Area: BKN F
Mission Name: 1BKNF312A
Parameters:
Altitude: 1200m;
Scan Frequency: 30Hz;
Scan Angle: 25 deg;
Overlap: 30%




Figure A-6.11 Swath for Flight No. 23520P

Flight No. : 23524P

Area: BKN D

Mission Name: 1BKND313A

Parameters:

Altitude: 1200m;

Scan Frequency: 30Hz;

Scan Angle: 25 deg;

Overlap: 30%




Figure A-6.12 Swath for Flight No. 23524P

Flight No. : 23534P
Area: BKN G
Mission Name: 1BKNG315A
Parameters:
Altitude: 1200m;
Scan Frequency: 30Hz;
Scan Angle: 25 deg;
Overlap: 30%




Figure A-6.13 Swath for Flight No. 23534P

Flight No. : 23536P

Area: BKN E

Mission Name: 1BKNE316A

Parameters:

Altitude: 1300m;

Scan Frequency: 30Hz;

Scan Angle: 25 deg;

Overlap: 30%




Figure A-6.14 Swath for Flight No. 23536P

Flight No. : 23540P
Area: BKN E
Mission Name: 1BKNE317A
Parameters:
Altitude: 1300m;
Scan Frequency: 30Hz;
Scan Angle: 25 deg;
Overlap: 30%




Figure A-6.15 Swath for Flight No. 23540P

Flight No. : 23544P

Area: BKN E

Mission Name: 1BKNE318A

Parameters:

Altitude: 1300m;

Scan Frequency: 30Hz;

Scan Angle: 25 deg;

Overlap: 30%




Figure A-6.16 Swath for Flight No. 23544P

Flight No. : 23546P
Area: BKN E
Mission Name: 1BKNG318B
Parameters:
Altitude: 1300m;
Scan Frequency: 30Hz;
Scan Angle: 25 deg;
Overlap: 30%




Figure A-6.17 Swath for Flight No. 23546P

Flight No. : 23548P

Area: BKN E, F

Mission Name: 1BKNEF319A

Parameters:

Altitude: 1300m;

Scan Frequency: 30Hz;

Scan Angle: 25 deg;

Overlap: 30%




Figure A-6.18 Swath for Flight No. 23548P

ANNEX 7. Mission Summary Reports

Table A-7.1 Mission Summary Report for Mission RX_BlKE_additional

Flight Area	Northern Mindanao
Mission Name	RX_BlKE_additional
Inclusive Flights	1569P, 1597P, 1629P, 1693P
Range data size	102.8 GB
Base data size	26.05 MB
POS	889 MB
Image	45.16 GB
Transfer date	August 1 and August 6, 2014
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.7
RMSE for East Position (<4.0 cm)	1.6
RMSE for Down Position (<8.0 cm)	4.5
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000586
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.002822
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0158
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	27.70%
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	3.07
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	542
<i>Maximum Height</i>	
Maximum Height	955.2
<i>Minimum Height</i>	
Minimum Height	68.58
<i>Classification (# of points)</i>	
Ground	311,248,111
Low vegetation	293,934,424
Medium vegetation	609,300,489
High vegetation	299,775,531
Building	11,325,562
Orthophoto	Yes
Processed by	Engr. Kenneth Solidum, Engr. Mark Joshua Salvacion, Engr. Roa Shalemar Redo



Figure A-7.1 Solution Status




Figure A-7.2 Smoothed Performance Metric Parameters




Figure A-7.3 Best Estimated Trajectory




Figure A-7.4 Coverage of LiDAR data




Figure A-7.5 Image of data overlap




Figure A-7.6 Density map of merged LIDAR data




Figure A-7.7 Elevation difference between flight lines

Table A-7.2 Mission Summary Report for Mission RX_Blke

Flight Area	Northern Mindanao
Mission Name	RX_Blke
Inclusive Flights	1517P
Range data size	27.7 GB
Base data size	9.7 MB
POS	235 MB
Image	n/a
Transfer date	June 10, 2014
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.0
RMSE for East Position (<4.0 cm)	1.45
RMSE for Down Position (<8.0 cm)	2.6
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000196
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.000571
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0068
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	52.88%
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	5.82
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	116
<i>Maximum Height</i>	
Maximum Height	665.98 m
<i>Minimum Height</i>	
Minimum Height	69.67 m
<i>Classification (# of points)</i>	
Ground	129,890,323
Low vegetation	122,339,927
Medium vegetation	238,939,048
High vegetation	182,392,328
Building	11,325,562
Orthophoto	No
Processed by	Engr. Jommer Medina, Engr. Antonio Chua Jr, Engr. Gladys Mae Apat




Figure A-7.8 Solution Status




Figure A-7.9 Smoothed Performance Metric Parameters




Figure A-7.10 Best Estimated Trajectory




Figure A-7.11 Coverage of LiDAR data




Figure A-7.12 Image of data overlap




Figure A-7.13 Density map of merged LiDAR data




Figure A-7.14 Elevation difference between flight lines

Table A-7.3 Mission Summary Report for Mission RX_Blke_additional2

Flight Area	Northern Mindanao
Mission Name	RX_Blke_additional2
Inclusive Flights	1569P
Range data size	21.3 GB
POS	237 MB
Image	NA
Transfer date	July 28, 2014
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	No
Processing Mode (<=1)	No
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.90
RMSE for East Position (<4.0 cm)	2.67
RMSE for Down Position (<8.0 cm)	4.48
<i>Boresight correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.000381
GPS position stdev (<0.01m)	0.0073
<i>Minimum % overlap (>25)</i>	
Ave point cloud density per sq.m. (>2.0)	18.33%
Elevation difference between strips (<0.20 m)	4.14
<i>Yes</i>	
Number of 1km x 1km blocks	279
Maximum Height	735.0 m.
Minimum Height	-2.37 m.
<i>Classification (# of points)</i>	
Ground	482,670,071
Low vegetation	247,589,891
Medium vegetation	452,463,888
High vegetation	622,419,309
Building	26,062,650
<i>Orthophoto</i>	
Processed by	Engr. Kenneth A. Solidum, Engr. Mark Joshua A. Salvacion, Engr. Roa Shalemar Redo




Figure A-7.15 Solution Status




Figure A-7.16 Smoothed Performance Metric Parameters




Figure A-7.17 Best Estimated Trajectory




Figure A-7.18 Coverage of LiDAR data




Figure A-7.19 Image of data overlap




Figure A-7.20 Density map of merged LiDAR data




Figure A-7.21 Elevation difference between flight lines

Table A-7.4 Mission Summary Report for Mission Blk64A

Flight Area	Bukidnon
Mission Name	Blk64A
Inclusive Flights	23492P
Range data size	20.9 GB
Base data size	217 MB
POS	230 MB
Image	N/A
Transfer date	November 7, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	No
PDOP (<3)	Yes
Baseline Length (<30km)	No
Processing Mode (<=1)	No
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.9815
RMSE for East Position (<4.0 cm)	3.045
RMSE for Down Position (<8.0 cm)	4.153
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000225
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.001070
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0120
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	30.77
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	2.43
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	299
<i>Maximum Height</i>	
Maximum Height	1102.3 m
<i>Minimum Height</i>	
Minimum Height	412.73 m
<i>Classification (# of points)</i>	
Ground	191,528,488
Low vegetation	145,533,151
Medium vegetation	322,909,291
High vegetation	362,589,170
Building	17,861,849
Orthophoto	No
Processed by	Engr. Jennifer Saguran, Engr. Harmond Santos, Alex John Escobido




Figure A-7.22 Solution Status




Figure A-7.23 Smoothed Performance Metric Parameters




Figure A-7.24 Best Estimated Trajectory




Figure A-7.25 Coverage of LiDAR data




Figure A-7.26 Image of data overlap




Figure A-7.27 Density map of merged LiDAR data




Figure A-7.28 Elevation difference between flight lines

Table A-7.5 Mission Summary Report for Mission Blk64A_Additinal

Flight Area	Bukidnon
Mission Name	Blk64A_Additional
Inclusive Flights	23534 P
Range data size	16.6 GB
Base data size	136 MB
POS	255 MB
Image	N/A
Transfer date	November 24, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	No
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.20
RMSE for East Position (<4.0 cm)	1.393
RMSE for Down Position (<8.0 cm)	4.290
<i>Boresight correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.001178
GPS position stdev (<0.01m)	0.0144
<i>Minimum % overlap (>25)</i>	
Ave point cloud density per sq.m. (>2.0)	4.92
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Maximum Height	682.03 m
Minimum Height	373.33 m
<i>Classification (# of points)</i>	
Ground	25,441,266
Low vegetation	22,546,966
Medium vegetation	61,054,975
High vegetation	80,759,028
Building	4,837,220
Orthophoto	No
Processed by	Engr. Jennifer Saguran, Engr. Chelou Prado, Engr. Karl Adrian Vergara




Figure A-7.29 Solution Status




Figure A-7.30 Smoothed Performance Metric Parameters




Figure A-7.31 Best Estimated Trajectory




Figure A-7.32 Coverage of LiDAR data




Figure A-7.33 Image of data overlap




Figure A-7.34 Density map of merged LiDAR data




Figure A-7.35 Elevation difference between flight lines

Table A-7.6 Mission Summary Report for Mission Blk64A_Supplement

Flight Area	Bukidnon
Mission Name	Blk64A_Supplement
Inclusive Flights	23536P
Range data size	22.90 GB
Base data size	146 MB
POS	235 MB
Image	N/A
Transfer date	November 24, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	No
PDOP (<3)	No
Baseline Length (<30km)	No
Processing Mode (<=1)	No
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.420
RMSE for East Position (<4.0 cm)	3.450
RMSE for Down Position (<8.0 cm)	3.628
<i>Boresight correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.000335
GPS position stdev (<0.01m)	0.0070
<i>Minimum % overlap (>25)</i>	
Ave point cloud density per sq.m. (>2.0)	7.08
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Maximum Height	1141.19 m
Minimum Height	407.8 m
<i>Classification (# of points)</i>	
Ground	140,873,960
Low vegetation	116,830,863
Medium vegetation	383,758,426
High vegetation	454,225,250
Building	30,777,474
Orthophoto	No
Processed by	Engr. Analyn Naldo, Engr. Merven Matthew Natino, Vincent Louise Azucena




Figure A-7.36 Solution Status




Figure A-7.37 Smoothed Performance Metric Parameters




Figure A-7.38 Best Estimated Trajectory




Figure A-7.39 Coverage of LiDAR data




Figure A-7.40 Image of data overlap




Figure A-7.41 Density map of merged LiDAR data




Figure A-7.42 Elevation difference between flight lines

Table A-7.7 Mission Summary Report for Mission Blk64B_Supplement2

Flight Area	Bukidnon
Mission Name	Blk64B_Supplement2
Inclusive Flights	23548P
Range data size	26.7 GB
Base data size	208 MB
POS	268 MB
Image	N/A
Transfer date	November 24, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.232
RMSE for East Position (<4.0 cm)	1.441
RMSE for Down Position (<8.0 cm)	2.99
<i>Boresight correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.000463
GPS position stdev (<0.01m)	0.0011
<i>Minimum % overlap (>25)</i>	
Ave point cloud density per sq.m. (>2.0)	5.80
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Maximum Height	1099.77 m
Minimum Height	629.02 m
<i>Classification (# of points)</i>	
Ground	355,349,842
Low vegetation	420,008,545
Medium vegetation	1,045,682,099
High vegetation	986,779,809
Building	94,950,490
Orthophoto	No
Processed by	Engr. Analyn Naldo, Aljon Rie Araneta, Engr. Gladys Mae Apat




Figure A-7.43 Solution Status




Figure A-7.44 Smoothed Performance Metric Parameters




Figure A-7.45 Best Estimated Trajectory




Figure A-7.46 Coverage of LiDAR data




Figure A-7.47 Image of data overlap




Figure A-7.48 Density map of merged LiDAR data




Figure A-7.49 Elevation difference between flight lines

Table A-7.8 Mission Summary Report for Mission Blk64B

Flight Area	Bukidnon
Mission Name	Blk64B
Inclusive Flights	23516P
Range data size	22.5 GB
Base data size	283 MB
POS	269MB
Image	N/A
Transfer date	November 16, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	No
PDOP (<3)	No
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.675
RMSE for East Position (<4.0 cm)	4.350
RMSE for Down Position (<8.0 cm)	3.335
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000531
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.001317
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0071
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	42.69
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	3.54
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	319
<i>Maximum Height</i>	
Maximum Height	834.68 m
<i>Minimum Height</i>	
Minimum Height	304.99 m
<i>Classification (# of points)</i>	
Ground	356,040,037
Low vegetation	326,910,127
Medium vegetation	525,652,904
High vegetation	512,546,318
Building	44,145,758
Orthophoto	No
Processed by	Engr Ben Joseph Harder, Engr James Kevin Dimaculangan, Engr. Justine Francisco




Figure A-7.50 Solution Status




Figure A-7.51 Smoothed Performance Metric Parameters




Figure A-7.52 Best Estimated Trajectory




Figure A-7.53 Coverage of LiDAR data




Figure A-7.54 Image of data overlap




Figure A-7.55 Density map of merged LiDAR data




Figure A-7.56 Elevation difference between flight lines

Table A-7.9 Mission Summary Report for Mission Blk64B_Supplement

Flight Area	Bukidnon
Mission Name	Blk64B_Supplement
Inclusive Flights	23548P
Range data size	26.7 GB
Base data size	208 MB
POS	268 MB
Image	N/A
Transfer date	November 24, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.232
RMSE for East Position (<4.0 cm)	1.441
RMSE for Down Position (<8.0 cm)	2.99
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000152
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.000776
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0011
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	59.75
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	3.58
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	242
<i>Maximum Height</i>	
Maximum Height	849.49 m
<i>Minimum Height</i>	
Minimum Height	58.35 m
<i>Classification (# of points)</i>	
Ground	302,590,947
Low vegetation	139,176,892
Medium vegetation	257,286,910
High vegetation	313,991,201
Building	28,292,278
Orthophoto	No
Processed by	Engr Ben Joseph Harder, Engr. Edgardo Gubatanga Jr, Engr. Czarina Jean Añonuevo




Figure A-7.57 Solution Status




Figure A-7.58 Smoothed Performance Metric Parameters




Figure A-7.59 Best Estimated Trajectory




Figure A-7.60 Coverage of LiDAR data




Figure A-7.61 Image of data overlap




Figure A-7.62 Density map of merged LiDAR data




Figure A-7.63 Elevation difference between flight lines

Table A-7.10 Mission Summary Report for Mission Blk64C

Flight Area	Bukidnon
Mission Name	Blk64C
Inclusive Flights	23520P
Range data size	24.5 GB
Base data size	158 MB
POS	274 MB
Image	N/A
Transfer date	November 16, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.541
RMSE for East Position (<4.0 cm)	1.748
RMSE for Down Position (<8.0 cm)	3.572
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000090
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.001178
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0144
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	30.29
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	3.18
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	221
<i>Maximum Height</i>	
Maximum Height	938.48 m
<i>Minimum Height</i>	
Minimum Height	114.92 m
<i>Classification (# of points)</i>	
Ground	293,747,127
Low vegetation	180,464,292
Medium vegetation	174,906,872
High vegetation	268,029,001
Building	7,345,248
Orthophoto	No
Processed by	Engr. Ben Joseph Harder, Engr James Kevin Dimaculangan, Engr. Jovelle Anjeanette Canlas, Maria Tamsyn Malabanan




Figure A-7.64 Solution Status




Figure A-7.65 Smoothed Performance Metric Parameters




Figure A-7.66 Best Estimated Trajectory




Figure A-7.67 Coverage of LiDAR data




Figure A-7.68 Image of data overlap




Figure A-7.69 Density map of merged LiDAR data




Figure A-7.70 Elevation difference between flight lines

Table A-7.11 Mission Summary Report for Mission Blk64A

Flight Area	Bukidnon
Mission Name	Blk64C_Additional
Inclusive Flights	23534P
Range data size	16.6 GB
Base data size	136 MB
POS	255MB
Image	N/A
Transfer date	November 24, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	No
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.20
RMSE for East Position (<4.0 cm)	1.393
RMSE for Down Position (<8.0 cm)	4.290
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000090
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.001178
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0144
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	55.90
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	7.18
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	104
<i>Maximum Height</i>	
Maximum Height	1033.35 m
<i>Minimum Height</i>	
Minimum Height	381.91 m
<i>Classification (# of points)</i>	
Ground	88,679,344
Low vegetation	69,388,074
Medium vegetation	242,773,781
High vegetation	357,660,401
Building	25,009,474
Orthophoto	No
Processed by	Engr. Ben Joseph Harder, Engr. James Kevin Dimaculangan, Aljon Rie Araneta, Engr. Wilbert Ian San Juan




Figure A-7.71 Solution Status




Figure A-7.72 Smoothed Performance Metric Parameters




Figure A-7.73 Best Estimated Trajectory




Figure A-7.74 Coverage of LiDAR data




Figure A-7.75 Image of data overlap




Figure A-7.76 Density map of merged LiDAR data




Figure A-7.77 Elevation difference between flight lines

Table A-7.12 Mission Summary Report for Mission Blk64C_Supplement

Flight Area	Bukidnon
Mission Name	Blk64C_Supplement
Inclusive Flights	23546P
Range data size	18.1 GB
Base data size	299 MB
POS	262 MB
Image	N/A
Transfer date	November 24, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	No
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.155
RMSE for East Position (<4.0 cm)	1.675
RMSE for Down Position (<8.0 cm)	4.400
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000166
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.000495
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0053
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	47.66
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	3.65
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	153
<i>Maximum Height</i>	
Maximum Height	917.61 m
<i>Minimum Height</i>	
Minimum Height	363.27 m
<i>Classification (# of points)</i>	
Ground	251,837,143
Low vegetation	194,428,563
Medium vegetation	141,971,724
High vegetation	233,521,779
Building	16,939,875
Orthophoto	No
Processed by	Engr. Kenneth Solidum, Engr. Christy Lubiano, Engr. Gladys Mae Apat




Figure A-7.78 Solution Status




Figure A-7.79 Smoothed Performance Metric Parameters




Figure A-7.80 Best Estimated Trajectory




Figure A-7.81 Coverage of LiDAR data




Figure A-7.82 Image of data overlap




Figure A-7.83 Density map of merged LiDAR data




Figure A-7.84 Elevation difference between flight lines

Table A-7.13 Mission Summary Report for Mission Blk64D

Flight Area	Bukidnon
Mission Name	Blk64D
Inclusive Flights	23524P
Range data size	27 GB
Base data size	141 MB
POS	237 MB
Image	N/A
Transfer date	November 16, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	Yes
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.067
RMSE for East Position (<4.0 cm)	1.225
RMSE for Down Position (<8.0 cm)	2.340
<i>Boresight correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.000170
GPS position stdev (<0.01m)	0.000230
<i>Minimum % overlap (>25)</i>	
Ave point cloud density per sq.m. (>2.0)	0.0013
Elevation difference between strips (<0.20 m)	56.46
<i>Number of 1km x 1km blocks</i>	
Maximum Height	130
Minimum Height	1222.82 m
<i>Classification (# of points)</i>	
Ground	387.74 m
Low vegetation	226,612,345
Medium vegetation	226,612,345
High vegetation	181,833,367
Building	288,808,400
Orthophoto	18,950,286
Processed by	No
	Engr. Don Matthew Banatin, Engr. Mark Joshua Salvacion, Engr. Gladys Mae Apat




Figure A-7.85 Solution Status




Figure A-7.86 Smoothed Performance Metric Parameters




Figure A-7.87 Best Estimated Trajectory




Figure A-7.88 Coverage of LiDAR data




Figure A-7.89 Image of data overlap




Figure A-7.90 Density map of merged LiDAR data




Figure A-7.91 Elevation difference between flight lines

Table A-7.14 Mission Summary Report for Mission Blk64D_Additional

Flight Area	Bukidnon
Mission Name	Blk64D_Additional
Inclusive Flights	23524P
Range data size	27 GB
Base data size	141 MB
POS	237 MB
Image	N/A
Transfer date	November 16, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	Yes
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.067
RMSE for East Position (<4.0 cm)	1.225
RMSE for Down Position (<8.0 cm)	2.340
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000170
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.000230
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0013
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	50.73
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	5.11
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	131
<i>Maximum Height</i>	
Maximum Height	1061.97 m
<i>Minimum Height</i>	
Minimum Height	387.14 m
<i>Classification (# of points)</i>	
Ground	209,407,639
Low vegetation	107,127,411
Medium vegetation	148,329,008
High vegetation	101,853,025
Building	6,859,755
Orthophoto	No
Processed by	Engr. Don Matthew Banatin, Engr. Edgardo Gubatanga Jr., Engr. Czarina Jean Añonuevo




Figure A-7.92 Solution Status




Figure A-7.93 Smoothed Performance Metric Parameters




Figure A-7.94 Best Estimated Trajectory




Figure A-7.95 Coverage of LiDAR data




Figure A-7.96 Image of data overlap




Figure A-7.97 Density map of merged LiDAR data




Figure A-7.98 Elevation difference between flight lines

Table A-7.15 Mission Summary Report for Mission Blk64D_Supplement

Flight Area	Bukidnon
Mission Name	Blk64D_Supplement
Inclusive Flights	23536P
Range data size	22.9 GB
Base data size	146 MB
POS	235 MB
Image	N/A
Transfer date	November 24, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	No
PDOP (<3)	No
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.420
RMSE for East Position (<4.0 cm)	3.457
RMSE for Down Position (<8.0 cm)	3.628
<i>Boresight correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.000310
GPS position stdev (<0.01m)	0.0134
<i>Minimum % overlap (>25)</i>	
Ave point cloud density per sq.m. (>2.0)	4.80
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Maximum Height	1023.54 m
Minimum Height	531.72 m
<i>Classification (# of points)</i>	
Ground	30,760,771
Low vegetation	30,494,239
Medium vegetation	73,287,936
High vegetation	77,556,593
Building	7,311,967
Orthophoto	No
Processed by	Engr. Analyn Naldo, Engr. Melanie Hingpit, Engr Wilbert Ian San Juan




Figure A-7.99 Solution Status




Figure A-7.100 Smoothed Performance Metric Parameters




Figure A-7.101 Best Estimated Trajectory




Figure A-7.102 Coverage of LIDAR data




Figure A-7.103 Image of data overlap




Figure A-7.104 Density map of merged LiDAR data




Figure A-7.105 Elevation difference between flight lines

Table A-7.16 Mission Summary Report for Mission Blk64E

Flight Area	Bukidnon
Mission Name	Blk64E
Inclusive Flights	23486P
Range data size	13.2 GB
Base data size	210 MB
POS	208 MB
Image	N/A
Transfer date	November 16, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	No
PDOP (<3)	Yes
Baseline Length (<30km)	No
Processing Mode (<=1)	No
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.368
RMSE for East Position (<4.0 cm)	1.164
RMSE for Down Position (<8.0 cm)	2.180
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000789
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.001000
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0110
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	39.02
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	3.30
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	196
<i>Maximum Height</i>	
Maximum Height	1082.18 m
<i>Minimum Height</i>	
Minimum Height	577.92 m
<i>Classification (# of points)</i>	
Ground	246,263,221
Low vegetation	131,891,179
Medium vegetation	241,703,402
High vegetation	138,637,545
Building	3,391,281
Orthophoto	No
Processed by	Engr. Analyn Naldo, Engr. Merven Matthew Natino, Alex John Escobido




Figure A-7.106 Solution Status




Figure A-7.107 Smoothed Performance Metric Parameters




Figure A-7.108 Best Estimated Trajectory




Figure A-7.109 Coverage of LiDAR data




Figure A-7.110 Image of data overlap




Figure A-7.111 Density map of merged LiDAR data




Figure A-7.112 Elevation difference between flight lines

Table A-7.17 Mission Summary Report for Mission Blk64E_Supplement

Flight Area	Bukidnon
Mission Name	Blk64E_Supplement
Inclusive Flights	1714A & 1734A
Range data size	21 GB
Base data size	272 MB
POS	255MB
Image	N/A
Transfer date	November 16, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	No
Processing Mode (<=1)	No
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.368
RMSE for East Position (<4.0 cm)	1.460
RMSE for Down Position (<8.0 cm)	1.755
<i>Boresight correction stdev (<0.001deg)</i>	
Boresight correction stdev (<0.001deg)	0.000789
<i>IMU attitude correction stdev (<0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.001000
<i>GPS position stdev (<0.01m)</i>	
GPS position stdev (<0.01m)	0.0110
<i>Minimum % overlap (>25)</i>	
Minimum % overlap (>25)	41.22
<i>Ave point cloud density per sq.m. (>2.0)</i>	
Ave point cloud density per sq.m. (>2.0)	4.02
<i>Elevation difference between strips (<0.20 m)</i>	
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Number of 1km x 1km blocks	85
<i>Maximum Height</i>	
Maximum Height	955.21 m
<i>Minimum Height</i>	
Minimum Height	432.51 m
<i>Classification (# of points)</i>	
Ground	68,846,353
Low vegetation	66,115,774
Medium vegetation	119,803,226
High vegetation	114,461,628
Building	9,444,092
Orthophoto	No
Processed by	Engr. Analyn Naldo, Engr. Ma. Joanne Balaga, Engr. Karl Adrian Vergara




Figure A-7.113 Solution Status




Figure A-7.114 Smoothed Performance Metric Parameters




Figure A-7.115 Best Estimated Trajectory




Figure A-7.116 Coverage of LiDAR data



Figure A-7.117 Image of data overlap




Figure A-7.118 Density map of merged LiDAR data




Figure A-7.119 Elevation difference between flight lines

ANNEX 8. Sawaga Model Basin Parameters

Table A-8.1 Sawaga Model Basin Parameters

Basin Number	SCS Curve Number Loss			Clark Unit Hydrograph Transform		Initial Type	Recession Baseflow			
	Initial Abstraction (mm)	Curve Number	Impervious (%)	Time of Concentration (HR)	Storage Coefficient (HR)		Initial Discharge (M ³ /S)	Recession Constant	Threshold Type	Ratio to Peak
W2080	21.17368	71.88156	0	0.829395	3.06166	Discharge	0.11731	1	Ratio to Peak	0.15
W2100	25.61856	69.55596	0	0.883743	3.262253	Discharge	0.09407	1	Ratio to Peak	0.15
W2120	35.1472	65.04413	0	0.636216	2.348543	Discharge	0.074156	1	Ratio to Peak	0.15
W2130	33.03872	65.99147	0	0.559608	2.065728	Discharge	0.080874	1	Ratio to Peak	0.15
W2150	22.02376	71.42499	0	0.691971	2.55436	Discharge	0.10426	1	Ratio to Peak	0.15
W2160	13.80808	76.09842	0	0.1423506	0.525493	Discharge	0.002364	1	Ratio to Peak	0.15
W2170	13.27304	76.42418	0	0.272118	1.004483	Discharge	0.005661	1	Ratio to Peak	0.15
W2190	23.15984	70.82307	0	0.687624	2.538305	Discharge	0.091709	1	Ratio to Peak	0.15
W2200	21.19832	71.86874	8	0.544761	2.010913	Discharge	0.091937	1	Ratio to Peak	0.15
W2220	22.58872	71.12489	0	0.810894	2.993355	Discharge	0.13148	1	Ratio to Peak	0.15
W2230	35.52032	64.87997	8	0.674289	2.489095	Discharge	0.11985	1	Ratio to Peak	0.15
W2240	13.32936	76.38912	8	0.21462	0.7923	Discharge	0.004841	1	Ratio to Peak	0.15
W2270	18.30928	73.46417	0	0.784896	2.897405	Discharge	0.17318	1	Ratio to Peak	0.15
W2280	25.86584	69.43113	8	0.458556	1.692758	Discharge	0.062105	1	Ratio to Peak	0.15
W2310	40.88744	62.59883	0	0.301392	1.112545	Discharge	0.022646	1	Ratio to Peak	0.15
W2330	37.44136	64.04378	0	0.860874	3.177845	Discharge	0.14372	1	Ratio to Peak	0.15
W2370	19.33008	72.89217	0	1.031226	3.806698	Discharge	0.14216	1	Ratio to Peak	0.15
W2410	14.14864	75.89237	0	0.686931	2.535788	Discharge	0.087423	1	Ratio to Peak	0.15
W2430	13.67344	76.17965	0	0.646149	2.385165	Discharge	0.071401	1	Ratio to Peak	0.15
W2450	24.72448	70.01168	0	0.653919	2.413903	Discharge	0.092073	1	Ratio to Peak	0.15

Basin Number	SCS Curve Number Loss			Clark Unit Hydrograph Transform		Initial Type	Recession Baseflow			
	Initial Abstraction (mm)	Curve Number	Impervious (%)	Time of Concentration (HR)	Storage Coefficient (HR)		Initial Discharge (M ³ /S)	Recession Constant	Threshold Type	Ratio to Peak
W2460	13.31792	76.39682	0	0.334509	1.23481	Discharge	0.011502	1	Ratio to Peak	0.15
W2520	13.64	76.095	0	0.376614	1.39023	Discharge	0.011873	1	Ratio to Peak	0.15
W2570	15.71328	74.96042	0	0.906822	3.347515	Discharge	0.023056	1	Ratio to Peak	0.15
W2600	28.8552	67.9554	0	0.699237	2.58115	Discharge	0.10158	1	Ratio to Peak	0.15
W2670	13.64	76.095	0	0.0960645	0.35461	Discharge	0.001369	1	Ratio to Peak	0.15
W2740	16.1656	74.69537	0	0.813099	3.001478	Discharge	0.053911	1	Ratio to Peak	0.15
W2850	13.64	76.095	0	0.1295511	0.47823	Discharge	0.00044	1	Ratio to Peak	0.15
W3440	25.86408	69.43199	0	0.629706	2.324508	Discharge	0.049794	1	Ratio to Peak	0.15
W3450	31.0948	66.88922	0	0.840735	3.10346	Discharge	0.040864	1	Ratio to Peak	0.15

ANNEX 9. Sawaga Model Reach Parameters

Table A-9.1 Sawaga Model Reach Parameters

Reach Number	Muskingum Cunge Channel Routing						
	Time Step Method	Length (m)	Slope	Manning's n	Shape	Width	Side Slope
R 1 060	Automatic Fixed Interval	5460.7	0.001091	0.05	Trapezoid	34	0.5
R 1 100	Automatic Fixed Interval	402.15	0.008053	0.01	Trapezoid	34	0.5
R 3 470	Automatic Fixed Interval	8703.2	0.006935	0.09	Trapezoid	34	0.5
R 400	Automatic Fixed Interval	13821	0.020375	0.01	Trapezoid	34	0.5
R 420	Automatic Fixed Interval	1431.9	0.022777	0.01	Trapezoid	34	0.5
R 430	Automatic Fixed Interval	2131.1	0.014451	0.0001	Trapezoid	34	0.5
R 490	Automatic Fixed Interval	5418.5	0.020571	0.05	Trapezoid	34	0.5
R 510	Automatic Fixed Interval	1981.9	0.017666	0.0001	Trapezoid	34	0.5
R 560	Automatic Fixed Interval	4593	0.018328	0.01	Trapezoid	34	0.5
R 570	Automatic Fixed Interval	2502.2	0.013575	0.1	Trapezoid	34	0.5
R 660	Automatic Fixed Interval	1297.8	0.012533	0.1	Trapezoid	34	0.5
R 680	Automatic Fixed Interval	6857.9	0.002785	1	Trapezoid	34	0.5
R 840	Automatic Fixed Interval	3339.2	0.00264	1	Trapezoid	34	0.5
R 880	Automatic Fixed Interval	591.25	0.004065	1	Trapezoid	34	0.5

ANNEX 10. Sawaga Field Validation Points

Table A-10.1 Sawaga Field Validation Points

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event	Rain Return/ Scenario
	Lat	Long					
1	8.11910	125.14531	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
2	8.11722	125.14577	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
3	8.12302	125.14084	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
4	8.12510	125.13943	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
5	8.12740	125.13881	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
6	8.13035	125.13678	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
7	8.13090	125.13519	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
8	8.13319	125.13446	0.23	0.00	-0.23	Pablo/4Dec2012	5YR
9	8.13437	125.13259	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
10	8.13739	125.13276	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
11	8.13914	125.13172	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
12	8.14126	125.13241	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
13	8.13748	125.12915	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
14	8.13560	125.12939	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
15	8.13131	125.13211	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
16	8.12689	125.12446	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
17	8.11489	125.13581	0.08	0.00	-0.08	Pablo/4Dec2012	5YR
18	8.10075	125.14046	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
19	8.09839	125.14884	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
20	8.10009	125.15165	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
21	8.10318	125.15587	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
22	8.10182	125.16125	6.72	0.00	-6.72	Pablo/4Dec2012	5YR
23	8.10478	125.16039	4.50	0.00	-4.50	Pablo/4Dec2012	5YR
24	8.10193	125.15997	6.53	0.00	-6.53	Pablo/4Dec2012	5YR
25	8.09804	125.16442	12.05	0.30	-11.75	Pablo/4Dec2012	5YR
26	8.09711	125.16862	2.82	0.78	-2.04	Pablo/4Dec2012	5YR
27	8.09681	125.17267	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
28	8.09448	125.17560	1.48	0.80	-0.68	Pablo/4Dec2012	5YR
29	8.09497	125.17931	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
30	8.07839	125.14722	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
31	8.08218	125.14704	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
32	8.07978	125.16353	4.74	0.00	-4.74	Pablo/4Dec2012	5YR
33	8.07838	125.16082	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
34	8.08481	125.14996	0.08	0.00	-0.08	Pablo/4Dec2012	5YR
35	8.03645	125.13822	0.08	0.00	-0.08	Pablo/4Dec2012	5YR
36	8.02659	125.13947	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
37	8.02327	125.13928	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
38	8.02040	125.14146	0.09	0.00	-0.09	Pablo/4Dec2012	5YR
39	8.01833	125.14197	0.06	0.00	-0.06	Pablo/4Dec2012	5YR

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event	Rain Return/ Scenario
	Lat	Long					
40	8.01795	125.14304	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
41	8.03065	125.14343	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
42	7.99650	125.15581	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
43	7.99528	125.14968	0.68	0.00	-0.68	Pablo/4Dec2012	5YR
44	7.99719	125.14723	0.89	0.00	-0.89	Pablo/4Dec2012	5YR
45	7.99126	125.14976	0.90	0.00	-0.90	Pablo/4Dec2012	5YR
46	7.98980	125.15284	0.08	0.00	-0.08	Pablo/4Dec2012	5YR
47	7.98838	125.15510	0.08	0.00	-0.08	Pablo/4Dec2012	5YR
48	7.98625	125.15622	0.31	0.00	-0.31	Pablo/4Dec2012	5YR
49	7.98136	125.14365	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
50	7.98018	125.14217	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
51	7.97815	125.14064	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
52	7.97404	125.13961	0.08	0.00	-0.08	Pablo/4Dec2012	5YR
53	7.97057	125.13696	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
54	7.97309	125.11676	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
55	7.97843	125.12517	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
56	8.06459	125.16093	6.03	0.00	-6.03	Pablo/4Dec2012	5YR
57	8.06555	125.16147	4.50	0.00	-4.50	Pablo/4Dec2012	5YR
58	8.06092	125.17001	1.13	0.00	-1.13	Pablo/4Dec2012	5YR
59	8.05853	125.17349	0.37	0.20	-0.17	Pablo/4Dec2012	5YR
60	8.06132	125.16734	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
61	8.06265	125.16697	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
62	8.06410	125.16748	0.09	0.00	-0.09	Pablo/4Dec2012	5YR
63	8.06134	125.16413	0.18	0.20	0.02	Pablo/4Dec2012	5YR
64	8.06077	125.16027	1.10	0.00	-1.10	Pablo/4Dec2012	5YR
65	8.05855	125.16120	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
66	8.05776	125.16339	1.49	0.40	-1.09	Pablo/4Dec2012	5YR
67	8.05728	125.16123	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
68	8.05782	125.15857	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
69	8.05577	125.15981	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
70	8.05218	125.16236	0.09	0.00	-0.09	Pablo/4Dec2012	5YR
71	8.05065	125.16176	0.09	0.00	-0.09	Pablo/4Dec2012	5YR
72	8.05001	125.16353	0.08	0.00	-0.08	Pablo/4Dec2012	5YR
73	8.04957	125.16531	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
74	8.05116	125.16782	1.45	0.00	-1.45	Pablo/4Dec2012	5YR
75	8.05398	125.16925	0.38	0.00	-0.38	Pablo/4Dec2012	5YR
76	8.05207	125.16554	9.15	0.15	-9.00	Pablo/4Dec2012	5YR
77	8.04899	125.16901	1.33	0.20	-1.13	Pablo/4Dec2012	5YR
78	8.04692	125.17067	1.19	0.30	-0.89	Pablo/4Dec2012	5YR
79	8.04548	125.17190	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
80	8.03973	125.16919	0.26	0.00	-0.26	Pablo/4Dec2012	5YR
81	8.04359	125.16815	2.30	0.20	-2.10	Pablo/4Dec2012	5YR

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event	Rain Return/ Scenario
	Lat	Long					
82	8.04239	125.16710	5.01	0.40	-4.61	Pablo/4Dec2012	5YR
83	8.04746	125.16826	2.43	0.15	-2.28	Pablo/4Dec2012	5YR
84	8.04123	125.16186	2.82	0.70	-2.12	Pablo/4Dec2012	5YR
85	8.03946	125.15835	3.31	0.40	-2.91	Pablo/4Dec2012	5YR
86	8.04065	125.16358	3.52	0.00	-3.52	Pablo/4Dec2012	5YR
87	8.04640	125.16200	0.42	0.00	-0.42	Pablo/4Dec2012	5YR
88	8.04716	125.16484	0.10	0.10	0.00	Pablo/4Dec2012	5YR
89	8.04475	125.15785	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
90	8.03956	125.15366	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
91	8.03639	125.15612	4.11	0.60	-3.51	Pablo/4Dec2012	5YR
92	8.03788	125.15645	5.79	0.10	-5.69	Pablo/4Dec2012	5YR
93	8.03708	125.16221	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
94	8.03793	125.16407	0.19	0.00	-0.19	Pablo/4Dec2012	5YR
95	8.03936	125.16648	0.55	0.00	-0.55	Pablo/4Dec2012	5YR
96	8.03181	125.16753	0.63	0.00	-0.63	Pablo/4Dec2012	5YR
97	8.03557	125.15395	0.74	0.00	-0.74	Pablo/4Dec2012	5YR
98	8.03406	125.14994	2.54	0.80	-1.74	Pablo/4Dec2012	5YR
99	8.03105	125.14989	3.00	0.80	-2.20	Pablo/4Dec2012	5YR
100	8.02995	125.14937	1.75	0.10	-1.65	Pablo/4Dec2012	5YR
101	8.02668	125.14816	1.19	0.00	-1.19	Pablo/4Dec2012	5YR
102	8.02300	125.14802	2.26	0.00	-2.26	Pablo/4Dec2012	5YR
103	8.02125	125.14812	3.17	0.10	-3.07	Pablo/4Dec2012	5YR
104	8.03125	125.15454	0.09	0.00	-0.09	Pablo/4Dec2012	5YR
105	8.02699	125.15628	1.35	0.00	-1.35	Pablo/4Dec2012	5YR
106	8.02527	125.15412	1.78	0.10	-1.68	Pablo/4Dec2012	5YR
107	8.02517	125.15372	1.78	0.20	-1.58	Pablo/4Dec2012	5YR
108	8.02689	125.15657	0.81	0.10	-0.71	Pablo/4Dec2012	5YR
109	8.02570	125.15757	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
110	8.01648	125.14895	0.63	0.15	-0.48	Pablo/4Dec2012	5YR
111	8.01515	125.14595	1.02	0.60	-0.42	Pablo/4Dec2012	5YR
112	8.01591	125.14540	1.16	0.80	-0.36	Pablo/4Dec2012	5YR
113	8.01387	125.14555	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
114	8.01250	125.14459	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
115	8.00819	125.14260	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
116	8.00702	125.14186	0.06	0.10	0.04	Pablo/4Dec2012	5YR
117	8.00252	125.14074	1.79	0.10	-1.69	Pablo/4Dec2012	5YR
118	8.00567	125.14499	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
119	8.00427	125.14496	0.38	0.00	-0.38	Pablo/4Dec2012	5YR
120	8.00483	125.15544	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
121	8.01515	125.15725	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
122	7.99258	125.12672	2.25	0.80	-1.45	Pablo/4Dec2012	5YR
123	7.99308	125.12504	0.47	0.40	-0.07	Pablo/4Dec2012	5YR

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event	Rain Return/ Scenario
	Lat	Long					
124	7.99294	125.12406	0.72	0.10	-0.62	Pablo/4Dec2012	5YR
125	7.99421	125.12166	1.64	0.96	-0.68	Pablo/4Dec2012	5YR
126	7.99581	125.12059	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
127	7.99590	125.11872	0.45	0.00	-0.45	Pablo/4Dec2012	5YR
128	7.99557	125.11600	0.09	0.00	-0.09	Pablo/4Dec2012	5YR
129	7.99418	125.11554	0.59	0.00	-0.59	Pablo/4Dec2012	5YR
130	7.99558	125.11392	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
131	7.99586	125.11067	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
132	8.01231	125.13431	1.03	0.60	-0.43	Pablo/4Dec2012	5YR
133	8.00498	125.13331	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
134	8.00311	125.13001	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
135	8.00090	125.12741	0.09	0.17	0.08	Pablo/4Dec2012	5YR
136	7.99677	125.12931	2.49	1.24	-1.25	Pablo/4Dec2012	5YR
137	7.99687	125.12585	1.90	0.40	-1.50	Pablo/4Dec2012	5YR
138	8.00485	125.12197	5.76	0.20	-5.56	Pablo/4Dec2012	5YR
139	7.99875	125.13212	0.10	0.10	0.00	Pablo/4Dec2012	5YR
140	7.99578	125.13598	2.25	0.00	-2.25	Pablo/4Dec2012	5YR
141	7.99643	125.13770	0.93	0.00	-0.93	Pablo/4Dec2012	5YR
142	7.99252	125.13393	2.30	0.40	-1.90	Pablo/4Dec2012	5YR
143	7.99201	125.13215	1.56	0.60	-0.96	Pablo/4Dec2012	5YR
144	7.99292	125.13200	1.55	0.60	-0.95	Pablo/4Dec2012	5YR
145	7.99135	125.13454	3.64	2.14	-1.50	Pablo/4Dec2012	5YR
146	7.98912	125.13417	1.04	1.20	0.16	Pablo/4Dec2012	5YR
147	7.98544	125.13453	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
148	7.98383	125.13382	1.16	0.00	-1.16	Pablo/4Dec2012	5YR
149	7.96449	125.13688	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
150	7.96247	125.13878	2.92	0.70	-2.22	Pablo/4Dec2012	5YR
151	7.96688	125.14028	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
152	7.97043	125.14114	0.73	0.60	-0.13	Pablo/4Dec2012	5YR
153	7.98372	125.13671	0.18	0.00	-0.18	Pablo/4Dec2012	5YR
154	7.98643	125.14190	3.64	1.60	-2.04	Pablo/4Dec2012	5YR
155	7.98416	125.14119	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
156	7.98734	125.13901	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
157	7.98799	125.13904	0.08	0.00	-0.08	Pablo/4Dec2012	5YR
158	7.98777	125.13914	0.06	0.20	0.14	Pablo/4Dec2012	5YR
159	7.98730	125.14025	0.06	1.60	1.54	Pablo/4Dec2012	5YR
160	7.98744	125.14081	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
161	7.98785	125.14010	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
162	7.98882	125.13994	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
163	7.98856	125.13893	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
164	7.98974	125.13871	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
165	7.99427	125.13838	1.59	0.00	-1.59	Pablo/4Dec2012	5YR

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event	Rain Return/ Scenario
	Lat	Long					
166	7.99361	125.13824	1.38	0.00	-1.38	Pablo/4Dec2012	5YR
167	7.99089	125.13784	0.52	0.00	-0.52	Pablo/4Dec2012	5YR
168	7.99070	125.13777	0.38	0.00	-0.38	Pablo/4Dec2012	5YR
169	7.99272	125.13776	1.17	0.00	-1.17	Pablo/4Dec2012	5YR
170	7.99149	125.13666	1.12	0.00	-1.12	Pablo/4Dec2012	5YR
171	7.99229	125.13537	1.65	0.00	-1.65	Pablo/4Dec2012	5YR
172	7.99301	125.13614	1.88	0.00	-1.88	Pablo/4Dec2012	5YR
173	7.99307	125.13721	1.79	0.00	-1.79	Pablo/4Dec2012	5YR
174	7.99358	125.13397	1.34	0.00	-1.34	Pablo/4Dec2012	5YR
175	7.99549	125.13279	2.76	0.00	-2.76	Pablo/4Dec2012	5YR
176	7.99429	125.13361	1.28	0.70	-0.58	Pablo/4Dec2012	5YR
177	7.98243	125.07909	3.54	0.00	-3.54	Pablo/4Dec2012	5YR
178	7.98262	125.07904	0.08	1.20	1.12	Pablo/4Dec2012	5YR
179	7.98315	125.08058	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
180	7.98351	125.08204	0.08	0.00	-0.08	Pablo/4Dec2012	5YR
181	7.98518	125.08515	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
182	7.98514	125.08594	0.10	0.10	0.00	Pablo/4Dec2012	5YR
183	7.98639	125.08502	0.65	0.14	-0.51	Pablo/4Dec2012	5YR
184	7.98771	125.08479	0.10	0.15	0.05	Pablo/4Dec2012	5YR
185	7.97813	125.05257	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
186	7.89410	125.07421	0.10	0.00	-0.10	Pablo/4Dec2012	5YR
187	7.99016	125.10144	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
188	7.99107	125.10119	1.96	0.00	-1.96	Pablo/4Dec2012	5YR
189	7.99135	125.10132	1.83	0.00	-1.83	Pablo/4Dec2012	5YR
190	7.99045	125.10335	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
191	7.99264	125.10537	3.02	0.00	-3.02	Pablo/4Dec2012	5YR
192	7.99107	125.10503	1.16	0.00	-1.16	Pablo/4Dec2012	5YR
193	7.99049	125.10595	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
194	7.99012	125.10722	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
195	7.99006	125.10900	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
196	7.98922	125.11728	0.09	0.00	-0.09	Pablo/4Dec2012	5YR
197	7.99282	125.11523	1.78	0.00	-1.78	Pablo/4Dec2012	5YR
198	7.99010	125.12104	0.39	0.00	-0.39	Pablo/4Dec2012	5YR
199	7.99219	125.12092	0.13	0.00	-0.13	Pablo/4Dec2012	5YR
200	7.99215	125.12229	1.62	0.00	-1.62	Pablo/4Dec2012	5YR
201	7.99208	125.12299	2.33	0.00	-2.33	Pablo/4Dec2012	5YR
202	7.98781	125.12911	1.05	0.00	-1.05	Pablo/4Dec2012	5YR
203	7.98893	125.13548	7.32	0.00	-7.32	Pablo/4Dec2012	5YR
204	7.99056	125.12930	2.76	0.10	-2.66	Pablo/4Dec2012	5YR
205	7.99028	125.12858	2.51	0.10	-2.41	Pablo/4Dec2012	5YR
206	7.99079	125.12677	0.98	0.00	-0.98	Pablo/4Dec2012	5YR
207	7.98736	125.06920	0.06	0.00	-0.06	Pablo/4Dec2012	5YR

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event	Rain Return/ Scenario
	Lat	Long					
208	7.99132	125.12676	3.06	0.00	-3.06	Pablo/4Dec2012	5YR
209	7.99132	125.12676	3.06	0.00	-3.06	Pablo/4Dec2012	5YR
210	7.98691	125.13239	1.63	0.00	-1.63	Pablo/4Dec2012	5YR
211	7.98669	125.13340	0.38	0.00	-0.38	Pablo/4Dec2012	5YR
212	7.98668	125.13341	0.38	0.00	-0.38	Pablo/4Dec2012	5YR
213	7.98677	125.13480	0.38	0.00	-0.38	Pablo/4Dec2012	5YR
214	7.98730	125.13740	2.26	0.00	-2.26	Pablo/4Dec2012	5YR
215	7.98769	125.13789	2.59	0.00	-2.59	Pablo/4Dec2012	5YR
216	7.98646	125.13727	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
217	7.98547	125.13774	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
218	7.87500	125.19466	0.93	0.52	-0.41	Pablo/4Dec2012	5YR
219	7.87577	125.19654	5.89	0.90	-4.99	Pablo/4Dec2012	5YR
220	7.87584	125.19230	2.12	1.00	-1.12	Pablo/4Dec2012	5YR
221	7.87586	125.19238	2.62	0.00	-2.62	Pablo/4Dec2012	5YR
222	7.87784	125.19069	3.63	0.70	-2.93	Pablo/4Dec2012	5YR
223	7.87817	125.19091	5.39	0.00	-5.39	Pablo/4Dec2012	5YR
224	7.88078	125.18753	1.19	0.10	-1.09	Pablo/4Dec2012	5YR
225	7.88459	125.18764	1.70	0.20	-1.50	Pablo/4Dec2012	5YR
226	7.88499	125.18607	2.41	0.50	-1.91	Pablo/4Dec2012	5YR
227	7.88922	125.18310	2.04	0.00	-2.04	Pablo/4Dec2012	5YR
228	7.89267	125.17876	0.68	0.50	-0.18	Pablo/4Dec2012	5YR
229	7.90059	125.13093	0.39	0.20	-0.19	Pablo/4Dec2012	5YR
230	7.90086	125.12312	0.13	0.00	-0.13	Pablo/4Dec2012	5YR
231	7.90084	125.12313	0.15	0.30	0.15	Pablo/4Dec2012	5YR
232	7.93285	125.10162	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
233	7.93204	125.09364	0.26	0.20	-0.06	Pablo/4Dec2012	5YR
234	7.92029	125.09243	0.19	2.00	1.81	Pablo/4Dec2012	5YR
235	7.89537	125.17766	0.23	0.80	0.57	Pablo/4Dec2012	5YR
236	7.89589	125.17616	0.10	0.70	0.60	Pablo/4Dec2012	5YR
237	7.89853	125.17667	1.17	1.05	-0.12	Pablo/4Dec2012	5YR
238	7.90170	125.17512	0.06	0.80	0.74	Pablo/4Dec2012	5YR
239	7.90018	125.18051	0.21	0.00	-0.21	Pablo/4Dec2012	5YR
240	7.90643	125.17934	0.38	0.00	-0.38	Pablo/4Dec2012	5YR
241	7.90523	125.17504	0.13	0.00	-0.13	Pablo/4Dec2012	5YR
242	7.90523	125.16772	0.23	0.42	0.19	Pablo/4Dec2012	5YR
243	7.90431	125.16518	0.87	0.45	-0.42	Pablo/4Dec2012	5YR
244	7.90359	125.16083	0.81	0.70	-0.11	Pablo/4Dec2012	5YR
245	7.90405	125.16003	0.06	0.30	0.24	Pablo/4Dec2012	5YR
246	7.90314	125.15760	0.21	0.48	0.27	Pablo/4Dec2012	5YR
247	7.90098	125.15694	0.45	0.40	-0.05	Pablo/4Dec2012	5YR
248	7.90093	125.15725	0.72	1.20	0.48	Pablo/4Dec2012	5YR
249	7.89833	125.14976	0.06	0.20	0.14	Pablo/4Dec2012	5YR

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event	Rain Return/ Scenario
	Lat	Long					
250	7.90073	125.14791	0.39	0.30	-0.09	Pablo/4Dec2012	5YR
251	7.90071	125.13925	0.06	0.00	-0.06	Pablo/4Dec2012	5YR
252	7.90662	125.15590	0.72	0.00	-0.72	Pablo/4Dec2012	5YR
253	7.90953	125.15612	0.86	0.30	-0.56	Pablo/4Dec2012	5YR
254	7.90978	125.15620	1.53	0.00	-1.53	Pablo/4Dec2012	5YR
255	7.90577	125.16048	0.38	0.55	0.17	Pablo/4Dec2012	5YR
256	7.90590	125.16044	0.31	0.00	-0.31	Pablo/4Dec2012	5YR
257	7.90891	125.16487	0.08	0.80	0.72	Pablo/4Dec2012	5YR
258	7.91271	125.17042	0.52	0.40	-0.12	Pablo/4Dec2012	5YR
259	7.91750	125.17247	0.16	0.16	0.00	Pablo/4Dec2012	5YR
260	7.91454	125.17368	0.52	0.00	-0.52	Pablo/4Dec2012	5YR
261	7.91528	125.17915	0.45	0.00	-0.45	Pablo/4Dec2012	5YR
262	7.91510	125.18481	0.97	0.00	-0.97	Pablo/4Dec2012	5YR
263	7.91557	125.18819	2.40	0.00	-2.40	Pablo/4Dec2012	5YR
264	7.91373	125.18992	0.40	0	-0.40	Pablo/4Dec2012	5YR
265	7.91645	125.19196	2.95	0.4	-2.55	Pablo/4Dec2012	5YR
266	7.91633	125.19207	2.47	1	-1.47	Pablo/4Dec2012	5YR
267	7.91724	125.19469	1.81	0.1	-1.71	Pablo/4Dec2012	5YR
268	7.94716	125.10493	0.08	0	-0.08	Pablo/4Dec2012	5YR
269	7.92931	125.09663	0.06	0	-0.06	Pablo/4Dec2012	5YR
270	7.92010	125.09236	0.10	0	-0.10	Pablo/4Dec2012	5YR
271	7.94416	125.10332	0.87	1.1	0.23	Pablo/4Dec2012	5YR
272	7.94398	125.10301	4.72	0.2	-4.52	Pablo/4Dec2012	5YR
273	7.94399	125.10292	4.80	1.5	-3.30	Pablo/4Dec2012	5YR
274	7.94909	125.10347	3.01	0.5	-2.51	Pablo/4Dec2012	5YR
275	7.94785	125.10430	2.48	1.2	-1.28	Pablo/4Dec2012	5YR
276	7.94193	125.10748	1.79	0.9	-0.89	Pablo/4Dec2012	5YR
277	7.94054	125.10749	1.38	0.45	-0.93	Pablo/4Dec2012	5YR
278	7.93916	125.10800	2.34	0.4	-1.94	Pablo/4Dec2012	5YR
279	7.93787	125.10852	1.04	0.3	-0.74	Pablo/4Dec2012	5YR
280	7.93759	125.10868	0.93	0.1	-0.83	Pablo/4Dec2012	5YR
281	7.93256	125.11006	1.07	0.3	-0.77	Pablo/4Dec2012	5YR
282	7.97220	125.23444	1.43	0.5	-0.93	Pablo/4Dec2012	5YR
283	7.95867	125.22288	0.10	0.25	0.15	Pablo/4Dec2012	5YR
284	7.94374	125.15541	3.23	0.8	-2.43	Pablo/4Dec2012	5YR
285	7.94065	125.15563	0.58	0	-0.58	Pablo/4Dec2012	5YR
286	7.96357	125.18858	1.38	0.2	-1.18	Pablo/4Dec2012	5YR
287	7.96468	125.19249	2.29	1.1	-1.19	Pablo/4Dec2012	5YR
288	7.89993	125.10539	0.22	1.6	1.38	Pablo/4Dec2012	5YR
289	7.90787	125.09480	0.41	0	-0.41	Pablo/4Dec2012	5YR
290	7.91003	125.09760	0.21	1.5	1.29	Pablo/4Dec2012	5YR
291	7.91004	125.09765	0.29	2.5	2.21	Pablo/4Dec2012	5YR

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event	Rain Return/ Scenario
	Lat	Long					
292	7.90783	125.09686	2.86	2.5	-0.36	Pablo/4Dec2012	5YR
293	7.91123	125.09332	1.17	0	-1.17	Pablo/4Dec2012	5YR
294	7.91231	125.09548	0.30	0	-0.30	Pablo/4Dec2012	5YR
295	7.91308	125.09681	0.42	1.9	1.48	Pablo/4Dec2012	5YR
296	7.91307	125.09684	0.42	0.6	0.18	Pablo/4Dec2012	5YR
297	7.91338	125.09642	0.06	0	-0.06	Pablo/4Dec2012	5YR
298	7.91427	125.09606	0.39	0	-0.39	Pablo/4Dec2012	5YR
299	7.91429	125.09611	0.32	1	0.68	Pablo/4Dec2012	5YR
300	7.91525	125.09529	1.35	0.6	-0.75	Pablo/4Dec2012	5YR
301	7.91526	125.09523	1.32	0.3	-1.02	Pablo/4Dec2012	5YR
302	7.91516	125.09413	0.42	0	-0.42	Pablo/4Dec2012	5YR
303	7.91357	125.09396	1.16	0	-1.16	Pablo/4Dec2012	5YR
304	7.98766	125.13781	2.60	0.3	-2.30	Pablo/4Dec2012	5YR
305	7.98747	125.13764	3.09	0.9	-2.19	Pablo/4Dec2012	5YR
306	7.99001	125.10896	0.06	0.3	0.24	Pablo/4Dec2012	5YR
307	7.98587	125.09918	0.06	0.3	0.24	Pablo/4Dec2012	5YR
308	7.99287	125.13769	1.34	0.2	-1.14	Pablo/4Dec2012	5YR
309	7.93698	125.12522	1.13	0.1	-1.03	Pablo/4Dec2012	5YR
310	7.92940	125.12175	1.10	0	-1.10	Pablo/4Dec2012	5YR
311	7.92038	125.12239	0.06	0	-0.06	Pablo/4Dec2012	5YR
312	7.91989	125.12042	0.06	0	-0.06	Pablo/4Dec2012	5YR
313	7.91501	125.11501	0.08	0	-0.08	Pablo/4Dec2012	5YR
314	7.91892	125.11500	0.06	0	-0.06	Pablo/4Dec2012	5YR
315	7.91906	125.11493	0.08	0	-0.08	Pablo/4Dec2012	5YR
316	7.91863	125.11286	0.10	0	-0.10	Pablo/4Dec2012	5YR
317	7.91992	125.10463	0.47	0	-0.47	Pablo/4Dec2012	5YR
318	7.90050	125.11138	0.06	0	-0.06	Pablo/4Dec2012	5YR
319	7.90390	125.11614	0.06	0	-0.06	Pablo/4Dec2012	5YR
320	7.90520	125.11918	0.06	0	-0.06	Pablo/4Dec2012	5YR
321	7.91155	125.12609	0.06	0	-0.06	Pablo/4Dec2012	5YR
322	7.91360	125.13369	0.09	0	-0.09	Pablo/4Dec2012	5YR
323	7.93993	125.16057	0.06	0	-0.06	Pablo/4Dec2012	5YR
324	7.94253	125.15861	4.45	0	-4.45	Pablo/4Dec2012	5YR
325	7.94309	125.15622	2.76	0	-2.76	Pablo/4Dec2012	5YR
326	7.94020	125.15426	0.13	0	-0.13	Pablo/4Dec2012	5YR
327	7.94029	125.15412	0.06	0.2	0.14	Pablo/4Dec2012	5YR
328	7.94238	125.15068	3.01	0	-3.01	Pablo/4Dec2012	5YR
329	7.94408	125.14477	3.64	0	-3.64	Pablo/4Dec2012	5YR
330	7.93382	125.15864	0.06	0	-0.06	Pablo/4Dec2012	5YR
331	7.93795	125.14506	0.10	0	-0.10	Pablo/4Dec2012	5YR
332	7.93811	125.13908	0.06	0	-0.06	Pablo/4Dec2012	5YR
333	7.93856	125.12827	1.62	0	-1.62	Pablo/4Dec2012	5YR

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event	Rain Return/ Scenario
	Lat	Long					
334	7.93988	125.11536	0.06	0	-0.06	Pablo/4Dec2012	5YR
335	7.93523	125.11494	1.13	0	-1.13	Pablo/4Dec2012	5YR
336	7.93428	125.11530	2.40	0	-2.40	Pablo/4Dec2012	5YR
337	7.92998	125.11416	0.06	0	-0.06	Pablo/4Dec2012	5YR
338	7.93004	125.11399	1.33	0	-1.33	Pablo/4Dec2012	5YR
339	7.92806	125.11451	1.70	0	-1.70	Pablo/4Dec2012	5YR
340	7.93486	125.10440	0.13	0	-0.13	Pablo/4Dec2012	5YR
341	7.93557	125.10533	0.93	0.25	-0.68	Pablo/4Dec2012	5YR
342	7.93560	125.10533	0.93	0	-0.93	Pablo/4Dec2012	5YR
343	7.96926	125.13745	0.39	0	-0.39	Pablo/4Dec2012	5YR
344	7.98717	125.13413	2.85	0.5	-2.35	Pablo/4Dec2012	5YR
345	7.90476	125.09809	2.12	2.5	0.38	Pablo/4Dec2012	5YR
346	7.90532	125.09986	1.69	2.15	0.46	Pablo/4Dec2012	5YR
347	7.90372	125.10327	0.06	0.9	0.84	Pablo/4Dec2012	5YR
348	7.90092	125.10483	0.16	1.7	1.54	Pablo/4Dec2012	5YR
349	7.89938	125.10635	0.13	1	0.87	Pablo/4Dec2012	5YR
350	7.89962	125.10470	0.42	1.55	1.13	Pablo/4Dec2012	5YR
351	7.90551	125.10738	0.06	0.9	0.84	Pablo/4Dec2012	5YR
352	7.90960	125.10865	0.06	0.4	0.34	Pablo/4Dec2012	5YR
353	7.90974	125.10853	0.06	0.2	0.14	Pablo/4Dec2012	5YR
354	7.90976	125.11195	0.06	0.5	0.44	Pablo/4Dec2012	5YR
355	7.90752	125.11193	0.13	0	-0.13	Pablo/4Dec2012	5YR
356	7.90517	125.11005	0.08	0.9	0.82	Pablo/4Dec2012	5YR
357	7.90513	125.11005	0.08	0.5	0.42	Pablo/4Dec2012	5YR
358	7.90741	125.10406	0.06	0.45	0.39	Pablo/4Dec2012	5YR
359	7.90787	125.10638	0.06	0.7	0.64	Pablo/4Dec2012	5YR
360	7.91071	125.10449	0.97	1.5	0.53	Pablo/4Dec2012	5YR
361	7.91387	125.10375	0.06	1.3	1.24	Pablo/4Dec2012	5YR
362	7.91475	125.10603	0.06	1	0.94	Pablo/4Dec2012	5YR
363	7.91819	125.10105	0.10	1.2	1.10	Pablo/4Dec2012	5YR
364	7.91594	125.09727	0.13	2	1.87	Pablo/4Dec2012	5YR
365	8.04938	125.16784	2.74	0	-2.74	Pablo/4Dec2012	5YR
366	8.04864	125.16915	1.71	0.3	-1.41	Pablo/4Dec2012	5YR
367	8.02570	125.15653	1.53	0	-1.53	Pablo/4Dec2012	5YR
368	8.02569	125.15662	1.15	0	-1.15	Pablo/4Dec2012	5YR
369	8.00326	125.15519	0.08	0	-0.08	Pablo/4Dec2012	5YR
370	7.97855	125.14886	1.49	0.4	-1.09	Pablo/4Dec2012	5YR
371	7.97849	125.14868	2.05	1	-1.05	Pablo/4Dec2012	5YR
372	7.97842	125.14835	1.29	0.35	-0.94	Pablo/4Dec2012	5YR
373	7.99980	125.19622	0.40	0.2	-0.20	Pablo/4Dec2012	5YR
374	7.94818	125.22582	1.50	0	-1.50	Pablo/4Dec2012	5YR
375	7.95010	125.21651	2.61	0.7	-1.91	Pablo/4Dec2012	5YR

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event	Rain Return/Scenario
	Lat	Long					
376	7.94874	125.21925	3.39	1.2	-2.19	Pablo/4Dec2012	5YR
377	7.95049	125.21418	3.06	1	-2.06	Pablo/4Dec2012	5YR
378	7.94740	125.21376	2.76	1.3	-1.46	Pablo/4Dec2012	5YR
379	7.94797	125.21633	2.53	0.1	-2.43	Pablo/4Dec2012	5YR
380	7.94302	125.20920	1.17	0.3	-0.87	Pablo/4Dec2012	5YR
381	7.94971	125.20814	2.00	1.2	-0.80	Pablo/4Dec2012	5YR
382	7.95289	125.19914	1.19	1.5	0.31	Pablo/4Dec2012	5YR
383	7.95346	125.19940	1.16	1.7	0.54	Pablo/4Dec2012	5YR
384	7.95345	125.19939	1.16	0.1	-1.06	Pablo/4Dec2012	5YR
385	7.96064	125.19750	0.06	1.3	1.24	Pablo/4Dec2012	5YR
386	7.96065	125.19751	0.06	0.25	0.19	Pablo/4Dec2012	5YR
387	7.96274	125.19557	1.13	2	0.87	Pablo/4Dec2012	5YR
388	7.96448	125.19425	0.31	1.5	1.19	Pablo/4Dec2012	5YR
389	7.96554	125.19313	1.02	0.3	-0.72	Pablo/4Dec2012	5YR
390	7.96553	125.19320	0.94	0.2	-0.74	Pablo/4Dec2012	5YR
391	7.96346	125.19146	2.20	0.45	-1.75	Pablo/4Dec2012	5YR
392	7.96378	125.19139	2.53	0.9	-1.63	Pablo/4Dec2012	5YR
393	7.96400	125.18978	1.13	0	-1.13	Pablo/4Dec2012	5YR
394	7.95896	125.18883	1.33	0.4	-0.93	Pablo/4Dec2012	5YR
395	7.95744	125.18357	2.47	1.4	-1.07	Pablo/4Dec2012	5YR
396	7.95635	125.18054	1.33	0.5	-0.83	Pablo/4Dec2012	5YR
397	7.95643	125.18054	1.33	1.5	0.17	Pablo/4Dec2012	5YR
398	7.95602	125.17902	1.47	1	-0.47	Pablo/4Dec2012	5YR
399	7.95299	125.18290	1.36	1	-0.36	Pablo/4Dec2012	5YR
400	7.94553	125.17717	1.02	0	-1.02	Pablo/4Dec2012	5YR
401	7.94574	125.17572	0.93	0	-0.93	Pablo/4Dec2012	5YR
402	7.94649	125.17485	2.05	0.3	-1.75	Pablo/4Dec2012	5YR
403	7.94363	125.16718	0.06	2	1.94	Pablo/4Dec2012	5YR
404	7.94437	125.16824	1.70	2	0.30	Pablo/4Dec2012	5YR

ANNEX 11. Educational Institutions Affected by flooding in Sawaga Flood Plain

Table A-11.1 Educational Institutions Affected by flooding in Sawaga Flood Plain

Bukidnon				
Lantapan				
Building Name	Barangay	Rainfall Scenario		
		5-year	25-year	100-year
Bantuanon Elementary School	Bantuanon			
Bugcaon Elementary School	Bugcaon			
Bugcaon National High School	Bugcaon		Medium	Medium
Elementary School	Kulasihan			
Valbueco Elementary School	Kulasihan		Low	High
Lantapan Central Elementary School	Poblacion	Low	Low	Medium

Bukidnon				
Malaybalay City				
Building Name	Barangay	Rainfall Scenario		
		5-year	25-year	100-year
Elementary School	Apo Macote			
Bangcud National High School	Bangcud	High	High	High
Tigre Day Care Center	Bangcud		Low	Medium
Casisang Elementary School	Barangay 7			
Natid Asan Elementary School	Barangay 9			
Agricultural Training Institute	Casisang			
Day Care Center	Casisang			
Jan Jose Elementary School	Casisang			
Mabuhay Elementary School	Casisang	Medium	High	High
Private School	Casisang			
Bishop Han Theological Seminary	Laguitas			
Laguitas Elementary School	Laguitas			
Laguitas Naional High School	Laguitas			
Aglayan Central School	Linabo	Medium	Medium	Medium
Aglayan National High School	Linabo			Low
Linabo Central Elementary School	Linabo			
Linabo Community Learning Center	Linabo			
Saint Micheal High Schoo	Linabo			
Day Carem Center	Managok	High	High	High

Managok Elementary School	Managok	Low	Low	Low
Managok National High School	Managok			
Sawaga Elementary school	Managok	High	High	High
Day Care Center	San Jose	High	High	High
Mabuhay Elementary School	San Jose	High	High	High
Malaybalay City National High School	San Jose	Low	Low	Low
Nalagpag Day Care Center	San Martin	Low	Low	Low
Padernal Elementary School	Santo Niño		Low	Low
Bangcud Central School	Simaya	Medium	High	High
Binalbagan Day Care Center	Simaya		Low	Low
Binalbagan Elementary School	Simaya		Low	Low
Bukidnon Fundamental Baptist Seminary	Simaya			
Child Friendly Day Care Center	Simaya		Low	Low
Elementary School	Simaya			
Nalagpag Elementary School	Simaya	Medium	Medium	Medium
San Martin Agro-industrial High School	Simaya			
San Martin Day Care Center	Simaya	Medium	Medium	Medium
San Martin Elementary School	Simaya	Medium	Medium	Medium
Simaya Elementary School	Simaya			
Sinanglanan Day Care Center	Simaya		Low	Low
Soso-on Day Care Center	Simaya	Medium	Medium	Medium
St. Isidore Academy	Simaya		Low	Low
SunBeam Christian Academy of Bangcud	Simaya	Low	Medium	Medium
Apo Macote Day Care Center	Sinanglanan	Low	Medium	Medium
Apo Macote Elementary School	Sinanglanan	Low	Medium	Medium
Elementary School	Sinanglanan			
Sunshine Day Care Center	Violeta	Medium	High	High

Bukidnon				
Valencia City				
Building Name	Barangay	Rainfall Scenario		
		5-year	25-year	100-year
ACLC	Bagontaas	High	High	High
Bagontaas Adventist Elementary School	Bagontaas			
Bagontaas Central Elementary School	Bagontaas			Low
Casiphia Baptist Christian Academ Inc.	Bagontaas	Low	Low	Low
Central Mindanao Theological School	Bagontaas	Medium	High	High
College	Bagontaas	Medium	High	High
Day Care Center	Bagontaas			
First Fruit Christian Academy	Bagontaas			
Mountain View College ANNEX	Bagontaas	Low	Low	Low
School	Bagontaas			Low
Valencia Colleges	Bagontaas			
Batangan Central School	Batangan		Medium	High
DayCare Center	Batangan		Medium	Medium
Jupiter Day Care Center	Batangan		Medium	High
Colonia elementary School	Colonia	Low	Medium	Medium
Day Care Center	Colonia	Low	Medium	Medium
Padernal Elementary School	Colonia			Low
Day Care Center	Kahapunan	High	High	High
Christian Learning Center	Laligan	Low	Medium	Medium
Gold Day Care Center	Laligan	Medium	Medium	Medium
Laligan Central School	Laligan	Medium	Medium	Medium
Saint Joseph High School	Laligan	Medium	High	High
Tongantongan National High School	Laligan	Medium	Medium	High
Day Care Center	Lumbayao	High	High	High
Lumbayao Elementary School	Lumbayao	High	High	High
High School	Lumbo			
I.B.A College of Mindanao	Lumbo			
San Agustin Institute of Technology	Lumbo	Low	Low	Low
San Agustin Institute of Technology ANNEX	Lumbo	Low	Low	Medium
TESDA School	Lumbo	Low	Low	Medium
Valencia National High School	Lumbo	Medium	Medium	Medium

Lurugan Elementary School	Lurogan			
Dabongdabong Elementary School	Mailag		Low	Low
Good Counsel High School	Mailag		Low	Low
Mailag Elementary School	Mailag		Low	
Seventh Day Adventist School	Mailag			
Nabag.O Elementary School	Nabago	Medium	Medium	High
Faith Christian School	Poblacion	Medium	Medium	High
High School	Poblacion	High	High	High
Review Center	Poblacion	Medium	High	High
STI	Poblacion		Medium	Medium
Valencia Baptist Christian Academy	Poblacion	Low	Low	Medium
Valencia City Adventist Elementary School	Poblacion	High	High	High
Valencia City Central School	Poblacion	Medium	High	High
Valencia National High School	Poblacion	Low	Medium	High
Lurugan Day Care Center	San Carlos			
Lurugan Elementary School	San Carlos			
Lurugan National High School	San Carlos			
San Carlos Elementary School	San Carlos			
San Isidro Elementary School	San Isidro	Medium	High	High
Valencia City High School	San Isidro	High	High	High
Sinabuagan Elementary School	Sinabuagan	Medium	High	High
Day Care Center	Sugod			
Scorpion Day Care Center	Sugod	Medium	Medium	Medium
Adarna Day Care Center	Tongantongan	Medium	High	High
Araneta Elementary School	Tongantongan			
Fundamental Baptist School	Tongantongan	Medium	Medium	Medium
Mercury Day Care Center	Tongantongan	Low	Low	Low
San Vicente Elementary School	Tongantongan		Low	Medium
Tongantongan Elementary School	Tongantongan	Low	Medium	Medium
Cidrec Cumlat Memorial Institute	Vintar	Medium	High	High
Kahaponan Elementary School	Vintar		Medium	High
Vintar Elementary School	Vintar	Low	Medium	High

ANNEX 12. Health Institutions affected by flooding in Sawaga Flood Plain

Table A-12.1 Health Institutions affected by flooding in Malaybalay City, Bukidnon in Sawaga Flood Plain

Bukidnon				
Malaybalay City				
Building Name	Barangay	Rainfall Scenario		
		5-year	25-year	100-year
Provincial Hospital	Barangay 7	Low	Medium	Medium
Provincial Hospital Establishment	Barangay 7			
Provincial Hospital	Casisang	Low	Low	Low
Provincial Hospital Establishment	Casisang		Low	Low
Barangay Health Station	Linabo	Medium	Medium	Medium
Health Center	Managok			Low
Barangay Health Station	Santo Niño		Low	Low
Barangay Health Center	Simaya		Low	Low
Health Center	Simaya			
Barangay Health Station	Sinanglanan	Low	Medium	Medium

Bukidnon				
Valencia City				
Building Name	Barangay	Rainfall Scenario		
		5-year	25-year	100-year
Barangay Health Station	Bagontaas			
Valencia Polymedic General Hospital	Bagontaas	High	High	High
Health Center	Laligan	Medium	Medium	Medium
Blanco Hospital	Lumbo		Low	Low
Bukidnon Community Health Care Center	Lumbo			
City Health Office Of Valencia City	Lumbo			
Lavicaa General Hospital	Lumbo			
Shiphrah and Puah Maternity Clinic	Lumbo	Medium	Medium	High
Mailag Barangay Health Station	Mailag	Medium	High	Medium
Barangay Health Station	Nabago		Medium	Medium
Abella Midway Hospital	Poblacion	Medium	High	High
Blanco Hospital	Poblacion	Medium	Medium	Medium
Clinic	Poblacion			Low
Lavicaa General Hospital	Poblacion			
Sanitarium Hospital	Poblacion	Low	Medium	High

Urgent Care Clinic	Poblacion	Medium	High	High
Valencia Medical Hospital	Poblacion	Medium	High	High
Yap Building	Poblacion	Low	Low	Medium
DOH MPC	San Carlos			
Baranga Health Center	San Isidro	Medium	High	High
Sinabuagan Health Center	Sinabuagan	High	High	High
Barangay Health Center	Sugod		Low	Low
Barangay Health Center	Tongantongan	Medium	Medium	Medium
Barangay Health Station	Vintar		Medium	Medium

UP Training Center for Applied Geodesy and Photogrammetry (TCAGP)
College of Engineering
University of the Philippines – Diliman
Quezon City 1101
PHILIPPINES