

Hazard Mapping of the Philippines Using LIDAR ( Phil-LIDAR 1 )

# **LiDAR Surveys and Flood Mapping of Ipil River**



University of the Philippines Training Center  
for Applied Geodesy and Photogrammetry  
University of San Carlos



APRIL 2017







© University of the Philippines Diliman and University of San Carlos 2017

Published by the UP Training Center for Applied Geodesy and Photogrammetry (TCAGP)  
College of Engineering  
University of the Philippines – Diliman  
Quezon City  
1101 PHILIPPINES

This research project is supported by the Department of Science and Technology (DOST) as part of its Grants-in-Aid Program and is to be cited as:

E. C. Paringit and R. S. Otadoy (eds.) (2017), *LiDAR Surveys and Flood Mapping of Ipil River*, Quezon City: University of the Philippines Training Center for Applied Geodesy and Photogrammetry-174pp.

The text of this information may be copied and distributed for research and educational purposes with proper acknowledgement. While every care is taken to ensure the accuracy of this publication, the UP TCAGP disclaims all responsibility and all liability (including without limitation, liability in negligence) and costs which might incur as a result of the materials in this publication being inaccurate or incomplete in any way and for any reason.

For questions/queries regarding this report, contact:

**Dr. Roland Emerito S. Otadoy**  
Project Leader, Phil-LiDAR 1 Program  
University of San Carlos  
Cebu City, Philippines 6000  
E-mail: rolandotadoy2012@gmail.com

**Enrico C. Paringit, Dr. Eng.**  
Program Leader, Phil-LiDAR 1 Program  
University of the Philippines Diliman  
Quezon City, Philippines 1101  
E-mail: ecparingit@up.edu.ph

National Library of the Philippines  
ISBN: 978-621-430-181-2



# TABLE OF CONTENTS

<b>LIST OF FIGURES .....</b>	<b>v</b>
<b>LIST OF TABLES .....</b>	<b>vii</b>
<b>LIST OF ACRONYMS AND ABBREVIATIONS .....</b>	<b>viii</b>
<b>CHAPTER 1: OVERVIEW OF THE PROGRAM AND IPIL RIVER.....</b>	<b>1</b>
1.1 Background of the Phil-LiDAR 1 Program .....	1
1.2 Overview of the Ipil River Basin.....	1
<b>CHAPTER 2: LIDAR DATA ACQUISITION OF THE IPIL FLOODPLAIN.....</b>	<b>3</b>
2.1 LiDAR Acquisition in Ipil Floodplain .....	3
2.1.1 Flight Plans .....	3
2.2 Ground Base Stations .....	5
2.3 Flight Missions .....	12
2.4 Survey Coverage .....	13
<b>CHAPTER 3: LIDAR DATA PROCESSING FOR IPIL FLOODPLAIN .....</b>	<b>16</b>
3.1 LiDAR Data Processing for Ipil Floodplain .....	16
3.1.1 Overview of the LiDAR Date Pre-Processing.....	16
3.2 Transmittal of Acquired LiDAR Data.....	17
3.3 Trajectory Computation.....	17
3.4 LiDAR Point Cloud Computation .....	19
3.5 LiDAR Data Quality Checking .....	19
3.6 LiDAR Point Cloud Classification and Rasterization.....	23
3.7 LiDAR Image Processing and Orthophotograph Rectification.....	25
3.8 DEM Editing and Hydro-Correction .....	25
3.9 Mosaicking of Blocks .....	26
3.10 Calibration and Validation of Mosaicked LiDAR DEM .....	28
3.11 Integration of Bathymetric Data into the LiDAR Digital Terrain Model.....	30
3.12 Feature Extraction .....	32
3.12.1 Quality Checking of Digitized Features' Boundary.....	32
3.12.2 Height Extraction .....	32
3.12.3 Feature Attribution .....	33
3.12.4 Final Quality Checking of Extracted Features .....	34
<b>CHAPTER 4: LIDAR VALIDATION SURVEY AND MEASUREMENTS OF THE IPIL RIVER BASIN .....</b>	<b>35</b>
4.1 Summary of Activities.....	35
4.2 Control Survey .....	36
4.3 Baseline Processing .....	38
4.4 Network Adjustment .....	39
4.5 Cross-section and Bridge As-Built survey and Water Level Marking .....	41
4.6 Validation Points Acquisition Survey .....	47
4.7 River Bathymetric Survey.....	49
<b>CHAPTER 5: Results and Discussion.....</b>	<b>53</b>
5.1 Data Used for Hydrologic Modeling.....	53
5.1.1 Hydrometry and Rating Curves.....	53
5.1.2 Precipitation .....	53
5.1.3 Rating Curves and River Outflow .....	54
5.2 RIDF Station .....	55
5.3 HMS Model.....	56
5.4 Cross-section Data .....	59
5.5 Flo 2D Model .....	60
5.6 Results of HMS Calibration .....	60
5.7 Calculated outflow hydrographs and discharge values for different rainfall return periods .....	61
5.7.1 Hydrograph using the Rainfall Runoff Model .....	61
5.8 River Analysis (RAS) Model Simulation .....	62
5.9 Flow Depth and Flood Hazard.....	63
5.10 Inventory of Areas Exposed to Flooding.....	70
5.11 Flood Validation.....	103
<b>REFERENCES .....</b>	<b>106</b>

<b>ANNEXES.....</b>	<b>107</b>
Annex 1. Technical Specifications of the LIDAR Sensors used in the Ipil Floodplain Survey .....	107
Annex 2. NAMRIA Certification of Reference Points Used in the LIDAR Survey .....	110
Annex 3. Baseline Processing Reports of Control Points used in the LIDAR Survey .....	113
Annex 4. The LIDAR Survey Team Composition .....	117
Annex 5. Data Transfer Sheet for Ipil Floodplain .....	118
Annex 6. Flight logs for the flight missions .....	120
Annex 7. Flight Status Reports.....	126
Annex 8: Mission Summary Reports .....	133
Annex 9. Ipil Model Basin Parameters.....	141
Annex 10. Ipil Model Reach Parameters.....	142
Annex 11. Ipil Field Validation Points.....	143
Annex 12. Educational Institutions Affected by flooding in Ipil Floodplain .....	147
Annex 13. Health Institutions affected by flooding in Ipil Flood Plain .....	148



## LIST OF FIGURES

Figure 1.	Map of the Ipil River Basin in brown .....	1
Figure 2.	Flight plans and base stations used for the Ipil floodplain survey.....	4
Figure 3.	GPS set-up over BHL-63 in Hagbuyo Bridge in Brgy. Hagbuyo, San Miguel, Bohol.....	5
Figure 4.	GPS set-up over BHL-95 in Brgy. Tiguis, Lila, Bohol (a) and NAMRIA reference point BHL-95 (b) as recovered by the field team .....	6
Figure 5.	GPS set-up over BHL-75 at Barangay Plaza of San Jose, Mabini, Bohol (a) and NAMRIA reference point BHL-75 (b) as recovered by the field team .....	7
Figure 6.	GPS set-up over established point 63A in Hagbuyo Bridge, Brgy, Hagbuyo, San Miguel, Bohol (a) .....	8
Figure 7.	GPS set-up over established point 75A at the Basketball court in the Barangay Plaza of San Jose, Mabini, Bohol (a). .....	9
Figure 8.	GPS set-up over established point Hotel at Panda Tea Garden Suites Tagbilaran, Bohol (a).....	10
Figure 9.	GPS set-up over established point EPHotel at Panda Tea Garden Suites Tagbilaran, Bohol (a).....	11
Figure 10.	Actual LiDAR survey coverage for Ipil floodplain .....	15
Figure 11.	Schematic Diagram for Data Pre-Processing Component .....	16
Figure 12.	Smoothed Performance Metric Parameters of an Ipil Flight 765P .....	17
Figure 13.	Solution Status Parameters of Ipil Flight 765P.....	18
Figure 14.	The best estimated trajectory of the LiDAR missions conducted over the Ipil floodplain.....	18
Figure 15.	Boundary of the processed LiDAR data over Ipil Floodplain .....	19
Figure 16.	Image of data overlap for Ipil floodplain .....	20
Figure 17.	Density map of merged LiDAR data for Ipil floodplain .....	21
Figure 18.	Elevation difference map between flight lines for Ipil floodplain.....	22
Figure 19.	Quality checking for a Ipil flight 765P using the Profile Tool of QT Modeler .....	22
Figure 20.	Tiles for Ipil floodplain (a) and classification results (b) in TerraScan .....	23
Figure 21.	Point cloud before (a) and after (b) classification.....	24
Figure 22.	The production of last return DSM (a) and DTM (b), first return DSM (c) and secondary DTM (d) in some portion of Ipil floodplain.....	24
Figure 23.	Portions in the DTM of Ipil floodplain – a mountain before (a) and (b) after data retrieval; and a bridge before (c) before and after (d) manual editing.....	26
Figure 24.	Map of Processed LiDAR Data for Ipil Flood Plain .....	27
Figure 25.	Map of Ipil Flood Plain with validation survey points in green.....	28
Figure 26.	Correlation plot between calibration survey points and LiDAR data.....	29
Figure 27.	Correlation plot between validation survey points and LiDAR data.....	30
Figure 28.	Map of Ipil Flood Plain with bathymetric survey points shown in blue .....	31
Figure 29.	Blocks (in blue) of Ipil building features that were subjected to QC .....	32
Figure 30.	Extracted features for Ipil floodplain .....	34
Figure 31.	Extent of the bathymetric survey (in blue) in Ipil River and the LiDAR data validation survey (in red).....	35
Figure 32.	GNSS Network covering Ipil River.....	36
Figure 33.	GNSS base set up, Trimble® SPS 882, at BHL-57 located along Ubay-Talibon Road, Brgy. Tanghaligue, Municipality of Talibon, Bohol.....	37
Figure 34.	NSS receiver setup, Trimble® SPS 882, at BHL-62 located along Ubay-Talibon Road, Brgy. Humayhumay, Municipality of Ubay, Bohol.....	37
Figure 35.	GNSS receiver setup, Trimble® SPS 852, at BH-393 located at the approach of Hinlayagan Bridge, Brgy. Hinlayagan Ilaya, Municipality of Trinidad, Bohol.....	38
Figure 36.	Tugas Bridge facing upstream.....	41
Figure 37.	Bridge As-Built Survey using PPK Technique in Tugas Bridge .....	41
Figure 38.	Trinidad Bridge facing downstream.....	42
Figure 39.	Bridge As-Built Survey using PPK Technique in Trinidad Bridge .....	42
Figure 40.	Tugas Bridge cross-section diagram .....	43
Figure 41.	Tugas bridge cross-section location map.....	43
Figure 42.	Trinidad Bridge cross-section diagram .....	44
Figure 43.	Trinidad bridge cross-section location map.....	44
Figure 44.	Bridge as-built form of Tugas Bridge .....	45
Figure 45.	Bridge as-built form of Trinidad Bridge .....	46
Figure 46.	Water-level markings on Tugas Bridge .....	47
Figure 47.	Water-level markings on Trinidad Bridge .....	47
Figure 48.	Validation points acquisition survey set up along Ipil River Basin .....	48
Figure 49.	Validation point acquisition survey of Ipil River Basin.....	48

Figure 50. Bathymetric survey using OHMEX™ single beam echo sounder in Ipil River .....	49
Figure 51. Bathymetric survey of Ipil River.....	50
Figure 52. Ipil Riverbed Profile, from Tugas Bridge in Brgy. Hinlayagan Ilaud upstream .....	51
Figure 53. Ipil Riverbed Profile, from Tugas Bridge in Brgy. Hinlayagan Ilaud .....	52
Figure 54. The location map of Ipil HEC-HMS model used for calibration .....	53
Figure 55. Cross-Section Plot of Tugas Bridge .....	54
Figure 56. Rating Curve at Tugas Bridge, Trinidad .....	54
Figure 57. Rainfall and outflow data at Ipil used for modeling .....	55
Figure 58. Tagbilaran Point RIDF location relative to Ipil River Basin .....	56
Figure 59. Synthetic storm generated for a 24-hr period rainfall for various return periods .....	56
Figure 60. The soil map of the Ipil River Basin used for the estimation of the CN parameter. (Source of data: Digital soil map of the Philippines published by the Bureau of Soil and Water Management – Department of Agriculture).....	57
Figure 61. The land cover map of the Ipil River Basin used for the estimation of the CN and watershed lag parameters of the rainfall-runoff model. (Source: National Mapping and Resource Information Authority).....	57
Figure 62. The slope map of the Ipil River Basin .....	58
Figure 63. Stream Delineation Map of Ipil River Basin .....	58
Figure 64. The Ipil River Basin Model Domain generated using HEC-HMS.....	59
Figure 65. River cross-section of Ipil River generated through Arcmap HEC GeORAS tool.....	59
Figure 66. Outflow Hydrograph of Ipil produced by the HEC-HMS model compared with observed outflow .....	60
Figure 67. Outflow hydrograph at Ipil generated using Tagbilaran PointRIDF simulated in HEC-HMS.....	62
Figure 68. Sample output of Ipil RAS Model .....	63
Figure 69. 100-year Flood Hazard Map for Ipil Floodplain .....	64
Figure 70. 100-year Flow Depth Map for Ipil Floodplain.....	65
Figure 71. 25-year Flood Hazard Map for Ipil Floodplain .....	66
Figure 72. 25-year Flow Depth Map for Ipil Floodplain.....	67
Figure 73. 5-year Flood Hazard Map for Ipil Floodplain .....	68
Figure 74. 5-year Flow Depth Map for Ipil Floodplain.....	69
Figure 75. Affected Areas in Alicia, Bohol during 5-Year Rainfall Return Period.....	70
Figure 76. Affected Areas in Bien Unido, Bohol during 5-Year Rainfall Return Period.....	71
Figure 77. Affected Areas in Dagohoy, Bohol during 5-Year Rainfall .....	72
Figure 78. Affected Areas in Danao, Bohol during 5-Year Rainfall Return Period.....	73
Figure 79. Figure. Affected Areas in Jetafe, Bohol during 5-Year Rainfall Return Period.....	74
Figure 80. Affected Areas in Pilar, Bohol during 5-Year Rainfall Return Period .....	75
Figure 81. Affected Areas in San Miguel, Bohol during 5-Year Rainfall Return Period .....	75
Figure 82. Affected Areas in Talibon, Bohol during 5-Year Rainfall Return Period.....	77
Figure 83. Affected Areas in Trinidad, Bohol during 5-Year Rainfall Return Period .....	78
Figure 84. Affected Areas in Ubay, Bohol during 5-Year Rainfall Return Period .....	80
Figure 85. Affected Areas in Alicia, Bohol during 25-Year Rainfall Return Period.....	81
Figure 86. Affected Areas in Bien Unido, Bohol during 25-Year Rainfall Return Period.....	82
Figure 87. Affected Areas in Dagohoy, Bohol during 25-Year Rainfall .....	83
Figure 88. Affected Areas in Danao, Bohol during 25-Year Rainfall Return Period.....	84
Figure 89. Affected Areas in Jetafe, Bohol during 25-Year Rainfall Return Period.....	85
Figure 90. Affected Areas in Pilar, Bohol during 25-Year Rainfall Return Period .....	86
Figure 91. Affected Areas in San Miguel, Bohol during 25-Year Rainfall Return Period .....	86
Figure 92. Affected Areas in Talibon, Bohol during 25-Year Rainfall Return Period.....	88
Figure 93. Affected Areas in Trinidad, Bohol during 25-Year Rainfall Return Period .....	89
Figure 94. Affected Areas in Ubay, Bohol during 25-Year Rainfall Return Period .....	91
Figure 95. Affected Areas in Alicia, Bohol during 100-Year Rainfall Return Period.....	92
Figure 96. Affected Areas in Bien Unido, Bohol during 100-Year Rainfall Return Period.....	93
Figure 97. Affected Areas in Dagohoy, Bohol during 100-Year Rainfall .....	94
Figure 98. Affected Areas in Danao, Bohol during 100-Year Rainfall Return Period.....	95
Figure 99. Affected Areas in Jetafe, Bohol during 100-Year Rainfall Return Period.....	96
Figure 100. Affected Areas in Pilar, Bohol during 100-Year Rainfall Return Period .....	97
Figure 101. Affected Areas in San Miguel, Bohol during 100-Year Rainfall Return Period .....	97
Figure 102. Affected Areas in Talibon, Bohol during 100-Year Rainfall Return Period.....	99
Figure 103. Affected Areas in Trinidad, Bohol during 100-Year Rainfall Return Period .....	100
Figure 104. Affected Areas in Ubay, Bohol during 100-Year Rainfall Return Period .....	102
Figure 105. Flood Validation Points of Ipil River Basin .....	104
Figure 106. Flood map depth vs actual flood depth.....	104

## LIST OF TABLES

Table 1.	Flight planning parameters for Pegasus LiDAR system .....	3
Table 2.	Details of the recovered NAMRIA horizontal control point BHL-63 used as base station for the LiDAR Acquisition .....	6
Table 3.	Details of the recovered NAMRIA horizontal control point BHL-95 used as base station for the LiDAR Acquisition .....	7
Table 4.	Details of the recovered NAMRIA horizontal control point BHL-75 used as base station for the LiDAR acquisition.....	8
Table 5.	Details of the established control point 63A used as base station for the LiDAR Acquisition .....	9
Table 6.	Details of the established control point 75A used as base station for the LiDAR Acquisition .....	10
Table 7.	Details of the established control point Hotel used as base station for the LiDAR Acquisition.....	11
Table 8.	Details of the established control point 63A used as base station for the LiDAR Acquisition .....	12
Table 9.	Ground control points used during LiDAR data acquisition.....	12
Table 10.	Flight missions under DREAM program which covers Ipil floodplain .....	12
Table 11.	Flight missions for LiDAR data acquisition in Ipil floodplain .....	13
Table 12.	Actual parameters used during LiDAR data acquisition .....	13
Table 13.	List of municipalities and cities surveyed during Ipil floodplain LiDAR survey .....	14
Table 14.	Self-Calibration Results values for Ipil flights.....	19
Table 15.	List of LiDAR blocks for Ipil floodplain .....	20
Table 16.	Ipil classification results in TerraScan .....	23
Table 17.	LiDAR blocks with its corresponding area .....	25
Table 18.	Shift Values of each LiDAR Block of Ipil floodplain .....	26
Table 19.	Calibration Statistical Measures .....	29
Table 20.	Validation Statistical Measures.....	30
Table 21.	Quality Checking Ratings for Ipil Building Features .....	32
Table 22.	Building Features Extracted for Ipil Floodplain.....	33
Table 23.	Total Length of Extracted Roads for Ipil Floodplain .....	33
Table 24.	Number of Extracted Water Bodies for Ipil Floodplain.....	34
Table 25.	List of Reference and Control Points occupied for Ipil River Survey .....	36
Table 26.	Baseline Processing Summary Report for Ipil River Survey .....	38
Table 27.	Control Point Constraints .....	39
Table 28.	Adjusted Grid Coordinates .....	39
Table 29.	Adjusted Geodetic Coordinates .....	40
Table 30.	Reference and control points used and its location .....	40
Table 31.	RIDF values for Tagbilaran Point Rain Gauge computed by PAGASA .....	55
Table 32.	Range of calibrated values for the Ipil River Basin. ....	60
Table 33.	Summary of the Efficiency Test of Ipil HMS Model.....	61
Table 34.	Peak values of the Ipil HECHMS Model outflow using the Tagbilaran RIDF.....	62
Table 35.	Affected Areas in Alicia, Bohol during 5-Year Rainfall Return Period.....	70
Table 36.	Affected Areas in Bien Unido, Bohol during 5-Year Rainfall Return Period.....	71
Table 37.	Affected Areas in Dagohoy, Bohol during 5-Year Rainfall Return Period .....	71
Table 38.	Affected Areas in Danao, Bohol during 5-Year Rainfall Return Period.....	72
Table 39.	Affected Areas in Jetafe, Bohol during 5-Year Rainfall Return Period.....	73
Table 40.	Affected Areas in Pilar, Bohol during 5-Year Rainfall Return Period .....	74
Table 41.	Affected Areas in San Miguel, Bohol during 5-Year Rainfall Return Period .....	76
Table 42.	Affected Areas in San Miguel, Bohol during 5-Year Rainfall Return Period .....	76
Table 43.	Affected Areas in Talibon, Bohol during 5-Year Rainfall Return Period.....	77
Table 44.	Affected Areas in Trinidad, Bohol during 5-Year Rainfall Return Period .....	79
Table 45.	Affected Areas in Trinidad, Bohol during 5-Year Rainfall Return Period .....	79
Table 46.	Affected Areas in Ubay, Bohol during 5-Year Rainfall Return Period .....	80
Table 47.	Affected Areas in Alicia, Bohol during 25-Year Rainfall Return Period.....	81
Table 48.	Affected Areas in Bien Unido, Bohol during 25-Year Rainfall Return Period.....	81
Table 49.	Affected Areas in Dagohoy, Bohol during 25-Year Rainfall Return Period .....	82
Table 50.	Affected Areas in Danao, Bohol during 25-Year Rainfall Return Period.....	83
Table 51.	Affected Areas in Jetafe, Bohol during 25-Year Rainfall Return Period.....	84
Table 52.	Affected Areas in Pilar, Bohol during 25-Year Rainfall Return Period .....	85
Table 53.	Affected Areas in San Miguel, Bohol during 25-Year Rainfall Return Period .....	87
Table 54.	Affected Areas in San Miguel, Bohol during 25-Year Rainfall Return Period .....	87
Table 55.	Affected Areas in Talibon, Bohol during 25-Year Rainfall Return Period.....	88
Table 56.	Table 56. Affected Areas in Trinidad, Bohol during 25-Year Rainfall Return Period.....	90
Table 57.	Affected Areas in Trinidad, Bohol during 25-Year Rainfall Return Period .....	90

Table 58.	Affected Areas in Ubay, Bohol during 25-Year Rainfall Return Period .....	91
Table 59.	Affected Areas in Alicia, Bohol during 100-Year Rainfall Return Period.....	92
Table 60.	Affected Areas in Bien Unido, Bohol during 100-Year Rainfall Return Period.....	92
Table 61.	Affected Areas in Dagohoy, Bohol during 100-Year Rainfall Return Period .....	93
Table 62.	Affected Areas in Danao, Bohol during 100-Year Rainfall Return Period.....	94
Table 63.	Affected Areas in Jetafe, Bohol during 100-Year Rainfall Return Period.....	95
Table 64.	Affected Areas in Pilar, Bohol during 100-Year Rainfall Return Period .....	96
Table 65.	Affected Areas in San Miguel, Bohol during 100-Year Rainfall Return Period .....	98
Table 66.	Affected Areas in San Miguel, Bohol during 100-Year Rainfall Return Period .....	98
Table 67.	Affected Areas in Talibon, Bohol during 100-Year Rainfall Return Period.....	99
Table 68.	Affected Areas in Trinidad, Bohol during 100-Year Rainfall Return Period .....	101
Table 69.	Affected Areas in Trinidad, Bohol during 100-Year Rainfall Return Period .....	101
Table 70.	Affected Areas in Ubay, Bohol during 100-Year Rainfall Return Period .....	102
Table 71.	Area covered by each warning level with respect to the rainfall scenario .....	103
Table 72.	Actual Flood Depth vs Simulated Flood Depth in Ipil .....	105
Table 73.	Summary of Accuracy Assessment in Ipil .....	105



## LIST OF ACRONYMS AND ABBREVIATIONS

<b>AAC</b>	Asian Aerospace Corporation
<b>Ab</b>	abutment
<b>ALTM</b>	Airborne LiDAR Terrain Mapper
<b>ARG</b>	automatic rain gauge
<b>ATQ</b>	Antique
<b>AWLS</b>	Automated Water Level Sensor
<b>BA</b>	Bridge Approach
<b>BM</b>	benchmark
<b>CAD</b>	Computer-Aided Design
<b>CN</b>	Curve Number
<b>CSRS</b>	Chief Science Research Specialist
<b>DAC</b>	Data Acquisition Component
<b>DEM</b>	Digital Elevation Model
<b>DENR</b>	Department of Environment and Natural Resources
<b>DOST</b>	Department of Science and Technology
<b>DPPC</b>	Data Pre-Processing Component
<b>DREAM</b>	Disaster Risk and Exposure Assessment for Mitigation [Program]
<b>DRRM</b>	Disaster Risk Reduction and Management
<b>DSM</b>	Digital Surface Model
<b>DTM</b>	Digital Terrain Model
<b>DVBC</b>	Data Validation and Bathymetry Component
<b>FMC</b>	Flood Modeling Component
<b>FOV</b>	Field of View
<b>GiA</b>	Grants-in-Aid
<b>GCP</b>	Ground Control Point
<b>GNSS</b>	Global Navigation Satellite System
<b>GPS</b>	Global Positioning System
<b>HEC-HMS</b>	Hydrologic Engineering Center - Hydrologic Modeling System
<b>HEC-RAS</b>	Hydrologic Engineering Center - River Analysis System
<b>HC</b>	High Chord
<b>IDW</b>	Inverse Distance Weighted [interpolation method]
<b>IMU</b>	Inertial Measurement Unit
<b>kts</b>	knots
<b>LAS</b>	LiDAR Data Exchange File format
<b>LC</b>	Low Chord
<b>LGU</b>	local government unit

<b>LiDAR</b>	Light Detection and Ranging
<b>LMS</b>	LiDAR Mapping Suite
<b>m AGL</b>	meters Above Ground Level
<b>MMS</b>	Mobile Mapping Suite
<b>MSL</b>	mean sea level
<b>NAMRIA</b>	National Mapping and Resource Information Authority
<b>NSTC</b>	Northern Subtropical Convergence
<b>PAF</b>	Philippine Air Force
<b>PAGASA</b>	Philippine Atmospheric Geophysical and Astronomical Services Administration
<b>PDOP</b>	Positional Dilution of Precision
<b>PPK</b>	Post-Processed Kinematic [technique]
<b>PRF</b>	Pulse Repetition Frequency
<b>PTM</b>	Philippine Transverse Mercator
<b>QC</b>	Quality Check
<b>QT</b>	Quick Terrain [Modeler]
<b>RA</b>	Research Associate
<b>RIDF</b>	Rainfall-Intensity-Duration-Frequency
<b>RMSE</b>	Root Mean Square Error
<b>SAR</b>	Synthetic Aperture Radar
<b>SCS</b>	Soil Conservation Service
<b>SRTM</b>	Shuttle Radar Topography Mission
<b>SRS</b>	Science Research Specialist
<b>SSG</b>	Special Service Group
<b>TBC</b>	Thermal Barrier Coatings
<b>UPC</b>	University of the Philippines Cebu
<b>UP-TCAGP</b>	University of the Philippines – Training Center for Applied Geodesy and Photogrammetry
<b>USC</b>	University of San Carlos
<b>UTM</b>	Universal Transverse Mercator
<b>WGS</b>	World Geodetic System



# CHAPTER 1: OVERVIEW OF THE PROGRAM AND IPIL RIVER

*Enrico C. Paringit, Dr. Eng., Dr. Roland Emerito S. Otadoy, and Engr. Aure Flo Oraya*

## 1.1 Background of the Phil-LIDAR 1 Program

The University of the Philippines Training Center for Applied Geodesy and Photogrammetry (UP-TCAGP) launched a research program entitled “Nationwide Hazard Mapping using LiDAR” or Phil-LiDAR 1, supported by the Department of Science and Technology (DOST) Grants-in-Aid (GiA) Program. The program was primarily aimed at acquiring a national elevation and resource dataset at sufficient resolution to produce information necessary to support the different phases of disaster management. Particularly, it targeted to operationalize the development of flood hazard models that would produce updated and detailed flood hazard maps for the major river systems in the country.

Also, the program was aimed at producing an up-to-date and detailed national elevation dataset suitable for 1:5,000 scale mapping, with 50 cm and 20 cm horizontal and vertical accuracies, respectively. These accuracies were achieved through the use of the state-of-the-art Light Detection and Ranging (LiDAR) airborne technology procured by the project through DOST.

The methods applied in this report are thoroughly described in a separate publication entitled “FLOOD MAPPING OF RIVERS IN THE PHILIPPINES USING AIRBORNE LIDAR: METHODS” (Paringit, et. Al. 2017).

The implementing partner university for the Phil-LiDAR 1 Program is the University of San Carlos (USC). USC is in charge of processing LiDAR data and conducting data validation reconnaissance, cross section, bathymetric survey, validation, river flow measurements, flood height and extent data gathering, flood modeling, and flood map generation for the 17 river basins in the Central Visayas Region. The university is located in Cebu City in the province of Cebu.

## 1.2 Overview of the Ipil River Basin




Figure 1. Map of the Ipil River Basin in brown

Ipil River Basin covers majority of the municipalities of Trinidad and San Miguel and minor portions of Bien Unido, Talibon, Danao, Pilar, Alicia and Ubay in the province of Bohol. The DENR River Basin Control Office identified the basin to have a drainage area of 252 km<sup>2</sup> and an estimated 151 million cubic meter annual run-off (MCM) (RBCO, 2015).

Its main stem, Ipil River, is part of the 17 river systems in Central Visayas Region. According to the 2015 national census of NSO, a total of 17,672 persons are residing within the immediate vicinity of the river which is distributed among seven (7) barangays in the Municipalities of Trinidad, Talibon and Bien Unido (NSO, 2015). The major industries in the municipalities near Ipil River are farming and fishing. Aside from these, the river also plays a vital part for the commercial activity of the municipality where traders transport their products. (<http://www.bohol-philippines.com/trinidad.html>, 2016). During the surge of typhoon Yolanda, internationally known as *Haiyan*, last November 2013 a total of 18,772 families or 90,201 individuals were affected by the typhoon from the municipalities of Trinidad and Talibon ([http://ndrrmc.gov.ph/attachments/article/1329/FINAL\\_REPORT\\_re\\_Effects\\_of\\_Typhoon\\_YOLANDA\\_\(HAIYAN\)\\_06-09NOV2013.pdf](http://ndrrmc.gov.ph/attachments/article/1329/FINAL_REPORT_re_Effects_of_Typhoon_YOLANDA_(HAIYAN)_06-09NOV2013.pdf)).



## CHAPTER 2: LIDAR DATA ACQUISITION OF THE IPIL FLOODPLAIN

*“Engr. Louie P. Balicanta, Engr. Christopher Cruz, Lovely Gracia Acuña, Engr. Gerome Hipolito, Ms. Julie Pearl S. Mars, Ms. Kristine Joy P. Andaya*  
”

The methods applied in this Chapter were based on the DREAM methods manual (Sarmiento, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

### 2.1 LiDAR Acquisition in Ipil Floodplain

#### 2.1.1 Flight Plans

Plans were made to acquire LiDAR data within the delineated priority area for Ipil floodplain in Davao del Sur. These missions were planned for 12 lines and ran for at most four and a half (4.5) hours including take-off, landing and turning time. The flight planning parameters for the LiDAR system is found in Table 1. Figure 2 shows the flight plan for Ipil floodplain.

Table 1. Flight planning parameters for Pegasus LiDAR system

Block Name	Flying Height (m AGL)	Overlap (%)	Field of View ( $\theta$ )	Pulse Repetition Frequency (PRF) (kHz)	Scan Frequency (Hz)	Average Speed (kts)	Average Turn Time (Minutes)
BLK51A	800/1000	30	50	200	30	130	5
BLK51B	800/1000	30	50	200	30	130	5
BLK51C	800/1000	30	50	200	30	130	5
BLK51F	800/1000	30	50	200	30	130	5
BLK51S	1000	30	50	200	30	130	5
BLK51LKS	1000	30	50	200	30	130	5
LOBOC	1000	30	50	200	30	130	5




Figure 2. Flight plans and base stations used for the Ipil floodplain survey

## 2.2 Ground Base Stations

The project team was able to recover three (3) NAMRIA ground control points: BHL-63, BHL-95 and BHL-75 which are of second (2<sup>nd</sup>), order accuracy, respectively. The project team also established one (4) ground control points, 63A, 75A, Hotel, and EPHotel. The certifications for the NAMRIA reference points are found in Annex 2 while the baseline processing reports for the established control point are found in Annex 3. These were used as base stations during flight operations for the entire duration of the survey (September 12 -23, 2015). Base stations were observed using dual frequency GPS receivers: TRIMBLE SPS 852, TRIMBLE SPS 882 and TRIMBLE SPS 985. Flight plans and location of base stations used during the aerial LiDAR acquisition in Ipil floodplain are also shown in Figure 2.

Figure 3 to Figure 9 show the recovered NAMRIA reference points within the area. In addition, Table 2 to Table 8 show the details about the following NAMRIA control stations and established points, while Table 9 shows the list of all ground control points occupied during the acquisition together with the corresponding dates of utilization.




Figure 3. GPS set-up over BHL-63 in Hagbuyo Bridge in Brgy. Hagbuyo, San Miguel, Bohol

Table 2. Details of the recovered NAMRIA horizontal control point BHL-63 used as base station for the LiDAR Acquisition

Station Name	BHL-63	
Order of Accuracy	2nd	
Relative Error (horizontal positioning)	1 in 50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude	10° 0' 13.31407"
	Longitude	124° 20' 43.46219"
	Ellipsoidal Height	20.48700 meters
Grid Coordinates, Philippine Transverse Mercator Zone 3 (PTM Zone 5 PRS 92)	Easting	428232.81 meters
	Northing	1106210.364 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude	10° 0' 9.30688" North
	Longitude	124° 20' 48.73327" East
	Ellipsoidal Height	84.04100 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting	647,463.40 meters
	Northing	1,106,052.78 meters



(a)



(b)

Figure 4. GPS set-up over BHL-95 in Brgy. Tiguis, Lila, Bohol (a) and NAMRIA reference point BHL-95 (b) as recovered by the field team



Table 3. Details of the recovered NAMRIA horizontal control point BHL-95 used as base station for the LiDAR Acquisition

Station Name	BHL-95	
Order of Accuracy	2 <sup>nd</sup>	
Relative Error (horizontal positioning)	1 in 50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude	9° 35' 30.9568"
	Longitude	124° 04' 30.0216"
	Ellipsoidal Height	19.00 meters
Grid Coordinates, Philippine Transverse Mercator Zone 5 (PTM Zone 5 PRS 92)	Easting	398459.94396 meters
	Northing	1060736.81055 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude	9° 35' 27.03243" North
	Longitude	124° 04' 35.33150" East
	Ellipsoidal Height	82.798 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting	618128.686 meters
	Northing	1060360.033 meters



(a)



(b)

Figure 5. GPS set-up over BHL-75 at Barangay Plaza of San Jose, Mabini, Bohol (a) and NAMRIA reference point BHL-75 (b) as recovered by the field team

Table 4. Details of the recovered NAMRIA horizontal control point BHL-75 used as base station for the LiDAR acquisition

Station Name	BHL-75	
Order of Accuracy	2 <sup>th</sup>	
Relative Error (horizontal positioning)	1 in 50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude	9° 57' 16.74294"
	Longitude	124° 32' 0.35318"
	Ellipsoidal Height	12.84500 meters
Grid Coordinates, Philippine Transverse Mercator Zone 3 (PTM Zone 5 PRS 92)	Easting	448840.052 meters
	Northing	1100750.724 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude	9° 57' 16.76483" North
	Longitude	124° 32' 5.62696" East
	Ellipsoidal Height	76.97400 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting	668,101.47 meters
	Northing	1,100,718.38 meters



(a)

Figure 6. GPS set-up over established point 63A in Hagbuyo Bridge, Brgy, Hagbuyo, San Miguel, Bohol (a)

Table 5. Details of the established control point 63A used as base station for the LiDAR Acquisition

Station Name	63A	
Order of Accuracy	2 <sup>nd</sup>	
Relative Error (horizontal positioning)	1 in 50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude	10° 00' 13.84084" North
	Longitude	124° 20' 43.58209" East
	Ellipsoidal Height	20.464 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting	647466.981 meters
	Northing	1106068.972 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude	10 00' 09.83363" North
	Longitude	124° 20' 48.85315" East
	Ellipsoidal Height	84.018 meters



(a)

Figure 7. GPS set-up over established point 75A at the Basketball court in the Barangay Plaza of San Jose, Mabini, Bohol (a).

Table 6. Details of the established control point 75A used as base station for the LiDAR Acquisition

Station Name	75A	
Order of Accuracy	2 <sup>nd</sup>	
Relative Error (horizontal positioning)	1 in 50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude	9° 57' 17.24192" North
	Longitude	124° 32' 00.58209" East
	Ellipsoidal Height	12.668 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting	668103.303 meters
	Northing	1100733.718 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude	9° 57' 13.26378" North
	Longitude	124° 32' 05.68974" East
	Ellipsoidal Height	76.796 meters



(a)

Figure 8. GPS set-up over established point Hotel at Panda Tea Garden Suites Tagbilaran, Bohol (a).



Table 7. Details of the established control point Hotel used as base station for the LiDAR Acquisition

Station Name	Hotel	
Order of Accuracy	2 <sup>nd</sup>	
Relative Error (horizontal positioning)	1 in 50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude	9° 39' 32.15822" North
	Longitude	123° 51' 54.83035" East
	Ellipsoidal Height	49.4981 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting	594927.168 meters
	Northing	1067756.448 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude	9° 39' 28.19791" North
	Longitude	123° 52' 00.13618" East
	Ellipsoidal Height	113.124 meters



(a)

Figure 9. GPS set-up over established point EPHotel at Panda Tea Garden Suites Tagbilaran, Bohol (a)

Table 8. Details of the established control point 63A used as base station for the LiDAR Acquisition

Station Name	EPHotel	
Order of Accuracy	2 <sup>nd</sup>	
Relative Error (horizontal positioning)	1 in 50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude	9° 39' 32.38755" North
	Longitude	123° 51' 54.91053" East
	Ellipsoidal Height	49.956 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting	594929.497 meters
	Northing	1067763.497 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude	9° 39' 28.42722" North
	Longitude	123° 52' 00.21636" East
	Ellipsoidal Height	113.100 meters

Table 9. Ground control points used during LiDAR data acquisition

Date Surveyed	Flight Number	Mission Name	Ground Control Points
September 12, 2015	3409P	1BLK51B255A	BHL-63 and 63A
September 12, 2015	3411P	1BLK51C255B	BHL-63 and 63A
September 15, 2015	4321P	1BLK51C258A	BHL-75 and 75A
September 17, 2015	3429P	1BLK51260A	BHL-75 and 75A
September 22, 2015	3449P	1BLK51G265A	BHL-75 and 75A
September 23, 2015	3453P	1BLK51S266A	Hotel and EPHotel

### 2.3 Flight Missions

Six (6) missions under DREAM program covered around 239.8 (Table 10) within Ipil floodplain. Six (6) missions under Phil-LiDAR program were conducted to complete the LiDAR data acquisition in Ipil floodplain, for a total of Twenty hours and Twenty-four minutes (20+24) of flying time for RP-C9122. The missions were acquired using the Gemini LiDAR system. Table 11 shows the total area of actual coverage and the corresponding flying hours per mission, while Table 12 presents the actual parameters used during the LiDAR data acquisition.

Table 10. Flight missions under DREAM program which covers Ipil floodplain

Flight Number	Mission Name	Area Surveyed within the Floodplain (km <sup>2</sup> )
765P	1BHL1C321A	54.47
769P	1BHL1BC322A	63.32
773P	1BHL1BS323A	16.17
777P	1BHL1D324A	39.30
793P	1BHL1BDS328A	8.13
833P	1BHL1E338A	58.41
TOTAL		239.8

Table 11. Flight missions for LiDAR data acquisition in Ipil floodplain

Date Surveyed	Flight Number	Flight Plan Area (km <sup>2</sup> )	Surveyed Area (km <sup>2</sup> )	Area Surveyed within the Floodplain (km <sup>2</sup> )	Area Surveyed Outside the Floodplain (km <sup>2</sup> )	No. of Images (Frames)	Flying Hours	
							Hr	Min
September 12, 2015	3409P	111.44	196.08	0	196.08	NA	4	23
September 12, 2015	3411P	295.43	109.96	0	109.96	NA	2	47
September 15, 2015	4321P	107.84	54.28	0	54.28	NA	2	35
September 17, 2015	3429P	107.84	234.68	0	234.68	NA	4	17
September 22, 2015	3449P	486.5	123.69	0	123.68	NA	3	47
September 23, 2015	3453P	147.15	124.39	0	124.39	NA	2	35
TOTAL		1256.2	843.08	0	843.07	NA	20	24

Table 12. Actual parameters used during LiDAR data acquisition

Flight Number	Flying Height (m AGL)	Overlap (%)	FOV (θ)	PRF (kHz)	Scan Frequency (Hz)	Average Speed (kts)	Average Turn Time (Minutes)
3409P	1000	30	50	200	30	130	5
3411P	800/1000	30	50	200	30	130	5
4321P	800/1000	30	50	200	30	130	5
3429P	800/1000	30	50	200	30	130	5
3449P	800/1000	30	50	200	30	130	5
3409P	1000	30	50	200	30	130	5

## 2.4 Survey Coverage

Ipil floodplain is located along the province of Bohol with majority of the floodplain situated within the municipalities of Alicia, Bien Unido, Pilar, San Miguel, Talibon, Trinidad and Ubay. The list of municipalities and cities surveyed, with at least one (1) square kilometer coverage, is shown in Table 13. The actual coverage of the LiDAR acquisition for Ipil floodplain is presented in Figure 10.



Table 13. List of municipalities and cities surveyed during Ipil floodplain LiDAR survey

Province	Municipality/City	Area of Municipality/City (km <sup>2</sup> )	Total Area Surveyed (km <sup>2</sup> )	Percentage of Area Surveyed
BOHOL	Albuquerque	26.84	9.46	35%
	Alicia	118.35	84.53	71%
	Balilihan	123.46	1.60	1%
	Batuan	90.27	2.93	3%
	Buenavista	107.95	7.50	7%
	Candijay	94.72	78.68	83%
	Carmen	221.41	3.05	1%
	Catigbian	84.38	4.34	5%
	Duero	74.75	11.07	15%
	Guindulman	100.84	35.31	35%
	Inabanga	103.67	19.33	19%
	Jetafe	99.31	18.08	18%
	Loay	29.63	11.57	39%
	Loboc	57.40	41.84	73%
	Mabini	87.74	87.52	100%
	Pilar	121.42	24.10	20%
	Pres. Carlos P. Garcia	48.06	45.09	94%
	Sevilla	68.37	2.17	3%
Sierra Bullones	85.93	4.00	5%	
Sikatuna	21.88	2.55	12%	
Ubay	232.66	109.18	47%	
Total		1999.04	603.9	30.21%




Figure 10. Actual LiDAR survey coverage for Ipil floodplain

## CHAPTER 3: LIDAR DATA PROCESSING FOR IPIL FLOODPLAIN

*Engr. Ma. Rosario Concepcion O. Ang, Engr. John Louie D. Fabila, Engr. Sarah Jane D. Samalbuero, Engr. Joida F. Prieto, Ailyn G. Biñas, Engr. Jennifer B. Saguran, Engr. Monalyne C. Rabino, Engr. Erica Erin E. Elazegui, Engr. Ma. Joanne I. Balaga, Engr. Erica Erin E. Elazegui*

The methods applied in this Chapter were based on the DREAM methods manual (Ang, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

### 3.1 LiDAR Data Processing for Ipil Floodplain

#### 3.1.1 Overview of the LiDAR Date Pre-Processing

The data transmitted by the Data Acquisition Component are checked for completeness based on the list of raw files required to proceed with the pre-processing of the LiDAR data. Upon acceptance of the LiDAR field data, georeferencing of the flight trajectory is done in order to obtain the exact location of the LiDAR sensor when the laser was shot. Point cloud georectification is performed to incorporate correct position and orientation for each point acquired. The georectified LiDAR point clouds are subject for quality checking to ensure that the required accuracies of the program, which are the minimum point density, vertical and horizontal accuracies, are met. The point clouds are then classified into various classes before generating Digital Elevation Models such as Digital Terrain Model and Digital Surface Model.

Using the elevation of points gathered in the field, the LiDAR-derived digital models are calibrated. Portions of the river that are barely penetrated by the LiDAR system are replaced by the actual river geometry measured from the field by the Data Validation and Bathymetry Component. LiDAR acquired temporally are then mosaicked to completely cover the target river systems in the Philippines. Orthorectification of images acquired simultaneously with the LiDAR data is done through the help of the georectified point clouds and the metadata containing the time the image was captured.

These processes are summarized in the flowchart shown in Figure 11.




Figure 11. Schematic Diagram for Data Pre-Processing Component

### 3.2 Transmittal of Acquired LiDAR Data

Data transfer sheets for all the LiDAR missions for Ipil floodplain can be found in **Annex 5**. Missions flown during the first survey conducted on November 2013 and second survey on September 2015 used the Airborne LiDAR Terrain Mapper (ALTM™ Optech Inc.) Pegasus system over Bohol. The Data Acquisition Component (DAC) transferred a total of 253.49 Gigabytes of Range data, 2.46 Gigabytes of POS data and 117.86 Megabytes of GPS base station data to the data server on December 11, 2013 for the first survey and September 23, 2015 for the second survey. The Data Pre-processing Component (DPPC) verified the completeness of the transferred data. The whole dataset for Ipil was fully transferred on October 28, 2015, as indicated on **Annex 5: Data Transfer Sheets for Ipil floodplain**.

### 3.3 Trajectory Computation

The Smoothed Performance Metrics of the computed trajectory for flight 765P, one of the Ipil flights, which is the North, East, and Down position RMSE values are shown in Figure 12. The x-axis corresponds to the time of flight, which is measured by the number of seconds from the midnight of the start of the GPS week, which on that week fell on November 17, 2013 00:00AM. The y-axis is the RMSE value for that particular position.




Figure 12. Smoothed Performance Metrics of an Ipil Flight 765P

The time of flight was from 26200 seconds to 34200 seconds, which corresponds to morning of November 17, 2013. The initial spike that is seen on the data corresponds to the time that the aircraft was getting into position to start the acquisition, and the POS system starts computing for the position and orientation of the aircraft. Redundant measurements from the POS system quickly minimized the RMSE value of the positions. The periodic increase in RMSE values from an otherwise smoothly curving RMSE values correspond to the turn-around period of the aircraft, when the aircraft makes a turn to start a new flight line. Figure 12 shows that the North position RMSE peaks at 1.50 centimeters, the East position RMSE peaks at 1.50 centimeters, and the Down position RMSE peaks at 4.90 centimeters, which are within the prescribed accuracies described in the methodology.






Figure 13. Solution Status Parameters of Ipil Flight 765P

The Solution Status parameters of flight 765P, one of the Ipil flights, which are the number of GPS satellites, Positional Dilution of Precision (PDOP), and the GPS processing mode used, are shown in Figure 13. The graphs indicate that the number of satellites during the acquisition did not go down to 6. Majority of the time, the number of satellites tracked was between 6 and 9. The PDOP value also did not go above the value of 3, which indicates optimal GPS geometry. The processing mode stayed at the value of 0 for majority of the survey. The value of 0 corresponds to a Fixed, Narrow-Lane mode, which is the optimum carrier-cycle integer ambiguity resolution technique available for POSPAC MMS. All of the parameters adhered to the accuracy requirements for optimal trajectory solutions, as indicated in the methodology. The computed best estimated trajectory for all Ipil flights is shown in Figure 14.




Figure 14. The best estimated trajectory of the LiDAR missions conducted over the Ipil floodplain

### 3.4 LiDAR Point Cloud Computation

The produced LAS data contains 117 flight lines, with each flight line containing two channels, since the Pegasus system contains two channels. The summary of the self-calibration results obtained from LiDAR processing in LiDAR Mapping Suite (LMS) software for all flights over Ipil floodplain are given in Table 14.

Table 14. Self-Calibration Results values for Ipil flights

Parameter		Computed Value
Boresight Correction stdev	(<0.001degrees)	0.000181
IMU Attitude Correction Roll and Pitch Corrections stdev	(<0.001degrees)	0.000962
GPS Position Z-correction stdev	(<0.01meters)	0.0028

The optimum accuracy is obtained for all Ipil flights based on the computed standard deviations of the corrections of the orientation parameters. Standard deviation values for individual blocks are available in the **Annex B-1. Mission Summary Reports**.

### 3.5 LiDAR Data Quality Checking

The boundary of the processed LiDAR data on top of a SAR Elevation Data over Ipil Floodplain is shown in Figure 15. The map shows gaps in the LiDAR coverage that are attributed to cloud coverage.




Figure 15. Boundary of the processed LiDAR data over Ipil Floodplain



The total area covered by the Ipil missions is 1,994.07 sq.km that is comprised of thirteen (13) flight acquisitions grouped and merged into twelve (12) blocks as shown in Table 15.

Table 15. List of LiDAR blocks for Ipil floodplain

LiDAR Blocks	Flight Numbers	Area (sq. km)
Bohol_Bl1B	769P	184.09
Bohol_Bl1B_supplement1	773P	91.00
Bohol_Bl1B_supplement2	793P	149.54
Bohol_Bl1C	765P	155.48
Bohol_Bl1D	777P 793P	107.10
Bohol_Bl1D_supplement	805P	248.32
Bohol_Bl1E	833P	317.41
Bohol_Bl51B	3409P	205.05
Bohol_Bl51C	3411P	107.09
Bohol_Bl51C_additional	3429P	203.43
Bohol_Bl51F	3421P 3453P	94.64
Bohol_Bl51A	3449P	130.92
<b>TOTAL</b>		<b>1,994.07 sq.km</b>

The overlap data for the merged LiDAR blocks, showing the number of channels that pass through a particular location is shown in Figure 16. Since the Pegasus system employs two channels, we would expect an average value of 2 (blue) for areas where there is limited overlap, and a value of 3 (yellow) or more (red) for areas with three or more overlapping flight lines.




Figure 16. Image of data overlap for Ipil floodplain

The overlap statistics per block for the Ipil floodplain can be found in **Annex B-1**. One pixel corresponds to 25.0 square meters on the ground. For this area, the minimum and maximum percent overlaps are 26.19% and 65.08% respectively, which passed the 25% requirement.

The pulse density map for the merged LiDAR data, with the red parts showing the portions of the data that satisfy the 2 points per square meter criterion is shown in Figure 17. It was determined that all LiDAR data for Ipil floodplain satisfy the point density requirement, and the average density for the entire survey area is 3.28 points per square meter.




Figure 17. Pulse density map of merged LiDAR data for Ipil floodplain

The elevation difference between overlaps of adjacent flight lines is shown in Figure 18. The default color range is from blue to red, where bright blue areas correspond to portions where elevations of a previous flight line, identified by its acquisition time, are higher by more than 0.20m relative to elevations of its adjacent flight line. Bright red areas indicate portions where elevations of a previous flight line are lower by more than 0.20m relative to elevations of its adjacent flight line. Areas with bright red or bright blue need to be investigated further using Quick Terrain Modeler software.






Figure 18. Elevation difference map between flight lines for Ipil floodplain

A screen capture of the processed LAS data from an Ipil flight 765P loaded in QT Modeler is shown in Figure 19. The upper left image shows the elevations of the points from two overlapping flight strips traversed by the profile, illustrated by a dashed yellow line. The x-axis corresponds to the length of the profile. It is evident that there are differences in elevation, but the differences do not exceed the 20-centimeter mark. This profiling was repeated until the quality of the LiDAR data becomes satisfactory. No reprocessing was done for this LiDAR dataset.




Figure 19. Quality checking for a Ipil flight 765P using the Profile Tool of QT Modeler

### 3.6 LiDAR Point Cloud Classification and Rasterization

Table 16. Ipil classification results in TerraScan

Pertinent Class	Total Number of Points
Ground	1,692,438,923
Low Vegetation	1,390,686,753
Medium Vegetation	2,073,165,732
High Vegetation	1,056,021,851
Building	32,131,151

The tile system that TerraScan employed for the LiDAR data and the final classification image for a block in Ipil floodplain is shown in Figure 20. A total of 2,892 1km by 1km tiles were produced. The number of points classified to the pertinent categories is illustrated in Table 16. The point cloud has a maximum and minimum height of 701.49 meters and 1.91 meters respectively.




Figure 20. Tiles for Ipil floodplain (a) and classification results (b) in TerraScan

An isometric view of an area before and after running the classification routines is shown in Figure 21. The ground points are in orange, the vegetation is in different shades of green, and the buildings are in cyan. It can be seen that residential structures adjacent or even below canopy are classified correctly, due to the density of the LiDAR data.






Figure 21. Point cloud before (a) and after (b) classification

The production of last return (V\_ASCII) and the secondary (T\_ASCII) DTM, first (S\_ASCII) and last (D\_ASCII) return DSM of the area in top view display are shown in Figure 22. It shows that DTMs are the representation of the bare earth while on the DSMs, all features are present such as buildings and vegetation.




Figure 22. The production of last return DSM (a) and DTM (b), first return DSM (c) and secondary DTM (d) in some portion of Ipil floodplain

### 3.7 LiDAR Image Processing and Orthophotograph Rectification

There are no available orthophotographs for the Ipil floodplain.

### 3.8 DEM Editing and Hydro-Correction

Twelve (12) mission blocks were processed for Ipil flood plain. These blocks are composed of Bohol blocks with a total area of 1,994.07 square kilometers. Table 17 shows the name and corresponding area of each block in square kilometers.

Table 17. LiDAR blocks with its corresponding area

LiDAR Blocks	Area (sq.km)
Bohol_Bl1B	184.09
Bohol_Bl1B_supplement1	91.00
Bohol_Bl1B_supplement2	149.54
Bohol_Bl1C	155.48
Bohol_Bl1D	107.10
Bohol_Bl1D_supplement	248.32
Bohol_Bl1E	317.41
Bohol_Bl51B	205.05
Bohol_Bl51C	107.09
Bohol_Bl51C_additional	203.43
Bohol_Bl51F	94.64
Bohol_Bl51A	130.92
TOTAL	1,994.07 sq.km

Portions of DTM before and after manual editing are shown in Figure 23. The mountain (Figure 23a) has been misclassified and removed during classification process and has to be retrieved to complete the surface (Figure 23b). Another, the bridge (Figure 23c) is also considered to be impedance to the flow of water along the river and has to be removed (Figure 23d) in order to hydrologically correct the river. These are shown in the figure below.






Figure 23. Portions in the DTM of Ipil floodplain – a mountain before (a) and (b) after data retrieval; and a bridge before (c) before and after (d) manual editing

### 3.9 Mosaicking of Blocks

No assumed reference block was used in mosaicking because the identified reference for shifting was an existing calibrated Bohol DEM overlapping with the blocks to be mosaicked. Table 18 shows the shift values applied to each LiDAR block during mosaicking.

Mosaicked LiDAR DTM for Ipil floodplain is shown in Figure 24. It can be seen that the entire Ipil floodplain is 100% covered by LiDAR data.

Table 18. Shift Values of each LiDAR Block of Ipil floodplain

Mission Blocks	Shift Values (meters)		
	x	y	z
Bohol_Bl1B	0.00	0.00	-0.40
Bohol_Bl1B_supplement1	0.00	0.00	+0.07
Bohol_Bl1B_supplement2	0.00	0.00	-5.62
Bohol_Bl1C	0.00	0.00	-0.40
Bohol_Bl1D	0.00	0.00	0.00
Bohol_Bl1D_supplement	0.00	0.00	-0.36
Bohol_Bl1E	0.00	0.00	-0.51
Bohol_Bl51B	0.00	0.00	-0.35
Bohol_Bl51C	0.00	0.00	-3.61
Bohol_Bl51C_additional	0.00	0.00	-3.48
Bohol_Bl51F	1.00	-3.00	-4.03
Bohol_Bl51A_	0.00	0.00	-3.77




Figure 24. Map of Processed LiDAR Data for Ipil Flood Plain



### 3.10 Calibration and Validation of Mosaicked LiDAR DEM

The extent of the validation survey done by the Data Validation and Bathymetry Component (DVBC) in Ipil to collect points with which the LiDAR dataset is validated is shown in Figure 25. A total of 1448 survey points were gathered for calibration and validation of Ipil LiDAR data. However, the point dataset was not used for the calibration of the LiDAR data for Ipil because during the mosaicking process, each LiDAR block was referred to the calibrated Bohol DEM. Therefore, the mosaicked DEM of Ipil can already be considered as a calibrated DEM.

A good correlation between the uncalibrated Bohol LiDAR DTM and ground survey elevation values is shown in Figure 26. Statistical values were computed from extracted LiDAR values using the selected points to assess the quality of data and obtain the value for vertical adjustment. The computed height difference between the LiDAR DTM and calibration points is 1.29 meters with a standard deviation of 0.19 meters. Calibration of Bohol LiDAR data was done by subtracting the height difference value, 1.29 meters, to Bohol mosaicked LiDAR data. Table 19 shows the statistical values of the compared elevation values between Bohol LiDAR data and calibration data. These values were also applicable to the Ipil DEM.




Figure 25. Map of Ipil Flood Plain with validation survey points in green




Figure 26. Correlation plot between calibration survey points and LiDAR data

Table 19. Calibration Statistical Measures

Calibration Statistical Measures	Value (meters)
Height Difference	1.29
Standard Deviation	0.19
Average	-1.28
Minimum	-1.65
Maximum	-0.86

All survey points were used for the validation of calibrated Ipil DTM. The good correlation between the calibrated mosaicked LiDAR elevation values and the ground survey elevation, which reflects the quality of the LiDAR DTM is shown in Figure 27. The computed RMSE between the calibrated LiDAR DTM and validation elevation values is 0.20 meters with a standard deviation of 0.18 meters, as shown in Table 20.




Figure 27. Correlation plot between validation survey points and LiDAR data

Table 20. Validation Statistical Measures

Validation Statistical Measures	Value (meters)
RMSE	0.20
Standard Deviation	0.18
Average	0.08
Minimum	-0.39
Maximum	0.40

### 3.11 Integration of Bathymetric Data into the LiDAR Digital Terrain Model

For bathy integration, centerline and zigzag data were available for Ipil with 13,300 bathymetric survey points. The resulting raster surface produced was done by Krigging interpolation method. After burning the bathymetric data to the calibrated DTM, assessment of the interpolated surface is represented by the computed RMSE value of 0.58 meters. The extent of the bathymetric survey done by the Data Validation and Bathymetry Component (DVBC) in Ipil integrated with the processed LiDAR DEM is shown in Figure 28.






Figure 28. Map of Ipil Flood Plain with bathymetric survey points shown in blue

### 3.12 Feature Extraction

The features salient in flood hazard exposure analysis include buildings, road networks, bridges and water bodies within the floodplain area with 200 m buffer zone. Mosaicked LiDAR DEM with 1 m resolution was used to delineate footprints of building features, which consist of residential buildings, government offices, medical facilities, religious institutions, and commercial establishments, among others. Road networks comprise of main thoroughfares such as highways and municipal and barangay roads essential for routing of disaster response efforts. These features are represented by a network of road centerlines.

#### 3.12.1 Quality Checking of Digitized Features' Boundary

Ipil floodplain, including its 200 m buffer, has a total area of 270.51 sq km. For this area, a total of 8.0 sq km, corresponding to a total of 1210 building features, are considered for QC. Figure 29 shows the QC blocks for Ipil floodplain.




Figure 29. Blocks (in blue) of Ipil building features that were subjected to QC

Quality checking of Ipil building features resulted in the ratings shown in Table 21.

Table 21. Quality Checking Ratings for Ipil Building Features

FLOODPLAIN	COMPLETENESS	CORRECTNESS	QUALITY	REMARKS
Ipil	99.91	100.00	84.79	PASSED

#### 3.12.2 Height Extraction

Height extraction was done for 26,511 building features in Ipil floodplain. Of these building features, 2,510 were filtered out after height extraction, resulting to 24,001 buildings with height attributes. The lowest building height is at 2.00 m, while the highest building is at 13.63 m.

### 3.12.3 Feature Attribution

In attribution, combination of participatory mapping and actual field validation was done. Representatives from LGU were invited to assist in the determination of the features. The remaining unidentified features were then validated on the field.

Table 22 summarizes the number of building features per type. On the other hand, Table 23 shows the total length of each road type, while Table 24 shows the number of water features extracted per type.

Table 22. Building Features Extracted for Ipil Floodplain

Facility Type	No. of Features
Residential	23,570
School	196
Market	28
Agricultural/Agro-Industrial Facilities	47
Medical Institutions	10
Barangay Hall	20
Military Institution	0
Sports Center/Gymnasium/Covered Court	16
Telecommunication Facilities	0
Transport Terminal	4
Warehouse	1
Power Plant/Substation	0
NGO/CSO Offices	4
Police Station	3
Water Supply/Sewerage	0
Religious Institutions	20
Bank	0
Factory	4
Gas Station	6
Fire Station	0
Other Government Offices	15
Other Commercial Establishments	57
Total	24,001

Table 23. Total Length of Extracted Roads for Ipil Floodplain

Floodplain	Road Network Length (km)					Total
	Barangay Road	City/Municipal Road	Provincial Road	National Road	Others	
Ipil	409.37	0	70.04	31.61	0	511.02



Table 24. Number of Extracted Water Bodies for Ipil Floodplain

Floodplain	Water Body Type					Total
	Rivers/Streams	Lakes/Ponds	Sea	Dam	Fish Pen	
Ipil	6	1	0	1	0	8

A total of 36 bridges and culverts over small channels that are part of the river network were also extracted for the floodplain.

### 3.12.4 Final Quality Checking of Extracted Features

All extracted ground features were completely given the required attributes. All these output features comprise the flood hazard exposure database for the floodplain. This completes the feature extraction phase of the project.

Figure 30 shows the Digital Surface Model (DSM) of Ipil floodplain overlaid with its ground features.




Figure 30. Extracted features for Ipil floodplain

## CHAPTER 4: LIDAR VALIDATION SURVEY AND MEASUREMENTS OF THE IPIL RIVER BASIN

*Engr. Louie P. Balicanta, Engr. Joemarie S. Caballero, Ms. Patrizia Mae. P. dela Cruz, Engr. Kristine Ailene B. Borromeo Ms. Jeline M. Amante, Marie Angelique R. Estipona, Charie Mae V. Manliguez, Engr. Janina Jupiter, and Vie Marie Paola M. Rivera*

The methods applied in this Chapter were based on the DREAM methods manual (Balicanta, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

### 4.1 Summary of Activities

The Data Validation and Bathymetry Component (DVBC) conducted a field survey in Ipil River on September 2-10, 2016 with the following scope of work: reconnaissance; control survey; cross-section and as-built survey at Tugas Bridge in Brgy. Hinlayagan Ilaud and Trinidad Bridge in Brgy. Poblacion, Trinidad, Bohol; validation points acquisition of about 89 km covering the Ipil River Basin area; and bathymetric survey from its upstream in Brgy. Hinlayagan Ilaud, Municipality of Trinidad to the mouth of the river located in Brgy. Balintawak, in the Municipality of Bien Unidos, with an approximate length of 13.739 km using Ohmex™ single beam echo sounder and Trimble® SPS 882 GNSS PPK survey technique (Figure 31).




Figure 31. Extent of the bathymetric survey (in blue) in Ipil River and the LiDAR data validation survey (in red)



## 4.2 Control Survey

The GNSS network used for Ipil River Basin is composed of a single loop established on September 3, 2016 occupying the following reference points: BHL-57, a second-order GCP in Brgy. Tanghaligue, Municipality of Talibon; BHL-62, a second-order GCP in Brgy. Humayhumay, Municipality of Ubay; and BH-393, a first-order BM at Hinlayagan Bridge, Brgy. Hinlayagan Ilaya, Municipality of Trinidad.

The summary of reference and control points and its location is summarized in Table 25 while the GNSS network established is illustrated in Figure 32.




Figure 32. GNSS Network covering Ipil River

Table 25. List of Reference and Control Points occupied for Ipil River Survey

Control Point	Order of Accuracy	Geographic Coordinates (WGS 84)				
		Latitude	Longitude	Ellipsoidal Height (m)	BM Ortho (m)	Date Established
BHL-57	2nd order, GCP	10°09'04.81120"N	124°15'25.59670"E	77.040	-	2013
BHL-62	2nd order, GCP	10°03'27.40372"N	124°24'59.17305"E	72.344	-	2013
BH-393	1st order, BM	-	-	-	10.781	2016

The GNSS set-ups on recovered reference points and established control points in Ipil River are shown in Figure 33 to Figure 35.



Figure 33. GNSS base set up, Trimble® SPS 882, at BHL-57 located along Ubay-Talibon Road, Brgy. Tanghaligue, Municipality of Talibon, Bohol




Figure 34. NSS receiver setup, Trimble® SPS 882, at BHL-62 located along Ubay-Talibon Road, Brgy. Humayhumay, Municipality of Ubay, Bohol



Figure 35. GNSS receiver setup, Trimble® SPS 852, at BH-393 located at the approach of Hinlayagan Bridge, Brgy. Hinlayagan Ilaya, Municipality of Trinidad, Bohol

### 4.3 Baseline Processing

GNSS Baselines were processed simultaneously in TBC by observing that all baselines have fixed solutions with horizontal and vertical precisions within +/- 20 cm and +/- 10 cm requirement, respectively. In case where one or more baselines did not meet all of these criteria, masking is performed. Masking is done by removing/masking portions of these baseline data using the same processing software. It is repeatedly processed until all baseline requirements are met. If the reiteration yields out of the required accuracy, resurvey is initiated. Baseline processing result of control points in Ipil River Basin is summarized in Table 26 generated by TBC software.

Table 26. Baseline Processing Summary Report for Ipil River Survey

Observation	Date of Observation	Solution Type	H.Prec. (Meter)	V.Prec. (Meter)	Geodetic Az.	Ellipsoid Dist. (Meter)	Height (Meter)
BMBH-393 --- BHL-57 (B3)	09-03-2016	Fixed	0.004	0.020	323°23'48"	16654.717	1.627
BMBH-393 --- BHL-62 (B2)	09-03-2016	Fixed	0.004	0.018	68°15'50"	8108.333	-3.073
BHL-57 --- BHL-62 (B1)	09-03-2016	Fixed	0.004	0.018	120°40'53"	20308.187	-4.683

As shown Table 26 a total of three (3) baselines were processed with reference points BHL-57 and BHL-62 held fixed for coordinate value; and BH-393 fixed for elevation values. All of them passed the required accuracy.

## 4.4 Network Adjustment

After the baseline processing procedure, network adjustment is performed using TBC. Looking at the Adjusted Grid Coordinates table of the TBC generated Network Adjustment Report, it is observed that the square root of the sum of the squares of x and y must be less than 20 cm and z less than 10 cm or in equation form:

$$z_e < 10 \text{ cm} < 20 \text{ cm} \text{ and } z_s < 10 \text{ cm}$$

Where:

$x_e$  is the Easting error,

$y_e$  is the Northing error, and

$z_e$  is the Elevation error

for each control point. See the Network Adjustment Report shown in Table 27 to Table 30 for complete details.

The three (3) control points, BHL-57, BHL-62, and BH-393 were occupied and observed simultaneously to form a GNSS loop. Coordinates of BHL-57 and BHL-62; and elevation value of BH-393 were held fixed during the processing of the control points as presented in Table 29. Through these reference points, the coordinates and elevation of the unknown control points will be computed.

Table 27. Control Point Constraints

Point ID	Type	East $\sigma$ (Meter)	North $\sigma$ (Meter)	Height $\sigma$ (Meter)	Elevation $\sigma$ (Meter)
BHL-57	Local	Fixed	Fixed		
BHL-62	Local	Fixed	Fixed		
BMBH-393	Grid				Fixed
Fixed = 0.000001 (Meter)					

The list of adjusted grid coordinates, i.e. Northing, Easting, Elevation and computed standard errors of the control points in the network is indicated in Table 28. The fixed controls BHL-57 and BHL-62 have no values for grid error elevation error.

Table 28. Adjusted Grid Coordinates

Point ID	Easting (Meter)	Easting Error (Meter)	Northing (Meter)	Northing Error (Meter)	Elevation (Meter)	Elevation Error (Meter)	Constraint
BHL-57	637719.837	?	1122411.173	?	12.562	0.029	LL
BHL-62	655222.653	?	1112117.428	?	7.569	0.028	LL
BMBH-393	647704.108	0.004	1109084.107	0.004	10.781	?	e

With the mentioned equation, for horizontal and for the vertical; the computation for the accuracy are as follows:

### a. BHL-57

horizontal accuracy = Fixed

vertical accuracy = 2.9 cm < 10 cm



**b. BHL-62**

horizontal accuracy = Fixed  
 vertical accuracy = 2.8 cm < 10 cm

**c. BH-393**

horizontal accuracy =  $\sqrt{(0.4)^2 + (0.4)^2}$   
 =  $\sqrt{0.16 + 0.16}$   
 = 0.32 < 20 cm  
 vertical accuracy = Fixed

Following the given formula, the horizontal and vertical accuracy result of the two occupied control points are within the required precision.

Table 29. Adjusted Geodetic Coordinates

Point ID	Latitude	Longitude	Ellipsoidal Height (Meter)	Height Error (Meter)	Constraint
BHL-57	N10°09'04.81120"	E124°15'25.59670"	77.040	0.029	LL
BHL-62	N10°03'27.40372"	E124°24'59.17305"	72.344	0.028	LL
BMBH-393	N10°01'49.69638"	E124°20'51.82322"	75.412	?	e

The corresponding geodetic coordinates of the observed points are within the required accuracy as shown in Table 29. Based on the result of the computation, the accuracy condition is satisfied; hence, the required accuracy for the program was met.

The summary of reference and control points used is indicated in Table 30.

Table 30. Reference and control points used and its location (Source: NAMRIA, UP-TCAGP)

Control Point	Order of Accuracy	Geographic Coordinates (WGS 84)			UTM ZONE 51 N		
		Latitude	Longitude	Ellipsoidal Height (m)	Northing	Easting	BM Ortho (m)
BHL-57	2nd order, GCP	10°09'04.81120"N	124°15'25.59670"E	77.040	1122411.173	637719.837	12.562
BHL-62	2nd order, GCP	10°03'27.40372"N	124°24'59.17305"E	72.344	1112117.428	655222.653	7.569
BH-393	1st order, BM	10°01'49.69638"N	124°20'51.82322"E	75.412	1109084.107	647704.108	10.781



## 4.5 Cross-section and Bridge As-Built survey and Water Level Marking

Cross-section and as-built survey were conducted on September 4, 2016 at the downstream side of Tugas Bridge in Brgy. Hinlayagan Ilaud, Municipality of Trinidad, Bohol, and Trinidad Bridge in Brgy. Poblacion, Municipality of Trinidad, Bohol as shown in Figure 36 and Figure 38. A Trimble® SPS 882 and Trimble® SPS 885 GNSS PPK survey technique were utilized for this survey as shown in Figure 37 and Figure 39.



Figure 36. Tugas Bridge facing upstream



Figure 37. Bridge As-Built Survey using PPK Technique in Tugas Bridge





Figure 38. Trinidad Bridge facing downstream



Figure 39. Bridge As-Built Survey using PPK Technique in Trinidad Bridge

The cross-sectional line of Tugas Bridge is about 49.733 m with nineteen (19) cross-sectional points using the control point BHL-57 as the GNSS base station; while the cross-sectional line of Trinidad Bridge is about 110.151 m with seventy-nine (79) cross-sectional points using the control point BH-393 as the GNSS base station. The cross-section diagrams and their location maps are shown in Figure 40 to Figure 43, while its bridge data forms are shown in Figure 44 and Figure 45, respectively.






Figure 42. Trinidad Bridge cross-section diagram




Figure 43. Trinidad bridge cross-section location map



**Bridge Data Form**

Bridge Name: <u>Tugas Bridge</u>	Date: <u>September 4, 2016</u>
River Name: <u>Ipil River</u>	Time: <u>12:00 PM</u>
Location (Brgy, City, Region): <u>Brgy. Hinlayagan Ilaud, Municipality of Trinidad, Bohol</u>	
Survey Team: <u>Mady Miras, Randell Pabroquez, Janina Jupiter</u>	
Flow condition: <u>normal</u>	Weather Condition: <u>fair</u>
Latitude: <u>10°02'58.90424" N</u>	Longitude: <u>124°21'07.67434" E</u>

Deck (Please start your measurement from the left side of the bank facing upstream)

Elevation: Not available      Width: 2.5 m      Span (BA3-BA2): 30.460 m

Station	High Chord Elevation	Low Chord Elevation
1	Not available	Not available

Bridge Approach (Please start your measurement from the left side of the bank facing upstream)

	Station (Distance from BA1)	Elevation		Station (Distance from BA1)	Elevation
BA1	0	4.990 m	BA3	39.378 m	4.961 m
BA2	8.919 m	5.417 m	BA4	50.989 m	2.306 m

**Abutment:** Is the abutment sloping? No; If yes, fill in the following information:

	Station (Distance from BA1)	Elevation
Ab1	Not available	Not available
Ab2	Not available	Not available

**Pier** (Please start your measurement from the left side of the bank facing upstream)

Shape: Not available      Number of Piers: Not available      Height of column footing: Not available

	Station (Distance from BA1)	Elevation	Pier Diameter
Not available	Not available	Not available	Not available

NOTE: Use the center of the pier as reference to its station

Figure 44. Bridge as-built form of Tugas Bridge

**Bridge Data Form**

<b>Bridge Name:</b> <u>Trinidad Bridge</u>		<b>Date:</b> <u>September 4, 2016</u>	
<b>River Name:</b> <u>Ipil River</u>		<b>Time:</b> <u>1:00 PM</u>	
<b>Location (Brgy, City, Region):</b> <u>Brgy. Poblacion, Municipality of Trinidad, Bohol</u>			
<b>Survey Team:</b> <u>Mady Miras, Randell Pabroquez, Janina Jupiter</u>			
<b>Flow condition:</b> <u>normal</u>		<b>Weather Condition:</b> <u>fair</u>	
<b>Latitude:</b> <u>10°04'46.03040" N</u>		<b>Longitude:</b> <u>124°20'40.49615" E</u>	

**Deck** (Please start your measurement from the left side of the bank facing upstream)  
**Elevation:** Not available      **Width:** 8.68 m      **Span (BA3-BA2):** 76.320 m

Station	High Chord Elevation	Low Chord Elevation
1	Not available	Not available

**Bridge Approach** (Please start your measurement from the left side of the bank facing upstream)

	Station(Distance from BA1)	Elevation		Station(Distance from BA1)	Elevation
BA1	0	6.383 m	BA3	91.689 m	6.182 m
BA2	15.369 m	6.455 m	BA4	110.312 m	5.703 m

**Abutment:** Is the abutment sloping? Yes; If yes, fill in the following information:

	Station (Distance from BA1)	Elevation
Ab1	Not available	Not available
Ab2	Not available	Not available

**Pier** (Please start your measurement from the left side of the bank facing upstream)

Shape: Not available      Number of Piers: Not available      Height of column footing: Not available

	Station (Distance from BA1)	Elevation	Pier Diameter
Pier 1	35.534 m	6.460 m	1 m
Pier 2	53.524 m	6.398 m	1 m
Pier 3	71.521 m	6.310 m	1 m

NOTE: Use the center of the pier as reference to its station

Figure 45. Bridge as-built form of Trinidad Bridge

Water surface elevation of Ipil River in Tugas Bridge was determined using Trimble® SPS 885 GNSS PPK survey technique on September 7, 2016 at 4:16 PM with a value of 0.813 m in MSL as shown in Figure 46. Meanwhile, water surface elevation of Ipil River in Trinidad Bridge was determined using Trimble® SPS 882 GNSS PPK survey technique on September 7, 2016 at 3:34 PM with a value of 0.848 m in MSL as shown in Figure 47. These were translated onto markings on the wall under the bridge using the same technique as shown in Figure 46 and Figure 47, respectively. The markings will serve as reference for flow data gathering and depth gauge deployment of partner HEI responsible for Ipil River, USC.





Figure 46. Water-level markings on Tugas Bridge



Figure 47. Water-level markings on Trinidad Bridge

#### 4.6 Validation Points Acquisition Survey

Validation points acquisition survey was conducted on September 5 and 7, 2016 using a survey-grade GNSS Rover receiver, Trimble® SPS 885, mounted in front of a vehicle as shown in Figure 48. It was secured with a nylon rope to ensure that it was horizontally and vertically balanced. The antenna heights were 2.168 m and 1.336 m and measured from the ground up to the bottom of notch of the GNSS Rover receiver. The PPK technique utilized for the conduct of the survey was set to continuous topo mode with BH-393 occupied as the GNSS base station.



Figure 48. Validation points acquisition survey set up along Ipil River Basin

The survey branched into two directions – the first branch started from Brgy. Sto. Niño, Municipality of Jetafe, going south it traversed thirteen (13) barangays and ended in Brgy. Concepcion, Municipality of Danao; and the second branch started in Brgy. Poblacion, Municipality of Jetafe, going east it traversed thirty-three (33) barangays and ended in Brgy. Cabatang, Municipality of Alicia. A total of 13,056 points were gathered with approximate length of 87.888 km using BH-393 as GNSS base station for the entire extent validation points acquisition survey as illustrated in the map in Figure 49.




Figure 49. Validation point acquisition survey of Ipil River Basin



## 4.7 River Bathymetric Survey

Bathymetric survey was executed on September 5 and 6, 2016 using an Ohmex™ single beam echo sounder and Trimble® SPS 885 in GNSS PPK survey technique in continuous topo mode as illustrated in Figure 50. The survey started at the upstream portion of the river in Brgy. Hinlayagan Ilaud, Municipality of Trinidad, with coordinates 10°02'58.32639"N, 124°21'08.27857"E, and ended at the mouth of the river in Brgy. Balintawak, Municipality of Talibon with coordinates 10°07'49.14771"N, 124°20'45.83735"E. The partner HEI, USC, suggested an additional 3 km to be surveyed from the major tributary of the river because of flood-affected communities residing there. The survey continued on September 7, 2016, starting in Brgy. Poblacion, Municipality of Trinidad, with coordinates 10°05'35.24563"N, 124°20'41.17341"E and ended in the same mouth of the river.



Figure 50. Bathymetric survey using OHMEX™ single beam echo sounder in Ipil River

The bathymetric survey for Ipil River gathered a total of 33,406 points covering a total estimated length of 13.739 km of the river traversing Barangays Hinlayagan Ilaud, Mabuhay Cabigohan, and Poblacion in Municipality of Trinidad; and Barangays San Roque, San Agustin, and Balintawak in Municipality of Talibon. A CAD drawing was also produced to illustrate the riverbed profile of Ipil River. As shown in Figure 52 and Figure 53, the highest and lowest elevation has a -7.159-m difference. The highest elevation observed was 0.073 m in MSL located in Brgy. Balintawak, Municipality of Talibon while the lowest was -7.086 m below MSL located at the middle portion of the river located in Brgy. Mabuhay Cabigohan, Municipality of Trinidad.




Figure 51. Bathymetric survey of Ipil River




Figure 52. Ipil Riverbed Profile, from Tugas Bridge in Brgy. Hinlayagan Ilaud upstream




Figure 53. Ipil Riverbed Profile, from Tugas Bridge in Brgy. Hinlayagan Ilaud



## CHAPTER 5: FLOOD MODELING AND MAPPING

*Dr. Alfredo Mahar Lagmay, Christopher Uichanco, Sylvia Sueno, Marc Moises, Hale Ines, Miguel del Rosario, Kenneth Punay, Neil Tingin, Pauline Racoma*

The methods applied in this Chapter were based on the DREAM methods manual (Lagmay, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

### 5.1 Data Used for Hydrologic Modeling

#### 5.1.1 Hydrometry and Rating Curves

All data that affect the hydrologic cycle of the river basin were monitored, collected, and analyzed. Rainfall, water level, and flow in a certain period of time, which may affect the hydrologic cycle of the Ipil River Basin were monitored, collected, and analyzed.

#### 5.1.2 Precipitation

Precipitation data was taken from automatic rain gauge (ARG) installed by the Department of Science and Technology – Advanced Science and Technology Institute (DOST-ASTI). The nearby rain gauge station of Ipil River basin is located in the Municipality of San Miguel.

The total rain from the San Miguel rain gauge is 12.5 mm. It peaked to 6 mm on September 11, 2016, 22:00. The lag time between the peak rainfall and discharge is 4 hours and 15 minutes, as shown in Figure 57.




Figure 54. The location map of Ipil HEC-HMS model used for calibration

### 5.1.3 Rating Curves and River Outflow

A rating curve was developed at Tugas Bridge, Trinidad (10°2'58.56"N and 124°21'7.2"E). It gives the relationship between the observed water levels and outflow of the watershed at this location.

For Tugas Bridge, the rating curve is expressed as shown in Figure 56.




Figure 55. Cross-Section Plot of Tugas Bridge




Figure 56. Rating Curve at Tugas Bridge, Trinidad

This rating curve equation was used to compute the river outflow at Tugas Bridge for the calibration of the HEC-HMS model shown in Figure 5. Peak discharge is 21.963 m<sup>3</sup>/s at 1:00, September 12, 2016.




Figure 57. Rainfall and outflow data at Ipil used for modeling

## 5.2 RIDF Station

The Philippines Atmospheric Geophysical and Astronomical Services Administration (PAGASA) computed Rainfall Intensity Duration Frequency (RIDF) values for the Tagbilaran Point Gauge. This station chosen based on its proximity to the Ipil watershed. The extreme values for this watershed were computed based on a 39-year record.

Table 31. RIDF values for Tagbilaran Point Rain Gauge computed by PAGASA

COMPUTED EXTREME VALUES (in mm) OF PRECIPITATION									
T (yrs)	10 mins	20 mins	30 mins	1 hr	2 hrs	3 hrs	6 hrs	12 hrs	24 hrs
2	14.4	21.9	26.5	34	43.7	50.4	62.6	73.8	84.1
5	23.1	35.4	41.8	54.6	65.1	76.5	95.1	108.2	121.2
10	28.8	44.3	52	68.3	79.3	93.7	116.7	131	145.7
15	32.1	49.3	57.7	76.1	87.3	103.5	128.8	143.9	159.6
20	34.3	52.8	61.7	81.5	92.9	110.3	137.3	152.9	169.3
25	36.1	55.5	64.8	85.6	97.3	115.5	143.8	159.8	176.7
50	41.5	63.8	74.4	98.5	110.6	131.7	164	181.1	199.7
100	46.8	72.1	83.8	111.2	123.8	147.7	184	202.3	222.6




Figure 58. Tagbilaran Point RIDF location relative to Ipil River Basin




Figure 59. Synthetic storm generated for a 24-hr period rainfall for various return periods

### 5.3 HMS Model

The soil shapefile (dated pre-2004) was taken from the Bureau of Soils and Water Management under the Department of Environment and Natural Resources Management (Figure 60). The land cover dataset is from the National Mapping and Resource information Authority (NAMRIA) and can be seen in Figure 61.






Figure 60. The soil map of the Ipil River Basin used for the estimation of the CN parameter. (Source of data: Digital soil map of the Philippines published by the Bureau of Soil and Water Management – Department of Agriculture)




Figure 61. The land cover map of the Ipil River Basin used for the estimation of the CN and watershed lag parameters of the rainfall-runoff model. (Source: National Mapping and Resource Information Authority)




Figure 62. The slope map of the Ipil River Basin




Figure 63. Stream Delineation Map of Ipil River Basin




Figure 64. The Ipil River Basin Model Domain generated using HEC-HMS.

### 5.4 Cross-section Data

Riverbed cross-sections of the watershed were necessary in the HEC-RAS model setup. The cross-section data for the HEC-RAS model was derived from the LiDAR DEM data. It was defined using the Arc GeorAS tool and was post-processed in ArcGIS.




Figure 65. River cross-section of Ipil River generated through Arcmap HEC GeorAS tool

## 5.5 Flo 2D Model

No input.

## 5.6 Results of HMS Calibration

After calibrating the Ipil HEC-HMS river basin model, its accuracy was measured against the observed values (see Annex 9: Ipil Model Basin Parameters). Figure 66 shows the comparison between the two discharge data.




Figure 66. Outflow Hydrograph of Ipil produced by the HEC-HMS model compared with observed outflow

Table 32. Range of calibrated values for the Ipil River Basin.

Hydrologic Element	Calculation Type	Method	Parameter	Range of Calibrated Values
Basin	Loss	SCS Curve Number	Initial Abstraction (mm)	0.51-4.95
			Curve Number	66.74-97.46
			Impervious (%)	0
	Transform	Clark Unit Hydrograph	Time of Concentration (hr)	0.44-12.06
			Storage Coefficient (hr)	1.48-11.38
	Baseflow	Recession	Recession Constant	0.64-1
Ratio to Peak			0.13-0.2	
Reach	Routing	Muskingum-Cunge	Manning's Coefficient	0.02-0.04

Initial abstraction defines the amount of precipitation that must fall before surface runoff. The magnitude of the outflow hydrograph increases as initial abstraction decreases. The range of values 0.51 to 4.95 mm means that there is minimal to average amount of infiltration or rainfall interception by vegetation.



Curve number is the estimate of the precipitation excess of soil cover, land use, and antecedent moisture. The magnitude of the outflow hydrograph increases as curve number increases. The range of 65 to 90 for curve number is advisable for Philippine watersheds depending on the soil and land cover of the area (M. Horritt, personal communication, 2012). For Ipil river basin, the curve number is 66.74 to 97.46.

Time of concentration and storage coefficient are the travel time and index of temporary storage of runoff in a watershed. The range of calibrated values 0.44 to 12.06 minutes determines the reaction time of the model with respect to the rainfall. The peak magnitude of the hydrograph also decreases when these parameters are increased.

Recession constant is the rate at which baseflow recedes between storm events and ratio to peak is the ratio of the baseflow discharge to the peak discharge. Recession constant of 0.64 to 1 indicates that the basin is unlikely to quickly go back to its original discharge and instead, will be higher. Ratio to peak of 0.13 to 0.2 indicates a steeper receding limb of the outflow hydrograph.

Manning's roughness coefficient of 0.02 to 0.04 corresponds to the common roughness in Ipil, which is determined to be cultivated with mature field crops (Brunner, 2010).

Table 33. Summary of the Efficiency Test of Ipil HMS Model

Accuracy Measure	Value
$r^2$	0.9437
NSE	0.9353
PBIAS	-1.3024
RSR	0.2522

The Root Mean Square Error (RMSE) method aggregates the individual differences of these two measurements. It was identified at 0.9806 m<sup>3</sup>/s.

The Pearson correlation coefficient ( $r^2$ ) assesses the strength of the linear relationship between the observations and the model. This value being close to 1 corresponds to an almost perfect match of the observed discharge and the resulting discharge from the HEC HMS model. Here, it measured 0.9437.

The Nash-Sutcliffe (E) method was also used to assess the predictive power of the model. Here the optimal value is 1. The model attained an efficiency coefficient of 0.9353.

A positive Percent Bias (PBIAS) indicates a model's propensity towards under-prediction. Negative values indicate bias towards over-prediction. Again, the optimal value is 0. In the model, the PBIAS is -1.3024.

The Observation Standard Deviation Ratio, RSR, is an error index. A perfect model attains a value of 0 when the error in the units of the valuable a quantified. The model has an RSR value of 0.28.

## 5.7 Calculated outflow hydrographs and discharge values for different rainfall return periods

### 5.7.1 Hydrograph using the Rainfall Runoff Model

The summary graph (Figure 67) shows the Ipil outflow using the Tagbilaran Point Rainfall Intensity-Duration-Frequency curves (RIDF) in 5 different return periods (5-year, 10-year, 25-year, 50-year, and 100-year rainfall time series) based on the Philippine Atmospheric Geophysical and Astronomical Services Administration (PAGASA) data. The simulation results reveal significant increase in outflow magnitude as the rainfall intensity increases for a range of durations and return periods.




Figure 67. Outflow hydrograph at Ipil generated using Tagbilaran PointRIDF simulated in HEC-HMS

A summary of the total precipitation, peak rainfall, peak outflow and time to peak of the Ipil River discharge using the Tagbilaran Point Rainfall Intensity-Duration-Frequency curves (RIDF) in five different return periods is shown in Table 34.

Table 34. Peak values of the Ipil HECHMS Model outflow using the Tagbilaran RIDF

RIDF Period	Total Precipitation (mm)	Peak rainfall (mm)	Peak outflow (m <sup>3</sup> /s)	Time to Peak
5-Year	116.5	21.8	446.442	02:50
10-Year	143.3	25.6	579.615	02:50
25-Year	177.2	30.3	750.749	02:50
50-Year	202.4	33.8	879.362	02:50
100-Year	227.3	37.2	1007.088	02:50

## 5.8 River Analysis (RAS) Model Simulation

The HEC-RAS Flood Model produced a simulated water level at every cross-section for every time step for every flood simulation created. The resulting model will be used in determining the flooded areas within the model. The simulated model will be an integral part in determining real-time flood inundation extent of the river after it has been automated and uploaded on the DREAM website. For this publication, only a sample output map river was to be shown. The sample generated map of Ipil River using the calibrated HMS base flow is shown in Figure 68.




Figure 68. Sample output of Ipil RAS Model

## 5.9 Flow Depth and Flood Hazard

The resulting hazard and flow depth maps have a 10m resolution. Figure 69 to Figure 74 shows the 5-, 25-, and 100-year rain return scenarios of the Ipil floodplain.






Figure 69. 100-year Flood Hazard Map for Ipil Floodplain






Figure 70. 100-year Flow Depth Map for Ipil Floodplain






Figure 71. 25-year Flood Hazard Map for Ipil Floodplain






Figure 72. 25-year Flow Depth Map for Ipil Floodplain






Figure 73. 5-year Flood Hazard Map for Ipil Floodplain






Figure 74. 5-year Flow Depth Map for Ipil Floodplain

## 5.10 Inventory of Areas Exposed to Flooding

Affected barangays in the Ipil river basin, grouped by municipality, are listed below. For the said basin, ten municipalities consisting of 67 barangays are expected to experience flooding when subjected to 5-yr rainfall return period. The complete list of educational and health institutions affected by flooding in Ipil Floodplain can be seen in Annexes 12-13.

For the 5-year return period, 1.02% of the municipality of Alicia with an area of 81.7 sq. km. will experience flood levels of less 0.20 meters. 0.023% of the area will experience flood levels of 0.21 to 0.50 meters while 0.12%, 0.0079%, and 0.002% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and, 2.01 to 5 meters, respectively. Listed in Table 35 are the affected areas in square kilometres by flood depth per barangay.

Table 35. Affected Areas in Alicia, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Alicia (in sq. km.)
	Katipunan
0.03-0.20	0.84
0.21-0.50	0.019
0.51-1.00	0.01
1.01-2.00	0.0064
2.01-5.00	0.0018
> 5.00	0



Figure 75. Affected Areas in Alicia, Bohol during 5-Year Rainfall Return Period

For the municipality of Bien Unido, with an area of 27.07 sq. km., 44.6% will experience flood levels of less 0.20 meters. 6.40% of the area will experience flood levels of 0.21 to 0.50 meters while 1.04%, and 0.08% of the area will experience flood depths of 0.51 to 1 meter, and 1.01 to 2 meters, respectively. Listed in Table 36 are the affected areas in square kilometres by flood depth per barangay.

Table 36. Affected Areas in Bien Unido, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Bien Unido (in sq. km.)						
	Liberty	Mandawa	Nueva Esperanza	Nueva Estrella	Poblacion	Puerto San Pedro	Tuboran
0.03-0.20	1.12	1.03	5.51	3.05	0.59	0.78	0.00017
0.21-0.50	0.15	0.057	0.78	0.55	0.062	0.13	0
0.51-1.00	0.058	0.0049	0.13	0.076	0.0088	0.002	0
1.01-2.00	0.0091	0	0.0079	0.0052	0	0	0
2.01-5.00	0	0	0	0	0	0	0
> 5.00	0	0	0	0	0	0	0




Figure 76. Affected Areas in Bien Unido, Bohol during 5-Year Rainfall Return Period

For the municipality of Dagohoy, with an area of 92.47 sq. km., 0.024% will experience flood levels of less 0.20 meters. 0.001% of the area will experience flood levels of 0.21 to 0.50 meters while 0.0002% of the area will experience flood depths of 0.51 to 1 meter. Listed in Table 37 are the affected areas in square kilometres by flood depth per barangay.

Table 37. Affected Areas in Dagohoy, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Dagohoy (in sq. km.)
	Cagawasan
0.03-0.20	0.023
0.21-0.50	0.00097
0.51-1.00	0.00019
1.01-2.00	0
2.01-5.00	0
> 5.00	0






Figure 77. Affected Areas in Dagohoy, Bohol during 5-Year Rainfall

For the municipality of Danao, with an area of 109 sq. km., 2.46% will experience flood levels of less 0.20 meters. 0.08% of the area will experience flood levels of 0.21 to 0.50 meters while 0.05%, 0.02%, 0.007%, and 0.0006% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 38 are the affected areas in square kilometres by flood depth per barangay.

Table 38. Affected Areas in Danao, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Danao (in sq. km.)	
	Dagohoy	San Miguel
0.03-0.20	0.89	1.74
0.21-0.50	0.035	0.051
0.51-1.00	0.024	0.031
1.01-2.00	0.0041	0.019
2.01-5.00	0.0033	0.0042
> 5.00	0	0.0006




Figure 78. Affected Areas in Danao, Bohol during 5-Year Rainfall Return Period

For the municipality of Jetafe, with an area of 94.04 sq. km., 0.025% will experience flood levels of less 0.20 meters. 0.0002% of the area will experience flood levels of 0.21 to 0.50 meters while 0.0001% of the area will experience flood depths of 0.51 to 1 meter. Listed in Table 39 are the affected areas in square kilometres by flood depth per barangay.

Table 39. Affected Areas in Jetafe, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Jetafe (in sq. km.)
	Cabasakan
0.03-0.20	0.024
0.21-0.50	0.0002
0.51-1.00	0.0001
1.01-2.00	0
2.01-5.00	0
> 5.00	0




Figure 79. Figure. Affected Areas in Jetafe, Bohol during 5-Year Rainfall Return Period

For the municipality of Pilar, with an area of 114.4 sq. km., 6.28% will experience flood levels of less 0.20 meters. 0.69% of the area will experience flood levels of 0.21 to 0.50 meters while 0.19%, 0.04%, and 0.03% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and, 2.01 to 5 meters, respectively. Listed in Table 40 are the affected areas in square kilometres by flood depth per barangay.

Table 40. Affected Areas in Pilar, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Pilar (in sq. km.)
	La Suerte
0.03-0.20	7.18
0.21-0.50	0.79
0.51-1.00	0.22
1.01-2.00	0.044
2.01-5.00	0.034
> 5.00	0






Figure 80. Affected Areas in Pilar, Bohol during 5-Year Rainfall Return Period

For the municipality of San Miguel, with an area of 107 sq. km., 86.93% will experience flood levels of less 0.20 meters. 4.52% of the area will experience flood levels of 0.21 to 0.50 meters while 3.43%, 2.02%, 0.57%, and 0.05% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 41 and 42 are the affected areas in square kilometres by flood depth per barangay.




Figure 81. Affected Areas in San Miguel, Bohol during 5-Year Rainfall Return Period

Table 41. Affected Areas in San Miguel, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in San Miguel (in sq. km.)									
	Bayongan	Bugang	Cabangahan	Caluasan	Camanaga	Cambangay Norte	Capayas	Corazon	Garcia	
<b>0.03-0.20</b>	5.62	5.41	7.58	4.8	4.3	3.54	4.57	4.14	7.38	
<b>0.21-0.50</b>	0.2	0.42	0.53	0.14	0.15	0.23	0.2	0.2	0.29	
<b>0.51-1.00</b>	0.23	0.45	0.27	0.091	0.12	0.2	0.18	0.26	0.16	
<b>1.01-2.00</b>	0.17	0.2	0.088	0.082	0.078	0.14	0.08	0.18	0.11	
<b>2.01-5.00</b>	0.008	0.0084	0.02	0.059	0.032	0.0056	0.044	0.011	0.088	
<b>&gt; 5.00</b>	0	0	0	0.0051	0.0001	0	0.0094	0	0.012	

Table 42. Affected Areas in San Miguel, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in San Miguel (in sq. km.)									
	Hagbuyo	Kagawasan	Mahayag	Poblacion	San Isidro	San Jose	San Vicente	Santo Niño	Tomoc	
<b>0.03-0.20</b>	7.88	3.17	5.39	1.63	3.81	3.81	1.78	10.07	8.42	
<b>0.21-0.50</b>	0.63	0.12	0.35	0.1	0.24	0.21	0.081	0.46	0.3	
<b>0.51-1.00</b>	0.38	0.11	0.17	0.14	0.24	0.2	0.047	0.26	0.18	
<b>1.01-2.00</b>	0.14	0.063	0.053	0.095	0.19	0.17	0.06	0.16	0.12	
<b>2.01-5.00</b>	0.034	0.027	0.013	0.023	0.034	0.092	0.0047	0.039	0.068	
<b>&gt; 5.00</b>	0.0013	0.002	0.0002	0.0035	0.0033	0.014	0.00055	0	0.0014	

For the municipality of Talibon, with an area of 148 sq. km., 31.2% will experience flood levels of less 0.20 meters. 2.41% of the area will experience flood levels of 0.21 to 0.50 meters while 1.51%, 0.61%, 0.17%, and 0.001% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 43 are the affected areas in square kilometres by flood depth per barangay.

Table 43. Affected Areas in Talibon, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Talibon (in sq. km.)									
	Balintawak	Magsaysay	Rizal	San Agustin	San Carlos	San Isidro	San Jose	San Roque	Sikatuna	Zamora
0.03-0.20	2.84	13.19	2.13	6.71	1.21	0.089	0.068	5.04	4.4	10.51
0.21-0.50	0.32	0.4	0.08	0.91	0.093	0.0016	0.0004	0.57	0.42	0.76
0.51-1.00	0.087	0.42	0.052	0.31	0.014	0.0011	0	0.21	0.57	0.57
1.01-2.00	0.013	0.31	0.029	0.05	0.0026	0	0	0.026	0.25	0.22
2.01-5.00	0	0.13	0.0071	0.035	0.0008	0	0	0.0013	0.0067	0.074
> 5.00	0	0.0001	0	0.0005	0	0	0	0	0	0.0012




Figure 82. Affected Areas in Talibon, Bohol during 5-Year Rainfall Return Period

For the municipality of Trinidad, with an area of 143 sq. km., 51.83% will experience flood levels of less 0.20 meters. 3.73% of the area will experience flood levels of 0.21 to 0.50 meters while 2.61%, 1.29%, 0.39%, and 0.01% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Tables 44-45 are the affected areas in square kilometres by flood depth per barangay.






Figure 83. Affected Areas in Trinidad, Bohol during 5-Year Rainfall Return Period

Table 44. Affected Areas in Trinidad, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Trinidad (in sq. km.)									
	Banlasan	Bongbong	Catoogan	Guinobatan	Hinlayagan Ilaud	Hinlayagan Ilaya	Kauswagan	Kinan-Oan	La Union	
<b>0.03-0.20</b>	8.03	5.8	0.076	3.62	1.65	4.78	15.29	3.8	2.89	
<b>0.21-0.50</b>	0.44	0.52	0.0042	0.27	0.28	0.4	0.55	0.23	0.22	
<b>0.51-1.00</b>	0.31	0.28	0.00007	0.17	0.17	0.41	0.35	0.13	0.16	
<b>1.01-2.00</b>	0.15	0.13	0	0.049	0.055	0.29	0.22	0.022	0.027	
<b>2.01-5.00</b>	0.078	0.077	0	0.0049	0.034	0.069	0.087	0.0014	0.0063	
<b>&gt; 5.00</b>	0.0064	0.0007	0	0	0	0	0.0012	0	0	

Table 45. Affected Areas in Trinidad, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Trinidad (in sq. km.)									
	La Victoria	Mabuhay Cabigoan	Mahagbu	Manuel M. Roxas	Poblacion	San Isidro	San Vicente	Santo Tomas		
<b>0.03-0.20</b>	2.31	1.8	3.92	2.73	3.1	5.25	5.58	3.39		
<b>0.21-0.50</b>	0.21	0.14	0.29	0.24	0.52	0.34	0.48	0.19		
<b>0.51-1.00</b>	0.13	0.051	0.38	0.33	0.26	0.19	0.26	0.14		
<b>1.01-2.00</b>	0.019	0.043	0.24	0.14	0.1	0.11	0.17	0.083		
<b>2.01-5.00</b>	0	0.014	0.0019	0.017	0.029	0.058	0.029	0.052		
<b>&gt; 5.00</b>	0	0	0	0	0	0.0001	0	0.0076		

For the municipality of Ubay, with an area of 264.8 sq. km., 6.09% will experience flood levels of less 0.20 meters. 0.26% of the area will experience flood levels of 0.21 to 0.50 meters while 0.17%, 0.09%, and 0.006% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and 2.01 to 5 meters, respectively. Listed in Table 46 are the affected areas in square kilometres by flood depth per barangay.

Table 46. Affected Areas in Ubay, Bohol during 5-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Ubay (in sq. km.)								
	Buenavista	Bulilis	Camali-An	Gabi	Hambabauran	Lomangog	Los Angeles	Pag-Asa	Tubog
0.03-0.20	0.052	0.78	4.07	1.36	6.82	1.26	0.52	1.22	0.032
0.21-0.50	0.0006	0.022	0.15	0.059	0.29	0.082	0.021	0.074	0.0016
0.51-1.00	0.0001	0.016	0.13	0.039	0.19	0.019	0.014	0.041	0.0001
1.01-2.00	0.0001	0.012	0.088	0.0095	0.11	0.0018	0.0064	0.012	0
2.01-5.00	0	0.0014	0.0033	0	0.0095	0	0.00048	0	0
> 5.00	0	0	0	0	0	0	0	0	0




Figure 84. Affected Areas in Ubay, Bohol during 5-Year Rainfall Return Period

For the 25-year return period, 1.01% of the municipality of Alicia with an area of 81.7 sq. km. will experience flood levels of less 0.20 meters. 0.025% of the area will experience flood levels of 0.21 to 0.50 meters while 0.015%, 0.012%, and 0.003% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and, 2.01 to 5 meters, respectively. Listed in Table 47 are the affected areas in square kilometres by flood depth per barangay.



Table 47. Affected Areas in Alicia, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Alicia (in sq. km.)
	Katipunan
0.03-0.20	0.83
0.21-0.50	0.02
0.51-1.00	0.012
1.01-2.00	0.0098
2.01-5.00	0.0022
> 5.00	0




Figure 85. Affected Areas in Alicia, Bohol during 25-Year Rainfall Return Period

For the municipality of Bien Unido, with an area of 27.07 sq. km., 40.21% will experience flood levels of less 0.20 meters. 8.16% of the area will experience flood levels of 0.21 to 0.50 meters while 3.49%, and 0.26% of the area will experience flood depths of 0.51 to 1 meter, and 1.01 to 2 meters, respectively. Listed in Table 48 are the affected areas in square kilometres by flood depth per barangay.

Table 48. Affected Areas in Bien Unido, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Bien Unido (in sq. km.)						
	Liberty	Mandawa	Nueva Esperanza	Nueva Estrella	Poblacion	Puerto San Pedro	Tuboran
0.03-0.20	1.01	0.96	4.92	2.78	0.54	0.68	0.00017
0.21-0.50	0.16	0.12	1.12	0.56	0.089	0.17	0
0.51-1.00	0.15	0.013	0.36	0.34	0.03	0.053	0
1.01-2.00	0.026	0.00039	0.031	0.013	0	0.0013	0
2.01-5.00	0	0	0	0	0	0	0
> 5.00	0	0	0	0	0	0	0




Figure 86. Affected Areas in Bien Unido, Bohol during 25-Year Rainfall Return Period

For the municipality of Dagohoy, with an area of 92.47 sq. km., 0.024% will experience flood levels of less 0.20 meters. 0.001% of the area will experience flood levels of 0.21 to 0.50 meters while 0.0002% of the area will experience flood depths of 0.51 to 1 meter. Listed in Table 49 are the affected areas in square kilometres by flood depth per barangay.

Table 49. Affected Areas in Dagohoy, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Dagohoy (in sq. km.)
	Cagawasan
0.03-0.20	0.022
0.21-0.50	0.0013
0.51-1.00	0.00019
1.01-2.00	0
2.01-5.00	0
> 5.00	0




Figure 87. Affected Areas in Dagohoy, Bohol during 25-Year Rainfall

For the municipality of Danao, with an area of 109 sq. km., 2.43% will experience flood levels of less 0.20 meters. 0.09% of the area will experience flood levels of 0.21 to 0.50 meters while 0.06%, 0.03%, 0.01%, and 0.0006% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 50 are the affected areas in square kilometres by flood depth per barangay.

Table 50. Affected Areas in Danao, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Danao (in sq. km.)	
	Dagohoy	San Miguel
0.03-0.20	0.88	1.71
0.21-0.50	0.032	0.06
0.51-1.00	0.029	0.037
1.01-2.00	0.01	0.027
2.01-5.00	0.0043	0.0074
> 5.00	0	0.0006






Figure 88. Affected Areas in Danao, Bohol during 25-Year Rainfall Return Period

For the municipality of Jetafe, with an area of 94.04 sq. km., 0.025% will experience flood levels of less 0.20 meters. 0.0002% of the area will experience flood levels of 0.21 to 0.50 meters while 0.0002%, and 0.0001% of the area will experience flood depths of 0.51 to 1 meter, and 1.01 to 2 meters, respectively. Listed in Table 51 are the affected areas in square kilometres by flood depth per barangay.

Table 51. Affected Areas in Jetafe, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Jetafe (in sq. km.)
	Cabasakan
0.03-0.20	0.024
0.21-0.50	0.00017
0.51-1.00	0.0002
1.01-2.00	0.0001
2.01-5.00	0
> 5.00	0




Figure 89. Affected Areas in Jetafe, Bohol during 25-Year Rainfall Return Period

For the municipality of Pilar, with an area of 114.4 sq. km., 5.78% will experience flood levels of less 0.20 meters. 0.7% of the area will experience flood levels of 0.21 to 0.50 meters while 0.62%, 0.08%, and 0.05% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and, 2.01 to 5 meters, respectively. Listed in Table 52 are the affected areas in square kilometres by flood depth per barangay.

Table 52. Affected Areas in Pilar, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Pilar (in sq. km.)
	La Suerte
0.03-0.20	6.61
0.21-0.50	0.8
0.51-1.00	0.71
1.01-2.00	0.088
2.01-5.00	0.053
> 5.00	0




Figure 90. Affected Areas in Pilar, Bohol during 25-Year Rainfall Return Period

For the municipality of San Miguel, with an area of 107 sq. km., 83.25% will experience flood levels of less 0.20 meters. 4.28% of the area will experience flood levels of 0.21 to 0.50 meters while 4.11%, 4.09%, 1.66%, and 0.14% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 53 are the affected areas in square kilometres by flood depth per barangay.




Figure 91. Affected Areas in San Miguel, Bohol during 25-Year Rainfall Return Period

Table 53. Affected Areas in San Miguel, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in San Miguel (in sq. km.)									
	Bayongan	Bugang	Cabangahan	Caluasan	Camanaga	Cambangay Norte	Capayas	Corazon	Garcia	
0.03-0.20	5.45	5.15	7.39	4.7	4.22	3.4	4.47	3.98	7.19	
0.21-0.50	0.23	0.24	0.4	0.14	0.14	0.17	0.17	0.18	0.31	
0.51-1.00	0.17	0.39	0.45	0.1	0.15	0.18	0.2	0.24	0.2	
1.01-2.00	0.29	0.59	0.21	0.084	0.1	0.27	0.13	0.32	0.15	
2.01-5.00	0.081	0.099	0.045	0.12	0.066	0.11	0.093	0.058	0.15	
> 5.00	0	0	0.0004	0.025	0.0027	0	0.018	0.0006	0.033	

Table 54. Affected Areas in San Miguel, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in San Miguel (in sq. km.)									
	Hagbuyo	Kagawasan	Mahayag	Poblacion	San Isidro	San Jose	San Vicente	Santo Niño	Tomoc	
0.03-0.20	6.97	3.12	5.12	1.51	3.62	3.64	1.73	9.47	8.23	
0.21-0.50	0.41	0.11	0.5	0.064	0.14	0.16	0.083	0.83	0.31	
0.51-1.00	0.79	0.12	0.24	0.11	0.22	0.19	0.06	0.35	0.25	
1.01-2.00	0.75	0.084	0.088	0.22	0.3	0.29	0.075	0.26	0.17	
2.01-5.00	0.15	0.057	0.033	0.083	0.23	0.18	0.025	0.086	0.12	
> 5.00	0.0086	0.007	0.0004	0.0092	0.01	0.026	0.001	0.0015	0.0097	



For the municipality of Talibon, with an area of 148 sq. km., 28.93% will experience flood levels of less 0.20 meters. 2.74% of the area will experience flood levels of 0.21 to 0.50 meters while 2.29%, 1.42%, 0.51%, and 0.009% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 55 are the affected areas in square kilometres by flood depth per barangay.

Table 55. Affected Areas in Talibon, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Talibon (in sq. km.)									
	Balintawak	Magsaysay	Rizal	San Agustin	San Carlos	San Isidro	San Jose	San Roque	Sikatuna	Zamora
0.03-0.20	2.69	12.96	2.1	4.99	1.19	0.088	0.068	4.58	4.22	9.94
0.21-0.50	0.36	0.37	0.076	1.66	0.087	0.0016	0.0004	0.68	0.2	0.64
0.51-1.00	0.18	0.34	0.066	1.09	0.041	0.0011	0	0.35	0.51	0.81
1.01-2.00	0.034	0.49	0.044	0.23	0.0034	0.0002	0	0.23	0.51	0.56
2.01-5.00	0.0008	0.28	0.017	0.042	0.0019	0	0	0.0096	0.21	0.19
> 5.00	0	0.0031	0	0.0029	0	0	0	0	0	0.0066




Figure 92. Affected Areas in Talibon, Bohol during 25-Year Rainfall Return Period

For the municipality of Trinidad, with an area of 143 sq. km., 48.26% will experience flood levels of less 0.20 meters. 2.98% of the area will experience flood levels of 0.21 to 0.50 meters while 3.7%, 3.18%, 1.69%, and 0.05% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Tables 56-57 are the affected areas in square kilometres by flood depth per barangay.




Figure 93. Affected Areas in Trinidad, Bohol during 25-Year Rainfall Return Period

Table 56. Table 56. Affected Areas in Trinidad, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Trinidad (in sq. km.)									
	Banlasan	Bongbong	Catoogan	Guinobatan	Hinlayagan Ilaud	Hinlayagan Ilaya	Kauswagan	Kinan-Oan	La Union	
0.03-0.20	7.76	5.39	0.073	3.27	1.28	4.48	15.03	3.72	2.77	
0.21-0.50	0.42	0.47	0.0058	0.19	0.096	0.2	0.55	0.2	0.15	
0.51-1.00	0.39	0.51	0.0011	0.39	0.19	0.33	0.44	0.18	0.19	
1.01-2.00	0.28	0.3	0	0.24	0.5	0.56	0.31	0.082	0.17	
2.01-5.00	0.14	0.13	0	0.012	0.12	0.36	0.16	0.0046	0.014	
> 5.00	0.023	0.0038	0	0.0003	0.0014	0.0091	0.0038	0	0.00069	

Table 57. Affected Areas in Trinidad, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Trinidad (in sq. km.)									
	La Victoria	Mabuhay Cabigohan	Mahagbu	Manuel M. Roxas	Poblacion	San Isidro	San Vicente	Santo Tomas		
0.03-0.20	2.18	1.47	3.69	2.21	2.12	4.98	5.32	3.18		
0.21-0.50	0.16	0.072	0.14	0.099	0.54	0.35	0.4	0.2		
0.51-1.00	0.26	0.12	0.23	0.17	0.92	0.31	0.45	0.2		
1.01-2.00	0.067	0.33	0.24	0.51	0.32	0.19	0.25	0.17		
2.01-5.00	0	0.051	0.53	0.48	0.11	0.1	0.099	0.1		
> 5.00	0	0.0001	0	0.0009	0	0.0027	0.0003	0.02		

For the municipality of Ubay, with an area of 264.8 sq. km., 5.91% will experience flood levels of less 0.20 meters. 0.33% of the area will experience flood levels of 0.21 to 0.50 meters while 0.19%, 0.16%, and 0.03% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and 2.01 to 5 meters, respectively. Listed in Table 58 are the affected areas in square kilometres by flood depth per barangay.

Table 58. Affected Areas in Ubay, Bohol during 25-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Ubay (in sq. km.)								
	Buonavista	Bullilis	Camali-An	Gabi	Hambabauran	Lomangog	Los Angeles	Pag-Asa	Tubog
0.03-0.20	0.052	0.76	3.92	1.33	6.65	1.21	0.51	1.18	0.031
0.21-0.50	0.00032	0.033	0.2	0.067	0.34	0.12	0.022	0.097	0.0029
0.51-1.00	0.0007	0.016	0.13	0.045	0.22	0.031	0.017	0.045	0.0002
1.01-2.00	0.0001	0.017	0.16	0.023	0.19	0.0092	0.0085	0.031	0
2.01-5.00	0	0.004	0.045	0.000003	0.024	0.0001	0.0016	0.0014	0
> 5.00	0	0	0	0	0	0	0	0	0




Figure 94. Affected Areas in Ubay, Bohol during 25-Year Rainfall Return Period

For the 100-year return period, 1.01% of the municipality of Alicia with an area of 81.7 sq. km. will experience flood levels of less 0.20 meters. 0.026% of the area will experience flood levels of 0.21 to 0.50 meters while 0.017%, 0.013%, and 0.004% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and, 2.01 to 5 meters, respectively. Listed in Table 59 are the affected areas in square kilometres by flood depth per barangay.



Table 59. Affected Areas in Alicia, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Alicia (in sq. km.)
	Katipunan
0.03-0.20	0.82
0.21-0.50	0.021
0.51-1.00	0.014
1.01-2.00	0.011
2.01-5.00	0.0033
> 5.00	0




Figure 95. Affected Areas in Alicia, Bohol during 100-Year Rainfall Return Period

For the municipality of Bien Unido, with an area of 27.07 sq. km., 37.65% will experience flood levels of less 0.20 meters. 7.74% of the area will experience flood levels of 0.21 to 0.50 meters while 5.99%, 0.26%, and 0.001 of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and 2.01 to 5 meters, respectively. Listed in Table 60 are the affected areas in square kilometres by flood depth per barangay.

Table 60. Affected Areas in Bien Unido, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Bien Unido (in sq. km.)						
	Liberty	Mandawa	Nueva Esperanza	Nueva Estrella	Poblacion	Puerto San Pedro	Tuboran
0.03-0.20	0.95	0.9	4.54	2.63	0.52	0.65	0.00017
0.21-0.50	0.075	0.17	1.13	0.52	0.077	0.13	0
0.51-1.00	0.25	0.022	0.66	0.51	0.063	0.13	0
1.01-2.00	0.065	0.00039	0.098	0.032	0	0.0046	0
2.01-5.00	0.0004	0	0	0	0	0	0
> 5.00	0	0	0	0	0	0	0




Figure 96. Affected Areas in Bien Unido, Bohol during 100-Year Rainfall Return Period

For the municipality of Dagohoy, with an area of 92.47 sq. km., 0.024% will experience flood levels of less 0.20 meters. 0.001% of the area will experience flood levels of 0.21 to 0.50 meters while 0.0006% of the area will experience flood depths of 0.51 to 1 meter. Listed in Table 61 are the affected areas in square kilometres by flood depth per barangay.

Table 61. Affected Areas in Dagohoy, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Dagohoy (in sq. km.)
	Cagawasan
0.03-0.20	0.022
0.21-0.50	0.0012
0.51-1.00	0.00056
1.01-2.00	0
2.01-5.00	0
> 5.00	0




Figure 97. Affected Areas in Dagohoy, Bohol during 100-Year Rainfall

For the municipality of Danao, with an area of 109 sq. km., 2.40% will experience flood levels of less 0.20 meters. 0.09% of the area will experience flood levels of 0.21 to 0.50 meters while 0.07%, 0.04%, 0.01%, and 0.0006% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 62 are the affected areas in square kilometres by flood depth per barangay.

Table 62. Affected Areas in Danao, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Danao (in sq. km.)	
	Dagohoy	San Miguel
0.03-0.20	0.88	1.7
0.21-0.50	0.031	0.063
0.51-1.00	0.03	0.044
1.01-2.00	0.016	0.03
2.01-5.00	0.0045	0.011
> 5.00	0	0.0007




Figure 98. Affected Areas in Danao, Bohol during 100-Year Rainfall Return Period

For the municipality of Jetafe, with an area of 94.04 sq. km., 0.025% will experience flood levels of less 0.20 meters. 0.0002% of the area will experience flood levels of 0.21 to 0.50 meters while 0.0002%, and 0.0001% of the area will experience flood depths of 0.51 to 1 meter, and 1.01 to 2 meters, respectively. Listed in Table 63 are the affected areas in square kilometres by flood depth per barangay.

Table 63. Affected Areas in Jetafe, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Jetafe (in sq. km.)
	Cabasakan
0.03-0.20	0.024
0.21-0.50	0.00024
0.51-1.00	0.0002
1.01-2.00	0.0001
2.01-5.00	0
> 5.00	0





Figure 99. Affected Areas in Jetafe, Bohol during 100-Year Rainfall Return Period

For the municipality of Pilar, with an area of 114.4 sq. km., 5.67% will experience flood levels of less 0.20 meters. 0.34% of the area will experience flood levels of 0.21 to 0.50 meters while 0.94%, 0.23%, and 0.06% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and, 2.01 to 5 meters, respectively. Listed in Table 64 are the affected areas in square kilometres by flood depth per barangay.

Table 64. Affected Areas in Pilar, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Pilar (in sq. km.)
	La Suerte
<b>0.03-0.20</b>	6.48
<b>0.21-0.50</b>	0.38
<b>0.51-1.00</b>	1.07
<b>1.01-2.00</b>	0.26
<b>2.01-5.00</b>	0.065
<b>&gt; 5.00</b>	0




Figure 100. Affected Areas in Pilar, Bohol during 100-Year Rainfall Return Period

For the municipality of San Miguel, with an area of 107 sq. km., 81.03% will experience flood levels of less 0.20 meters. 4.43% of the area will experience flood levels of 0.21 to 0.50 meters while 3.87%, 4.63%, 3.32%, and 0.25% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 65 are the affected areas in square kilometres by flood depth per barangay.




Figure 101. Affected Areas in San Miguel, Bohol during 100-Year Rainfall Return Period

Table 65. Affected Areas in San Miguel, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in San Miguel (in sq. km.)									
	Bayongan	Bugang	Cabangahan	Caluasan	Camanaga	Cambangay Norte	Capayas	Corazon	Garcia	
<b>0.03-0.20</b>	5.28	4.98	7.29	4.64	4.05	3.3	4.39	3.85	7.06	
<b>0.21-0.50</b>	0.26	0.2	0.32	0.15	0.27	0.16	0.16	0.2	0.3	
<b>0.51-1.00</b>	0.21	0.29	0.43	0.11	0.14	0.17	0.21	0.22	0.23	
<b>1.01-2.00</b>	0.28	0.55	0.35	0.095	0.12	0.27	0.17	0.37	0.17	
<b>2.01-5.00</b>	0.2	0.45	0.11	0.14	0.097	0.22	0.12	0.15	0.21	
<b>&gt; 5.00</b>	0.0001	0.0001	0.0014	0.04	0.0081	0	0.029	0.001	0.06	

Table 66. Affected Areas in San Miguel, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in San Miguel (in sq. km.)								
	Hagbuyo	Kagawasan	Mahayag	Poblacion	San Isidro	San Jose	San Vicente	Santo Niño	Tomoc
<b>0.03-0.20</b>	6.77	3.07	4.99	1.45	3.54	3.56	1.69	9	8.08
<b>0.21-0.50</b>	0.32	0.11	0.46	0.059	0.12	0.14	0.088	1.09	0.34
<b>0.51-1.00</b>	0.57	0.11	0.36	0.073	0.17	0.14	0.06	0.43	0.24
<b>1.01-2.00</b>	0.98	0.099	0.13	0.23	0.28	0.25	0.071	0.32	0.23
<b>2.01-5.00</b>	0.44	0.087	0.047	0.17	0.39	0.35	0.06	0.16	0.17
<b>&gt; 5.00</b>	0.016	0.011	0.0006	0.013	0.017	0.041	0.0014	0.0036	0.022

For the municipality of Talibon, with an area of 148 sq. km., 27.58% will experience flood levels of less 0.20 meters. 2.62% of the area will experience flood levels of 0.21 to 0.50 meters while 2.68%, 2.07%, 0.92%, and 0.028% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 67 are the affected areas in square kilometres by flood depth per barangay.

Table 67. Affected Areas in Talibon, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Talibon (in sq. km.)									
	Balintawak	Magsaysay	Rizal	San Agustin	San Carlos	San Isidro	San Jose	San Roque	Sikatuna	Zamora
0.03-0.20	2.58	12.8	2.08	4.38	1.18	0.088	0.068	3.96	4.09	9.61
0.21-0.50	0.38	0.36	0.073	1.41	0.075	0.0017	0.0004	0.86	0.17	0.56
0.51-1.00	0.25	0.34	0.073	1.7	0.063	0.0012	0.0001	0.6	0.26	0.68
1.01-2.00	0.055	0.4	0.054	0.48	0.0059	0.0005	0	0.33	0.81	0.93
2.01-5.00	0.0013	0.53	0.024	0.05	0.0021	0	0	0.086	0.31	0.36
> 5.00	0	0.022	0.0001	0.0041	0	0	0	0	0	0.015




Figure 102. Affected Areas in Talibon, Bohol during 100-Year Rainfall Return Period

For the municipality of Trinidad, with an area of 143 sq. km., 46.73% will experience flood levels of less 0.20 meters. 2.37% of the area will experience flood levels of 0.21 to 0.50 meters while 3.34%, 3.69%, 3.54%, and 0.2% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Tables 68-69 are the affected areas in square kilometres by flood depth per barangay.






Figure 103. Affected Areas in Trinidad, Bohol during 100-Year Rainfall Return Period

Table 68. Affected Areas in Trinidad, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Trinidad (in sq. km.)									
	Banlasan	Bongbong	Catoogan	Guinobatan	Hinlayagan Ilaud	Hinlayagan Ilaya	Kauswagan	Kinan-Oan	La Union	
0.03-0.20	7.58	5.19	0.071	3.16	1.2	4.32	14.85	3.66	2.71	
0.21-0.50	0.4	0.3	0.006	0.14	0.059	0.17	0.55	0.21	0.12	
0.51-1.00	0.44	0.59	0.0027	0.19	0.12	0.24	0.48	0.16	0.2	
1.01-2.00	0.34	0.47	0	0.45	0.28	0.43	0.39	0.15	0.17	
2.01-5.00	0.21	0.24	0	0.18	0.5	0.75	0.23	0.0091	0.1	
> 5.00	0.044	0.015	0	0.0048	0.028	0.031	0.012	0	0.0013	

Table 69. Affected Areas in Trinidad, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth ( in m.)	Area of affected barangays in Trinidad (in sq. km.)									
	La Victoria	Mabuhay Cabigohan	Mahagbu	Manuel M. Roxas	Poblacion	San Isidro	San Vicente	Santo Tomas		
0.03-0.20	2.13	1.41	3.54	2.03	1.85	4.81	5.16	3.05		
0.21-0.50	0.13	0.063	0.13	0.078	0.19	0.33	0.34	0.18		
0.51-1.00	0.23	0.076	0.19	0.1	0.72	0.34	0.49	0.2		
1.01-2.00	0.18	0.1	0.21	0.22	1	0.29	0.36	0.22		
2.01-5.00	0.0007	0.36	0.72	1.01	0.23	0.16	0.17	0.18		
> 5.00	0	0.031	0.034	0.022	0.019	0.01	0.0017	0.036		

For the municipality of Ubay, with an area of 264.8 sq. km., 5.74% will experience flood levels of less 0.20 meters. 0.41% of the area will experience flood levels of 0.21 to 0.50 meters while 0.21%, 0.2%, and 0.06% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, and 2.01 to 5 meters, respectively. Listed in Table 70 are the affected areas in square kilometres by flood depth per barangay.

Table 70. Affected Areas in Ubay, Bohol during 100-Year Rainfall Return Period

Affected area (sq. km.) by flood depth (in m.)	Area of affected barangays in Ubay (in sq. km.)								
	Buenavista	Buililis	Camali-An	Gabi	Hambabauran	Lomangog	Los Angeles	Pag-Asa	Tubog
0.03-0.20	0.052	0.75	3.76	1.31	6.5	1.17	0.51	1.14	0.03
0.21-0.50	0.00062	0.043	0.26	0.078	0.4	0.15	0.023	0.12	0.0034
0.51-1.00	0.0003	0.017	0.15	0.046	0.23	0.035	0.019	0.044	0.00031
1.01-2.00	0.0004	0.02	0.19	0.036	0.22	0.019	0.011	0.041	0
2.01-5.00	0.0001	0.0053	0.091	0.0001	0.057	0.0011	0.0024	0.008	0
> 5.00	0	0	0	0	0	0	0	0	0




Figure 104. Affected Areas in Ubay, Bohol during 100-Year Rainfall Return Period

Among the barangays in the municipality of Alicia, Katipunan is projected to have the highest percentage of area that will experience flood levels at 1.07%.

Among the barangays in the municipality of Bien Unido, Nueva Esperanza is projected to have the highest percentage of area that will experience flood levels at 23.74%. Meanwhile, Liberty posted the second highest percentage of area that may be affected by flood depths at 4.94%.

Among the barangays in the municipality of Dagohoy, Cagawasan is projected to have the highest percentage of area that will experience flood levels at 0.03%.

Among the barangays in the municipality of Danao, San Miguel is projected to have the highest percentage of area that will experience flood levels at 1.85%. Meanwhile, Dagohoy posted the second highest percentage of area that may be affected by flood depths at 0.96%.

Among the barangays in the municipality of Jetafe, Cabasakan is projected to have the highest percentage of area that will experience flood levels at 0.03%.

Among the barangays in the municipality of Pilar, La Suerte is projected to have the highest percentage of area that will experience flood levels at 7.23%.

Among the barangays in the municipality of San Miguel, Santo Niño is projected to have the highest percentage of area that will experience flood levels at 10.24%. Meanwhile, Tomoc posted the second highest percentage of area that may be affected by flood depths at 8.47%.

Among the barangays in the municipality of Talibon, Magsaysay is projected to have the highest percentage of area that will experience flood levels at 13.46%. Meanwhile, Zamora posted the second highest percentage of area that may be affected by flood depths at 11.32%.

Among the barangays in the municipality of Trinidad, Kauswagan is projected to have the highest percentage of area that will experience flood levels at 11.55%. Meanwhile, Banlasan posted the second highest percentage of area that may be affected by flood depths at 6.32%.

Among the barangays in the municipality of Ubay, Hambabauran is projected to have the highest percentage of area that will experience flood levels at 2.80%. Meanwhile, Lomangog posted the second highest percentage of area that may be affected by flood depths at 0.52%.

Moreover, the generated flood hazard maps for the Ipil Floodplain were used to assess the vulnerability of the educational and medical institutions in the floodplain. Using the flood depth units of PAG-ASA for hazard maps - "Low", "Medium", and "High" - the affected institutions were given their individual assessment for each Flood Hazard Scenario (5 yr, 25 yr, and 100 yr).

Table 71. Area covered by each warning level with respect to the rainfall scenario

Warning Level	Area Covered in sq. km.		
	5 year	25 year	100 year
Low	17.45	17.17	15.89
Medium	14.70	22.76	24.69
High	3.19	10.14	17.28
<b>TOTAL</b>	<b>35.34</b>	<b>50.07</b>	<b>57.86</b>

Of the 31 identified Education Institutions in the Ipil Flood plain, 2 schools were assessed to be exposed to Low level flooding during a 5 year scenario. In the 25 year scenario, 2 schools were assessed to be exposed to low level flooding. In the 100 year scenario, 3 schools were assessed to be exposed to low level flooding. See Appendix D for a detailed enumeration of schools in the Ipil floodplain.

Of the 8 identified Medical Institutions in the Abatan Flood Plain, no medical institutions were assessed to be exposed to any of the flooding scenarios. See **Appendix E** for a detailed enumeration of hospitals and clinics in the Ipil floodplain.

## 5.11 Flood Validation

A survey was done along the floodplain of Ipil River to validate the generated flood maps. The team gathered secondary data regarding flood occurrence in the area. Ground validation points were acquired as well as the other necessary details like date of occurrence, name of typhoon and actual flood depth.

During validation, the team was assisted by the local Disaster Risk Reduction and Management representatives from the Municipalities of Talibon, Bien Unido and Trinidad. Residents along the floodplain were interviewed of the historical flood events they experiences.

Actual flood depth acquired from the ground validation were then computed and compared to the flood depth simulated by the model. An RMSE value of 0.57 was obtained.






Figure 105. Flood Validation Points of Ipil River Basin




Figure 106. Flood map depth vs actual flood depth

Table 72. Actual Flood Depth vs Simulated Flood Depth in Ipil

Actual Flood Depth (m)	Modeled Flood Depth (m)						Total
	0-0.20	0.21-0.50	0.51-1.00	1.01-2.00	2.01-5.00	> 5.00	
0-0.20	35	3	0	0	0	0	38
0.21-0.50	39	8	3	0	0	0	50
0.51-1.00	21	1	6	1	0	0	29
1.01-2.00	13	1	3	4	1	0	22
2.01-5.00	1	0	1	0	0	0	2
> 5.00	0	0	0	0	0	0	0
<b>Total</b>	<b>109</b>	<b>13</b>	<b>13</b>	<b>5</b>	<b>1</b>	<b>0</b>	<b>141</b>

The overall accuracy generated by the flood model is estimated at 37.59% with 53 points correctly matching the actual flood depths. In addition, there were 50 points estimated one level above and below the correct flood depths while there were 23 points and 14 points estimated two levels above and below, and three or more levels above and below the correct flood. A total of 4 points were overestimated while a total of 80 points were underestimated in the modelled flood depths of Ipil.

Table 73. Summary of Accuracy Assessment in Ipil River Basin Survey

No. of Points	%	
Correct	53	37.59
Overestimated	8	5.67
Underestimated	80	56.74
<b>Total</b>	<b>141</b>	<b>100.00</b>

## REFERENCES

- Ang M.O., Paringit E.C., et al. 2014. *DREAM Data Processing Component Manual*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- Balicanta L.P., Paringit E.C., et al. 2014. *DREAM Data Validation Component Manual*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- Brunner, G. H. 2010a. HEC-RAS River Analysis System Hydraulic Reference Manual. Davis, CA: U.S. Army Corps of Engineers, Institute for Water Resources, Hydrologic Engineering Center.
- Lagmay A.F., Paringit E.C., et al. 2014. *DREAM Flood Modeling Component Manual*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- Paringit E.C, Balicanta L.P., Ang, M.O., Sarmiento, C. 2017. *Flood Mapping of Rivers in the Philippines Using Airborne Lidar: Methods*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- Sarmiento C., Paringit E.C., et al. 2014. *DREAM Data Acquisition Component Manual*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.
- UP TCAGP 2016, *Acceptance and Evaluation of Synthetic Aperture Radar Digital Surface Model (SAR DSM) and Ground Control Points (GCP)*. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry.

## ANNEXES

### Annex 1. Technical Specifications of the LIDAR Sensors used in the Ipil Floodplain Survey

#### 1. PEGASUS SENSOR




Figure A-1.1. Pegasus Sensor

Table A-1.1. Parameters and Specification of Pegasus Sensor

Parameter	Specification
Operational envelope (1,2,3,4)	150-5000 m AGL, nominal
Laser wavelength	1064 nm
Horizontal accuracy (2)	1/5,500 x altitude, $1\sigma$
Elevation accuracy (2)	< 5-20 cm, $1\sigma$
Effective laser repetition rate	Programmable, 100-500 kHz
Position and orientation system	POS AV™ AP50 (OEM)
Scan width (FOV)	Programmable, 0-75°
Scan frequency (5)	Programmable, 0-140 Hz (effective)
Sensor scan product	800 maximum
Beam divergence	0.25 mrad (1/e)
Roll compensation	Programmable, $\pm 37^\circ$ (FOV dependent)



Vertical target separation distance	<0.7 m
Range capture	Up to 4 range measurements, including 1st, 2nd, 3rd, and last returns
Intensity capture	Up to 4 intensity returns for each pulse, including last (12 bit)
Image capture	5 MP interline camera (standard); 60 MP full frame (optional)
Full waveform capture	12-bit Optech IWD-2 Intelligent Waveform Digitizer
Data storage	Removable solid state disk SSD (SATA II)
Power requirements	28 V, 800 W, 30 A
Dimensions and weight	Sensor: 630 x 540 x 450 mm; 65 kg;
	Control rack: 650 x 590 x 490 mm; 46 kg
Operating Temperature	-10°C to +35°C
Relative humidity	0-95% non-condensing

1 Target reflectivity  $\geq 20\%$

2 Dependent on selected operational parameters using nominal FOV of up to 40° in standard atmospheric conditions with 24-km visibility

3 Angle of incidence  $\leq 20^\circ$

4 Target size  $\geq$  laser footprint<sup>5</sup> Dependent on system configuration

## 2. D-8900 AERIAL DIGITAL CAMERA

Table A-1.2. Parameters and Specification of D-8900 AERIAL DIGITAL CAMERA

Parameter	Specification
<b>Camera Head</b>	
Sensor type	60 Mpix full frame CCD, RGB
Sensor format (H x V)	8, 984 x 6, 732 pixels
Pixel size	6 $\mu$ m x 6 $\mu$ m
Frame rate	1 frame/2 sec.
FMC	Electro-mechanical, driven by piezo technology (patented)
Shutter	Electro-mechanical iris mechanism 1/125 to 1/500++ sec. f-stops: 5.6, 8, 11, 16
Lenses	50 mm/70 mm/120 mm/210 mm
Filter	Color and near-infrared removable filters
Dimensions (H x W x D)	200 x 150 x 120 mm (70 mm lens)
Weight	~4.5 kg (70 mm lens)
<b>Controller Unit</b>	
Computer	Mini-ITX RoHS-compliant small-form-factor embedded computers with AMD TurionTM 64 X2 CPU 4 GB RAM, 4 GB flash disk local storage IEEE 1394 Firewire interface
Removable storage unit	~500 GB solid state drives, 8,000 images
Power consumption	~8 A, 168 W
Dimensions	2U full rack; 88 x 448 x 493 mm
Weight	~15 kg
<b>Image Pre-Processing Software</b>	
Capture One	Radiometric control and format conversion, TIFF or JPEG
Image output	8,984 x 6,732 pixels 8 or 16 bits per channel (180 MB or 360 MB per image)

## Annex 2. NAMRIA Certification of Reference Points Used in the LiDAR Survey

### 1 BHL-63






	Republic of the Philippines Department of Environment and Natural Resources <b>NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY</b>	
	November 19, 2013	
<b>CERTIFICATION</b>		
To whom it may concern:		
This is to certify that according to the records on file in this office, the requested survey information is as follows -		
Province: <b>BOHOL</b>		
Station Name: <b>BHL-63</b>		
Order: <b>2nd</b>		
Island: <b>VISAYAS</b>		Barangay: <b>HAGBUYO</b>
Municipality: <b>SAN MIGUEL</b>		
<i>PRS92 Coordinates</i>		
Latitude: <b>10° 0' 13.39830"</b>	Longitude: <b>124° 20' 43.44081"</b>	Ellipsoidal Hgt: <b>17.31900 m.</b>
<i>WGS84 Coordinates</i>		
Latitude: <b>10° 0' 9.39110"</b>	Longitude: <b>124° 20' 48.71189"</b>	Ellipsoidal Hgt: <b>80.87300 m.</b>
<i>PTM Coordinates</i>		
Northing: <b>1106212.953 m.</b>	Easting: <b>428232.164 m.</b>	Zone: <b>5</b>
<i>UTM Coordinates</i>		
Northing: <b>1,106,055.36</b>	Easting: <b>647,462.74</b>	Zone: <b>51</b>
Location Description		
BHL-63		
To reach the station travel from San Miguel Town Proper for about 2.5 Km. and look for Hagbuyo Bridge before Hagbuyo Primary School which is about 150 m NE. Mark is the head of a 3 in. copper nail set on a drilled hole on the concrete sidewalk of Hagbuyo Bridge Km. 131+630 embedded with concrete cement putty 30 cm x 30 cm x 15 cm with inscriptions "BHL-63, 2007, NAMRIA". Ref. no. 1 is an electric post about 30 m NW at the opposite side of the road; Ref. no. 2 is a 6.1 pipe with Bridge Tonnage sign about 25 m SW.		
Requesting Party:	<b>UP-TCAGP/DOST</b>	
Purpose:	<b>Reference</b>	
OR Number:	<b>3947235 B</b>	
T.N.:	<b>2013-1253</b>	
	 <b>RUEL M. BELEN, MNSA</b> Director/Mapping And Geodesy Branch	
	 9 9 1 1 1 9 2 0 1 3 1 1 1 1 0 0	
	NAMRIA OFFICES: Main - Lawton Avenue, Fort Bonifacio, 1634 Taguig City, Philippines Tel. No.: (632) 810-4831 to 41 Branch - 421 Barrera St. San Nicolas, 1010 Manila, Philippines, Tel. No. (632) 241-3494 to 98 <a href="http://www.namria.gov.ph">www.namria.gov.ph</a>	

Figure A-2.1. BHL-63

2. BHL-95



Republic of the Philippines  
Department of Environment and Natural Resources  
**NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY**

November 19, 2013

### CERTIFICATION

To whom it may concern:

This is to certify that according to the records on file in this office, the requested survey information is as follows -


<b>Province: BOHOL</b>		
<b>Station Name: BHL-95</b>		
Island: <b>VISAYAS</b>	<b>Order: 2nd</b>	Barangay: <b>TIGUIS</b>
<i>PRS92 Coordinates</i>		
Latitude: <b>9° 35' 30.96174"</b>	Longitude: <b>124° 4' 30.01696"</b>	Ellipsoidal Hgt: <b>19.23800 m.</b>
<i>WGS84 Coordinates</i>		
Latitude: <b>9° 35' 27.03717"</b>	Longitude: <b>124° 4' 35.32705"</b>	Ellipsoidal Hgt: <b>83.04800 m.</b>
<i>PTM Coordinates</i>		
Northing: <b>1060736.963 m.</b>	Easting: <b>398459.803 m.</b>	Zone: <b>5</b>
<i>UTM Coordinates</i>		
Northing: <b>1,060,413.57</b>	Easting: <b>617,967.70</b>	Zone: <b>51</b>

Location Description


**BHL-95**

From Loay Town travel NE to Lila, Bohol about 2.5 Km. from Lila Proper on the left side of the road. Mark is the head of a 3 in. copper nail embedded on a concrete monument 30 cm x 30 cm x 1.20 cm set to the ground 0.20 cm above ground level with inscriptions, BHL-95, 2007, NAMRIA". Ref. no. 1 Electric post about 30 m SW; Ref. no. 2 Molave Tree near concrete post about 25 m NVV; Station is about 60 m to the corner of Brgy. Tiguis on the NE.


Requesting Party:	<b>UP-TCAGP/DOST</b>
Purpose:	<b>Reference</b>
OR Number:	<b>3947235 B</b>
T.N.:	<b>2013-1274</b>



**RUEL M. BELEN, MNSA**  
Director, Mapping And Geodesy Branch



9 9 1 1 1 9 2 0 1 3 1 1 2 4 5 5



CERTIFICATION  
INTERNATIONAL  
ISO 9001:2008  
CIP/4701/12/09/814

**NAMRIA OFFICES:**  
Main : Lawton Avenue, Fort Bonifacio, 1634 Taguig City, Philippines Tel. No.: (632) 810-4831 to 41  
Branch : 421 Barroca St. San Nicolas, 1010 Manila, Philippines, Tel. No. (632) 241-3494 to 98  
[www.namria.gov.ph](http://www.namria.gov.ph)

Figure A-2.2. BHL-95



3. BHL-75



Republic of the Philippines  
Department of Environment and Natural Resources  
**NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY**

September 21, 2015

### CERTIFICATION

To whom it may concern:

This is to certify that according to the records on file in this office, the requested survey information is as follows -

Island: <b>VISAYAS</b> Municipality: <b>MABINI</b>	Province: <b>BOHOL</b> Station Name: <b>BHL-75</b> Order: <b>2nd</b> Barangay: <b>SAN JOSE</b> MSL Elevation: <b>PRS92 Coordinates</b>	
Latitude: <b>9° 57' 16.74294"</b>	Longitude: <b>124° 32' 0.35318"</b>	Ellipsoidal Hgt: <b>12.84500 m.</b>
<b>WGS84 Coordinates</b>		
Latitude: <b>9° 57' 12.76483"</b>	Longitude: <b>124° 32' 5.62696"</b>	Ellipsoidal Hgt: <b>76.97400 m.</b>
<b>PTM / PRS92 Coordinates</b>		
Northing: <b>1100750.724 m.</b>	Easting: <b>448840.052 m.</b>	Zone: <b>5</b>
<b>UTM / PRS92 Coordinates</b>		
Northing: <b>1,100,718.38</b>	Easting: <b>668,101.47</b>	Zone: <b>51</b>

Location Description

**BHL-75**

To reach the station travel from Mabini Town Proper for about 16 Km. to Brgy. San Jose and at the Brgy. Plaza is the chapel and basketball court. Mark is the head of a 3 in. copper nail set on a drilled hole on a concrete post foundation embedded with concrete cement putty 30 cm x 30 cm x 5 cm with inscriptions, BHL-75, 2007, NAMRIA". Ref. no. 1 is a post of chapel at the right about 15 m SW; Ref. no. 2 basketball court about 25 m NE.

Requesting Party: **UP-DREAM**  
Purpose: **Reference**  
OR Number: **8087355 I**  
T.N.: **2015-2821**

  
**RUEL M. BELEN, MNSA**  
 Director, Mapping And Geodesy Branch

  
 9 9 0 9 2 1 2 0 1 3 1 2 4 2 3 5



**NAMRIA OFFICES:**  
 Main : Lawton Avenue, Fort Bonifacio, 1534 Taguig City, Philippines Tel. No. (832) 810-4811 to 41  
 Branch : 421 Baraca St. San Nicolas, 1010 Manila, Philippines, Tel. No. (832) 241-0494 to 98  
[www.namria.gov.ph](http://www.namria.gov.ph)  
 ISO 9001: 2008 CERTIFIED FOR MAPPING AND GEOSPATIAL INFORMATION MANAGEMENT

Figure A-2.3. BHL-75

### Annex 3. Baseline Processing Reports of Control Points used in the LiDAR Survey

1. 63A

Table A-3.1. 63A

Vector Components (Mark to Mark)					
From:		BHL-63			
Grid		Local		Global	
Easting	647463.396 m	Latitude	N10°00'13.31406"	Latitude	N10°00'09.30688"
Northing	1106052.775 m	Longitude	E124°20'43.46219"	Longitude	E124°20'48.73327"
Elevation	19.432 m	Height	20.487 m	Height	84.041 m
To:		BHL-63A			
Grid		Local		Global	
Easting	647466.981 m	Latitude	N10°00'13.84084"	Latitude	N10°00'09.83363"
Northing	1106068.972 m	Longitude	E124°20'43.58209"	Longitude	E124°20'48.85315"
Elevation	19.409 m	Height	20.464 m	Height	84.018 m
Vector					
ΔEasting	3.585 m	NS Fwd Azimuth	12°42'51"	ΔX	-1.416 m
ΔNorthing	16.197 m	Ellipsoid Dist.	16.591 m	ΔY	-4.400 m
ΔElevation	-0.023 m	ΔHeight	-0.023 m	ΔZ	15.934 m
Standard Errors					
Vector errors:					
σ ΔEasting	0.001 m	σ NS fwd Azimuth	0°00'10"	σ ΔX	0.001 m
σ ΔNorthing	0.001 m	σ Ellipsoid Dist.	0.001 m	σ ΔY	0.001 m
σ ΔElevation	0.001 m	σ ΔHeight	0.001 m	σ ΔZ	0.001 m
Aposteriori Covariance Matrix (Meter <sup>2</sup> )					
	X	Y	Z		
X	0.0000011627				
Y	-0.0000004536	0.0000009291			
Z	-0.0000002192	0.0000000346	0.0000003582		

2. 75A

Table A-3.2. 75A

Vector Components (Mark to Mark)					
From:		BHL-75			
Grid		Local		Global	
Easting	668101.461 m	Latitude	N9°57'16.74294"	Latitude	N9°57'12.76483"
Northing	1100718.380 m	Longitude	E124°32'00.35318"	Longitude	E124°32'05.62696"
Elevation	12.452 m	Height	12.845 m	Height	76.974 m
To:		75			
Grid		Local		Global	
Easting	668103.303 m	Latitude	N9°57'17.24192"	Latitude	N9°57'13.26378"
Northing	1100733.718 m	Longitude	E124°32'00.41598"	Longitude	E124°32'05.68974"
Elevation	12.274 m	Height	12.668 m	Height	76.796 m
Vector					
ΔEasting	1.842 m	NS Fwd Azimuth	7°06'44"	ΔX	0.026 m
ΔNorthing	15.338 m	Ellipsoid Dist.	15.449 m	ΔY	-3.411 m
ΔElevation	-0.178 m	ΔHeight	-0.177 m	ΔZ	15.069 m
Standard Errors					
Vector errors:					
σ ΔEasting	0.000 m	σ NS fwd Azimuth	0°00'06"	σ ΔX	0.001 m
σ ΔNorthing	0.000 m	σ Ellipsoid Dist.	0.000 m	σ ΔY	0.001 m
σ ΔElevation	0.001 m	σ ΔHeight	0.001 m	σ ΔZ	0.001 m
Aposteriori Covariance Matrix (Meter <sup>2</sup> )					
	X	Y	Z		
X	0.0000008194				
Y	-0.0000008289	0.0000012571			
Z	-0.0000003177	0.0000004601	0.0000003613		

3. Hotel

Table A-3.3. Hotel

Vector Components (Mark to Mark)					
From: BHL-95					
Grid		Local		Global	
Easting	617964.842 m	Latitude	N9°35'31.05836"	Latitude	N9°35'27.13378"
Northing	1060416.528 m	Longitude	E124°04'29.92362"	Longitude	E124°04'35.23370"
Elevation	26.191 m	Height	26.080 m	Height	89.890 m
To: Hotel					
Grid		Local		Global	
Easting	594927.168 m	Latitude	N9°39'32.15822"	Latitude	N9°39'28.19791"
Northing	1067756.448 m	Longitude	E123°51'54.83035"	Longitude	E123°52'00.13618"
Elevation	49.511 m	Height	49.981 m	Height	113.124 m
Vector					
$\Delta$ Easting	-23037.674 m	NS Fwd Azimuth	287°51'07"	$\Delta$ X	19772.484 m
$\Delta$ Northing	7339.920 m	Ellipsoid Dist.	24184.956 m	$\Delta$ Y	11856.935 m
$\Delta$ Elevation	23.320 m	$\Delta$ Height	23.900 m	$\Delta$ Z	7306.139 m
Standard Errors					
Vector errors:					
$\sigma$ $\Delta$ Easting	0.025 m	$\sigma$ NS fwd Azimuth	0°00'00"	$\sigma$ $\Delta$ X	0.027 m
$\sigma$ $\Delta$ Northing	0.009 m	$\sigma$ Ellipsoid Dist.	0.023 m	$\sigma$ $\Delta$ Y	0.035 m
$\sigma$ $\Delta$ Elevation	0.037 m	$\sigma$ $\Delta$ Height	0.037 m	$\sigma$ $\Delta$ Z	0.011 m
Aposteriori Covariance Matrix (Meter <sup>2</sup> )					
	X	Y	Z		
X	0.0007210250				
Y	-0.0002800594	0.0012254248			
Z	-0.0001804231	0.0001515697	0.0001230081		



4. EPHotel

Table A-3.4. EPHotel

Vector Components (Mark to Mark)					
From: Hotel					
Grid		Local		Global	
Easting	594927.168 m	Latitude	N9°39'32.15823"	Latitude	N9°39'28.19791"
Northing	1067756.448 m	Longitude	E123°51'54.83035"	Longitude	E123°52'00.13618"
Elevation	49.511 m	Height	49.981 m	Height	113.124 m
To: EP Hotel					
Grid		Local		Global	
Easting	594929.594 m	Latitude	N9°39'32.38755"	Latitude	N9°39'28.42722"
Northing	1067763.497 m	Longitude	E123°51'54.91053"	Longitude	E123°52'00.21635"
Elevation	49.487 m	Height	49.956 m	Height	113.100 m
Vector					
ΔEasting	2.426 m	NS Fwd Azimuth	19°08'04"	ΔX	-1.357 m
ΔNorthing	7.049 m	Ellipsoid Dist.	7.457 m	ΔY	-2.364 m
ΔElevation	-0.025 m	ΔHeight	-0.024 m	ΔZ	6.941 m
Standard Errors					
Vector errors:					
σ ΔEasting	0.002 m	σ NS fwd Azimuth	0°00'49"	σ ΔX	0.003 m
σ ΔNorthing	0.001 m	σ Ellipsoid Dist.	0.001 m	σ ΔY	0.002 m
σ ΔElevation	0.003 m	σ ΔHeight	0.003 m	σ ΔZ	0.001 m
Aposteriori Covariance Matrix (Meter <sup>2</sup> )					
	X	Y	Z		
X	0.0000064477				
Y	-0.0000028257	0.0000057669			
Z	-0.0000013924	0.0000012411	0.0000013056		

## Annex 4. The LIDAR Survey Team Composition

Table A-4.1. The LIDAR Survey Team Composition

Data Acquisition Component Sub-Team	Designation	Name	Agency/Affiliation
PHIL-LIDAR 1	Program Leader	ENRICO C. PARINGIT, D.ENG	UP-TCAGP
Data Acquisition Component Leader	Data Component Project Leader – I	ENGR. CZAR JAKIRI SARMIENTO	UP-TCAGP
Survey Supervisor	Chief Science Research Specialist (CSRS)	ENGR. CHRISTOPHER CRUZ	UP-TCAGP
LiDAR Operation	Supervising Science Research Specialist (Supervising SRS)	LOVELY GRACIA ACUÑA	UP-TCAGP
		LOVELYN ASUNCION	UP-TCAGP
<b>FIELD TEAM</b>			
LiDAR Operation	Senior Science Research Specialist (SSRS)	JASMINE ALVIAR	UP-TCAGP
	Research Associate (RA)	IRO NIEL ROXAS	UP-TCAGP
		KRISTINE JOY ANDAYA	UP-TCAGP
Ground Survey, Data Download and Transfer	RA	MA. KATRINA RANESES	UP-TCAGP
LiDAR Operation	Airborne Security	SSG. MIKE BERONILLA	PHILIPPINE AIR FORCE (PAF)
	Pilot	CAPT. CESAR ALFONSO III	ASIAN AEROSPACE CORPORATION (AAC)
		CAPT. RANDY LAGCO	AAC

Annex 5. Data Transfer Sheet for Ipil Floodplain

DATA TRANSFER SHEET  
bohol 9/17/15

DATE	FLIGHT NO.	MISSION NAME	SENSOR	RAW LAS		LOGS(MB)	POS	RAW IMAGES/CASI	MISSION LOG FILES/CASI LOGS	RANGE	DIGITIZER	BASE STATIONS		OPERATOR LOGS (PLOG)	FLIGHT PLAN		SERVER LOCATION
				Output LAS	KMIL ( swath)							BASE STATIONS	Base info (LH)		Actual	KMIL	
10-Sep	3401P	1BLK51LS253A	pegasus	1.7	657/318	7.44	163	na	na	17.4	na	10.2	1KB	1KB	38/65/25	na	Z:\CACRRAW DATA
11-Sep	3405P	1BLK51LS254A	pegasus	1.87	2806/667	8.31	178	na	na	19.4	na	6.81	1KB	1KB	38/65/25	na	Z:\CACRRAW DATA
12-Sep	3409P	1BLK51B255A	pegasus	1.6	525/635	14.1	302	na	na	32.8	na	15.7	1KB	1KB	42	na	Z:\CACRRAW DATA
12-Sep	3411P	1BLK51C255B	pegasus	1.24	1826/263	5.78	151	na	na	12.9	na	15.7	1KB	1KB	na	na	Z:\CACRRAW DATA

<p>Received from</p> <p>Name: <i>[Signature]</i></p> <p>Position: <i>[Signature]</i></p> <p>Signature: <i>[Signature]</i></p>	<p>Received by</p> <p>Name: <i>AC Borja</i></p> <p>Position: <i>SPES</i></p> <p>Signature: <i>[Signature]</i></p> <p>Date: <i>9/21/15</i></p>
---	---

IT-24

Figure A-5.1. Transfer Sheet for Ipil Floodplain - A

DATA TRANSFER SHEET  
Bohol 10/01/15

DATE	FLIGHT NO.	MISSION NAME	SENSOR	RAW LAS		LOGS(MB)	POS	RAW IMAGES/CAS	MISSION LOG FILES/CAS LOGS	RANGE	DIGITIZER	BASE STATION(S)		OPERATOR LOGS (OPLOG)	FLIGHT PLAN		SERVER LOCATION
				Output_LAS	KML (swath)							BASE STATION(S)	Base Info (.txt)		Actual	KML	
15-Sep	3421P	1BLK51C265A	pegasus	731	na	5.94	152	na	na	8.79	na	7.05	1KB	1KB	na	na	Z:\DACRAW DATA
17-Sep	3429P	1BLK51260A	pegasus	237	na	12.2	251	na	na	23.8	na	8.35	1KB	1KB	na	na	Z:\DACRAW DATA
21-Sep	3445P	1BLK51S264A	pegasus	542	na	4.54	124	na	na	5.95	na	9.84	1KB	1KB	12/1/21	na	Z:\DACRAW DATA
22-Sep	3449P	1BLK51G265A	pegasus	122	na	9.1	221	na	na	18	na	13.1	1KB	1KB	7566	na	Z:\DACRAW DATA
23-Sep	3453P	1BLK51S266A	pegasus	591	25/123	7.82	148	na	na	15.5	na	4.75	1KB	1KB	na	na	Z:\DACRAW DATA

Received from

Name *C. Juan-in*  
Position  
Signature *[Signature]*

Received by

Name *JOLIA F. PRIETO*  
Position *SRS*  
Signature *[Signature]* 10/23/2015

Figure A-5.2. Transfer Sheet for Ipil Floodplain - B



## Annex 6. Flight logs for the flight missions

### 1. Flight Log for Mission 1BLK51B255A

PHIL-LiDAR 1 Data Acquisition Flight Log					
1 LiDAR Operator: <u>J. Reyes</u>	2 ALTM Model: <u>Roarce</u>	3 Mission Name: <u>BLK 51B255A</u>	4 Type: <u>VFR</u>	5 Aircraft Type: <u>Cessna T206H</u>	6 Aircraft Identification: <u>P-C902</u>
7 Pilot: <u>C. Alarcon III</u>	8 Co-Pilot: <u>P. Lopez</u>	9 Route: <u>Tegayalaran - Tagbilaran</u>	12 Airport of Arrival (Airport, City/Province): <u>Tagbilaran</u>		
10 Date: <u>Sept 12, 2015</u>	11 Airport of Departure (Airport, City/Province): <u>Tagbilaran</u>		16 Take off: <u>0614H</u>	17 Landing: <u>0921H</u>	18 Total Flight Time: <u>4:13</u>
13 Engine On: <u>0614H</u>	14 Engine Off: <u>1037H</u>	15 Total Engine Time: <u>4:23</u>	19 Weather: <u>Partly cloudy</u>		
20 Flight Classification					
20.a Billable		20.b Non Billable		20.c Others	
<input checked="" type="radio"/> Acquisition Flight <input type="radio"/> Ferry Flight <input type="radio"/> System Test Flight <input type="radio"/> Calibration Flight		<input type="radio"/> Aircraft Test Flight <input type="radio"/> AAC Admin Flight <input type="radio"/> Others: _____		<input type="radio"/> LiDAR System Maintenance <input type="radio"/> Aircraft Maintenance <input type="radio"/> Phil-LiDAR Admin Activities	
21 Remarks: <u>Surveyed BLK 51B</u>					
22 Problems and Solutions					
<input type="radio"/> Weather Problem <input type="radio"/> System Problem <input type="radio"/> Aircraft Problem <input type="radio"/> Pilot Problem <input type="radio"/> Others: _____					
Acquisition Flight Approved by <u>J. Reyes</u> Signature over Printed Name (End User Representative)		Acquisition Flight Certified by <u>C. Alarcon III</u> Signature over Printed Name (PAF Representative)		LIDAR Operator <u>J. Reyes</u> Signature over Printed Name	
		Pilot-in-Command <u>C. Alarcon III</u> Signature over Printed Name		Aircraft Mechanic/ LiDAR Technician <u>MA</u> Signature over Printed Name	

Figure A-6. 1. Flight Log for Mission 1BLK51B255A

2. Flight Log for Mission 1BLK51C255B

Flight log No.: 341P

**PHIL-LIDAR 1 Data Acquisition Flight Log**

1 LIDAR Operator: J. Alvarez	2 ALTM Model: Pegasus	3 Mission Name: 1BLK51C255B	4 Type: VFR	5 Aircraft Type: Casma T206H	6 Aircraft Identification: PP-C9022
7 Pilot: C. Alonzo	8 Co-Pilot: J. Alvarez	9 Route: Tagbilaran - Tagbilaran	12 Airport of Arrival (Airport, City/Province): Tagbilaran		
10 Date: Sept 12, 2015	12 Airport of Departure (Airport, City/Province): Tagbilaran		15 Total Engine Time: 2:47		
13 Engine On: 12:57 H	14 Engine Off: 15:24 H	16 Take off: 12:42 H	17 Landing: 15:14 H	18 Total Flight Time: 2:37	
19 Weather: cloudy					
20 Flight Classification					
20.a Billable		20.b Non Billable		20.c Others	
<input checked="" type="checkbox"/> Acquisition Flight <input type="checkbox"/> Ferry Flight <input type="checkbox"/> System Test Flight <input type="checkbox"/> Calibration Flight		<input type="checkbox"/> Aircraft Test Flight <input type="checkbox"/> AAC Admin Flight <input type="checkbox"/> Others: _____		<input type="checkbox"/> LIDAR System Maintenance <input type="checkbox"/> Aircraft Maintenance <input type="checkbox"/> PHIL-LIDAR Admin Activities	
21 Remarks: Surveyed BLK 51C. Revised plan according to build up in the area.					
22 Problems and Solutions					
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____					

Acquisition Flight Approved by J. Alvarez Signature over Printed Name (End User Representative)	Acquisition Flight Certified by CS Peralta Signature over Printed Name (PFR Representative)	Pilot-in-Command C. Alonzo Signature over Printed Name	LIDAR Operator J. Alvarez Signature over Printed Name
		Aircraft Mechanic/ LIDAR Technician	Signature over Printed Name

Figure A-6.2. Flight Log for Mission 1BLK51C255B

3. Flight Log for Mission 1BLK51C258A

PHIL-LiDAR 1 Data Acquisition Flight Log						Flight Log No.: 34217
1 LiDAR Operator: <u>ANDRINA</u>	2 ALTM Model: <u>P4</u>	3 Mission Name: <u>2   PAKSICASA</u>	4 Type: VFR	5 Aircraft Type: <u>Cesna T206H</u>	6 Aircraft Identification: <u>PP-C9022</u>	
7 Pilot: <u>C. P. FERNANDEZ</u>	8 Co-Pilot: <u>WAGAP</u>	9 Route: <u>TRISULARAN - TRISULARAN</u>	12 Airport of Arrival (Airport, City/Province): <u>TRISULARAN</u>			
10 Date: <u>Sept 15, 2015</u>	11 Airport of Departure (Airport, City/Province): <u>TRISULARAN</u>	13 Engine On: <u>0623H</u>	14 Engine Off: <u>0923H</u>	15 Total Engine Time: <u>2435</u>	16 Take off: <u>0653H</u>	
17 Landing: <u>0918H</u>	18 Total Flight Time: <u>2+25</u>	19 Weather: <u>Cloudy</u>				
20 Flight Classification						
20.a Billable	20.b Non Billable	20.c Others				
<input checked="" type="checkbox"/> Acquisition Flight	<input type="checkbox"/> Aircraft Test Flight	<input type="checkbox"/> LiDAR System Maintenance				
<input type="checkbox"/> Ferry Flight	<input type="checkbox"/> AAC Admin Flight	<input type="checkbox"/> Aircraft Maintenance				
<input type="checkbox"/> System Test Flight	<input type="checkbox"/> Others: _____	<input type="checkbox"/> Phil-LiDAR Admin Activities				
<input type="checkbox"/> Calibration Flight						
21 Remarks: <u>Airwayd BLK 57C at 800m</u>						
22 Problems and Solutions						
<input type="checkbox"/> Weather Problem						
<input type="checkbox"/> System Problem						
<input type="checkbox"/> Aircraft Problem						
<input type="checkbox"/> Pilot Problem						
<input type="checkbox"/> Others: _____						
Acquisition Flight Approved by <u>[Signature]</u> Signature over Printed Name (End User Representative)	Acquisition Flight Certified by <u>[Signature]</u> Signature over Printed Name (PAF Representative)	Pilot-in-Command <u>C. Alfonso III</u> Signature over Printed Name	LiDAR Operator <u>K. Andoy</u> Signature over Printed Name	Aircraft Mechanic/ LiDAR Technician <u>[Signature]</u> Signature over Printed Name		

Figure A-6.3. Flight Log for Mission 1BLK51C258A

4. Flight Log for Mission 1BLK51260A

PHIL-LIDAR 1 Data Acquisition Flight Log						Flight Log No.: <u>744 P</u>			
1 LIDAR Operator: <u>ROXAS</u>	2 ALTM Model: <u>ROXAS</u>	3 Mission Name: <u>1BLK51260A</u>	4 Type: VFR	5 Aircraft Type: Casrnat206H	6 Aircraft Identification: <u>RF-C022</u>				
7 Pilot: <u>PURONG</u>	8 Co-Pilot: <u>LAGO</u>	9 Route: <u>TABALARAN - TABALARAN</u>	10 Date: <u>Sept 17 2015</u>	11 Airport of Arrival (Airport, City/Province): <u>TABALARAN</u>	12 Airport of Departure (Airport, City/Province): <u>TABALARAN</u>				
13 Engine On: <u>0604</u>	14 Engine Off: <u>1106</u>	15 Total Engine Time: <u>4+17</u>	16 Take off: <u>0634</u>	17 Landing: <u>1101</u>	18 Total Flight Time: <u>4+07</u>				
19 Weather: <u>Partly Cloudy</u>									
20 Flight Classification									
20.a Billable	20.b Non Billable	20.c Others							
<input checked="" type="checkbox"/> Acquisition Flight	<input type="checkbox"/> Aircraft Test Flight	<input type="checkbox"/> LIDAR System Maintenance							
<input type="checkbox"/> Ferry Flight	<input type="checkbox"/> AAC Admin Flight	<input type="checkbox"/> Aircraft Maintenance							
<input type="checkbox"/> System Test Flight	<input type="checkbox"/> Others: _____	<input type="checkbox"/> Phil-LIDAR Admin Activities							
<input type="checkbox"/> Calibration Flight									
21 Remarks: <u>Summary BLK 51260A</u>									
22 Problems and Solutions									
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____									
Acquisition Flight Approved by		Acquisition Flight Certified by		Pilot-in-Command		LDAR Operator		Aircraft Mechanic/ LDAR Technician	
<u>J. Purong</u>		<u>SS Purong</u>		<u>C. Albaso III</u>		<u>J. Purong</u>		<u>FA</u>	
Signature over Printed Name (End User Representative)		Signature over Printed Name (PAF Representative)		Signature over Printed Name		Signature over Printed Name		Signature over Printed Name	

Figure A-6.4. Flight Log for Mission 1BLK51260A



5. Flight Log for Mission 1BLK51G265A






PHIL-LiDAR 1 Data Acquisition Flight Log						Flight Log No.: 349 P
1 LiDAR Operator: <u>Roxas</u>	2 ALTM Model: <u>Leg</u>	3 Mission Name: <u>1BLK51G265A</u>	4 Type: VFR	5 Aircraft Type: <u>Cesna T206H</u>	6 Aircraft Identification: <u>7022</u>	
7 Pilot: <u>C. Alfonso III</u>	8 Co-Pilot: <u>R. Lagda</u>	9 Route: <u>Tagbilaran - Tagbilaran</u>	12 Airport of Arrival (Airport, City/Province): <u>Tagbilaran</u>			
10 Date: <u>Sept 24, 2015</u>	11 Airport of Departure (Airport, City/Province): <u>Tagbilaran</u>		18 Total Flight Time: <u>3:37</u>			
13 Engine On: <u>0654</u>	14 Engine Off: <u>1041</u>	15 Total Engine Time: <u>3:47</u>	16 Take off: <u>0659</u>	17 Landing: <u>1036</u>		
19 Weather: <u>Cloudy</u>						
20 Flight Classification						
20.a Billable	20.b Non Billable	20.c Others				
<input checked="" type="checkbox"/> Acquisition Flight <input type="checkbox"/> Ferry Flight <input type="checkbox"/> System Test Flight <input type="checkbox"/> Calibration Flight	<input type="checkbox"/> Aircraft Test Flight <input type="checkbox"/> AAC Admin Flight <input type="checkbox"/> Others: _____	<input type="checkbox"/> LiDAR System Maintenance <input type="checkbox"/> Aircraft Maintenance <input type="checkbox"/> Phil-LiDAR Admin Activities				
21 Remarks <u>Summary BLK 51A</u>						
22 Problems and Solutions						
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____						
Acquisition Flight Approved by		Acquisition Flight Certified by		Pilot-in-Command		
 Signature over Printed Name (End User Representative)		 Signature over Printed Name (PAF Representative)		 Signature over Printed Name		
				LIDAR Operator		
				 Signature over Printed Name		
				Aircraft Mechanic/ LiDAR Technician		
				 Signature over Printed Name		

Figure A-6.5. Flight Log for Mission 1BLK51G265A

6. Flight Log for Mission 1BLK51S266A

Flight Log No.: 349 P

PHIL-LIDAR 1 Data Acquisition Flight Log

1 LIDAR Operator: <u>Armas</u>	2 ALTM Model: <u>1BLK51S266A</u>	3 Mission Name:	4 Type: VFR	5 Aircraft Type: Cesna T206H	6 Aircraft Identification: <u>7022</u>
7 Pilot: <u>C. Alfonso III</u>	8 Co-Pilot: <u>R. Casala</u>	9 Route: <u>TABILARAN - TABILARAN</u>	10 Date: <u>Sept 26, 2015</u>	11 Airport of Departure (Airport, City/Province): <u>TABILARAN</u>	12 Airport of Arrival (Airport, City/Province): <u>TABILARAN</u>
13 Engine On: <u>0654</u>	14 Engine Off: <u>1041</u>	15 Total Engine Time: <u>3747</u>	16 Take off: <u>0659</u>	17 Landing: <u>1036</u>	18 Total Flight Time: <u>3+37</u>
19 Weather: <u>Cloudy</u>	20 Flight Classification				
20.a Billable		20.b Non Billable		20.c Others	
<input checked="" type="checkbox"/> Acquisition Flight <input type="checkbox"/> Ferry Flight <input type="checkbox"/> System Test Flight <input type="checkbox"/> Calibration Flight		<input type="checkbox"/> Aircraft Test Flight <input type="checkbox"/> AAC Admin Flight <input type="checkbox"/> Others: _____		<input type="checkbox"/> LIDAR System Maintenance <input type="checkbox"/> Aircraft Maintenance <input type="checkbox"/> Phil-LIDAR Admin Activities	
21 Remarks: <u>Surveyed BLK 51 A</u>					
22 Problems and Solutions					
<input type="checkbox"/> Weather Problem <input type="checkbox"/> System Problem <input type="checkbox"/> Aircraft Problem <input type="checkbox"/> Pilot Problem <input type="checkbox"/> Others: _____					



Acquisition Flight Approved by  Signature over Printed Name (End User Representative)	Acquisition Flight Certified by  Signature over Printed Name (PAF Representative)	Pilot-in-Command <u>Alfonso III</u> <u>C. Alfonso III</u> Signature over Printed Name	LIDAR Operator <u>J. P. De la Cruz</u> Signature over Printed Name	Aircraft Mechanic/ LIDAR Technician <u>MA</u> Signature over Printed Name
---	---	--	--	---

Figure A-6.6. Flight Log for Mission 1BLK51S266A

## Annex 7. Flight Status Reports

BOHOL

(September 12-23, 2015)

Table A-7.1. Flight Status Report

FLIGHT NO	AREA	MISSION	OPERATOR	DATE FLOWN	REMARKS
3409P	BLK 51S INABANGA FP AND BLK 51B MATULID FP	1BLK51B255A	I ROXAS	SEPT 12	SURVEYED BLK 51B AT 1000M THEN 850M ALT; ABNORMAL AVPOSVIEW TERMINATION; DIGI HD WRITING ERROR; SWATH NOT UPDATING – RESTARTED LASER – INC SWATH AND LAS
3411P	BLK 51C AND 51F MATULID FP	1BLK51C255B	J ALVIAR	SEPT 12	SURVEYED BLK 51C AND PARTS OF BLK 51F AT 800M ALT; LOST CHANNEL A PROMPT BUT BOTH LASERS WERE STILL ACQUIRING RANGES
3421P	BLK 51F	1BLK51C258A	KJ ANDAYA	SEPT 15	SURVEYED BLK 51F AT 800M; TOO CLOUDY
3429P	BLK 51C, 51B, 51F	1BLK51260A	I ROXAS	SEPT 17	SURVEYED BLK 51B, 51F, AND 51C; CHANGED MISSION NAME FROM 1BLK75260A TO 1BLK51260A; DESCENDED FROM 1000M TO 800M
3449P	BLK 51A	1BLK51G265A	I ROXAS	SEPT 22	SURVEYED BLK 51A AT 800M
3453P	BLK 51LKS, 51F LOBOC FP	1BLK51S266A	J ALVIAR	SEPT 23	SURVEYED GAPS IN LOBOC FP; IRREGULAR SWATH AND LAS

### LAS/SWATH BOUNDARIES PER MISSION FLIGHT

Flight No.: 3409P  
Area: BLK51S,BLK51B  
Mission Name: 1BLK51B255A  
Parameters: Altitude: 1000m; Scan Frequency: 30; Scan Angle: 50




Figure A-7.1. Swath for Flight No. 3409P



Flight No.: 3411P  
Area: BLK51C, BLK51F  
Mission Name: 1BLK51C255B  
Parameters: Altitude: 800-1000m; Scan Frequency: 30; Scan Angle: 50




Figure A-7.2. Swath for Flight No. 3411P

Flight No.: 3421P  
Area: BLK51F  
Mission Name: 1BLK51C258A  
Parameters: Altitude: 800-1000m; Scan Frequency: 30; Scan Angle: 50




Figure A-7.3. Swath for Flight No. 3421P



Flight No.: 3429P  
Area: BLK51B, BLK51F, BLK51C  
Mission Name: 1BLK51260A  
Parameters: Altitude: 800-1000m; Scan Frequency: 30; Scan Angle: 50




Figure A-7.4. Swath for Flight No. 3429P

Flight No.: 3449P  
Area: BLK51A  
Mission Name: 1BLK51G265A  
Parameters: Altitude: 800-1000m; Scan Frequency: 30; Scan Angle: 50



Figure A-7.5. Swath for Flight No. 3449P



Flight No.: 3453P  
Area: BLK51F, BLK51LKS  
Mission Name: 1BLK51S266A  
Parameters: Altitude:1000m; Scan Frequency: 30; Scan Angle: 50




Figure A-7.6. Swath for Flight No. 3453P

## Annex 8: Mission Summary Reports

Table A-8.1. Mission Summary Report for Mission Blk51B

Flight Area	Bohol
Mission Name	<b>Blk51B</b>
Inclusive Flights	3409P
Range data size	32.8 GB
POS	302 MB
Base Data	15.7 MB
Image	NA
Transfer date	September 21, 2015
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	Yes
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.318
RMSE for East Position (<4.0 cm)	1.080
RMSE for Down Position (<8.0 cm)	2.870
Boresight correction stdev (<0.001deg)	0.000157
IMU attitude correction stdev (<0.001deg)	0.000393
GPS position stdev (<0.01m)	0.0008
Minimum % overlap (>25)	31.38
Ave point cloud density per sq.m. (>2.0)	2.78
Elevation difference between strips (<0.20 m)	Yes
Number of 1km x 1km blocks	258
Maximum Height	510.48 m
Minimum Height	65.54 m
Classification (# of points)	
Ground	35,543,081
Low vegetation	22,577,357
Medium vegetation	31,702,271
High vegetation	38,654,593
Building	1,252,854
Orthophoto	No
Processed by	Engr. Angelo Carlo Bongat, Engr. Christy Lubiano, Kathryn Claudine Zarate




Figure A-8.1. Solution Status




Figure A-8.2. Smoothed Performance Metric Parameters






Figure A-8.3. Best Estimate Trajectory




Figure A-8.4. Coverage of LiDAR data






Figure A-8.5. Image of data overlap




Figure A-8.6. Density Map of merged LiDAR data





Figure A-8.7. Elevation Difference Between flight lines

Table A-8.2. Mission Summary Report for Mission Blk51C

Flight Area	Bohol
Mission Name	<b>Blk51C</b>
Inclusive Flights	3411P, 3429P
Range data size	12.9 GB
POS	151 MB
Base Data	24.05 MB
Image	NA
Transfer date	September 21, 2015
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	Yes
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.350
RMSE for East Position (<4.0 cm)	1.416
RMSE for Down Position (<8.0 cm)	3.280
<i>Boresight correction stdev (&lt;0.001deg)</i>	
	0.000206



IMU attitude correction stdev (<0.001deg)	0.000581
GPS position stdev (<0.01m)	0.0091
Minimum % overlap (>25)	20.51
Ave point cloud density per sq.m. (>2.0)	3.55
Elevation difference between strips (<0.20 m)	Yes
Number of 1km x 1km blocks	149
Maximum Height	398.62 m
Minimum Height	58.94 m
<i>Classification (# of points)</i>	
Ground	31,388,745
Low vegetation	12,005,662
Medium vegetation	16,254,529
High vegetation	41,356,718
Building	946,900
Orthophoto	No
Processed by	Engr. Jennifer Saguran, Engr. Edgardo Gubatanga, Engr. Krisha Marie Bautista






Figure A-8.9. Smoothed Performance Metric Parameters




Figure A-8.10. Best Estimate Trajectory






Figure A-8.11. Coverage of LiDAR data




Figure A-8.12. Image of data overlap






Figure A-8.13. Density Map of merged LiDAR data




Figure A-8.14. Elevation Difference Between flight lines

Table A-8.3. Mission Summary Report for Mission Blk51C Additional

Flight Area	Bohol
Mission Name	<b>Blk51C_additional</b>
Inclusive Flights	3429P
Range data size	23.8 GB
POS	261 MB
Base Data	8.35 MB
Image	NA
Transfer date	October 28, 2015
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	No
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	0.966
RMSE for East Position (<4.0 cm)	1.029
RMSE for Down Position (<8.0 cm)	2.475
<i>Boresight correction stdev (&lt;0.001deg)</i>	
IMU attitude correction stdev (<0.001deg)	0.000581
GPS position stdev (<0.01m)	0.0091
<i>Minimum % overlap (&gt;25)</i>	
Ave point cloud density per sq.m. (>2.0)	2.67
Elevation difference between strips (<0.20 m)	Yes
<i>Number of 1km x 1km blocks</i>	
Maximum Height	493.11 m
Minimum Height	66.88 m
<i>Classification (# of points)</i>	
Ground	47,220,916
Low vegetation	24,759,582
Medium vegetation	33,557,086
High vegetation	62,237,981
Building	1,894,697
<i>Orthophoto</i>	
Processed by	Engr. Jennifer Saguran, Engr. Chelou Prado, Kathryn Claudyn Zarate




Figure A-8.15. Solution Status




Figure A-8.16. Smoothed Performance Metric Parameters






Figure A-8.17. Best Estimate Trajectory




Figure A-8.18. Coverage of LiDAR data






Figure A-8.19. Image of data overlap




Figure A-8.20. Density Map of merged LiDAR data




Figure A-8.21. Elevation Difference Between flight lines

Table A-8.4. Mission Summary Report for Mission Blk51F

Flight Area	Bohol
Mission Name	<b>Blk51F</b>
Inclusive Flights	3421P, 3453P
Range data size	8.79 GB
POS	152 MB
Base Data	11.8 MB
Image	NA
Transfer date	October 28, 2015
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	Yes
Processing Mode (<=1)	Yes
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	0.878
RMSE for East Position (<4.0 cm)	1.017
RMSE for Down Position (<8.0 cm)	1.852
Boresight correction stdev (<0.001deg)	0.000328



IMU attitude correction stdev (<0.001deg)	0.001372
GPS position stdev (<0.01m)	0.0177
Minimum % overlap (>25)	41.46
Ave point cloud density per sq.m. (>2.0)	4.14
Elevation difference between strips (<0.20 m)	Yes
Number of 1km x 1km blocks	155
Maximum Height	395.58 m
Minimum Height	67.56 m
<i>Classification (# of points)</i>	
Ground	20,632,320
Low vegetation	9,004,364
Medium vegetation	9,589,867
High vegetation	14,454,767
Building	338,961
Orthophoto	No
Processed by	Engr. Analyn Naldo, Engr. Merven Matthew Natino, Marie Denise Bueno




Figure A-8.22. Figure 1.4.1. Solution Status






Figure A-8.23. Smoothed Performance Metric Parameters




Figure A-8.24. Best Estimate Trajectory




Figure A-8.25. Coverage of LiDAR data




Figure A-8.26. Image of data overlap






Figure A-8.27. Density Map of merged LiDAR data




Figure A-8.28. Elevation Difference Between flight lines

Table A-8.4. Mission Summary Report for Mission Blk51A

<b>Flight Area</b>	<b>Bohol</b>
Mission Name	<b>Blk51A</b>
Inclusive Flights	3449P
Range data size	18 GB
POS	221 MB
Base Data	13.1 MB
Image	NA
Transfer date	October 28, 2015
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	Yes
Processing Mode (<=1)	No
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	0.976
RMSE for East Position (<4.0 cm)	1.195
RMSE for Down Position (<8.0 cm)	3.12
Boresight correction stdev (<0.001deg)	0.000181
IMU attitude correction stdev (<0.001deg)	0.000962
GPS position stdev (<0.01m)	0.0028
Minimum % overlap (>25)	24.82
Ave point cloud density per sq.m. (>2.0)	2.74
Elevation difference between strips (<0.20 m)	Yes
Number of 1km x 1km blocks	210
Maximum Height	249.28 m
Minimum Height	67.91 m
<i>Classification (# of points)</i>	
Ground	27,982,165
Low vegetation	21,612,607
Medium vegetation	19,117,741
High vegetation	20,385,805
Building	828,221
Orthophoto	No
Processed by	Engr. Regis Guhiting, Engr. Harond Santos, Kathryn Claudine Zarate






Figure A-8.29. Solution Status




Figure A-8.30. Smoothed Performance Metric Parameters




Figure A-8.31. Best Estimate Trajectory




Figure A-8.32. Coverage of LiDAR data




Figure A-8.33. Image of data overlap




Figure A-8.34. Density Map of merged LiDAR data






Figure A-8.35. Elevation Difference Between flight lines



**Annex 9. Ipil Model Basin Parameters**

Table A-9.1. Ipil Model Basin Parameters

Basin Number	SCS Curve Number Loss Model		Clark Transform Model		Recession Constant Baseflow Model					
	Initial Abstraction	Curve Number	Impervious	Time of Concentration	Storage Coefficient	Initial Type	Initial Discharge	Recession Constant	Threshold Type	Ratio to Peak
W140	4.948	68.105	0	0.44063	1.5269	Discharge	0.004109	1	Ratio to Peak	0.13333
W150	2.5742	97.458	0	2.7814	1.8817	Discharge	0.095626	1	Ratio to Peak	0.18824
W160	3.2817	66.743	0	2.4588	1.6054	Discharge	0.025748	1	Ratio to Peak	0.2
W170	3.0798	85.586	0	3.5917	1.5875	Discharge	0.10022	1	Ratio to Peak	0.2
W180	3.841	72.088	0	12.064	8.0833	Discharge	0.72018	1	Ratio to Peak	0.2
W190	0.53014	93.414	0	3.5563	3.383	Discharge	0.76921	0.64027	Ratio to Peak	0.2
W200	0.50966	96.056	0	2.1682	1.4798	Discharge	0.2069	1	Ratio to Peak	0.18447
W210	2.4329	84.407	0	2.6257	2.5758	Discharge	0.21866	1	Ratio to Peak	0.2
W220	1.7817	89.016	0	2.4641	5.1678	Discharge	0.56872	1	Ratio to Peak	0.2
W230	4.3282	83.812	0	1.5289	3.5523	Discharge	0.33535	1	Ratio to Peak	0.2
W240	4.35	79.74	0	3.2887	11.379	Discharge	0.45576	1	Ratio to Peak	0.2
W250	2.9125	79.468	0	0.99754	1.5268	Discharge	0.28536	1	Ratio to Peak	0.196
W260	4.7832	73.376	0	2.8932	4.319	Discharge	0.27915	1	Ratio to Peak	0.2

## Annex 10. Ipil Model Reach Parameters

Table A-10.1. Ipil Model Reach Parameters

Reach Number	Muskingum Cunge Routing Model						
	Time Step Method	Length (m)	Slope	Manning's n	Shape	Width	Side Slope
R10	Automatic Fixed Interval	428.85	5E-04	0.0299019	Trapezoid	15	1
R110	Automatic Fixed Interval	5206.2	0.004	0.0197094	Trapezoid	15	1
R20	Automatic Fixed Interval	916.1	1E-04	0.0292154	Trapezoid	15	1
R30	Automatic Fixed Interval	3106.3	0.002	0.0407621	Trapezoid	15	1
R50	Automatic Fixed Interval	3851.9	0.002	0.0150973	Trapezoid	15	1
R90	Automatic Fixed Interval	5538.4	0.001	0.0178049	Trapezoid	15	1

**Annex 11. Ipil Field Validation Points**

Table A-11.1.1. Ipil Field Validation Points

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error (m)	Event / Date	Return Period of Event
	Longitude	Latitude					
1	124.33705	9.9833412	0.25	0.5	0.0625	Ruby	100 Year
2	124.33721	9.9834355	0.35	0.3	0.0025	Ruby	100 Year
3	124.33835	9.9841551	0.71	0.7	0.0001	Seniang	100 Year
4	124.33829	9.9841569	0.58	0.5	0.0064	Yolanda	100 Year
5	124.33759	9.9842347	0.42	0.3	0.0144	Seniang	100 Year
6	124.33749	9.9843194	0.45	0.3	0.0225	Ruby	100 Year
7	124.33744	9.9845967	0.6	0.5	0.01	Queenie	100 Year
8	124.33716	9.9846039	0.19	0.3	0.0121	Ruby	100 Year
9	124.33974	9.9848267	0.03	0.7	0.4489	Ruby	100 Year
10	124.34038	9.9851157	0.03	0.7	0.4489	Ruby	100 Year
11	124.33969	9.9853496	0.03	0.9	0.7569	Seniang	100 Year
12	124.33903	9.9868484	0.03	0.5	0.2209	Ruby	100 Year
13	124.3392	9.9877807	0.03	0.2	0.0289	Ruby	100 Year
14	124.34333	9.9988243	0.4	0.2	0.04	Ruby	100 Year
15	124.3471	10.002355	0.68	2.1	2.0164	Yolanda	100 Year
16	124.34732	10.002875	0.03	0.5	0.2209	Seniang	100 Year
17	124.37035	10.021354	0.03	0.5	0.2209	Seniang	100 Year
18	124.37202	10.022183	0.03	1.1	1.1449	Seniang	100 Year
19	124.37092	10.027091	0.03	0.9	0.7569	Ruby	100 Year
20	124.34291	10.02972	0.03	0.5	0.2209	Ruby	100 Year
21	124.34281	10.029748	0.03	0.2	0.0289	Ruby	100 Year
22	124.37076	10.030026	0.03	0.5	0.2209	Queenie	100 Year
23	124.34093	10.030533	0.03	0.2	0.0289	Ruby	100 Year

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error (m)	Event / Date	Return Period of Event
	Longitude	Latitude					
24	124.37012	10.031257	0.03	0.2	0.0289	Ruby	100 Year
25	124.37019	10.032118	0.03	0.7	0.4489	Seniang	100 Year
26	124.34732	10.032917	0.03	0.7	0.4489	Ruby	100 Year
27	124.34722	10.032925	0.03	2.1	4.2849	Seniang	100 Year
28	124.34745	10.033067	0.03	0.3	0.0729	Ruby	100 Year
29	124.34783	10.033799	0.03	0.5	0.2209	Ruby	100 Year
30	124.34821	10.034323	0.03	1.3	1.6129	Ruby	100 Year
31	124.34773	10.034582	0.11	0.9	0.6241	Ruby	100 Year
32	124.34769	10.034754	0.03	0.5	0.2209	Ruby	100 Year
33	124.34824	10.034825	0.03	0.35	0.1024	Ruby	100 Year
34	124.36782	10.042379	0.03	0.4	0.1369	Ruby	100 Year
35	124.36427	10.044475	0.03	1.1	1.1449	Ruby	100 Year
36	124.36422	10.044479	0.03	0.5	0.2209	Ruby	100 Year
37	124.36343	10.044826	0.03	0.4	0.1369	Ruby	100 Year
38	124.32239	10.047115	0.68	0.9	0.0484	Seniang	100 Year
39	124.32228	10.047186	0.91	1.1	0.0361	Seniang	100 Year
40	124.32203	10.047269	0.59	0.5	0.0081	Ruby	100 Year
41	124.35474	10.048345	0.27	0.2	0.0049	Ruby	100 Year
42	124.35362	10.048428	1.46	1.1	0.1296	Seniang	100 Year
43	124.35367	10.048548	0.92	0.6	0.1024	Seniang	100 Year
44	124.35146	10.048895	0.03	0.2	0.0289	Ruby	100 Year
45	124.35152	10.049012	0.6	0.6	0	Seniang	100 Year
46	124.35173	10.049014	1.24	1.1	0.0196	Seniang	100 Year
47	124.36082	10.049173	0.03	0.3	0.0729	Ruby	100 Year
48	124.34315	10.049721	2.54	1.9	0.4096	Seniang	100 Year
49	124.35931	10.049937	0.03	1.1	1.1449	Seniang	100 Year



Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error (m)	Event / Date	Return Period of Event
	Longitude	Latitude					
50	124.3662	10.061405	0.03	0.3	0.0729	Ruby	100 Year
51	124.36634	10.061473	0.03	0.3	0.0729	Seniang	100 Year
52	124.3569	10.062657	0.03	0.2	0.0289	Seniang	100 Year
53	124.35789	10.065454	0.03	0.5	0.2209	Seniang	100 Year
54	124.3576	10.066364	0.04	0.2	0.0256	Ruby	100 Year
55	124.35776	10.066465	0.07	0.5	0.1849	Ruby	100 Year
56	124.34183	10.071758	0.03	0.9	0.7569	Seniang	100 Year
57	124.34224	10.072682	0.03	1.1	1.1449	Seniang	100 Year
58	124.35698	10.072996	0.03	0.9	0.7569	Seniang	100 Year
59	124.35633	10.073556	0.03	0.2	0.0289	Seniang	100 Year
60	124.35626	10.074051	0.03	0	0.0009	Seniang	100 Year
61	124.35656	10.074103	0.03	0.1	0.0049	Seniang	100 Year
62	124.34343	10.07513	0.03	0.2	0.0289	Seniang	100 Year
63	124.34334	10.076312	0.03	0	0.0009	Seniang	100 Year
64	124.34373	10.076453	0.03	0	0.0009	Ruby	100 Year
65	124.35002	10.076522	0.03	0.2	0.0289	Seniang	100 Year
66	124.34958	10.076602	0.03	1.3	1.6129	Seniang	100 Year
67	124.34959	10.076798	0.03	0.2	0.0289	Seniang	100 Year
68	124.34372	10.076854	0.03	0.3	0.0729	Ruby	100 Year
69	124.34965	10.07685	0.03	0.5	0.2209	Ruby	100 Year
70	124.34365	10.077647	0.03	0.2	0.0289	Senaing	100 Year
71	124.3435	10.077939	0.03	1.1	1.1449	Yolanda	100 Year
72	124.34987	10.078004	0.03	0.2	0.0289	Seniang	100 Year
73	124.34347	10.078393	0.06	0.2	0.0196	Ruby	100 Year
74	124.35332	10.078435	0.03	0.5	0.2209	Ruby	100 Year
75	124.35302	10.078501	0.18	0.9	0.5184	Ruby	100 Year
76	124.34987	10.078691	0.03	1.1	1.1449	Yolanda	100 Year
77	124.35029	10.078832	0.03	0.2	0.0289	Seniang	100 Year
78	124.34381	10.079926	0.03	0.5	0.2209	Yolanda	100 Year
79	124.34344	10.079956	0.03	0.7	0.4489	Yolanda	100 Year
80	124.34618	10.080021	0.03	0.2	0.0289	Yolanda	100 Year
81	124.34487	10.080036	0.91	1.5	0.3481	Seniang	100 Year
82	124.3449	10.080082	1.35	1.7	0.1225	Yolanda	100 Year
83	124.3434	10.080099	0.03	0.9	0.7569	Seniang	100 Year
84	124.34492	10.080101	1.7	1.5	0.04	Yolanda	100 Year
85	124.34533	10.081115	0.03	0.2	0.0289	Yolanda	100 Year
86	124.35588	10.082329	0.03	0.7	0.4489	Yolanda	100 Year
87	124.35601	10.082567	0.03	0.2	0.0289	Yolanda	100 Year
88	124.3531	10.084039	0.03	0.4	0.1369	Seniang	100 Year
89	124.35156	10.085705	0.03	0.5	0.2209	Ruby	100 Year
90	124.35072	10.085929	0.03	0.2	0.0289	Ruby	100 Year
91	124.35084	10.085952	0.03	0.6	0.3249	Yolanda	100 Year

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error (m)	Event / Date	Return Period of Event
	Longitude	Latitude					
92	124.34779	10.087821	0.03	0.3	0.0729	Seniang	100 Year
93	124.34968	10.088201	0.04	0.85	0.6561	Ruby	100 Year
94	124.35652	10.08836	0.03	1.1	1.1449	Ruby	100 Year
95	124.35724	10.091578	0.03	0.9	0.7569	Ruby	100 Year
96	124.36119	10.094375	0.03	0.2	0.0289	Seniang	100 Year
97	124.36154	10.095149	0.03	0	0.0009	Seniang	100 Year
98	124.31671	10.097115	0.03	0	0.0009	Seniang	100 Year
99	124.31695	10.09739	0.03	0.5	0.2209	Ruby	100 Year
100	124.36266	10.097607	0.07	0.9	0.6889	Ruby	100 Year
101	124.31683	10.098161	0.03	0.2	0.0289	Seniang	100 Year
102	124.3166	10.098849	0.03	0.2	0.0289	Yolanda	100 Year
103	124.31686	10.098905	0.03	0.7	0.4489	Yolanda	100 Year
104	124.31645	10.098933	0.03	0.5	0.2209	Ruby	100 Year
105	124.31662	10.099193	0.03	0.5	0.2209	Ruby	100 Year
106	124.31964	10.10235	0.24	0.5	0.0676	Ruby	100 Year
107	124.31947	10.102655	0.3	0.9	0.36	Ruby	100 Year
108	124.31699	10.102921	0.03	0.5	0.2209	Ruby	100 Year
109	124.31834	10.103489	0.64	0.9	0.0676	Yolanda	100 Year
110	124.3171	10.103509	0.33	0.3	0.0009	Yolanda	100 Year
111	124.31583	10.104585	1	1.5	0.25	Yolanda	100 Year
112	124.31718	10.104599	1.36	0.9	0.2116	Yolanda	100 Year
113	124.31772	10.105576	0.42	0.3	0.0144	Ruby	100 Year
114	124.34364	10.112718	0.03	0.2	0.0289	Ruby	100 Year
115	124.34364	10.112823	0.03	0.2	0.0289	Ruby	100 Year
116	124.34364	10.112833	0.05	0.4	0.1225	Ruby	100 Year
117	124.34394	10.112955	0.03	0.3	0.0729	Ruby	100 Year
118	124.34382	10.11296	0.03	0.3	0.0729	Ruby	100 Year
119	124.3537	10.116678	0.42	0.5	0.0064	Ruby	100 Year
120	124.3533	10.116789	0.21	1.2	0.9801	Yolanda	100 Year
121	124.35257	10.117098	0.05	0.9	0.7225	Ruby	100 Year
122	124.35889	10.118398	0.72	0.9	0.0324	Seniang	100 Year
123	124.35879	10.118447	0.23	0.2	0.0009	Seniang	100 Year
124	124.34762	10.118581	0.1	0.2	0.01	Seniang	100 Year
125	124.35815	10.118577	0.03	0.2	0.0289	Yolanda	100 Year
126	124.34753	10.118717	0.04	1.1	1.1236	Yolanda	100 Year
127	124.34748	10.118773	0.04	0.3	0.0676	Ruby	100 Year
128	124.34689	10.118922	0.03	0.3	0.0729	Yolanda	100 Year
129	124.34701	10.118938	0.03	1.1	1.1449	Yolanda	100 Year
130	124.3446	10.11941	0.03	0.5	0.2209	Ruby	100 Year
131	124.3305	10.121271	0.03	0.2	0.0289	Ruby	100 Year
132	124.33034	10.121708	0.03	0.2	0.0289	Yolanda	100 Year
133	124.32994	10.121864	0.03	1.1	1.1449	Seniang	100 Year

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error (m)	Event / Date	Return Period of Event
	Longitude	Latitude					
134	124.32966	10.124426	0.03	0.3	0.0729	Ruby	100 Year
135	124.33011	10.124717	0.03	0.2	0.0289	Ruby	100 Year
136	124.32976	10.124753	0.03	1.3	1.6129	Yolanda	100 Year
137	124.32994	10.124896	0.03	0.3	0.0729	Seniang	100 Year
138	124.33165	10.125086	0.08	0.9	0.6724	Seniang	100 Year
139	124.31712	10.130834	0.03	0.5	0.2209	Seniang	100 Year
140	124.31764	10.130907	0.03	0.9	0.7569	Ruby	100 Year
141	124.3176	10.130996	0.03	0.5	0.2209	Seniang	100 Year

## Annex 12. Educational Institutions Affected by flooding in Ipil Floodplain

Table A-12.1. Educational Institutions Affected by flooding in Ipil Floodplain

Bohol				
Inabanga				
Building Name	Barangay	Rainfall Scenario		
		5-year	25-year	100-year
La Victoria Elem School	Liberty			
Bien Unido Academy	Mandawa	Low	Low	Low
Bien Unido Central Elem. School	Poblacion			
Holy Child Academy	Poblacion			
Montessori School Inc.	Poblacion			
Pres. CPG National Highschool	Puerto San Pedro			
Puerto San Pedro Primary School	Puerto San Pedro			
Hagbuyo Elem School	Hagbuyo			
San Miguel Central School	Poblacion			
San Miguel Vocational School	Poblacion			
San Agustin Elem School	San Agustin			
San Agustin High School	San Agustin			
Zamora Elem School	Zamora			
Hinlayagan Ilaya Elem School	Bongbong			
Kinan-oan elementary school	Bongbong			
Kinan-oan National High School	Bongbong			
Bohol Maranatha Christian Academy	Guinobatan			
Guinobatan Elementary School	Guinobatan			
Hin Ilaud Elem School	Hinlayagan Ilaya			
Hinlayagan National HS	Hinlayagan Ilaya			
Mabuhay Elementary School (Cabiguhan)	Hinlayagan Ilaya			
Manukan Daycare	Hinlayagan Ilaya			
La Union Elem School	La Union	Low	Low	Low
La Victoria Elem School	La Victoria			
St. Isidore Academy	Mabuhay Cabigohan			
Mahagbu Elem School	Mahagbu			
Daycare Center	Poblacion			Low
St. Isidore Academy	Poblacion			
Trinidad Central School	Poblacion			
Trinidad Municipal College	Poblacion			
San Roque Elem School	San Vicente			



### Annex 13. Health Institutions affected by flooding in Ipil Floodplain

Table A-13.1. Health Institutions affected by flooding in Ipil Flood Plain

Bohol				
Inabanga				
Building Name	Barangay	Rainfall Scenario		
		5-year	25-year	100-year
Birth Center	Poblacion			
HEALTH STATION	Poblacion			
Brgy.Puertos San Pedro Health Center	Puerto San Pedro			
Hinlayagan ilaya Health Station	Hagbuyo			
Hospital	Poblacion			
Garcia Provincial Hospital	San Jose			
Brgy Mahagbu Health Center	Mahagbu			
Trinidad Health Center	Poblacion			