

Hazard Mapping of the Philippines Using LIDAR (Phil-LiDAR 1)

LiDAR Surveys and Flood Mapping of Baua River



University of the Philippines Training Center
for Applied Geodesy and Photogrammetry
Isabela State University



© University of the Philippines Diliman and Isabela State University 2017

Published by the UP Training Center for Applied Geodesy and Photogrammetry (TCAGP)
College of Engineering
University of the Philippines – Diliman
Quezon City
1101 PHILIPPINES

E.C. Paringit, and J. Floresca, (Eds.). (2017), LiDAR Surveys and Flood Mapping Report of Baua River, in Enrico C. Paringit, (Ed.), Flood Hazard Mapping of the Philippines using LIDAR, Quezon City: University of the Philippines Training Center for Applied Geodesy and Photogrammetry-131pp

The text of this information may be copied and distributed for research and educational purposes with proper acknowledgement. While every care is taken to ensure the accuracy of this publication, the UP TCAGP disclaims all responsibility and all liability (including without limitation, liability in negligence) and costs which might incur as a result of the materials in this publication being inaccurate or incomplete in any way and for any reason.

For questions/queries regarding this report, contact:

Dr. Januel Floresca

Project Leader, Phil-LiDAR 1 Program
Isabela State University
Echague, Isabela 3309
E-mail: januelpf@yahoo.com.ph

Enrico C. Paringit, Dr. Eng.

Program Leader, Phil-LiDAR 1 Program
University of the Philippines Diliman
Quezon City, Philippines 1101
E-mail: ecparingit@up.edu.ph

National Library of the Philippines
ISBN: 978-621-430-035-8

TABLE OF CONTENTS

LIST OF TABLES v

LIST OF FIGURES.....	vi
LIST OF ACRONYMS AND ABBREVIATIONS.....	viii
CHAPTER 1: OVERVIEW OF THE PROGRAM AND BAUA RIVER	1
1.1 Background of the Phil-LIDAR 1 Program	1
1.2 Overview of the Baua River Basin.....	1
CHAPTER 2: LIDAR DATA ACQUISITION OF THE BAUA FLOODPLAIN	4
2.1 Flight Plans.....	4
2.2 Ground Base Station	5
2.3 Flight Missions	9
2.4. Survey Coverage	9
CHAPTER 3: LIDAR DATA PROCESSING OF THE BAUA FLOODPLAIN	12
3.1 Overview of the LIDAR Data Pre-Processing	12
3.2 Transmittal of Acquired LiDAR Data	13
3.3 Trajectory Computation	13
3.4 LiDAR Point Cloud Computation	15
3.5 LiDAR Data Quality Checking	16
3.6 LiDAR Point Cloud Classification and Rasterization.....	20
3.7 LiDAR Image Processing and Orthophotograph Rectification.....	22
3.8 DEM Editing and Hydro-Correction.....	23
3.9 Mosaicking of Blocks.....	24
3.10 Calibration and Validation of Mosaicked LiDAR Digital Elevation Model.....	25
3.11 Integration of Bathymetric Data into the LiDAR Digital Terrain Model	28
3.12 Feature Extraction.....	29
3.12.1 Quality Checking of Digitized Features' Boundary	30
3.12.2 Height Extraction.....	30
3.12.3 Feature Attribution.....	30
3.12.4 Final Quality Checking of Extracted Features.....	32
CHAPTER 4: LIDAR VALIDATION SURVEY AND MEASUREMENTS OF BAUA RIVER BASIN.....	33
4.1 Summary of Activities	33
4.2 Control Survey	35
4.3 Baseline Processing.....	40
4.4 Network Adjustment	42
4.5 Cross-section and Bridge As-Built Survey, and Water Level Marking.....	46
4.6 Validation Points Acquisition Survey.....	51
4.7 Bathymetric Survey.....	53
CHAPTER 5: FLOOD MODELING AND MAPPING	59
5.1 Data used in Hydrologic Modeling.....	59
5.1.1 Hydrometry and Rating Curves	59
5.1.2 Precipitation.....	59
5.1.3 Rating Curve and River Outflow	60
5.2 RIDF Station	62
5.3 HMS Model	64
5.4 Cross-section Data	69
5.5 Flo 2D Model	70
5.6 Results of HMS Calibration	71
5.7 Calculated Outflow hydrographs and Discharge Values for different Rainfall Return Periods.....	72
5.7.1 Hydrograph using the Rainfall Runoff Model	72
5.8 River Analysis Model Simulation.....	73
5.9 Flood Hazard and Flow Depth Map	74
5.10 Areas Exposed to Flooding.....	81
5.11 Flood Validation	84
REFERENCES	86
ANNEXES.....	87
Annex 1. Optech Technical Specification of the Pegasus and Gemini Sensors.....	87
Annex 2. NAMRIA Certificates of Reference Points Used	89
Annex 3. Baseline Processing Reports of Control Points used in the LIDAR Survey.....	92
Annex 4. The LiDAR Survey Team Composition	93
Annex 5. Data Transfer Sheets	94
Annex 6. Flight Logs	95
Annex 7. Flight Status Report.....	99
Annex 8. Mission Summary Report	104

Annex 9. Baua Model Basin Parameters	114
Annex 10. Baua Model Reach Parameters.....	117
Annex 11. Baua Flood Validation Data.....	118
Annex 12. Educational Institutions Affected in Baua Floodplain	123
Annex 13. Health Institutions Affected in Baua Floodplain	123

LIST OF TABLES

Table 1. Flight planning parameters for Pegasus LiDAR system.....	4
Table 2. Flight planning parameters for Gemini LiDAR system	4

Table 3. Details of the recovered NAMRIA horizontal control point CGY-102 used as base station for the LiDAR acquisition.....	6
Table 4. Details of the recovered NAMRIA horizontal control point CGY-92 used as base station for the LiDAR acquisition.....	7
Table 5. Details of point CG-258 used as vertical reference point and established base station for the LiDAR acquisition.....	8
Table 6. Ground control used during LiDAR data acquisition	8
Table 7. Flight missions for LiDAR data acquisition in Baua Floodplain	9
Table 8. Actual parameters used during LiDAR data acquisition	9
Table 9. List of municipalities and cities surveyed during Baua floodplain LiDAR survey.....	10
Table 10. Self-Calibration Results values for Baua flights.	15
Table 11. List of LiDAR blocks for Baua Floodplain.	16
Table 12. Baua classification results in TerraScan.....	20
Table 13. LiDAR blocks with its corresponding area.	23
Table 14. Shift Values of each LiDAR Block of Baua Floodplain.	24
Table 15. Calibration Statistical Measures.....	27
Table 16. Validation Statistical Measures.	28
Table 17. Quality Checking Ratings for Baua Building Features.....	30
Table 18. Building Features Extracted for Baua Floodplain.	31
Table 19. Total Length of Extracted Roads for Baua Floodplain.....	31
Table 20. Number of Extracted Water Bodies for Baua Floodplain.	31
Table 21. List of reference and control points used in Baua River Basin survey.....	37
Table 22. 1 st Session Baseline Processing Report for Baua River Static Survey.....	40
Table 23. 2 nd Session Baseline Processing Report for Baua River Static Survey.....	41
Table 24. 1 st Session Control Point Constraints.....	42
Table 25. 2 nd Session Control Point Constraints.....	42
Table 26. 1 st Session Adjusted Grid Coordinates.....	43
Table 27. 2 nd Session Adjusted Grid Coordinates.....	43
Table 28. 1 st Session Adjusted Geodetic Coordinates	44
Table 29. 2 nd Session Adjusted Geodetic Coordinates	44
Table 30. Reference and control points and its location (Source: NAMRIA, UP-TCAGP)	45
Table 31. RIDF values for Aparri Rain Gauge computed by PAGASA.....	62
Table 32. Range of calibrated values for Baua Watershed	71
Table 33. Summary of the Efficiency Test of Baua HMS Model	72
Table 34. Peak values of the Baua HECHMS Model outflow using the Aparri RIDF.....	73
Table 35. Municipalities affected in Baua Floodplain	74
Table 36. Affected Areas in Gonzaga, Cagayan during 5-Year Rainfall Return Period	81
Table 37. Affected Areas in Gonzaga, Cagayan during 25-Year Rainfall Return Period	82
Table 38. Affected Areas in Gonzaga, Cagayan during 100-Year Rainfall Return Period	82
Table 39. Area covered by each warning level with respect to the rainfall scenario.....	83
Table 40. Actual flood vs simulated flood depth of Baua River Basin.....	85
Table 41. Summary of the Accuracy Assessment in the Baua River Basin Survey	85

LIST OF FIGURES

Figure 1. Map of Baua River Basin.....	2
Figure 2. Protected Areas within Baua River Basin.....	3

Figure 3. Flight plans and base stations used for Baua Floodplain.....	5
Figure 4. GPS set-up over CGY-102 located about two (2) meters from the south corner of the triangular island at the intersection of the national highway and the road to Port Irene in Santa Ana, Cagayan, and CGY-102 (b) as recovered by the field team. ...	6
Figure 5. GPS set-up over CGY-92 located inside the Lal-lo National High School, about five (5) meters west of the flagpole (a), and CGY-92 (b) as recovered by the field team.	7
Figure 6. GPS set-up over CG-258 located along the national road and about 200 meters northeast of kilometer post no. 608 in Gonzaga, Cagayan (a) and NAMRIA benchmark CG-258 (b) as recovered by the field team.....	8
Figure 7. Actual LiDAR survey coverage for Baua Floodplain.	11
Figure 8. Schematic Diagram for Data Pre-Processing Component.....	12
Figure 9. Smoothed Performance Metric Parameters of Baua Flight 3991G.....	13
Figure 10. Solution Status Parameters of Baua Flight 3991G.	14
Figure 11. Best Estimated Trajectory for Baua Floodplain.....	15
Figure 12. Boundary of the processed LiDAR data over Baua Floodplain	16
Figure 13. Image of data overlap for Baua Floodplain.....	17
Figure 14. Pulse density map of merged LiDAR data for Baua Floodplain.....	18
Figure 15. Elevation difference map between flight lines for Baua Floodplain.	19
Figure 16. Quality checking for Baua Flight 3991G.....	19
Figure 17. Tiles for Baua Floodplain (a) and classification results (b) in TerraScan.	20
Figure 18. Point cloud before (a) and after (b) classification.....	21
Figure 19. The production of last return DSM (a) and DTM (b), first return DSM (c) and secondary DTM (d) in some portion of Baua Floodplain.....	21
Figure 20. Baua floodplain with available orthophotographs.	22
Figure 21. Sample orthophotograph tiles for Baua floodplain.	23
Figure 22. Portions in the DTM of Baua floodplain – a bridge before (a) and after (b) manual editing; a mountain base before (c) and after object retrieval (d); interpolated ridge before (e) and after (f) object retrieval; and a building before (g) and after (h) manual editing.	24
Figure 23. Map of Processed LiDAR Data for Baua Floodplain.	25
Figure 24. Map of Baua Floodplain with validation survey points in green.	26
Figure 25. Correlation plot between calibration survey points and LiDAR data.....	27
Figure 26. Correlation plot between validation survey points and LiDAR data.	28
Figure 27. Map of Baua Floodplain with bathymetric survey points shown in blue.	29
Figure 28. QC blocks for Baua building features.....	30
Figure 29. Extracted features for Baua Floodplain.	32
Figure 30. Baua River Survey Extent.....	34
Figure 31. GNSS Network covering Baua River.....	36
Figure 32. GNSS base set up, Trimble® SPS 885, at PAT-2, located at the approach of Pate Bridge in Brgy. Pateng, Gonzaga, Cagayan.....	37
Figure 33. GNSS receiver set up, Trimble® SPS 885, at CGY-101, located at the side of the basketball court in Brgy. Magrafil, Gonzaga, Cagayan.....	38
Figure 34. GNSS receiver set up, Trimble® SPS 985, at CG-258, located at the approach of the bridge near the welcome arch of Brgy. Tapel, Gonzaga, Cagayan.....	38
Figure 35. GNSS receiver set up, Trimble® SPS 885, at UP-BAU-1, located at the approach of Baua Bridge in Brgy. Baua, Gonzaga, Cagayan.....	39
Figure 36. GNSS receiver set-up, Trimble® SPS 885, at CGY-102, located at the center island in front of the barangay marker of Brgy. Casambalangan in Brgy. San Jose, Gonzaga, Cagayan.....	39
Figure 37. GNSS receiver set-up, Trimble® SPS 885, at CG-234, located at the approach of Diara Bridge in Brgy. Diara-Zinungan, Sta. Ana, Cagayan	40
Figure 38. Baua Bridge facing upstream.....	46
Figure 39. As-built survey of Baua Bridge.....	46
Figure 40. Gathering of random cross-section points along Baua Bridge	47
Figure 41. Location map of Baua Bridge cross-section survey	48
Figure 42. Baua Bridge Cross-section Diagram.....	49
Figure 43. Baua Bridge Data Form.....	50
Figure 44. Water level markings on the riprap of Baua Bridge.....	51
Figure 45. Validation points acquisition survey set-up for Baua River.....	51
Figure 46. LiDAR Validation points acquisition survey for Baua River Basin.....	52
Figure 47. Manual bathymetric survey of HONS along Baua River	53
Figure 48. Gathering of random bathymetric points along Baua River	54

Figure 49. Bathymetric survey of Baua River.....	55
Figure 50. Quality checking points gathered along Baua River by DVBC.....	56
Figure 51. Baua Riverbed Profile	57
Figure 52. Baua Riverbed Profile (tributary).....	58
Figure 53. Location map of Baua HEC-HMS model used for calibration.....	60
Figure 54. Cross-Section Plot of Baua Bridge	61
Figure 55. Rating curve at Baua Bridge, Gonzaga, Cagayan.....	61
Figure 56. Rainfall and outflow data at Baua Bridge used for modeling	62
Figure 57. Location of Aparri RIDF Station relative to Baua River Basin.....	63
Figure 58. Synthetic storm generated for a 24-hr period rainfall for various return periods.	63
Figure 59. Soil map of the Baua River Basin used for the estimation of the CN parameter. (Source: DA)	64
Figure 60. Land cover map of Ocoy River Basin used for the estimation of the Curve Number (CN) and the watershed lag parameters of the rainfall-runoff model. (Source: NAMRIA)	65
Figure 61. Slope map of Baua River Basin	66
Figure 62. Stream delineation map of Baua River Basin	67
Figure 63. HEC-HMS generated Baua River Basin Model.	68
Figure 64. River cross-section of Baua River generated through Arcmap HEC GeorAS tool.....	69
Figure 65. Screenshot of subcatchment with the computational area to be modeled in FLO-2D GDS Pro.....	70
Figure 66. Outflow Hydrograph of Baua produced by the HEC-HMS model compared with observed outflow.	71
Figure 67. Outflow hydrograph at Baua Station generated using Aparri RIDF simulated in HEC-HMS.....	73
Figure 68. Sample output of Baua RAS Model	74
Figure 69. 100-year Flood Hazard Map for Baua Floodplain overlaid on Google Earth imagery...	75
Figure 70. 100-year Flow Depth Map for Baua Floodplain overlaid on Google Earth imagery	76
Figure 71. 25-year Flood Hazard Map for Baua Floodplain overlaid on Google Earth imagery.....	77
Figure 72. 25-year Flow Depth Map for Baua Floodplain overlaid on Google Earth imagery	78
Figure 73. 5-year Flood Hazard Map for Baua Floodplain overlaid on Google Earth imagery.....	79
Figure 74. 5-year Flood Depth Map for Baua Floodplain overlaid on Google Earth imagery	80
Figure 75. Affected Areas in Gonzaga, Cagayan during 5-Year Rainfall Return Period.....	81
Figure 76. Affected Areas in Gonzaga, Cagayan during 25-Year Rainfall Return Period.....	82
Figure 77. Affected Areas in Gonzaga, Cagayan during 100-Year Rainfall Return Period.....	83
Figure 78. Validation points for 5-year Flood Depth Map of Baua Floodplain	84
Figure 79. Flood map depth vs. actual flood depth.....	85

LIST OF ACRONYMS AND ABBREVIATIONS

AAC	Asian Aerospace Corporation	ISU	Isabela State University
Ab	abutment	kts	knots
ALTM	Airborne LiDAR Terrain Mapper	LAS	LiDAR Data Exchange File format
ARG	automatic rain gauge	LC	Low Chord
AWLS	Automated Water Level Sensor	LGU	local government unit
BA	Bridge Approach	LiDAR	Light Detection and Ranging
BM	benchmark	LMS	LiDAR Mapping Suite
BSWM	Bureau of Soil and Water Management	m AGL	meters Above Ground Level
CAD	Computer-Aided Design	MMS	Mobile Mapping Suite
CN	Curve Number	MSL	mean sea level
CSRS	Chief Science Research Specialist	NAMRIA	National Mapping and Resource Information Authority
DA	Department of Agriculture	NSTC	Northern Subtropical Convergence
DAC	Data Acquisition Component	PAF	Philippine Air Force
DEM	Digital Elevation Model	PAGASA	Philippine Atmospheric Geophysical and Astronomical Services Administration
DENR	Department of Environment and Natural Resources	PDOP	Positional Dilution of Precision
DOST	Department of Science and Technology	PPK	Post-Processed Kinematic [technique]
DPPC	Data Pre-Processing Component	PRF	Pulse Repetition Frequency
DREAM	Disaster Risk and Exposure Assessment for Mitigation [Program]	PTM	Philippine Transverse Mercator
DRRM	Disaster Risk Reduction and Management	QC	Quality Check
DSM	Digital Surface Model	QT	Quick Terrain [Modeler]
DTM	Digital Terrain Model	RA	Research Associate
DVBC	Data Validation and Bathymetry Component	RIDF	Rainfall-Intensity-Duration-Frequency
FMC	Flood Modeling Component	RBCO River Basin Control Office	Root Mean Square Error
FOV	Field of View	RMSE	Root Mean Square Error
GiA	Grants-in-Aid	SAR	Synthetic Aperture Radar
GCP	Ground Control Point	SCS	Soil Conservation Service
GNSS	Global Navigation Satellite System	SRTM	Shuttle Radar Topography Mission
GPS	Global Positioning System	SRS	Science Research Specialist
HEC-HMS	Hydrologic Engineering Center - Hydrologic Modeling System	SSG	Special Service Group
HEC-RAS	Hydrologic Engineering Center - River Analysis System	TBC	Thermal Barrier Coatings
HC	High Chord	UP-TCAGP	University of the Philippines – Training Center for Applied Geodesy and Photogrammetry
IDW	Inverse Distance Weighted [interpolation method]	UTM	Universal Transverse Mercator
IMU	Inertial Measurement Unit	WGS	World Geodetic System

CHAPTER 1: OVERVIEW AND BACKGROUND OF THE PROGRAM

1.1 Background of the Phil-LiDAR 1 Program

The University of the Philippines Training Center for Applied Geodesy and Photogrammetry (UP-TCAGP) launched a research program entitled “Nationwide Hazard Mapping using LiDAR” or Phil-LiDAR 1, supported by the Department of Science and Technology (DOST) Grants-in-Aid (GiA) Program. The program was primarily aimed at acquiring a national elevation and resource dataset at sufficient resolution to produce information necessary to support the different phases of disaster management. Particularly, it targeted to operationalize the development of flood hazard models that would produce updated and detailed flood hazard maps for the major river systems in the country.

Also, the program was aimed at producing an up-to-date and detailed national elevation dataset suitable for 1:5,000 scale mapping, with 50 cm and 20 cm horizontal and vertical accuracies, respectively. These accuracies were achieved through the use of the state-of-the-art Light Detection and Ranging (LiDAR) airborne technology procured by the project through DOST.


The implementing partner university for the Phil-LiDAR 1 Program is the Isabela State University (ISU). ISU is in charge of processing LiDAR data and conducting data validation reconnaissance, cross section, bathymetric survey, validation, river flow measurements, flood height and extent data gathering, flood modeling, and flood map generation for the eight (8) river basins in the Northeastern Luzon Region. The university is located in the Municipality of Echague in the province of Isabela.

1.2 Overview of the Baua River Basin

The Baua River Basin covers the Municipality of Gonzaga in Cagayan. The DENR River Basin Control Office (RBCO) states that the Baua Basin has a drainage area of 110 km² and an estimated 233 cubic meter (MCM) annual run-off (RBCO, 2015).

The Baua River Basin has a tropical climate and experiences significant rainfall most months with a short dry season. The climate here is classified as Am by the Köppen-Geiger system. The temperature averages 25.9 °C and the amount of precipitation is around 2361 mm. The least amount of rainfall occurs in April. In November, the precipitation reaches its peak and the temperatures are highest in June. January is the coldest month of the year.

Its main stem, Baua River, is among the ten (10) river systems in Cagayan Valley. The Baua River is located at Gonzaga, Cagayan. According to the 2015 national census of PSA, a total of 8,737 persons are residing within the immediate vicinity of the river, which is distributed among barangays Amunitan, Cabiraoan, Sta. Maria, and Baua in the Municipality of Gonzaga.



The water of Baua river is used mainly for irrigation. In fact, the economy of Cagayan Province, as well as the source of livelihood of communities along Baua River, largely rests on agriculture with rice, corn, and banana as the main crops and products (Philippine Statistics Authority, 2017). The Baua river is also used for other purposes such as fishery, transport and recreation. Another major use of the river and its bank is for sand and gravel extraction for concrete aggregates.

Meanwhile, Gonzaga, where the Baua River passes through, is a first class municipality located at the northeastern tip of the province of Cagayan, bordered by the municipality of Santa Ana to the northeast, to the west is the municipality of Santa Teresita, and the municipality of Lal-lo to the south. It has a total land area of 56,743 hectares. Only the northwestern part of the municipality has been settled by constituents. Larger portions of the municipality are classified as forest. The highest elevation of the municipality is believed to be at Mount Cagua in barangay Magrafil. It is being considered as a potential source of geothermal energy.

Similar to the rest of Cagayan province, Gonzaga is an agricultural municipality with more than half of the workforce employed primarily as either farmers or fishers. It is bestowed with forest and aquatic resources. It is a haven of rivers flow down to irrigation structures allowing a regular two-cropping season for rice farming, the main industry.

The municipality of Gonzaga was among the areas devastated by Typhoon Angela (Local Code Name: Rubing) on October 8, 1989 as well as Typhoon Haima (Local Code Name: Lawin) on October 20, 2016. Last November 17, 2016, Quibal-Nanguillatan-Baggao provincial road in Cagayan and Abusag Bridge in Baggao Town were not passable due to floods due to heavy rains brought on by the tail-end of a cold front (Visaya, 2016).




Figure 2. Protected Areas within Bawa River Basin.

In addition, there are two (2) Watershed Reserves situated in the municipality of Gonzaga and Lallo. The Bawa Watershed was proclaimed as Watershed Forest Reserve by virtue of Presidential Proclamation No. 108 on May 13, 1987 to protect the area from deforestation and degradation. Bawa Watershed Forest Reserve covers a total area of 8, 995 hectares. It composed of Bawa River - one of the major river systems in the municipality of Gonzaga. The other one is Wangag Watershed Forest Reserve.

Sources:

<https://en.climate-data.org>

<http://cagayan.gov.ph>

http://www.gonzaga.gov.ph/?page_id=17

http://www.phivolcs.dost.gov.ph/html/update_VMEPD/Volcano/VolcanoList/cagua.htm

<https://www.silent-gardens.com/climate.php>

Philippine Statistics Authority, 2010

CHAPTER 2: LIDAR DATA ACQUISITION OF THE BAUA FLOODPLAIN

The methods applied in this Chapter were based on the DREAM methods manual (Sarmiento, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

2.1 Flight Plans

Plans were made to acquire LiDAR data within the delineated priority area for Baua floodplain in Cagayan province. These missions were planned for 21 lines and ran for at most four and a half (4.5) hours including take-off, landing and turning time. The flight planning parameters for the LiDAR system is found in Table 1. Figure 3 shows the flight plan for Baua floodplain.

Table 1. Flight planning parameters for Pegasus LiDAR system.

Block Name	Flying Height (m AGL)	Overlap (%)	Field of View (θ)	Pulse Repetition Frequency (PRF) (kHz)	Scan Frequency (Hz)	Average Speed (kts)	Average Turn Time (Minutes)
BLK3B	850	35	50	200	30	130	5

Table 2. Flight planning parameters for Gemini LiDAR system

Block Name	Flying Height (m AGL)	Overlap (%)	Field of View (θ)	Pulse Repetition Frequency (PRF) (kHz)	Scan Frequency (Hz)	Average Speed (kts)	Average Turn Time (Minutes)
BLK3A	850	35	50	125	40	130	5
BLK3B	900	35	125	200	40	130	5




Figure 3. Flight plans and base stations used for Baua Floodplain

2.2 Ground Base Station

The project team was able to recover two (2) NAMRIA horizontal control points, CGY-102 and CGY-92 which are of second (2nd) order accuracy. The field team also recovered one (1) NAMRIA benchmark, CG-258, which was reprocessed as a horizontal ground control point. The certifications for the NAMRIA reference points are found in Annex 2 and the baseline processing report for CG-258 is found in Annex 3. These were used as base stations during flight operations for the entire duration of the survey (November 30, 2015 and April 28 to May 6, 2016). Base stations were observed using dual frequency GPS receivers, TRIMBLE SPS 882 and SPS 852. Flight plans and location of base stations used during the aerial LiDAR acquisition in Baua floodplain are shown in Figure 2. The list of LiDAR acquisition team members are found in Annex 4.

Figure 4 to Figure 6 show the recovered NAMRIA reference points within the area. In addition, Table 3 to

Table 5 show the details about the following NAMRIA control stations, while Table 6 shows the list of all ground control points occupied during the acquisition together with the corresponding dates of utilization.



(b)

Two (2) meters from the south corner of the triangular island at the intersection of the national highway and the road to Port Irene in Santa Ana, Cagayan, and CGY-102 (b) as recovered by the field team.

Table 3. Details of the recovered NAMRIA horizontal control point CGY-102 used as base station for the LiDAR acquisition.

Station Name	CGY-102	
Order of Accuracy	2 nd	
Relative Error (horizontal positioning)	1 in 50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude	18°22'15.98573" North
	Longitude	122°6'41.74346" East
	Ellipsoidal Height	22.60800 meters
Grid Coordinates, Philippine Transverse Mercator Zone 5 (PTM Zone 5 PRS 92)	Easting	617476.569 meters
	Northing	2032192.366 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude	18°22'9.81367" North
	Longitude	122°6'46.31361" East
	Ellipsoidal Height	57.19500 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting	406145.45 meters
	Northing	203135134 meters




Figure 5. GPS set-up over CGY-92 located inside the Lal-lo National High School, about five (5) meters west of the flagpole (a), and CGY-92 (b) as recovered by the field team.

Table 4. Details of the recovered NAMRIA horizontal control point CGY-92 used as base station for the LiDAR acquisition.

Station Name	CGY-92	
Order of Accuracy	2nd	
Relative Error (horizontal positioning)	1 in 50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude Longitude Ellipsoidal Height	18° 12' 11.42361" North 121° 39' 42.14392" East 14.47400 meters
Grid Coordinates, Philippine Transverse Mercator Zone 3 (PTM Zone 5 PRS 92)	Easting Northing	569996.115 meters 2013373.807 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude Longitude Ellipsoidal Height	18° 12' 5.25321" North 121° 39' 46.73084" East 48.54000 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North (UTM 51N PRS 1992)	Easting Northing	358475.41 meters 2013059.26 meters




Figure 6. GPS set-up over CG-258 located along the national road and about 200 meters northeast of kilometer post no. 608 in Gonzaga, Cagayan (a) and NAMRIA benchmark CG-258 (b) as recovered by the field team.

Table 5. Details of point CG-258 used as vertical reference point and established base station for the LiDAR acquisition.

Station Name	CG-258	
Order of Accuracy	2 nd	
Elevation	6.5266 +/- 0.0455 meters	
Relative Error (horizontal positioning)	1:50,000	
Geographic Coordinates, Philippine Reference of 1992 Datum (PRS 92)	Latitude	18°17'21.328997" North
	Longitude	122°01'21.83970" East
	Ellipsoidal Height	12.774 meters
Geographic Coordinates, World Geodetic System 1984 Datum (WGS 84)	Latitude	18°17'15.16762" North
	Longitude	122°01'26.41723" East
	Ellipsoidal Height	47.419 meters
Grid Coordinates, Universal Transverse Mercator Zone 51 North UTM 51N PRS 92)	Easting	396708.418 meters
	Northing	2022343.154 meters

Table 6. Ground control used during LiDAR data acquisition

Date Surveyed	Flight Number	Mission Name	Ground Control Points
November 30, 2015	2916P	1BLK21AB323A	CGY-102, CGY-92
April 28, 2016	3971G	2BLK3CAG2MQR119A	CGY-102, CG-258
May 3, 2016	3991G	2BLK3CAG2MSQS124B	CGY-102, CG-258
May 6, 2016	4001G	2BLK3CAG2MRS127A	CGY-102, CG-258

2.3 Flight Missions

Four (4) missions were conducted to complete the LiDAR data acquisition in Baua floodplain, for a total of 13 hours and ten minutes (13+10) of flying time for RP-C9122 and RP-C9022. All missions were acquired using the Pegasus and Gemini LiDAR systems. Table 7 shows the total area of actual coverage and the corresponding flying hours per mission, while Table 8 presents the actual parameters used during the LiDAR data acquisition.

Table 7. Flight missions for LiDAR data acquisition in Baua Floodplain

Date Surveyed	Flight Number	Flight Plan Area (km ²)	Surveyed Area (km ²)	Area Surveyed within the Floodplain (km ²)	Area Surveyed outside the Floodplain (km ²)	No. of Images (Frames)	Flying Hours	
							Hr	Min
November 30, 2015	2916P	229.33	111.30	19.29	92.01	-	2	29
April 28, 2016	3971G	401.86	162.97	23.53	139.44	-	4	15
May 3, 2016	3991G	401.86	121.82	24.69	97.13	-	2	26
May 6, 2016	4001G	401.86	127.08	0.54	126.54	-	4	00
TOTAL		631.19	523.17	68.05	455.12	-	13	10

Table 8. Actual parameters used during LiDAR data acquisition

Flight Number	Flying Height (m AGL)	Overlap (%)	FOV (θ)	PRF (kHz)	Scan Frequency (Hz)	Average Speed (kts)	Average Turn Time (Minutes)
2916P	900	30	50	200	30	130	5
3971G	850	30	50	125	50	130	5
3991G	800	30	50	125	50	130	5
4001G	800	30	50	125	50	130	5

2.4. Survey Coverage

Baua floodplain is located in the province of Cagayan. The survey covered the municipalities of Santa Ana and Gonzaga. The details of the survey coverage in these municipalities are shown in Table 9. The actual coverage of the LiDAR acquisition for Baua Floodplain is presented in Figure 7.

Table 9. List of municipalities and cities surveyed during Baua floodplain LiDAR survey.

Province	Municipality/City	Area of Municipality/City (km ²)	Total Area Surveyed (km ²)	Percentage of Area Surveyed
Cagayan	Santa Ana	437.13	167.47	38.31%
	Gonzaga	497.62	175.18	35.20%
	Total	934.75	342.65	36.66%




Figure 7. Actual LiDAR survey coverage for Baula Floodplain.

CHAPTER 3: LIDAR DATA PROCESSING OF THE BAUA FLOODPLAIN

Engr. Ma. Rosario Concepcion O. Ang, Engr. John Louie D. Fabila, Engr. Sarah Jane D. Samalbuero, Engr. Joida F. Prieto, Engr. Edgardo V. Gubatanga Jr., Engr. Analyn M. Naldo, Engr. Mark Joshua A. Salvacion, Maria Tamsyn C. Malabanan, Engr. Don Matthew B. Banatin, Engr. Sheila-Maye F. Santillan

The methods applied in this Chapter were based on the DREAM methods manual (Ang, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

3.1 Overview of the LIDAR Data Pre-Processing

The data transmitted by the Data Acquisition Component are checked for completeness based on the list of raw files required to proceed with the pre-processing of the LiDAR data. Upon acceptance of the LiDAR field data, georeferencing of the flight trajectory is done in order to obtain the exact location of the LiDAR sensor when the laser was shot. Point cloud georectification is performed to incorporate correct position and orientation for each point acquired. The georectified LiDAR point clouds are subject for quality checking to ensure that the required accuracies of the program, which are the minimum point density, vertical and horizontal accuracies, are met. The point clouds are then classified into various classes before generating Digital Elevation Models such as Digital Terrain Model and Digital Surface Model.

Using the elevation of points gathered in the field, the LiDAR-derived digital models are calibrated. Portions of the river that are barely penetrated by the LiDAR system are replaced by the actual river geometry measured from the field by the Data Validation and Bathymetry Component. LiDAR acquired temporally are then mosaicked to completely cover the target river systems in the Philippines. Orthorectification of images acquired simultaneously with the LiDAR data is done through the help of the georectified point clouds and the metadata containing the time the image was captured.

These processes are summarized in the flowchart shown in Figure 8.




Figure 8. Schematic Diagram for Data Pre-Processing Component

3.2 Transmittal of Acquired LiDAR Data

Data transfer sheets for all the LiDAR missions for Baua floodplain can be found in Annex 5. Missions flown during the first survey conducted on September 2015 used the Airborne LiDAR Terrain Mapper (ALTM™ Optech Inc.) Gemini and Pegasus systems while missions acquired during the second survey on June 2016 were flown using the Gemini system over Gonzaga, Cagayan.

The Data Acquisition Component (DAC) transferred a total of 57.55 Gigabytes of Range data, 7.90 Gigabytes of POS data, 130.83 Megabytes of GPS base station data, and 17.9 Gigabytes of raw image data to the data server on September 22, 2015 for the first survey and June 21, 2016 for the second survey. The Data Pre-processing Component (DPPC) verified the completeness of the transferred data. The whole dataset for Baua was fully transferred on June 21, 2016, as indicated on the Data Transfer Sheets for Baua floodplain.

3.3 Trajectory Computation

The Smoothed Performance Metrics of the computed trajectory for flight 3991G, one of the Baua flights, which is the North, East, and Down position RMSE values are shown in Figure 9. The x-axis corresponds to the time of flight, which is measured by the number of seconds from the midnight of the start of the GPS week, which on that week fell on May 03, 2016 00:00AM. The y-axis is the RMSE value for that particular position.




Figure 9. Smoothed Performance Metrics of Baua Flight 3991G.

The time of flight was from 195500 seconds to 200500 seconds, which corresponds to afternoon of May 03, 2016. The initial spike that is seen on the data corresponds to the time that the aircraft was getting into position to start the acquisition, and the POS system starts computing for the position and orientation of the aircraft.

Redundant measurements from the POS system quickly minimized the RMSE value of the positions. The periodic increase in RMSE values from an otherwise smoothly curving RMSE values correspond to the turn-around period of the aircraft, when the aircraft makes a turn to start a new flight line. Figure 9 shows that the North position RMSE peaks at 2.50 centimeters, the East position RMSE peaks at 1.70 centimeters, and the Down position RMSE peaks at 2.40 centimeters, which are within the prescribed accuracies described in the methodology.




Figure 10. Solution Status Parameters of Baua Flight 3991G.

The Solution Status parameters of flight 3991G, one of the Baua flights, which are the number of GPS satellites, Positional Dilution of Precision (PDOP), and the GPS processing mode used, are shown in Figure 10. The graphs indicate that the number of satellites during the acquisition did not go down to 6. Majority of the time, the number of satellites tracked was between 6 and 10. The PDOP value also did not go above the value of 3, which indicates optimal GPS geometry. The processing mode stayed at the value of 1 for majority of the survey with some peaks up to 2 attributed to the turns performed by the aircraft. The value of 0 corresponds to a Fixed, Narrow-Lane mode, which is the optimum carrier-cycle integer ambiguity resolution technique available for POSPAC MMS. All of the parameters adhered to the accuracy requirements for optimal trajectory solutions, as indicated in the methodology. The computed best estimated trajectory for all Baua flights is shown in Figure 11.




Figure 11. Best Estimated Trajectory for Baua Floodplain.

3.4 LiDAR Point Cloud Computation

The produced LAS data contains 46 flight lines, with each flight line containing one or two channels, since the Gemini system contains one channel and the Pegasus system contains two channels. The summary of the self-calibration results obtained from LiDAR processing in LiDAR Mapping Suite (LMS) software for all flights over Baua floodplain are given in Table 10.

Table 10. Self-Calibration Results values for Baua flights.

Parameter		Computed Value
Boresight Correction stdev	(<0.001degrees)	0.000876
IMU Attitude Correction Roll and Pitch Corrections stdev	(<0.001degrees)	0.015089
GPS Position Z-correction stdev	(<0.01meters)	0.0024

The optimum accuracy is obtained for all Baua flights based on the computed standard deviations of the corrections of the orientation parameters. Standard deviation values for individual blocks are available in Annex 8: Mission Summary Reports.

3.5 LiDAR Data Quality Checking

The boundary of the processed LiDAR data on top of a SAR Elevation Data over Baua Floodplain is shown in Figure 12. The map shows gaps in the LiDAR coverage that are attributed to cloud coverage.




Figure 12. Boundary of the processed LiDAR data over Baua Floodplain

The total area covered by the Baua missions is 217.07 sq.km that is comprised of four (4) flight acquisitions grouped and merged into two (2) blocks as shown in Table 11.

Table 11. List of LiDAR blocks for Baua Floodplain.

LiDAR Blocks	Flight Numbers	Area (sq.km)
Cagayan_reflights_Bl3A	3971G	108.73
	3991G	
	4001G	
Cagayan_reflights_Tuegarao_Bl3A	2916P	108.34
TOTAL		217.07 sq.km

The overlap data for the merged LiDAR blocks, showing the number of channels that pass through a particular location is shown in Figure 13. Since the Gemini system employs one channel and the Pegasus system employs two channels, we would expect an average value of 1 (blue) for Gemini and 2 for Pegasus for areas where there is limited overlap, and a value of 2 (yellow) or more (red) for Gemini and 3 for Pegasus for areas with three or more overlapping flight lines.




Figure 13. Image of data overlap for Baua Floodplain.

The overlap statistics per block for the Baua floodplain can be found in Annex B-1. One pixel corresponds to 25.0 square meters on the ground. For this area, the minimum and maximum percent overlaps are 30.46% and 42.36% respectively, which passed the 25% requirement.

The pulse density map for the merged LiDAR data, with the red parts showing the portions of the data that satisfy the 2 points per square meter criterion is shown in Figure 14. It was determined that all LiDAR data for Baua floodplain satisfy the point density requirement, and the average density for the entire survey area is 3.28 points per square meter.




Figure 14. Pulse density map of merged LiDAR data for Baua Floodplain.

The elevation difference between overlaps of adjacent flight lines is shown in Figure 15. The default color range is from blue to red, where bright blue areas correspond to portions where elevations of a previous flight line, identified by its acquisition time, are higher by more than 0.20m relative to elevations of its adjacent flight line. Bright red areas indicate portions where elevations of a previous flight line are lower by more than 0.20m relative to elevations of its adjacent flight line. Areas with bright red or bright blue need to be investigated further using Quick Terrain Modeler software.




Figure 15. Elevation difference map between flight lines for Baua Floodplain.

A screen capture of the processed LAS data from a Baua flight 3991G loaded in QT Modeler is shown in Figure 16. The upper left image shows the elevations of the points from two overlapping flight strips traversed by the profile, illustrated by a dashed red line. The x-axis corresponds to the length of the profile. It is evident that there are differences in elevation, but the differences do not exceed the 20-centimeter mark. This profiling was repeated until the quality of the LiDAR data becomes satisfactory. No reprocessing was done for this LiDAR dataset.




Figure 16. Quality checking for Baua Flight 3991G using the Profile Tool of QT Modeler.

3.6 LiDAR Point Cloud Classification and Rasterization

Table 12. Baua classification results in TerraScan.

Pertinent Class	Total Number of Points
Ground	179,691,005
Low Vegetation	147,015,389
Medium Vegetation	332,562,577
High Vegetation	409,934,706
Building	14,197,860

The tile system that TerraScan employed for the LiDAR data and the final classification image for a block in Baua floodplain is shown in Figure 17. A total of 294 1km by 1km tiles were produced. The number of points classified to the pertinent categories is illustrated in Table 12. The point cloud has a maximum and minimum height of 677.25 meters and 38.95 meters respectively.




Figure 17. Tiles for Baua Floodplain (a) and classification results (b) in TerraScan.

An isometric view of an area before and after running the classification routines is shown in Figure 18. The ground points are in orange, the vegetation is in different shades of green, and the buildings are in cyan. It can be seen that residential structures adjacent or even below canopy are classified correctly, due to the density of the LiDAR data.




Figure 18. Point cloud before (a) and after (b) classification.

The production of last return (V_ASCII) and the secondary (T_ASCII) DTM, first (S_ASCII) and last (D_ASCII) return DSM of the area in top view display are shown in Figure 19. It shows that DTMs are the representation of the bare earth while on the DSMs, all features are present such as buildings and vegetation.




Figure 19. The production of last return DSM (a) and DTM (b), first return DSM (c) and secondary DTM (d) in some portion of Baua Floodplain.

3.7 LiDAR Image Processing and Orthophotograph Rectification

The 114 1km by 1km tiles area covered by Baua floodplain is shown in Figure 20. After tie point selection to fix photo misalignments, color points were added to smoothen out visual inconsistencies along the seamlines where photos overlap. The Baua floodplain has a total of 85.78 sq.km orthophotograph coverage comprised of 216 images. A zoomed in version of sample orthophotographs named in reference to its tile number is shown in Figure 21.




Figure 20. Baua Floodplain with available orthophotographs.




Figure 21. Sample orthophotograph tiles for Baua Floodplain.

3.8 DEM Editing and Hydro-Correction

Two (2) mission blocks were processed for Baua flood plain. These blocks are composed of Cagayan reflights and Cagayan reflights Tugegarao blocks with a total area of 217.07 square kilometers. Table 13 shows the name and corresponding area of each block in square kilometers.

Table 13. LiDAR blocks with its corresponding area

LiDAR Blocks	Area (sq.km)
Cagayan_reflights_Bl3A	108.73
Cagayan_reflights_Tugegarao_Bl3A	108.34
TOTAL	217.07 sq.km

Portions of DTM before and after manual editing are shown in Figure 22. The bridge (Figure 22a) is also considered to be an impedance to the flow of water along the river and has to be removed (Figure 22b) in order to hydrologically correct the river. An interpolated base of a mountain (Figure 22c) was retrieved (Figure 22d) in order to hydrologically correct the surrounding river system. Another example is an interpolated ridge (Figure 22e) has to be retrieved using object retrieval to achieve the actual surface (Figure 22f). Another example is a building that is still present in the DTM after classification (Figure 22g) and has to be removed through manual editing (Figure 22h).




Figure 22. Portions in the DTM of Baua Floodplain – a bridge before (a) and after (b) manual editing; a mountain base before (c) and after object retrieval (d); interpolated ridge before (e) and after (f) object retrieval; and a building before (g) and after (h) manual editing.

3.9 Mosaicking of Blocks

No assumed reference block was used in mosaicking because the identified reference for shifting was an existing Aunugay DEM which was calibrated using Cagayan DEM overlapping with the blocks to be mosaicked. Table 14 shows the shift values applied to each LiDAR block during mosaicking.

Mosaicked LiDAR DTM for Baua floodplain is shown in Figure 23. It can be seen that the entire Baua floodplain is 100% covered by LiDAR data.

Table 14. Shift Values of each LiDAR Block of Baua Floodplain.

Mission Blocks	Shift Values (meters)		
	x	y	z
Cagayan_reflights_Bl3A	6.32	1.18	-4.72
Cagayan_reflights_Tugegarao_Bl3A	5.69	-0.32	-4.95




Figure 23. Map of Processed LiDAR Data for Baua Floodplain.

3.10 Calibration and Validation of Mosaicked LiDAR Digital Elevation Model

The extent of the validation survey done by the Data Validation and Bathymetry Component (DVBC) in Cagayan to collect points with which the LiDAR dataset is validated is shown in Figure 24. A total of 6,209 survey points were gathered for all the floodplains within Cagayan wherein the Baua is located. However, the point dataset was not used for the calibration of the LiDAR data for Baua because during the mosaicking process, each LiDAR block was referred to the calibrated Cagayan DEM. Therefore, the mosaicked DEM of Baua can already be considered as a calibrated DEM.

A good correlation between the uncalibrated Cagayan LiDAR DTM and ground survey elevation values is shown in Figure 25. Statistical values were computed from extracted LiDAR values using the selected points

to assess the quality of data and obtain the value for vertical adjustment. The computed height difference between the LiDAR DTM and calibration points is 4.07 meters with a standard deviation of 0.14 meters. Calibration of Cagayan LiDAR data was done by subtracting the height difference value, 4.07 meters, to Cagayan mosaicked LiDAR data. Table 15 shows the statistical values of the compared elevation values between Cagayan LiDAR data and calibration data. These values were also applicable to the Baua DEM.




Figure 24. Map of Baua Floodplain with validation survey points in green.




Figure 25. Correlation plot between calibration survey points and LiDAR data.

Table 15. Calibration Statistical Measures.

Calibration Statistical Measures	Value (meters)
Height Difference	4.07
Standard Deviation	0.14
Average	-4.07
Minimum	-4.50
Maximum	-3.77

The remaining 20% of the total survey points, resulting to 186 points, were used for the validation of calibrated Baua DTM. The good correlation between the calibrated mosaicked LiDAR elevation values and the ground survey elevation, which reflects the quality of the LiDAR DTM is shown in Figure 26. The computed RMSE between the calibrated LiDAR DTM and validation elevation values is 0.198 meters with a standard deviation of 0.07 meters, as shown in Table 16.




Figure 26. Correlation plot between validation survey points and LiDAR data.

Table 16. Validation Statistical Measures.

Validation Statistical Measures	Value (meters)
RMSE	0.48
Standard Deviation	0.09
Average	0.47
Minimum	0.14
Maximum	0.65

3.11 Integration of Bathymetric Data into the LiDAR Digital Terrain Model

For bathy integration, only zigzag data was available for Baua with 2,516 bathymetric survey points. The resulting raster surface produced was done by Inverse Distance Weighted (IDW) interpolation method. After burning the bathymetric data to the calibrated DTM, assessment of the interpolated surface is represented by the computed RMSE value of 0.07 meters. The extent of the bathymetric survey done by the Data Validation and Bathymetry Component (DVBC) in Baua integrated with the processed LiDAR DEM is shown in Figure 27.




Figure 27. Map of Baua Floodplain with bathymetric survey points shown in blue.

3.12 Feature Extraction

The features salient in flood hazard exposure analysis include buildings, road networks, bridges and water bodies within the floodplain area with 200 m buffer zone. Mosaicked LiDAR DEM with 1 m resolution was used to delineate footprints of building features, which consist of residential buildings, government offices, medical facilities, religious institutions, and commercial establishments, among others. Road networks comprise of main thoroughfares such as highways and municipal and barangay roads essential for routing of disaster response efforts. These features are represented by a network of road centerlines.

3.12.1 Quality Checking of Digitized Features' Boundary

Baua floodplain, including its 200 m buffer, has a total area of 51.78 sq km. For this area, a total of 5.0 sq km, corresponding to a total of 560 building features, are considered for QC. Figure 28 shows the QC blocks for Baua floodplain.




Figure 28. QC blocks for Baua building features.

Quality checking of Baua building features resulted in the ratings shown in Table 17.

Table 17. Quality Checking Ratings for Baua Building Features.

FLOODPLAIN	COMPLETENESS	CORRECTNESS	QUALITY	REMARKS
Baua	97.56	100	93.93	PASSED

3.12.2 Height Extraction

Height extraction was done for 3,043 building features in Baua floodplain. Of these building features, none was filtered out after height extraction, resulting to 3,043 buildings with height attributes. The lowest building height is at 2.86 m, while the highest building is at 12.87 m.

3.12.3 Feature Attribution

The digitized features were identified using participatory mapping. Stakeholders (preferably barangay officials) were invited in a forum and were given maps of their respective barangays. They attributed first non-residential buildings like barangay hall, schools, churches, commercial buildings, etc. then other building left were then coded as residential. An nDSM was generated using the LiDAR DEMs to extract the heights of the buildings. A minimum height of 2 meters was used to filter out the terrain features that were digitized as buildings. Buildings that were not yet constructed during the time of LiDAR acquisition were noted as new buildings in the attribute table.

Table 18 summarizes the number of building features per type. On the other hand, Table 19 shows the total length of each road type, while Table 20 shows the number of water features extracted per type.

Table 18. Building Features Extracted for Baua Floodplain.

Facility Type	No. of Features
Residential	2,918
School	77
Market	6
Agricultural/Agro-Industrial Facilities	0
Medical Institutions	0
Barangay Hall	5
Military Institution	0
Sports Center/Gymnasium/Covered Court	3
Telecommunication Facilities	0
Transport Terminal	0
Warehouse	0
Power Plant/Substation	0
NGO/CSO Offices	0
Police Station	0
Water Supply/Sewerage	0
Religious Institutions	19
Bank	0
Factory	0
Gas Station	8
Fire Station	0
Other Government Offices	6
Other Commercial Establishments	1
Total	3,043

Table 19. Total Length of Extracted Roads for Baua Floodplain.

Floodplain	Road Network Length (km)					Total
	Barangay Road	City/Municipal Road	Provincial Road	National Road	Others	
Baua	41.08	0.00	5.11	7.96	43.32	97.49

Table 20. Number of Extracted Water Bodies for Baua Floodplain.

Floodplain	Water Body Type					Total
	Rivers/Streams	Lakes/Ponds	Sea	Dam	Fish Pen	
Baua	7	0	0	0	0	7

A total of 12 bridges and culverts over small channels that are part of the river network were also extracted for the floodplain.

3.12.4 Final Quality Checking of Extracted Features

All extracted ground features were completely given the required attributes. All these output features comprise the flood hazard exposure database for the floodplain. This completes the feature extraction phase of the project.

Figure 29 shows the Digital Surface Model (DSM) of Baua floodplain overlaid with its ground features.




Figure 29. Extracted features for Baua Floodplain.

CHAPTER 4: LIDAR VALIDATION SURVEY AND MEASUREMENTS OF BAUA RIVER BASIN

Engr. Louie P. Balicanta, Engr. Joemarie S. Caballero, Ms. Patrizia Mae. P. dela Cruz, Engr. Kristine Ailene B. Borromeo, Ms. Jeline M. Amante, Marie Angeliq R. Estipona, Charie Mae V. Manliguez, Engr. Janina Jupiter, Vie Marie Paola M. Rivera

The methods applied in this Chapter were based on the DREAM methods manual (Balicanta, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

4.1 Summary of Activities

H.O. Noveloso Surveying (HONS) conducted a field survey in Baua River on Jan. 20-21, 2017, on Jan 23, 2017, on Jan. 30, 2017, on Feb. 4, 2017, on Feb. 6, 2017, on Feb. 11, 2017, on Feb. 14, 2017, and on Feb. 23 to 26, 2017 with the following scope: reconnaissance; control survey; cross-section and as-built survey of Baua Bridge in Brgy. Baua, Gonzaga, Cagayan; and bathymetric survey of the river from the upstream in Brgy. Amunitan to the mouth of the river in Brgy. Baua, Gonzaga, Cagayan with an approximate length of 15.62 km. Random checking points for the contractor's cross-section and bathymetry data were gathered by DVBC on October 11-22, 2016 using an Ohmex™ Single Beam Echo Sounder and Trimble® SPS 985 GNSS PPK survey technique. In addition to this, validation points acquisition survey was conducted covering the Baua River Basin area. The entire survey extent is illustrated in Figure 30.




Figure 30. Buaa River Survey Extent

4.2 Control Survey

The GNSS network used for Baua River is composed of two (2) networks. The 1st session is composed of two (2) loops established on October 12, 2016 occupying the following reference point: PAT-2, a DREAM-DVC established point last November 13-20, 2014, in Brgy. Pateng, Gonzaga, Cagayan.

Two (2) NAMRIA established control points, CGY-101, a second-order GCP in Brgy. Magrafil, Gonzaga, Cagayan and CG-258, a first-order BM in Brgy. Tapel, Gonzaga, Cagayan were used as markers along with one (1) established point in the area: UP-BAU-1 in Brgy. Baua, Gonzaga, Cagayan.

The 2nd session is also composed of two (2) loops established on October 13, 2016 occupying the following reference points: CGY-101 and UP-BAU-1.

Two (2) NAMRIA established control points, CGY-102, a second-order GCP in Brgy. San Jose, Gonzaga, Cagayan and CG-234, a first-order BM in Brgy. Diora-Zinungan, Sta. Ana, Cagayan were used as markers.

The summary of reference and control points and its location is summarized in Table 21 while the GNSS network established is illustrated in Figure 31.




Figure 31. GNSS Network covering Buaa River

Table 21. List of reference and control points used in Baua River Basin survey
(Source: NAMRIA, UP-TCAGP)

Control Point	Order of Accuracy	Geographic Coordinates (WGS 84)				Date of Establishment
		Latitude	Longitude	Ellipsoid Height (m)	Elevation (MSL) (m)	
1 st session						
PAT-2	Established	18°15'20.41664"N	121°59'13.60140"E	-	21.505	2014
CGY-101	Used as marker	-	-	-	-	2007
CG-258	Used as marker	-	-	-	-	2007

The GNSS set-ups on recovered reference points and established control points in Baua River are shown from Figure 32 to Figure 37.




Figure 32. GNSS base set up, Trimble® SPS 885, at PAT-2, located at the approach of Pateng Bridge in Brgy. Pateng, Gonzaga, Cagayan




Figure 33. GNSS receiver set up, Trimble® SPS 885, at CGY-101, located at the side of the basketball court in Brgy. Magrafil, Gonzaga, Cagayan



Figure 34. GNSS receiver set up, Trimble® SPS 985, at CG-258, located at the approach of the bridge near the welcome arch of Brgy. Tapel, Gonzaga, Cagayan



Figure 35. GNSS receiver set up, Trimble® SPS 885, at UP-BAU-1, located at the approach of Baula Bridge in Brgy. Baula, Gonzaga, Cagayan



Figure 36. GNSS receiver set-up, Trimble® SPS 885, at CGY-102, located at the center island in front of the barangay marker of Brgy. Casambalangan in Brgy. San Jose, Gonzaga, Cagayan



Figure 37. GNSS receiver set-up, Trimble® SPS 885, at CG-234, located at the approach of Diara Bridge in Brgy. Diara-Zinungan, Sta. Ana, Cagayan

4.3 Baseline Processing

GNSS Baselines were processed simultaneously in TBC by observing that all baselines have fixed solutions with horizontal and vertical precisions within +/- 20 cm and +/- 10 cm requirement, respectively. In case where one or more baselines did not meet all of these criteria, masking is performed. Masking is done by removing/masking portions of these baseline data using the same processing software. It is repeatedly processed until all baseline requirements are met. If the reiteration yields out of the required accuracy, resurvey is initiated. Baseline processing result of control points in Baua River Basin is summarized in Table 22 and Table 23 generated by TBC software.

Table 22. 1st Session Baseline Processing Report for Baua River Static Survey
(Source: NAMRIA, UP-TCAGP)

Observation	Date of Observation	Solution Type	H. Prec. (Meter)	V. Prec. (Meter)	Geodetic Az.	Ellipsoid Dist. (Meter)	Height (m)
CGY-101 --- CG-258	10-12-2016	Fixed	0.003	0.017	68°41'13"	4298.952	39.432
CGY-101--- PAT-2	10-12-2016	Fixed	0.004	0.036	57°12'53"	9404.155	23.252
CG-258--- PAT-2	10-12-2016	Fixed	0.004	0.020	47°52'13"	5260.711	-16.180
UP-BAU-1 --- CGY-101	10-12-2016	Fixed	0.003	0.015	31°30'31"	6423.441	-36.889
UP-BAU-1 --- CG-258	10-12-2016	Fixed	0.004	0.028	226°18'00"	10185.210	-2.561
UP-BAU-1 --- CGY-101	10-12-2016	Fixed	0.006	0.034	31°30'32"	6423.433	-36.919

Table 23. 2nd Session Baseline Processing Report for Buaa River Static Survey
(Source: NAMRIA, UP-TCAGP)

Observation	Date of Observation	Solution Type	H. Prec. (Meter)	V. Prec. (Meter)	Geodetic Az.	Ellipsoid Dist. (Meter)	Height (m)
UP-BAU-1 --- CGY-101	10-13-2016	Fixed	0.003	0.015	211°31'07"	6423.441	36.890
CGY-102--- CGY-101	10-13-2016	Fixed	0.005	0.033	35°41'58"	9232.606	-29.695
CG-234--- CGY-102	10-13-2016	Fixed	0.003	0.017	13°22'55"	7169.699	-12.718
CGY-102 --- UP-BAU-1	10-13-2016	Fixed	0.003	0.021	45°08'22"	2865.049	7.194
UP-BAU-1 --- CGY-101	10-13-2016	Fixed	0.006	0.035	211°31'07"	6423.432	36.915
CG-234 --- UP- BAU-1	10-13-2016	Fixed	0.005	0.029	22°17'57"	9723.343	-5.507

As shown Table 22 and Table 23, a total of twelve (12) baselines were processed with coordinate and elevation values of PAT-2 held fixed for the 1st session and the coordinate and elevation values of CGY-101 and UP-BAU-1 held fixed for the 2nd session. All of them passed the required accuracy.

4.4 Network Adjustment

After the baseline processing procedure, network adjustment is performed using TBC. Looking at the Adjusted Grid Coordinates table of the TBC generated Network Adjustment Report, it is observed that the square root of the sum of the squares of x and y must be less than 20 cm and z less than 10 cm or in equation form:

$$\sqrt{(x_e)^2 + (y_e)^2} < 20cm \text{ and } z_e < 10 cm$$

Where:

- x_e is the Easting Error,
- y_e is the Northing Error, and
- z_e is the Elevation Error

for each control point. See the Network Adjustment Report shown in Table 24 to Table 29 for the complete details.

The four (4) control points, PAT-2, CGY-101, CG-258, and UP-BAU-1, were occupied and observed simultaneously to form a GNSS loop for the 1st session and the four (4) control points, CGY-101, UP-BAU-1, CGY-102, and CG-234, were also occupied and observed simultaneously to form a GNSS loop for the 2nd session. The coordinate and elevation values of PAT-2 held fixed for the 1st session and the coordinate and elevation values of CGY-101 and UP-BAU-1 held fixed for the 2nd session are presented in Table 24 and Table 25, respectively. Through this reference point, the coordinates and elevations of the unknown control points will be computed.

Table 24. 1st Session Control Point Constraints

Point ID	Type	East σ (Meter)	North σ (Meter)	Height σ (Meter)	Elevation σ (Meter)
PAT-2	Grid				Fixed
PAT-2	Global	Fixed	Fixed		
Fixed = 0.000001(Meter)					

Table 25. 2nd Session Control Point Constraints

Point ID	Type	East σ (Meter)	North σ (Meter)	Height σ (Meter)	Elevation σ (Meter)
CGY-101	Grid				Fixed
CGY-101	Global	Fixed	Fixed		
UP-BAU-1 Grid Fixed					
UP-BAU-1	Global	Fixed	Fixed		
Fixed = 0.000001(Meter)					

The list of adjusted grid coordinates, i.e. Northing, Easting, Elevation and computed standard errors of the control points in the network is indicated in Table 26 and Table 27.

Table 26. 1st Session Adjusted Grid Coordinates

Point ID	Easting (Meter)	Easting Error (Meter)	Northing (Meter)	Northing Error (Meter)	Elevation (Meter)	Elevation Error (Meter)	Constraint
CG-258	396844.016	0.009	2022275.238	0.007	5.558	0.070	
CGY-101	400856.162	0.009	2023815.895	0.007	45.099	0.081	
PAT-2	392924.044	?	2018768.902	?	21.505	?	LLe
UP-BAU-1	404240.430	0.011	2029273.374	0.009	8.626	0.090	

With the mentioned equation, $\sqrt{((x_e)^2 + (y_e)^2)} < 20\text{cm}$ and $z_e < 10\text{ cm}$ for horizontal and for the vertical, respectively; the computation for the accuracy are as follows:

a. CG-258

$$\begin{aligned} \text{horizontal accuracy} &= \sqrt{(0.9)^2 + (0.7)^2} \\ &= \sqrt{0.81 + 0.49} \\ &= 1.14 < 20 \text{ cm} \\ \text{vertical accuracy} &= 7.0 < 10 \text{ cm} \end{aligned}$$

b. CGY-101

$$\begin{aligned} \text{horizontal accuracy} &= \sqrt{(0.9)^2 + (0.7)^2} \\ &= \sqrt{0.81 + 0.49} \\ &= 1.14 < 20 \text{ cm} \\ \text{vertical accuracy} &= 8.1 < 10 \text{ cm} \end{aligned}$$

c. PAT-2

$$\begin{aligned} \text{horizontal accuracy} &= \text{Fixed} \\ \text{vertical accuracy} &= \text{Fixed} \end{aligned}$$

d. UP-BAU-1

$$\begin{aligned} \text{horizontal accuracy} &= \sqrt{(1.1)^2 + (0.9)^2} \\ &= \sqrt{1.21 + 0.81} \\ &= 1.42 < 20 \text{ cm} \\ \text{vertical accuracy} &= 9.0 < 10 \text{ cm} \end{aligned}$$

Table 27. 2nd Session Adjusted Grid Coordinates

Point ID	Easting (Meter)	Easting Error (Meter)	Northing (Meter)	Northing Error (Meter)	Elevation (Meter)	Elevation Error (Meter)	Constraint
CG-234	407973.653	0.011	2038248.421	0.009	3.769	0.051	
CGY-101	400856.162	?	2023815.895	?	45.099	?	LLe
CGY-102	406280.704	0.007	2031283.618	0.005	15.970	0.043	
UP-BAU-1	404240.430	?	2029273.374	?	8.626	?	LLe

With the mentioned equation, for horizontal and for the vertical; the computation for the accuracy are as follows:

a. CG-234

$$\begin{aligned} \text{horizontal accuracy} &= \sqrt{(1.1)^2 + (0.9)^2} \\ &= \sqrt{1.21 + 0.81} \\ &= 1.42 < 20 \text{ cm} \\ \text{vertical accuracy} &= 5.1 < 10 \text{ cm} \end{aligned}$$

b. CGY-101

horizontal accuracy = Fixed

vertical accuracy = Fixed

c. CGY-102

$$\begin{aligned} \text{horizontal accuracy} &= \sqrt{(0.7)^2 + (0.5)^2} \\ &= \sqrt{0.49 + 0.25} \\ &= 0.86 < 20 \text{ cm} \end{aligned}$$

$$\text{vertical accuracy} = 4.3 < 10 \text{ cm}$$

d. UP-BAU-1

horizontal accuracy = Fixed

vertical accuracy = Fixed

Following the given formula, the horizontal and vertical accuracy result of the three (3) occupied control points for the 1st session and two (2) occupied control points for the 2nd session are within the required precision.

Table 28. 1st Session Adjusted Geodetic Coordinates

Point ID	Latitude	Longitude	Height (Meter)	Height Error (Meter)	Constraint
CG-258	N18°17'15.18320"	E122°01'26.44115"	43.357	0.070	
CGY-101	N18°18'05.99072"	E122°03'42.81396"	82.793	0.081	
PAT-2	N18°15'20.41664"	E121°59'13.60140"	59.538	?	LLe
UP-BAU-1	N18°21'04.10030"	E122°05'37.15852"	45.903	0.090	

Table 29. 2nd Session Adjusted Geodetic Coordinates

Point ID	Latitude	Longitude	Height (Meter)	Height Error (Meter)	Constraint
CG-234	N18°25'56.68760"	E122°07'42.88310"	40.384	0.051	
CGY-101	N18°18'05.99072"	E122°03'42.81396"	82.793	?	LLe
CGY-102	N18°22'09.82860"	E122°06'46.33709"	53.100	0.043	
UP-BAU-1	N18°21'04.10030"	E122°05'37.15852"	45.903	?	LLe

The corresponding geodetic coordinates of the observed points are within the required accuracy as shown in Table 28 and Table 29. Based on the result of the computation, the equation is satisfied; hence, the required accuracy for the program was met.

The summary of reference control points used is indicated in Table 30.

Table 30. Reference and control points and its location (Source: NAMRIA, UP-ICAGP)

Control Point	Order of Accuracy	Geographic Coordinates (WGS 84)			UTM ZONE 51 N			
		Latitude	Longitude	Ellipsoidal Height (Meter)	Northing (m)	Easting (m)	BM Ortho (m)	
1 st session								
PAT-2	Established	18°15'20.41664"N	121°59'13.60140"E	62.912	2018768.902	392924.044	21.505	
CGY-101	Used as marker	18°18'05.99063"N	122°03'42.81382"E	86.168	2023815.893	400856.157	45.1	
CG-258	Used as marker	18°17'15.18313"N	122°01'26.44108"E	46.732	2022275.236	396844.013	5.559	
UP-BAU-1	Established	18°21'04.10012"N	122°05'37.15832"E	49.278	2029273.368	404240.424	8.627	
2 nd session								
CGY-101	1 st order, GCP	18°18'05.99063"N	122°03'42.81382"E	86.168	2023815.893	400856.157	45.1	
UP-BAU-1	Established	18°21'04.10012"N	122°05'37.15832"E	49.278	2029273.368	404240.424	8.627	
CGY-102	Used as marker	18°22'09.82839"N	122°06'46.33686"E	56.475	2031283.611	406280.697	15.971	
CG-234	Used as marker	18°25'56.68727"N	122°07'42.88284"E	43.759	2038248.411	407973.645	3.77	

4.5 Cross-section and Bridge As-Built Survey, and Water Level Marking

Cross-section and as-built surveys were conducted on February 11, 2017 at the downstream side of Baua Bridge in Brgy. Baua, Gonzaga, Cagayan as shown in Figure 38. A Sokkia™ Set CX Total Station was utilized for this survey as shown in Figure 39. The Automated Water Level System (AWLS) is located on the upstream side of the bridge and its elevation was measured 10.510 m above MSL.



Figure 38. Baua Bridge facing upstream



Figure 39. As-built survey of Baua Bridge

Gathering of random points for the checking of HONS's bridge cross-section and bridge points data was performed by DVBC on October 17, 2016 using a survey grade GNSS Rover receiver attached to a 2-m pole as seen in Figure 40.



Figure 40. Gathering of random cross-section points along Baua Bridge

Linear square correlation (R^2) and RMSE analysis were performed on the two (2) datasets. The linear square coefficient range is determined to ensure that the submitted data of the contractor is within the accuracy standard of the project which is ± 20 cm and ± 10 cm for horizontal and vertical, respectively. The R^2 value must be within 0.85 to 1. An R^2 approaching 1 signifies a strong correlation between the vertical (elevation values) of the two datasets. A computed R^2 value of 0.963 was obtained by comparing the data of the contractor and DVBC; signifying a strong correlation between the two (2) datasets.

In addition to the Linear Square correlation, Root Mean Square (RMSE) analysis is also performed in order to assess the difference in elevation between the DVBC checking points and the contractor's. The RMSE value should only have a maximum radial distance of 5 m and the difference in elevation within the radius of 5 meters should not be beyond 0.50 m. For the bridge cross-section data, a computed value of 0.365 was acquired while a computed value of 0.227 was computed for the bridge points data. The computed R^2 and RMSE values are within the accuracy requirement of the program.

The cross-sectional line of Baua Bridge is about 131 m with two hundred fifty-nine (259) cross-sectional points using the control points UP-BAU-1 and UP-BAU-2 as the GNSS base stations. The location map, cross-section diagram, and the bridge data form are shown in Figure 41 to Figure 43.




Figure 41. Location map of Baua Bridge cross-section survey




Figure 42. Baua Bridge Cross-section Diagram

BRIDGE DATA FORM

Bridge Name: Baua Bridge

River Name: Baua River

Location (Brgy., City, Region): Brgy. Baua, Gonzaga, Cagayan

Survey Team: Jesus De Tagle, Alfie Paras, Isidro Basco, Mardy Feria, Rogelio Itorma and Myton Obaña

Date and Time: February 11, 2017 @ 9:30 am

Flow Condition: Low Normal High

Weather Condition: Fair Rainy

Cross-sectional View (not to scale)

The diagram shows a cross-section of the bridge. From left to right: Bridge Approach BA1, Bridge Approach BA2, Abutment Ab1, Pier P, Pier P, Abutment Ab2, Bridge Approach BA3, and Bridge Approach BA4. The water level (WL) is shown between the two piers. The deck (D) is supported by the piers. The datum (MSL) is shown on the right. Red circles indicate measurement values. Labels include: BA = Bridge Approach, P = Pier, Ab = Abutment, D = Deck, WL = Water Level/Surface, MSL = Mean Sea Level, and a red circle = Measurement Value.

Legend:
 BA = Bridge Approach
 P = Pier
 Ab = Abutment
 D = Deck
 WL = Water Level/Surface
 MSL = Mean Sea Level
 ○ = Measurement Value

Line Segment	Measurement, m	Remarks
1. BA1-BA2	8.651 m.	Concrete
2. BA2-BA3	130.673 m.	Concrete
3. BA3-BA4	12.751 m.	Concrete
4. BA1-Ab1	19.425 m.	Concrete
5. Ab2-BA4	19.289 m.	Concrete
6. Deck/Beam thickness	0.519 m.	Steel Truss
7. Deck Elevation	9.593 m. MSL	Concrete

Note: Observer should be facing downstream

Figure 43. Baua Bridge Data Form

Water surface elevation of Baua River was determined by a Sokkia™ Set CX Total Station on February 11, 2017 at 9:30 AM at Baua Bridge area in Brgy. Baua, Gonzaga, Cagayan with a value of 0.072 m in MSL as shown in Figure 42. This was translated into marking on the bridge’s riprap as shown in Figure 44. The marking will serve as reference for flow data gathering and depth gauge deployment of the partner HEI responsible for Baua River, the Isabela State University.



Figure 44. Water level markings on the riprap of Baua Bridge

4.6 Validation Points Acquisition Survey

Validation points acquisition survey was conducted by DVBC on October 16, 2016 using a survey grade GNSS Rover receiver, Trimble® SPS 985, mounted on a range pole which was attached on the side of the vehicle as shown in Figure 45. It was secured with cable ties and ropes to ensure that it was horizontally and vertically balanced. The antenna height was 2.460 m and measured from the ground up to the bottom of the antenna mount of the GNSS Rover receiver. The PPK technique utilized for the conduct of the survey was set to continuous topo mode with CGY-102 occupied as the GNSS base station in the conduct of the survey.




Figure 45. Validation points acquisition survey set-up for Baua River

The survey started from Brgy. Pateng, Gonzaga, Cagayan going northeast along the national highway, covering eleven (11) barangays in Gonzaga, eight (8) barangays in Sta. Ana, and ended in Brgy. San Vicente, Sta. Ana, Cagayan. The survey gathered a total of 8,092 points with approximate length of 44.91 km using CGY-102 and PAT-2 as GNSS base stations for the entire extent of validation points acquisition survey as illustrated in the map in Figure 46.



Figure 46. LiDAR Validation points acquisition survey for Bua River Basin

4.7 Bathymetric Survey

Manual bathymetric survey was executed on February 23 to 26, 2017 using a Sokkia™ Set CX Total Station as illustrated in Figure 47. The control points UP-BAU-1, UP-BAU-3, UP-BAU-4, UP-BAU-5, UP-BAU-6, and UP-BAU-7 were used as GNSS base stations all throughout the entire survey.

For the main river, the survey started in Brgy. Amunitan, Gonzaga, Cagayan, with coordinates 18°16'27.8247"N, 122°06'49.0628"E and ended at the mouth of the river in Brgy. Baua, also in Gonzaga, with coordinates 18°21'24.0195"N, 122°05'05.1713"E.

For the tributary, the survey started in Brgy. Cabiraoan, Gonzaga, Cagayan, with coordinates 18°17'46.0715"N, 122°07'39.0679"E and ended also in Brgy. Cabiraoan, with coordinates 18°18'29.3917"N, 122°07'25.7885"E.




Figure 47. Manual bathymetric survey of HONS along Baua River

Gathering of random points for the checking of HONS's bathymetric data was performed by DVBC on October 14, 2016 using a survey grade GNSS Rover receiver attached to a boat as seen in Figure 48. The entire bathymetric survey extent of Baua River is illustrated in Figure 49. A map showing the DVBC bathymetric checking points is shown in Figure 50.



Figure 48. Gathering of random bathymetric points along Baua River

Linear square correlation (R^2) and RMSE analysis were also performed on the two (2) datasets and a computed R^2 value of 0.884 for the bathymetric data is within the required range for R^2 , which is 0.85 to 1. Additionally, an RMSE value of 0.291 for the bathymetric data was obtained. Both the computed R^2 and RMSE values are within the accuracy required by the program.

The bathymetric survey for Baua River gathered a total of 4,503 points covering 13.791 km of the river traversing barangays Amunitan, Cabiraoan, Sta. Maria, and Baua in the Municipality of Gonzaga.




Figure 49. Bathymetric survey of Baua River




Figure 50. Quality checking points gathered along Bua River by DVBC

A CAD drawing was also produced to illustrate the riverbed profile of Bua River. As shown in Figure 51 and Figure 52, the highest and lowest elevation has a 117-m difference. The highest elevation observed was 115.060 m above MSL located in Brgy. Amunitan, Gonzaga, Cagayan while the lowest was -2.434 m below MSL located in Brgy. Bua, Gonzaga, Cagayan.




Figure 51. Baua Riverbed Profile




Figure 52. Baua Riverbed Profile (tributary)

CHAPTER 5: FLOOD MODELING AND MAPPING

*Dr. Alfredo Mahar Lagmay, Christopher Uichanco, Sylvia Sueno, Marc Moises, Hale Ines,
Miguel del Rosario, Kenneth Punay, Neil Tingin, Mariel Monteclaro*

The methods applied in this Chapter were based on the DREAM methods manual (Lagmay, et al., 2014) and further enhanced and updated in Paringit, et al. (2017).

5.1 Data used in Hydrologic Modeling

5.1.1 Hydrometry and Rating Curves

All components and data that affect the hydrologic cycle of the Baua River Basin were monitored, collected, and analyzed. Rainfall, water level, and flow in a certain period of time, which may affect the hydrologic cycle of the Baua River Basin were monitored, collected, and analyzed.

5.1.2 Precipitation

Cagayan, including the Baua River basin, experienced heavy and long term rain such as Monsoon Rain during the month of December. The hydrologic data collection covered the period 2:00 P.M. on 27 December 2016 until 8:40 P.M. on 28 December 2016. Hydrologic data include the river velocity, water depth and rain collected from data logging sensors (mechanical velocity meter, depth gauge and rain gauges) in specific time period. Precipitation data was taken from the Brgy. San Jose, Cagayan ARG. The location of the rain gauge is seen in Figure 7. Rainfall data were downloaded from the web portal of Philippine E-Science Grid-ASTI (<http://fmon.asti.dost.gov.ph/weather/predict/>).

Total rain from the Brgy. San Jose, Cagayan ARG is 85 mm. It peaked to 2.5 mm. on 28 December 2016 2:00 A.M. The lag time between the peak rainfall and discharge is 16 hours and 30 minutes. The ARG for Baua River Basin is shown Figure 53.




Figure 53. Location map of Baula HEC-HMS model used for calibration.

5.1.3 Rating Curve and River Outflow

Monsoon rain that occurred on 27 December 2016 – 28 December 2016 contributed to a (-) 0.258 meter water level rise with peak discharge of 177.8 m³/s recorded at 9:10 AM on 28 December 2016 with accumulated rainfall 85 mm. These hydrologic data is the actual event of Baula River and inputted to hydrologic modeling. Hydrologic measurements were taken from Baula Bridge, Gonzaga, Cagayan.




Figure 54. Cross-Section Plot of Baua Bridge

A rating curve was generated for the observed flow and water level. It shows the relationship of the two hydrologic data. It is expressed in the form of the following equation:

$$Q = a^{nh}$$

where, Q : Discharge (m^3/s),
 h : Gauge height (reading from Baua Bridge depth gauge sensor), and
 a and n : Constants.

The Baua River Rating Curve measured at Baua Bridge is expressed as $Q = 73.115e^{3.4448x}$ (Figure 55).




Figure 55. Rating curve at Baua Bridge, Gonzaga, Cagayan

This rating curve equation was used to compute the river outflow at Baua Bridge for the calibration of the HEC-HMS model shown in Figure 56.




Figure 56. Rainfall and outflow data at Baua Bridge used for modeling

5.2 RIDF Station

The Philippine Atmospheric Geophysical and Astronomical Services Administration (PAGASA) computed for Rainfall Intensity Duration Frequency (RIDF) values for the Aparri Rain Gauge. The RIDF rainfall amount for 24 hours was converted to a synthetic storm by interpolating and re-arranging the values in such a way a certain peak value will be attained at a certain time. This station is chosen based on its proximity to the Baua watershed. The extreme values for this watershed were computed based on a 47-year record, shown in Table 31.

Table 31. RIDF values for Aparri Rain Gauge computed by PAGASA

COMPUTED EXTREME VALUES (in mm) OF PRECIPITATION									
T (yrs)	10 mins	20 mins	30 mins	1 hr	2 hrs	3 hrs	6 hrs	12 hrs	24 hrs
2	20.1	31.4	39.4	53.3	75.6	92.2	119.4	147.7	167.9
5	28.5	44.9	55.8	78.7	110.4	137	173.6	221.2	252.5
10	34.1	53.8	66.6	95.6	133.4	166.6	209.5	269.9	308.5
15	37.2	58.8	72.7	105.1	146.5	183.4	229.7	297.4	340.2
20	39.4	62.3	77	111.8	155.6	195.1	243.9	316.6	362.3
25	41.1	65	80.3	116.9	162.6	204.1	254.8	331.4	379.3
50	46.3	73.4	90.5	132.7	184.2	231.9	288.4	377.1	431.9
100	51.4	81.7	100.6	148.4	205.6	259.5	321.7	422.4	484




Figure 57. Location of Aparri RIDF Station relative to Baua River Basin




Figure 58. Synthetic storm generated for a 24-hr period rainfall for various return periods.

5.3 HMS Model

The soil dataset was generated before 2004 by the Bureau of Soils and Water Management under the Department of Agriculture (DA-BSWM). The land cover dataset is from the National Mapping and Resource information Authority (NAMRIA). The soil and land cover of the Baua River Basin are shown in Figure 59 and Figure 60, respectively.




Figure 59. Soil map of the Baua River Basin used for the estimation of the CN parameter.
(Source: DA)




Figure 60. Land cover map of Baua River Basin used for the estimation of the Curve Number (CN) and the watershed lag parameters of the rainfall-runoff model. (Source: NAMRIA)

For the Baua river basin, three (3) soil classes were identified. The Baua river basin has portions of clay loam and silt loam, while the rest is undifferentiated. Moreover, four (4) land cover classes were identified. Most of the Baua river basin is largely closed forest, and small parts are open forest, forest plantation, and cultivated areas.




Figure 61. Slope map of Buaa River Basin




Figure 62. Stream delineation map of Baua River Basin

A drainage system includes the basin boundary, subbasin and the stream networks of the basin. Using ArcMap 10.2 with HEC-GeoHMS version 10.2 extension, the Baua River centerline and SAR-DEM 10m resolution served as primary data, delineating the drainage system of the Baua river basin. The river centerline was digitized starting from upstream towards downstream in Google Earth (2014). Default threshold area used is 140 hectares.

Using the SAR-based DEM, the Baua basin was delineated and further subdivided into subbasins. The Baua basin model consists of 55 subbasins, 27 reaches, and 27 junctions. The main outlet is at Outlet 1. This basin model is illustrated in Figure 63. The basins were identified based on soil and land cover characteristics of the area. Precipitation from the 27 December 2016 to 28 December 2016 (Monsoon Rain) was taken from Brgy. San Jose, Cagayan ARG. Finally, it was calibrated using data from the Baua depth gauge sensor.




Figure 63. HEC-HMS generated Baua River Basin Model.

5.4 Cross-section Data

Riverbed cross-sections of the watershed are crucial in the HEC-RAS model setup. The cross-section data for the HEC-RAS model was derived using the LiDAR DEM data. It was defined using the Arc GeoRAS tool and was post-processed in ArcGIS.




Figure 64. River cross-section of Baua River generated through Arcmap HEC GeoRAS tool

5.5 Flo 2D Model

The automated modelling process allows for the creation of a model with boundaries that are almost exactly coincidental with that of the catchment area. As such, they have approximately the same land area and location. The entire area is divided into square grid elements, 10 meter by 10 meter in size. Each element is assigned a unique grid element number which serves as its identifier, then attributed with the parameters required for modelling such as x-and y-coordinate of centroid, names of adjacent grid elements, Manning coefficient of roughness, infiltration, and elevation value. The elements are arranged spatially to form the model, allowing the software to simulate the flow of water across the grid elements and in eight directions (north, south, east, west, northeast, northwest, southeast, southwest).

Based on the elevation and flow direction, it is seen that the water will generally flow from the southeast of the model to the northwest, following the main channel. As such, boundary elements in those particular regions of the model are assigned as inflow and outflow elements respectively.




Figure 65. Screenshot of subcatchment with the computational area to be modeled in FLO-2D GDS Pro

The simulation is then run through FLO-2D GDS Pro. This particular model had a computer run time of 28.67212 hours. After the simulation, FLO-2D Mapper Pro is used to transform the simulation results into spatial data that shows flood hazard levels, as well as the extent and inundation of the flood. Assigning the appropriate flood depth and velocity values for Low, Medium, and High creates the following flood hazard map. Most of the default values given by FLO-2D Mapper Pro are used, except for those in the Low hazard level. For this particular level, the minimum h (Maximum depth) is set at 0.2 m while the minimum vh (Product of maximum velocity (v) times maximum depth (h)) is set at $0 \text{ m}^2/\text{s}$.

The creation of a flood hazard map from the model also automatically creates a flow depth map depicting the maximum amount of inundation for every grid element. The legend used by default in Flo-2D Mapper is not a good representation of the range of flood inundation values, so a different legend is used for the layout. In this particular model, the inundated parts cover a maximum land area of 45299400.00 m^2 .

There is a total of 52789084.78 m^3 of water entering the model. Of this amount, 20034425.58 m^3 is due to rainfall while 32754659.20 m^3 is inflow from other areas outside the model. 4674584.50 m^3 of this water is lost to infiltration and interception, while 2563791.01 m^3 is stored by the flood plain. The rest, amounting up to 45550705.86 m^3 , is outflow.

5.6 Results of HMS Calibration

After calibrating the Baua HEC-HMS river basin model, its accuracy was measured against the observed values. Figure 66 shows the comparison between the two discharge data.




Figure 66. Outflow Hydrograph of Baua produced by the HEC-HMS model compared with observed outflow.

Enumerated in Table 32 are the adjusted ranges of values of the parameters used in calibrating the model.

Table 32. Range of calibrated values for Baua Watershed

Hydrologic Element	Calculation Type	Method	Parameter	Range of Calibrated Values
Basin	Loss	SCS Curve number	Initial Abstraction (mm)	1.98 – 12.47
			Curve Number	77 - 99
	Transform	Clark Unit Hydrograph	Time of Concentration (hr)	0.29 – 4.34
			Storage Coefficient (hr)	0.40 – 5.9
Reach	Routing	Muskingum-Cunge	Recession Constant	1
			Ratio to Peak	0.2
			Manning's Coefficient	0.035

Initial abstraction defines the amount of precipitation that must fall before surface runoff. The magnitude of the outflow hydrograph increases as initial abstraction decreases. The range of values from 1.98 mm to 12.47 mm signifies that there is minimal amount of infiltration or rainfall interception by vegetation.

The curve number is the estimate of the precipitation excess of soil cover, land use, and antecedent moisture. The magnitude of the outflow hydrograph increases as curve number increases. The range for the curve number of Baua River Basin is 77 to 99. For Baua, the basin mostly consists of closed forest and the soil mostly consists of undifferentiated soil.

The time of concentration and storage coefficient are the travel time and index of temporary storage of runoff in a watershed. The range of calibrated values from 0.29 hour to 5.9 hours determines the reaction time of the model with respect to the rainfall. The peak magnitude of the hydrograph also decreases when these parameters are increased.

Recession constant is the rate at which baseflow recedes between storm events, while ratio to peak is the ratio of the baseflow discharge to the peak discharge. Recession constant of 1 indicates that the basin is highly unlikely to quickly go back to its original discharge and instead, will be higher. Ratio to peak of 0.2 indicates a steeper receding limb of the outflow hydrograph.

Manning’s roughness coefficient of 0.035 corresponds to the common roughness in Baua watershed, which is determined to be cultivated with mature row crops (Brunner, 2010).

Table 33. Summary of the Efficiency Test of Baua HMS Model

Accuracy measure	Value
RMSE	4.8
r^2	0.956
NSE	0.85
PBIAS	0.56
RSR	0.38

The Root Mean Square Error (RMSE) method aggregates the individual differences of these two measurements. It was computed as 4.8 (m³/s).

The Pearson correlation coefficient (r^2) assesses the strength of the linear relationship between the observations and the model. This value being close to 1 corresponds to an almost perfect match of the observed discharge and the resulting discharge from the HEC HMS model. Here, it measured 0.956.

The Nash-Sutcliffe (E) method was also used to assess the predictive power of the model. Here the optimal value is 1. The model attained an efficiency coefficient of 0.85.

A positive Percent Bias (PBIAS) indicates a model’s propensity towards under-prediction. Negative values indicate bias towards over-prediction. Again, the optimal value is 0. In the model, the PBIAS is 0.56.

The Observation Standard Deviation Ratio, RSR, is an error index. A perfect model attains a value of 0 when the error in the units of the valuable a quantified. The model has an RSR value of 0.38.

5.7 Calculated Outflow hydrographs and Discharge Values for different Rainfall Return Periods

5.7.1 Hydrograph using the Rainfall Runoff Model

The summary graph (Figure 67) shows the Baua River outflow using the Aparri Rainfall Intensity-Duration-Frequency curves (RIDF) in 5 different return periods (5-year, 10-year, 25-year, 50-year, and 100-year rainfall time series) based on the Philippine Atmospheric Geophysical and Astronomical Services Administration (PAG-ASA) data. The simulation results reveal significant increase in outflow magnitude as the rainfall intensity increases for a range of durations and return periods.




Figure 67. Outflow hydrograph at Baua Station generated using Aparri RIDF simulated in HEC-HMS

A summary of the total precipitation, peak rainfall, peak outflow and time to peak of the Baua discharge using the Aparri Rainfall Intensity-Duration-Frequency curves (RIDF) in five different return periods is shown in Table 34.

Table 34. Peak values of the Baua HEC-HMS Model outflow using the Aparri RIDF

RIDF Period	Total Precipitation (mm)	Peak Rainfall (mm)	Peak Outflow	Time to Peak
5-year RIDF	252.5	28.5	851.1	2 hours, 30 minutes
10-year RIDF	308.5	34.1	1050.0	2 hours, 20 minutes
25-year RIDF	379.3	41.1	1301.7	2 hours, 20 minutes
50-year RIDF	431.9	46.3	1486.2	2 hours, 20 minutes
100-year RIDF	484	51.4	1670.2	2 hours, 20 minutes

5.8 River Analysis Model Simulation

The HEC-RAS Flood Model produced a simulated water level at every cross-section for every time step for every flood simulation created. The resulting model will be used in determining the flooded areas within the model. The simulated model will be an integral part in determining real-time flood inundation extent of the river after it has been automated and uploaded on the DREAM website. For this publication, only a sample output map river was to be shown. The sample generated map of Baua River using the calibrated HMS is shown in Figure 68.



Figure 68. Sample output of Baua RAS Model

5.9 Flood Hazard and Flow Depth Map

The resulting hazard and flow depth maps have a 10m resolution. The generated flood hazard maps for the Baua Floodplain were used to assess the vulnerability of the educational and medical institutions in the floodplain. Using the flood depth units of PAGASA for hazard maps - “Low”, “Medium”, and “High” - the affected institutions were given their individual assessment for each Flood Hazard Scenario (5 yr, 25 yr, and 100 yr). Figure 69 to Figure 74 shows the 5-, 25-, and 100-year rain return scenarios of the Baua floodplain. The floodplain, with an area of 57.04 sq. km., covers one municipality namely Gonzaga. Table 35 shows the percentage of area affected by flooding in the municipality.

Table 35. Municipalities affected in Baua Floodplain

Municipality	Total Area	Area Flooded	% Flooded
Gonzaga	497.62	57.04	11%




Figure 70. 100-year Flow Depth Map for Baua Floodplain overlaid on Google Earth imagery




Figure 72. 25-year Flow Depth Map for Baua Floodplain overlaid on Google Earth imagery




Figure 73. 5-year Flood Hazard Map for Baua Floodplain overlaid on Google Earth imagery




Figure 74. 5-year Flood Depth Map for Baua Floodplain overlaid on Google Earth imagery

5.10 Areas Exposed to Flooding

Affected barangays in Baua river basin, grouped by municipality, are listed below. For the said basin, one (1) municipality consisting of 6 barangays are expected to experience flooding when subjected to 5-, 25-, and 100-yr rainfall return period.

For the 5-year return period, 8.50% of the municipality of Gonzaga with an area of 497.62 sq. km. will experience flood levels of less than 0.20 meters. 0.77% of the area will experience flood levels of 0.21 to 0.50 meters while 0.63%, 0.82%, 0.59%, and 0.14% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 36 and shown in Figure 75 are the affected areas in square kilometers by flood depth per barangay.

Table 36. Affected Areas in Gonzaga, Cagayan during 5-Year Rainfall Return Period

Affected Area (sq. km.) by flood depth (in m.)	Area of affected barangays in Gonzaga (in sq. km)					
	Amunitan	Baua	Cabiraogan	San Jose	Santa Cruz	Santa Maria
0.03-0.20	4.65	1.35	17.18	3.78	2.68	12.68
0.21-0.50	0.29	0.33	1.24	0.56	0.45	0.98
0.51-1.00	0.25	0.54	0.59	0.56	0.51	0.7
1.01-2.00	0.3	0.78	0.56	0.93	0.46	1.07
2.01-5.00	0.074	0.47	0.56	0.58	0.076	1.16
> 5.00	0.048	0.12	0.17	0	0	0.37




Figure 75. Affected Areas in Gonzaga, Cagayan during 5-Year Rainfall Return Period

For the 25-year return period, 8.04% of the municipality of Gonzaga with an area of 497.62 sq. km. will experience flood levels of less than 0.20 meters. 0.87% of the area will experience flood levels of 0.21 to 0.50 meters while 0.61%, 0.84%, 0.92%, and 0.18% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 37 and shown in Figure 76 are the affected areas in square kilometers by flood depth per barangay.

Table 37. Affected Areas in Gonzaga, Cagayan during 25-Year Rainfall Return Period

Affected Area (sq. km.) by flood depth (in m.)	Area of affected barangays in Gonzaga (in sq. km)					
	Amunitan	Baua	Cabiraosan	San Jose	Santa Cruz	Santa Maria
0.03-0.20	4.48	1.08	16.44	3.48	2.38	12.17
0.21-0.50	0.3	0.27	1.56	0.6	0.45	1.14
0.51-1.00	0.25	0.44	0.69	0.54	0.55	0.56
1.01-2.00	0.32	0.92	0.6	0.93	0.56	0.84
2.01-5.00	0.2	0.74	0.75	0.86	0.23	1.81
> 5.00	0.066	0.14	0.26	0.0001	0	0.43




Figure 76. Affected Areas in Gonzaga, Cagayan during 25-Year Rainfall Return Period

For the 100-year return period, 7.73% of the municipality of Gonzaga with an area of 497.62 sq. km. will experience flood levels of less than 0.20 meters. 0.95% of the area will experience flood levels of 0.21 to 0.50 meters while 0.62%, 0.79%, 1.15%, and 0.22% of the area will experience flood depths of 0.51 to 1 meter, 1.01 to 2 meters, 2.01 to 5 meters, and more than 5 meters, respectively. Listed in Table 38 and shown in Figure 77 are the affected areas in square kilometers by flood depth per barangay.

Table 38. Affected Areas in Gonzaga, Cagayan during 100-Year Rainfall Return Period

Affected Area (sq. km.) by flood depth (in m.)	Area of affected barangays in Gonzaga (in sq. km)					
	Amunitan	Baua	Cabiraosan	San Jose	Santa Cruz	Santa Maria
0.03-0.20	4.37	0.9	15.86	3.32	2.2	11.81
0.21-0.50	0.31	0.28	1.83	0.59	0.45	1.28
0.51-1.00	0.26	0.36	0.78	0.56	0.55	0.58
1.01-2.00	0.29	0.92	0.61	0.84	0.65	0.64
2.01-5.00	0.31	0.97	0.9	1.1	0.32	2.11
> 5.00	0.072	0.17	0.32	0.0001	0	0.53




Figure 77. Affected Areas in Gonzaga, Cagayan during 100-Year Rainfall Return Period

Among the barangays in the municipality of Gonzaga in Cagayan, Cabiraoan is projected to have the highest percentage of area that will experience flood levels at 4.08%. Meanwhile, Santa Maria posted the second highest percentage of area that may be affected by flood depths at 3.41%.

Moreover, the generated flood hazard maps for the Baua Floodplain were used to assess the vulnerability of the educational and medical institutions in the floodplain. Using the flood depth units of PAG-ASA for hazard maps - “Low”, “Medium”, and “High” - the affected institutions were given their individual assessment for each Flood Hazard Scenario (5 yr, 25 yr, and 100 yr).

Table 39. Area covered by each warning level with respect to the rainfall scenario

Warning Level	Area Covered in sq. km.		
	5 year	25 year	100 year
Low	3.92	4.43	4.87
Medium	5.20	5.21	5.06
High	5.87	7.69	9.02
Total	14.99	17.33	18.95

Of the 15 identified educational institutions in Baua Flood Plain, two (2) schools were discovered exposed to low-level flooding while three (3) schools were found exposed to medium-level flooding, both during the 5-year scenario.

For the 25-year scenario, one (1) school was discovered exposed to low-level flooding while two (2) schools were found exposed to medium-level flooding. In the same scenario, two (2) schools were discovered exposed to high-level flooding.

For the 100-year scenario, two (2) schools were discovered exposed to low-level flooding while one (1) school was found exposed to medium-level flooding. In the same scenario, three (3) schools were discovered exposed to high-level flooding.

The educational institutions exposed to flooding are shown in Annex 12.

No medical institutions were identified to be affected by flooding in Baua Floodplain.

5.11 Flood Validation

Survey was done along the floodplain of Baua River to validate the generated flood maps. The team gathered secondary data regarding flood occurrence in the area. Ground validation points were acquired as well as the other necessary details like date of occurrence, name of typhoon and actual flood depth.

During validation, the team was assisted by the local Disaster Risk Reduction and Management representative. Residents along the floodplain were interviewed of the historical flood events they experiences.

Actual flood depth acquired from the ground validation were then computed and compared to the flood depth simulated by the model (Figure 79). The flood validation consists of 160 points randomly selected all over the Baua flood plain. It has an RMSE value of 1.208.




Figure 78. Validation points for 5-year Flood Depth Map of Baua Floodplain




Figure 79. Flood map depth vs. actual flood depth

Table 40. Actual flood vs simulated flood depth of Baua River Basin.

Actual Flood Depth (m)	Modeled Flood Depth (m)						Total
	0-0.20	0.21-0.50	0.51-1.00	1.01-2.00	2.01-5.00	> 5.00	
0-0.20	82	17	10	4	4	0	117
0.21-0.50	16	2	1	1	0	0	20
0.51-1.00	3	1	2	0	4	0	10
1.01-2.00	1	1	1	1	4	3	11
2.01-5.00	2	0	0	0	0	0	2
> 5.00	0	0	0	0	0	0	0
Total	104	21	14	6	12	3	160

The overall accuracy generated by the flood model is estimated at 54.38% with 87 points correctly matching the actual flood depths. In addition, there were 39 points estimated one level above and below the correct flood depths while there were 22 points and 11 points estimated two levels above and below, and three or more levels above and below the correct flood. A total of 4 points were overestimated while a total of 25 points were underestimated in the modelled flood depths of Baua. The summary of the accuracy assessment is presented in Table 41.

Table 41. Summary of the Accuracy Assessment in the Baua River Basin Survey

	No. of Points	%
Correct	87	54.38
Overestimated	48	30.00
Underestimated	25	15.63
Total	160	100.00

REFERENCES

Ang M.C., Paringit E.C., et al. 2014. DREAM Data Processing Component Manual. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry

Balicanta L.P, Paringit E.C., et al. 2014. DREAM Data Validation Component Manual. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry

Brunner, G. H. 2010a. HEC-RAS River Analysis System Hydraulic Reference Manual. Davis, CA: U.S. Army Corps of Engineers, Institute for Water Resources, Hydrologic Engineering Center.

Lagmay A.F., Paringit E.C., et al. 2014. DREAM Flood Modeling Component Manual. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry

Paringit, E.C., Balicanta, L.P., Ang, M.C., Lagmay, A.F., Sarmiento, C. 2017, Flood Mapping of Rivers in the Philippines Using Airborne LiDAR: Methods. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry

Sarmiento C.J.S., Paringit E.C., et al. 2014. DREAM Data Aquisition Component Manual. Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry

UP TCAGP 2016. Acceptance and Evaluation of Synthetic Aperture Radar Digital Surface Model (SAR DSM) and Ground Control Points (GCP). Quezon City, Philippines: UP Training Center for Applied Geodesy and Photogrammetry

ANNEXES

Annex 1. Optech Technical Specification of the Pegasus and Gemini Sensors




Figure A-1.1 Pegasus Sensor

Table A-1.1 Parameters and Specifications of the Pegasus Sensor

Parameter	Specification
Operational envelope (1,2,3,4)	150-5000 m AGL, nominal
Laser wavelength	1064 nm
Horizontal accuracy (2)	1/5,500 x altitude, 1 σ
Elevation accuracy (2)	< 5-20 cm, 1 σ
Effective laser repetition rate	Programmable, 100-500 kHz
Position and orientation system	POS AV TM AP50 (OEM)
Scan width (FOV)	Programmable, 0-75 °
Scan frequency (5)	Programmable, 0-140 Hz (effective)
Sensor scan product	800 maximum
Beam divergence	0.25 mrad (1/e)
Roll compensation	Programmable, $\pm 37^\circ$ (FOV dependent)
Vertical target separation distance	<0.7 m
Range capture	Up to 4 range measurements, including 1st, 2nd, 3rd, and last returns
Intensity capture	Up to 4 intensity returns for each pulse, including last (12 bit)
Image capture	5 MP interline camera (standard); 60 MP full frame (optional)
Full waveform capture	12-bit Optech IWD-2 Intelligent Waveform Digitizer
Data storage	Removable solid state disk SSD (SATA II)
Power requirements	28 V, 800 W, 30 A
Dimensions and weight	Sensor: 630 x 540 x 450 mm; 65 kg; Control rack: 650 x 590 x 490 mm; 46 kg
Operating Temperature	-10°C to +35°C
Relative humidity	0-95% non-condensing

¹ Target reflectivity $\geq 20\%$

² Dependent on selected operational parameters using nominal FOV of up to 40° in standard atmospheric conditions with 24-km visibility

³ Angle of incidence $\leq 20^\circ$

⁴ Target size \geq laser footprint ⁵ Dependent on system configuration



Figure A-1.2 Gemini Sensor

Table A-1.2 Parameters and Specifications of the Gemini Sensor

Parameter	Specification
Operational envelope (1,2,3,4)	150-4000 m AGL, nominal
Laser wavelength	1064 nm
Horizontal accuracy (2)	1/5,500 x altitude, (m AGL)
Elevation accuracy (2)	<5-35 cm, 1 σ
Effective laser repetition rate	Programmable, 33-167 kHz
Position and orientation system	POS AV™ AP50 (OEM); 220-channel dual frequency GPS/GNSS/Galileo/L-Band receiver
Scan width (WOV)	Programmable, 0-50°
Scan frequency (5)	Programmable, 0-70 Hz (effective)
Sensor scan product	1000 maximum
Beam divergence	Dual divergence: 0.25 mrad (1/e) and 0.8 mrad (1/e), nominal
Roll compensation	Programmable, $\pm 5^\circ$ (FOV dependent)
Range capture	Up to 4 range measurements, including 1st, 2nd, 3rd, and last returns
Intensity capture	Up to 4 intensity returns for each pulse, including last (12 bit)
Video Camera	Internal video camera (NTSC or PAL)
Image capture	Compatible with full Optech camera line (optional)
Full waveform capture	12-bit Optech IWD-2 Intelligent Waveform Digitizer (optional)
Data storage	Removable solid state disk SSD (SATA II)
Power requirements	28 V; 900 W; 35 A(peak)
Dimensions and weight	Sensor: 260 mm (w) x 190 mm (l) x 570 mm (h); 23 kg Control rack: 650 mm (w) x 590 mm (l) x 530 mm (h); 53 kg
Operating temperature	-10°C to +35°C (with insulating jacket)
Relative humidity	0-95% no-condensing

Annex 2. NAMRIA Certificates of Reference Points Used

1. CGY-102



Republic of the Philippines
Department of Environment and Natural Resources
NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY

December 02, 2015

CERTIFICATION

To whom it may concern:


This is to certify that according to the records on file in this office, the requested survey information is as follows -

Province: CAGAYAN		
Station Name: CGY-102		
Order: 2nd		
Island: LUZON	Barangay: CASAMBALANGAN	
Municipality: SANTA ANA	MSL Elevation:	
PRS92 Coordinates		
Latitude: 18° 22' 15.98573"	Longitude: 122° 6' 41.74346"	Ellipsoidal Hgt: 22.60800 m.
WGS84 Coordinates		
Latitude: 18° 22' 9.81367"	Longitude: 122° 6' 46.31361"	Ellipsoidal Hgt: 57.19500 m.
PTM / PRS92 Coordinates		
Northing: 2032192.366 m.	Easting: 617476.569 m.	Zone: 3
UTM / PRS92 Coordinates		
Northing: 2,031,351.34	Easting: 406,145.45	Zone: 51

Location Description

CGY-102
From Gonzaga, travel along the nat'l. highway to Santa Ana. Station is located about 2 m. from the S corner of the triangular island at the intersection of the nat'l. highway and the road to Port Irene. Mark is the head of a copper nail centered and flushed on a 30 cm. x 30 cm. concrete monument, with inscriptions "CGY-102 2007 NAMRIA".

Requesting Party: UP DREAM
Purpose: Reference
OR Number: 8088735 I
T.N.: 2015-3961



RUEL M. BELEN, MNSA
Director, Mapping And Geodesy Branch



9 9 1 2 0 2 2 0 1 3 1 0 5 7 1 7



NAMRIA OFFICES:
Main : Lawton Avenue, Fort Bonifacio, 1634 Taguig City, Philippines Tel. No. (02) 810-4021 to 41
Branch : 401 Barasoain St. San Nicolas, 1010 Manila, Philippines, Tel. No. (02) 241-3494 to 95
www.namria.gov.ph

ISO 9001: 2008 CERTIFIED FOR MAPPING AND GEOSPATIAL INFORMATION MANAGEMENT

Figure A-2.1 CGY-102

2. CGY-92



Republic of the Philippines
 Department of Environment and Natural Resources
NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY

October 29, 2013

CERTIFICATION

To whom it may concern:

This is to certify that according to the records on file in this office, the requested survey information is as follows -

Province: CAGAYAN		
Station Name: CGY-92		
Order: 2nd		
Island: LUZON	Barangay: POBLACION	
Municipality: LAL-LO		
PRS92 Coordinates		
Latitude: 18° 12' 11.42361"	Longitude: 121° 39' 42.14392"	Ellipsoidal Hgt: 14.47400 m.
WGS84 Coordinates		
Latitude: 18° 12' 5.25321"	Longitude: 121° 39' 46.73084"	Ellipsoidal Hgt: 48.54000 m.
PTM Coordinates		
Northing: 2013373.807 m.	Easting: 569996.115 m.	Zone: 3
UTM Coordinates		
Northing: 2,013,059.26	Easting: 358,475.41	Zone: 51

Location Description

CGY-92

Is located inside the Lal-lo Nat'l. High School, about 5 m. W of the flagpole. Said school is 95 m. E of the Tuguegarao-Aparri nat'l. road, between Km Posts 562 and 563 and about 40 m. N of Lal-lo Mun. Hall. Mark is the head of a copper nail centered and flushed on a 30 cm. x 30 cm. cement putty, with inscriptions "CGY-92 2007 NAMRIA".

Requesting Party: **UP-DREAM**
 Purpose: **Reference**
 OR Number: **3947103 B**
 T.N.: **2013-1171**

RUEL DM. BELEN, MNSA
 Director, Mapping And Geodesy Branch



NAMRIA OFFICES:
 Main : Lawton Avenue, Fort Bonifacio, 1634 Taguig City, Philippines Tel. No.: (632) 810-4631 to 41
 Branch : 421 Barraco St. San Nicolas, 1010 Manila, Philippines, Tel. No. (632) 241-3494 to 98
www.namria.gov.ph

Figure A-2.2 CGY-92

3. CG-258



Republic of the Philippines
Department of Environment and Natural Resources
NATIONAL MAPPING AND RESOURCE INFORMATION AUTHORITY

May 17, 2016

CERTIFICATION

To whom it may concern:

This is to certify that according to the records on file in this office, the requested survey information is as follows -

Province: CAGAYAN		
Station Name: CG-258		
Island: Luzon	Municipality: GONZAGA	Barangay: TAPEL
Elevation: 6.5266 +/- 0.0455 m.	Accuracy Class at 95% C.L: 4 cm	Datum: Mean Sea Level
Latitude: 18° 17' 15.50000"	Longitude: 122° 1' 26.40000"	

The accuracy standards reported herein (FGDC-STD-007-1998) supersedes and replace the previous accuracy standards found in FGCC 1984 and FGCC 1988. Classified control points are verified as being consistent w/ all other points in the network, not merely those within that particular survey.

Location Description

BM CG-258 is in the Province of Cagayan, Municipality of Gonzaga, Brgy. of Tapel, along the national road and about 200 m NE of Kilometer post no. 608, It is embedded in a hole drilled on top of and near the West end of the North sidewalk of a concrete bridge. It is 0.22 m above the bridge floor, almost 4.33 m North of the centerline of the bridge. It is located at the right side of the national road going to Aparri, almost 37.7 m North post of the Tapel Brgy. marker.


Mark is a 1/2" x 2" brass rod embedded in a drilled hole, with an inscription on the cement putty placed around the mark as shown; CG-258; 2007; NAMRIA

Requesting Party: **UP-DREAM**

Purpose: **Reference**

OR Number: **8090370 I**

T.N.: **2016-1109**



RUEL M. BELEN, MNSA
Director, Mapping And Geodesy Branch



9 9 0 5 1 7 2 0 1 6 0 9 5 8 0 7



CIP/4701/12/09/814

NAMRIA OFFICES:
Main : Lawton Avenue, Fort Bonifacio, 1634 Taguig City, Philippines Tel. No.: (632) 810-4831 to 41
Branch : 421 Barraca St. San Nicolas, 1010 Manila, Philippines, Tel. No. (632) 241-3494 to 98
www.namria.gov.ph
ISO 9001:2008 CERTIFIED FOR MAPPING AND GEOSPATIAL INFORMATION MANAGEMENT

Figure A-2.3 CG-258

Annex 3. Baseline Processing Reports of Control Points used in the LiDAR Survey

1. CGY-102

Vector Components (Mark to Mark)

From: CGY-102					
Grid		Local		Global	
Easting	406145.451 m	Latitude	N18°22'15.98572"	Latitude	N18°22'09.81367"
Northing	2031351.336 m	Longitude	E122°06'41.74346"	Longitude	E122°06'46.31361"
Elevation	20.066 m	Height	22.609 m	Height	57.195 m

To: CG-258					
Grid		Local		Global	
Easting	396708.418 m	Latitude	N18°17'21.32897"	Latitude	N18°17'15.16762"
Northing	2022343.154 m	Longitude	E122°01'21.83970"	Longitude	E122°01'26.41723"
Elevation	9.620 m	Height	12.774 m	Height	47.419 m

Vector					
ΔEasting	-9437.033 m	NS Fwd Azimuth	226°03'09"	ΔX	6452.377 m
ΔNorthing	-9008.183 m	Ellipsoid Dist.	13049.913 m	ΔY	7393.391 m
ΔElevation	-10.445 m	ΔHeight	-9.835 m	ΔZ	-8602.642 m

Standard Errors

Vector errors:					
σ ΔEasting	0.001 m	σ NS fwd Azimuth	0°00'00"	σ ΔX	0.005 m
σ ΔNorthing	0.001 m	σ Ellipsoid Dist.	0.001 m	σ ΔY	0.007 m
σ ΔElevation	0.009 m	σ ΔHeight	0.009 m	σ ΔZ	0.003 m

Aposteriori Covariance Matrix (Meter²)

	X	Y	Z
X	0.0000235542		
Y	-0.0000335823	0.0000546286	
Z	-0.0000130276	0.0000212981	0.0000098327

Figure A-3.1 CGY-102

Annex 4. The LiDAR Survey Team Composition

Table A-4.1 LiDAR Survey Team Composition

Data Acquisition Component Sub -Team	Designation	Name	Agency / Affiliation
PHIL-LIDAR 1	Program Leader	ENRICO C. PARINGIT, D.ENG	UP-TCAGP
Data Acquisition Component Leader	Data Component Project Leader – I	ENGR. CZAR JAKIRI SARMIENTO	UP-TCAGP
Survey Supervisor	Chief Science Research Specialist (CSRS)	ENGR. CHRISTOPHER CRUZ	UP-TCAGP
	Supervising Science Research Specialist (Supervising SRS)	LOVELY GRACIA ACUÑA	UP-TCAGP
		LOVELYN ASUNCION	UP-TCAGP
FIELD TEAM			
LiDAR Operation	Senior Science Research Specialist (SSRS)	JASMINE ALVIAR	UP-TCAGP
		ENGR. IRO NIEL ROXAS	UP-TCAGP
	Research Associate (RA)	ENGR. KENNETH QUISADO	UP-TCAGP
	RA	KRISTINE JOY ANDAYA	UP-TCAGP
	RA	JONATHAN ALMALVEZ	UP-TCAGP
	RA	SANDRA POBLETE	UP-TCAGP
Ground Survey, Data Download and Transfer	RA	MA. REMEDIOS VILLANUEVA	UP-TCAGP
	RA	DARRYL AUSTRIA	UP-TCAGP
LiDAR Operation	Airborne Security	SSG. ERWIN DELOS SANTOS	PHILIPPINE AIR FORCE (PAF)
		SSG. JOHN ERIC CACANINDIN	PHILIPPINE AIR FORCE
	Pilot	CAPT. CESAR ALFONSO III	ASIAN AEROSPACE CORPORATION (AAC)
		CAPT. JERICO JECIEL	AAC
		CAPT. JEROME MOONEY	AAC

Annex 5. Data Transfer Sheets

DATA TRANSFER SHEET
cagayan2_12/2/15

DATE	FLIGHT NO.	MISSION NAME	SENSOR	RAW LAS		LOGS(MB)	POS	RAW IMAGES/CAS	MISSION LOG FILE/CASI LOGS	RANGE	DIGITIZER	BASE STATION(S)		OPERATOR LOGS (OPLOG)	FLIGHT PLAN		SERVER LOCATION
				Output LAS	KML (swath)							BASE STATION(S)	Base Info (.txt)		Actual	KWL	
18-Nov	2866P	1BLK2IG322A	pegasus	2.33	na	11.8	266	34.7	258	22.8	na	15.6	1KB	1KB	129	NA	Z:\DAC\RAW DATA
18-Nov	2868P	1BLK2HS322B	pegasus	1.87	na	7.94	157	27.7	207	18	na	15.6	1KB	1KB	74	NA	Z:\DAC\RAW DATA
19-Nov	2870P	1BLK21AB323A	pegasus	2.11	na	11.6	255	23.2	211	22.8	na	10.3	1KB	1KB	46	NA	Z:\DAC\RAW DATA
20-Nov	2874P	1BLK21C324A	pegasus	1.22	na	8.12	195	7.3	80	12	na	10.8	1KB	1KB	57/90	NA	Z:\DAC\RAW DATA
21-Nov	2880P	1BLK2HS325A	pegasus	1.76	na	12.2	231	30	240/1	17.7	na	11.4	1KB	1KB	84/76/74	NA	Z:\DAC\RAW DATA

Received from
Name _____
Position _____
Signature _____

Signature
Name *AC Borjat*
Position *12/4/15*
Signature *[Signature]*

Received by
Name _____
Position _____
Signature _____

Figure A-5.1 Data Transfer Sheet for Baua Floodplain - A

2. Flight Log for 3971G Mission



UP DREAM Data Acquisition Flight Log		Flight Log No.: 3971			
1. LiDAR Operator: J. ALMAYEZ	2. ALTM Model: GEMINI	3. Mission Name: 2BLK-CPA2-MBR19M	Type: VFR	5. Aircraft Type: Casina T20GH	6. Aircraft Identification: RP-C9022
7. Pilot: J. MOONEY	8. Co-Pilot: D. CORPUZ	9. Route: TUGUEGARAO - TUGUEGARAO	12. Airport of Arrival (Airport, City/Province): TUGUEGARAO		
10. Date: APRIL 28, 2014	11. Airport of Departure (Airport, City/Province): TUGUEGARAO		16. Take off: 10:14 H	17. Landing: 14:19 H	18. Total Flight Time: 04:05
13. Engine On: 10:09 H	14. Engine Off: 14:24 H	15. Total Engine Time: 04:15			
19. Weather: FAIR					
20. Flight Classification	21. Remarks: Successful Flight Covered Bana, Casambalangan & Palawing Floodplains				
20.a. Billable	20.b. Non Billable	20.c. Others			
<input checked="" type="radio"/> Acquisition Flight <input type="radio"/> Ferry Flight <input type="radio"/> System Test Flight <input type="radio"/> Calibration Flight	<input type="radio"/> Aircraft Test Flight <input type="radio"/> AAC Admin Flight <input type="radio"/> Others: _____	<input type="radio"/> LiDAR System Maintenance <input type="radio"/> Aircraft Maintenance <input type="radio"/> Phil-LiDAR Admin Activities			
22. Problems and Solutions					
<input type="radio"/> Weather Problem <input type="radio"/> System Problem <input type="radio"/> Aircraft Problem <input type="radio"/> Pilot Problem <input type="radio"/> Others: _____					
Acquisition Flight Approved by  Signature over Printed Name (End User Representative)		Acquisition Flight Certified by  Signature over Printed Name (PAF Representative)		LiDAR Operator  Signature over Printed Name	
		Pilot-in-Command		Aircraft Mechanic/ LiDAR Technician	

Figure A-6.2 Flight Log for 3971G Mission

Flight Log No.: 3991




UP DREAM Data Acquisition Flight Log		1 Mission Name: 28UK9R652M4S12114 Type: VFR		5 Aircraft Type: Cesna T206H		6 Aircraft Identification: RP-09022	
1 LiDAR Operator: J. ALMAYNE		2 ALTM Model: 6 EMIN		9 Route: TUGUEGARAO - TUGUEGARAO		12 Airport of Arrival (Airport, City/Province): TUGUEGARAO	
7 Pilot: J. MOONEY		8 Co-Pilot: D. CORPUZ		12 Airport of Departure (Airport, City/Province): TUGUEGARAO		16 Take off: 1339 H	
10 Date: MAY 3, 2014		15 Total Engine Time: 2 + 26		17 Landing: 1555 H		18 Total Flight Time: 2 + 16	
13 Engine On: 1034 H		14 Engine Off: 1600 H		19 Weather: PRETTY CLOUDY			
20 Flight Classification		20.b Non Billable		21 Remarks			
20.a Billable <input type="radio"/> Acquisition Flight <input type="radio"/> Ferry Flight <input type="radio"/> System Test Flight <input type="radio"/> Calibration Flight		<input type="radio"/> Aircraft Test Flight <input type="radio"/> AAC Admin Flight <input type="radio"/> Others: _____		Successful flight Covered CAGZM and DA			
22 Problems and Solutions		20.c Others		LIDAR Operator  Signature over Printed Name			
<input type="radio"/> Weather Problem <input type="radio"/> System Problem <input type="radio"/> Aircraft Problem <input type="radio"/> Pilot Problem <input type="radio"/> Others: _____		Acquisition Flight Certified by  Signature over Printed Name (PAF Representative)		Aircraft Mechanic/ LIDAR Technician _____ Signature over Printed Name			
Acquisition Flight Approved by  Signature over Printed Name (End User Representative)		Acquisition Flight Certified by  Signature over Printed Name (PAF Representative)		Pilot-in-Command  Signature over Printed Name			

Figure A-6.3 Flight Log for 3991G Mission

Flight Log No.: 4001




UP ORCAAM Data Acquisition Flight Log		3 Mission Name: 2BUK5/AG 248227A4 Type: VFR		5 Aircraft Type: Cessna T206H		6 Aircraft Identification: RP-09022	
1 LiDAR Operator: J. ALMALARZALM Model: GEMINI		9 Route: TUGUEGARAO - TUGUEGARAO		12 Airport of Arrival (Airport, City/Province): TUGUEGARAO		18 Total Flight Time: 3 + 50	
7 Pilot: J. MOONEY		8 Co-Pilot: D. CORPUZ		16 Take off: 1038 H		17 Landing: 1428 H	
10 Date: May 6, 2016		12 Airport of Departure (Airport, City/Province): TUGUEGARAO		15 Total Engine Time: 4 + 00			
13 Engine On: 1033 H		14 Engine Off: 1433 H		19 Weather: PARTLY CLOUDY			
20 Flight Classification		20.a Billable		20.b Non Billable		20.c Others	
<input checked="" type="radio"/> Acquisition Flight <input type="radio"/> Ferry Flight <input type="radio"/> System Test Flight <input type="radio"/> Calibration Flight		<input type="radio"/> Aircraft Test Flight <input type="radio"/> AAC Admin Flight <input type="radio"/> Others: _____		<input type="radio"/> LIDAR System Maintenance <input type="radio"/> Aircraft Maintenance <input type="radio"/> Phil-LIDAR Admin Activities		21 Remarks Successful Flight Completed CRG2M and Gumbalangan Floodplain	
22 Problems and Solutions		Acquisition Flight Approved by  Signature over Printed Name (End User Representative)		Acquisition Flight Certified by  Signature over Printed Name (PAF Representative)		LIDAR Operator  Signature over Printed Name	
<input type="radio"/> Weather Problem <input type="radio"/> System Problem <input type="radio"/> Aircraft Problem <input type="radio"/> Pilot Problem <input type="radio"/> Others: _____		Pilot-in-Command  Signature over Printed Name		Aircraft Mechanic/ LIDAR Technician _____ Signature over Printed Name			

Figure A-6.4 Flight Log for 4001G Mission

Annex 7. Flight Status Report

Table A-7.1 Flight Status Report

CAGAYAN REFLIGHTS (NOVEMBER 30, 2015, APRIL 28 – MAY 6, 2016)					
FLIGHT NO	AREA	MISSION	OPERATOR	DATE FLOWN	REMARKS
2916P	BLK 3A AUNUGAY FP, BAUA FP	1BLK3A334B	KJ ANDAYA	NOV 30, 2015	SURVEYED AUNUGAY AND BAUA FPs 120.97 SQ.KM
3971G	CAG2M, CAG2Q, CAG2R	2BLK3CAG2MQR119A	J. ALMALVEZ	APRIL 28, 2016	COVERED BAUA, CASAMBALANGAN AND PALAWIG FLOODPLAINS
3991G	CAG2M, CAG2Q, CAG2R	2BLK3CAG2MSQS124B	J. ALMALVEZ	May 3, 2016	COVERED CAG2Q AND R
4001G	CAG2M, CAG2R	2BLK3CAG2MRS127A	J. ALMALVEZ	May 6, 2016	COMPLETED CAG2M AND

LAS BOUNDARIES PER FLIGHT

Flight No. : 2916P
Area: BLK 3A
Mission Name: 1BLK3A334B
Parameters: PRF 200 SF 30 FOV 50

LAS/SWATH




Figure A-7.1 Swath for Flight No. 2916P

FLIGHT NO.: 3971G
AREA: CAG2M, CAG2Q, CAG2R
MISSION NAME: 2BLK3CAG2MQR119A




Figure A-7.2 Swath for Flight No. 3971G

FLIGHT NO.: 3991G
AREA: CAG2M, CAG2Q, CAG2R
MISSION NAME: 2BLK3CAG2MSQS124B




Figure A-7.3 Swath for Flight No. 3991G

FLIGHT NO.: 4001G
AREA: CAG2M, CAG2R
MISSION NAME: 2BLK3CAG2MRS127A




Figure A-7.4 Swath for Flight No. 4001G

Annex 8. Mission Summary Report

Table A-8.1 Mission Summary Report for Mission Blk3A

Flight Area	Cagayan Reflights(Tuguegarao)
Mission Name	Blk3A
Inclusive Flights	2916P
Range data size	11.8GB
POS	150MB
Image	17.9MB
Transfer date	December 8, 2015
<i>Solution Status</i>	
Number of Satellites (>6)	Yes
PDOP (<3)	Yes
Baseline Length (<30km)	Yes
Processing Mode (<=1)	No
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	1.87
RMSE for East Position (<4.0 cm)	1.65
RMSE for Down Position (<8.0 cm)	2.61
Boresight correction stdev (<0.001deg)	0.000319
IMU attitude correction stdev (<0.001deg)	0.001384
GPS position stdev (<0.01m)	0.0023
Minimum % overlap (>25)	30.46
Ave point cloud density per sq.m. (>2.0)	
Elevation difference between strips (<0.20 m)	Yes
Number of 1km x 1km blocks	138
Maximum Height	677.25 m
Minimum Height	57.52 m
<i>Classification (# of points)</i>	
Ground	109,071,592
Low vegetation	74,643,090
Medium vegetation	133,250,063
High vegetation	287,388,029
Building	8,589,940
Orthophoto	Yes
Processed by	Engr. Angelo Carlo Bongat, Engr. Ma. Joanne Balaga, Jovy Narisma




Figure A-8.1. Solution Status




Figure A-8.2. Smoothed Performance Metric Parameters




Figure A-8.3 Best Estimated Trajectory




Figure A-8.4. Coverage of LiDAR data




Figure A-8.5 Image of data overlap




Figure A.8.6 Image of data overlap




Figure A-8.7 Elevation Difference Between flight lines

Table A-8.2 Mission Summary Report for Mission Cagayan_reflights_Bl3A

Flight Area	Cagayan
Mission Name	Cagayan_reflights_Bl3A
Inclusive Flights	3971G, 3991G, 4001G
Range data size	45.75 GB
POS data size	640 MB
Base data size	33.73 MB
Image	NA
Transfer date	June 21, 2016
<i>Solution Status</i>	
Number of Satellites (>6)	No
PDOP (<3)	Yes
Baseline Length (<30km)	Yes
Processing Mode (<=1)	No
<i>Smoothed Performance Metrics (in cm)</i>	
RMSE for North Position (<4.0 cm)	2.5
RMSE for East Position (<4.0 cm)	1.7
RMSE for Down Position (<8.0 cm)	2.4
Boresight correction stdev (<0.001deg)	0.000876
IMU attitude correction stdev (<0.001deg)	0.015089
GPS position stdev (<0.01m)	0.0024
Minimum % overlap (>25)	42.36%
Ave point cloud density per sq.m. (>2.0)	3.56
Elevation difference between strips (<0.20 m)	Yes
Number of 1km x 1km blocks	156
Maximum Height	526.96 m
Minimum Height	39.41 m
<i>Classification (# of points)</i>	
Ground	70,619,413
Low vegetation	72,372,299
Medium vegetation	199,312,514
High vegetation	122,546,677
Building	5,607,920
Orthophoto	No
Processed by	Engr. Don Matthew Banatin, Engr. Christy Lubiano, Engr. Karl Adrian Vergara




Figure A-8.8. Solution Status




Figure A-8.9. Smoothed Performance Metric Parameters




Figure A-8.10. Best Estimated Trajectory




Figure A-8.11. Coverage of LiDAR Data




Figure A-8.12. Image of data overlap




Figure A-8.13. Density map of merged LiDAR data




Figure A-8.14. Elevation difference between flight lines

Annex 9. Baua Model Basin Parameters

Table A-9.1 Baua Model Basin Parameters

Basin Number	SCS Curve Number Loss			Clark Unit Hydrograph Transform			Recession Baseflow				
	Initial Abstraction (mm)	Curve Number	Impervious (%)	Time of Concentration (HR)	Storage Coefficient (HR)	Initial Type	Initial Discharge (M3/S)	Recession Constant	Threshold Type	Ratio to Peak	
W1000	12.469	77	0.0	2.6397	3.5900	Discharge	6.8750	1	Ratio to Peak	0.2	
W1010	12.469	77	0.0	1.4658	1.9935	Discharge	2.2387	1	Ratio to Peak	0.2	
W1020	12.469	77	0.0	2.2406	3.0472	Discharge	4.4983	1	Ratio to Peak	0.2	
W1030	12.469	77	0.0	1.3527	1.8396	Discharge	1.9409	1	Ratio to Peak	0.2	
W1040	12.469	77	0.0	1.1568	1.5733	Discharge	1.9254	1	Ratio to Peak	0.2	
W1050	12.469	77	0.0	1.5567	2.1171	Discharge	2.8718	1	Ratio to Peak	0.2	
W1060	12.469	77	0.0	2.5543	3.4738	Discharge	8.9623	1	Ratio to Peak	0.2	
W1070	12.469	77	0.0	0.66415	0.90324	Discharge	0.41189	1	Ratio to Peak	0.2	
W1080	12.469	77	0.0	1.2291	1.6716	Discharge	1.5667	1	Ratio to Peak	0.2	
W1090	12.469	77	0.0	0.87673	1.1923	Discharge	0.96269	1	Ratio to Peak	0.2	
W1100	12.469	77	0.0	1.4535	1.9767	Discharge	3.5938	1	Ratio to Peak	0.2	
W560	1.9759	99	0.0	2.0744	2.8212	Discharge	3.4096	1	Ratio to Peak	0.2	
W570	5.0930	99	0.0	2.4590	3.3443	Discharge	1.8168	1	Ratio to Peak	0.2	
W580	7.0690	95.638	0.0	1.4911	2.0279	Discharge	4.4083	1	Ratio to Peak	0.2	
W590	12.323	77.408	0.0	1.3622	1.8526	Discharge	2.3771	1	Ratio to Peak	0.2	
W600	7.2152	95.016	0.0	0.44883	0.61042	Discharge	0.36130	1	Ratio to Peak	0.2	
W610	7.1145	95.444	0.0	2.7401	3.7266	Discharge	1.7824	1	Ratio to Peak	0.2	
W620	8.0448	91.631	0.0	2.7096	3.6850	Discharge	3.9123	1	Ratio to Peak	0.2	
W630	12.469	77	0.0	1.0914	1.4843	Discharge	1.8112	1	Ratio to Peak	0.2	
W640	8.6244	89.405	0.0	3.5387	4.8126	Discharge	5.7059	1	Ratio to Peak	0.2	
W650	8.0378	91.658	0.0	0.54704	0.74397	Discharge	0.0633384	1	Ratio to Peak	0.2	
W660	12.469	77	0.0	1.0086	1.3717	Discharge	1.7506	1	Ratio to Peak	0.2	

Basin Number	SCS Curve Number Loss			Clark Unit Hydrograph Transform			Recession Baseflow			
	Initial Abstraction (mm)	Curve Number	Impervious (%)	Time of Concentration (HR)	Storage Coefficient (HR)	Initial Type	Initial Discharge (M ³ /S)	Recession Constant	Threshold Type	Ratio to Peak
W670	11.216	80.648	0.0	1.2631381	1.7179	Discharge	1.5705	1	Ratio to Peak	0.2
W680	9.5269	86.1472883	0.0	0.85803	1.1669	Discharge	0.41007	1	Ratio to Peak	0.2
W690	12.161	77.866	0.0	2.3031	3.1322	Discharge	5.2077	1	Ratio to Peak	0.2
W700	10.210	83.8354049	0.0	0.86477	1.1761	Discharge	0.48343	1	Ratio to Peak	0.2
W710	12.469	77	0.0	1.7106	2.3264	Discharge	2.6308	1	Ratio to Peak	0.2
W720	12.003	78.318	0.0	2.0924	2.8456	Discharge	4.0213	1	Ratio to Peak	0.2
W730	12.469	77	0.0	0.99365	1.3514	Discharge	0.85539	1	Ratio to Peak	0.2
W740	12.469	77	0.0	1.8508	2.5171	Discharge	4.6748	1	Ratio to Peak	0.2
W750	12.334	77.377	0.0	4.3414	5.9042	Discharge	9.9565	1	Ratio to Peak	0.2
W760	12.469	77	0.0	1.4503	1.9724	Discharge	3.3941	1	Ratio to Peak	0.2
W770	12.031	78.238	0.0	2.3506	3.1968	Discharge	2.8123	1	Ratio to Peak	0.2
W780	12.454	77.042	0.0	1.8382	2.5000	Discharge	2.5761	1	Ratio to Peak	0.2
W790	12.469	77	0.0	1.3949	1.8971	Discharge	1.5415	1	Ratio to Peak	0.2
W800	12.469	77	0.0	1.0164	1.3823	Discharge	0.38614	1	Ratio to Peak	0.2

Basin Number	SCS Curve Number Loss			Clark Unit Hydrograph Transform			Recession Baseflow			
	Initial Abstraction (mm)	Curve Number	Impervious (%)	Time of Concentration (HR)	Storage Coefficient (HR)	Initial Type	Initial Discharge (M ³ /S)	Recession Constant	Threshold Type	Ratio to Peak
W850	12.469	77	0.0	1.3968	1.8997	Discharge	1.8118	1	Ratio to Peak	0.2
W860	12.469	77	0.0	0.29304	0.39853	Discharge	0.0045520	1	Ratio to Peak	0.2
W870	12.469	77	0.0	1.2275	1.6694	Discharge	1.7762069	1	Ratio to Peak	0.2
W880	12.469	77	0.0	0.66114	0.89915	Discharge	0.45442	1	Ratio to Peak	0.2
W890	12.469	77	0.0	1.4683	1.9969	Discharge	1.2184	1	Ratio to Peak	0.2
W900	12.469	77	0.0	1.7053	2.3192	Discharge	2.2152	1	Ratio to Peak	0.2
W910	12.469	77	0.0	1.2336	1.6777	Discharge	1.4351	1	Ratio to Peak	0.2
W920	12.469	77	0.0	2.0926	2.8459	Discharge	3.1297	1	Ratio to Peak	0.2
W930	12.469	77	0.0	0.47228	0.64231	Discharge	0.17558	1	Ratio to Peak	0.2
W940	12.469	77	0.0	1.2715	1.7292	Discharge	2.2172	1	Ratio to Peak	0.2
W950	12.469	77	0.0	0.60102	0.81739	Discharge	0.28171	1	Ratio to Peak	0.2
W960	12.469	77	0.0	1.4063	1.9126	Discharge	1.9056	1	Ratio to Peak	0.2
W970	12.469	77	0.0	1.5676	2.1320	Discharge	2.8816	1	Ratio to Peak	0.2
W980	12.469	77	0.0	2.7166	3.6946	Discharge	5.7635	1	Ratio to Peak	0.2
W990	12.469	77	0.0	0.98610	1.3411	Discharge	0.97102	1	Ratio to Peak	0.2

Annex 10. Baula Model Reach Parameters

Table A-10.1 Baula Model Reach Parameters

Reach Number	MuskingumCunge Channel Routing						
	Time Step Method	Length (m)	Slope	Manning's n	Shape	Width	Side Slope
R10	Automatic Fixed Interval	2570.0	0.0067295	0.035	Trapezoid	78.73881	0.0564
R100	Automatic Fixed Interval	246.57	0.0141973	0.035	Trapezoid	78.73881	0.0564
R110	Automatic Fixed Interval	1993.4	0.0594735	0.035	Trapezoid	78.73881	0.0564
R120	Automatic Fixed Interval	801.84	0.0167591	0.035	Trapezoid	78.73881	0.0564
R140	Automatic Fixed Interval	666.98	0.0164793	0.035	Trapezoid	78.73881	0.0564
R150	Automatic Fixed Interval	2686.2	0.0386112	0.035	Trapezoid	78.73881	0.0564
R170	Automatic Fixed Interval	1159.8	0.0758038	0.035	Trapezoid	78.73881	0.0564
R200	Automatic Fixed Interval	4956.1	0.0203050	0.035	Trapezoid	78.73881	0.0564
R220	Automatic Fixed Interval	1492.0	0.0168190	0.035	Trapezoid	78.73881	0.0564
R240	Automatic Fixed Interval	784.26	0.0107762	0.035	Trapezoid	78.73881	0.0564
R250	Automatic Fixed Interval	90.711	0.0140724	0.035	Trapezoid	78.73881	0.0564
R260	Automatic Fixed Interval	28.284	0.001	0.035	Trapezoid	78.73881	0.0564
R30	Automatic Fixed Interval	1895.5	0.0056477	0.035	Trapezoid	78.73881	0.0564
R310	Automatic Fixed Interval	1474.3	0.0442737	0.035	Trapezoid	78.73881	0.0564
R320	Automatic Fixed Interval	572.84	0.0604411	0.035	Trapezoid	78.73881	0.0564
R340	Automatic Fixed Interval	410.42	0.0718342	0.035	Trapezoid	78.73881	0.0564
R360	Automatic Fixed Interval	1067.1	0.0427851	0.035	Trapezoid	78.73881	0.0564
R370	Automatic Fixed Interval	1341.8	0.0444133	0.035	Trapezoid	78.73881	0.0564
R380	Automatic Fixed Interval	337.28	0.12654	0.035	Trapezoid	78.73881	0.0564
R410	Automatic Fixed Interval	2115.1	0.0396921	0.035	Trapezoid	78.73881	0.0564
R440	Automatic Fixed Interval	1029.5	0.0495979	0.035	Trapezoid	78.73881	0.0564
R470	Automatic Fixed Interval	2330.7	0.0451154	0.035	Trapezoid	78.73881	0.0564
R50	Automatic Fixed Interval	408.70	0.0170005	0.035	Trapezoid	78.73881	0.0564
R500	Automatic Fixed Interval	296.98	0.001	0.035	Trapezoid	78.73881	0.0564
R510	Automatic Fixed Interval	746.69	0.0625617	0.035	Trapezoid	78.73881	0.0564
R520	Automatic Fixed Interval	565.56	0.0443851	0.035	Trapezoid	78.73881	0.0564
R70	Automatic Fixed Interval	2093.1	0.0081210	0.035	Trapezoid	78.73881	0.0564

Annex 11. Baua Flood Validation Data

Table A-11.1 Baua Flood Validation Data

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event/Date	Rain Return/ Scenario
	Lat	Long					
1	18.29129	122.10874	0.030	0.0	-0.03		5 Yr
2	18.29138	122.10906	0.060	0.0	-0.06		5 Yr
3	18.29143	122.10905	0.060	0.0	-0.06		5 Yr
4	18.29168	122.10909	0.060	0.0	-0.06		5 Yr
5	18.29372	122.10913	0.280	0.0	-0.28		5 Yr
6	18.29654	122.10909	0.140	0.0	-0.14		5 Yr
7	18.29835	122.10915	0.040	0.0	-0.04		5 Yr
8	18.30077	122.10917	0.030	0.0	-0.03		5 Yr
9	18.30083	122.11792	4.590	0.0	-4.59		5 Yr
10	18.30108	122.11776	2.550	0.0	-2.55		5 Yr
11	18.30141	122.11755	1.350	0.0	-1.35		5 Yr
12	18.30203	122.09659	1.010	0.0	-1.01		5 Yr
13	18.30239	122.09439	0.050	0.0	-0.05		5 Yr
14	18.30243	122.09586	0.220	0.0	-0.22		5 Yr
15	18.30248	122.09410	0.030	0.0	-0.03		5 Yr
16	18.30262	122.10917	0.030	0.0	-0.03		5 Yr
17	18.30293	122.10919	0.030	0.0	-0.03		5 Yr
18	18.30348	122.09833	0.030	0.0	-0.03		5 Yr
19	18.30427	122.11818	0.080	0.0	-0.08		5 Yr
20	18.30425	122.09382	0.030	0.0	-0.03		5 Yr
21	18.30438	122.10921	0.150	0.0	-0.15		5 Yr
22	18.30455	122.09952	0.030	0.0	-0.03		5 Yr
23	18.30504	122.09349	0.030	0.0	-0.03		5 Yr
24	18.30544	122.10079	0.030	0.0	-0.03		5 Yr
25	18.30553	122.10918	0.220	0.0	-0.22		5 Yr
26	18.30623	122.10334	0.290	0.0	-0.29		5 Yr
27	18.30653	122.10915	0.110	0.0	-0.11		5 Yr
28	18.30662	122.10603	0.030	0.0	-0.03		5 Yr
29	18.30670	122.09275	0.170	0.0	-0.17		5 Yr
30	18.30694	122.11716	0.300	0.0	-0.30		5 Yr
31	18.30698	122.11645	0.400	0.0	-0.40		5 Yr
32	18.30698	122.11341	0.030	0.0	-0.03		5 Yr
33	18.30700	122.11511	0.060	0.0	-0.06		5 Yr
34	18.30698	122.11082	0.090	0.0	-0.09		5 Yr
35	18.30699	122.10865	0.050	0.0	-0.05		5 Yr
36	18.30700	122.10984	0.070	0.0	-0.07		5 Yr
37	18.30700	122.10733	0.150	0.0	-0.15		5 Yr
38	18.30710	122.09074	0.030	0.4	0.37	TS Lawin/ October 2016	5 Yr

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event/Date	Rain Return/ Scenario
	Lat	Long					
39	18.30718	122.09038	0.030	0.4	0.37	TS Lawin/ October 2016	5 Yr
40	18.30764	122.10903	0.090	0.0	-0.09		5 Yr
41	18.30773	122.08766	0.050	0.0	-0.05		5 Yr
42	18.30792	122.08667	0.030	0.0	-0.03		5 Yr
43	18.30883	122.08520	0.100	0.0	-0.10		5 Yr
44	18.31003	122.08480	0.110	0.0	-0.11		5 Yr
45	18.31127	122.08441	0.030	0.0	-0.03		5 Yr
46	18.31150	122.10889	0.030	0.0	-0.03		5 Yr
47	18.31232	122.10900	0.040	0.0	-0.04		5 Yr
48	18.31280	122.08410	0.260	0.4	0.14	TS Lawin/ October 2016	5 Yr
49	18.31401	122.10901	0.220	0.0	-0.22		5 Yr
50	18.31395	122.08412	0.090	0.0	-0.09		5 Yr
51	18.31565	122.08419	0.070	0.0	-0.07		5 Yr
52	18.31715	122.10901	0.070	0.0	-0.07		5 Yr
53	18.31722	122.08447	0.030	0.0	-0.03		5 Yr
54	18.31856	122.08473	0.200	0.4	0.20	TS Lawin/ October 2016	5 Yr
55	18.31954	122.08486	0.030	0.0	-0.03		5 Yr
56	18.32054	122.10896	0.060	0.4	0.34	TS Lawin/ October 2016	5 Yr
57	18.32247	122.10898	0.050	0.0	-0.05		5 Yr
58	18.32265	122.08408	0.030	0.0	-0.03		5 Yr
59	18.32264	122.08003	0.060	0.3	0.24	TS Lawin/ October 2016	5 Yr
60	18.32280	122.07808	0.030	0.0	-0.03		5 Yr
61	18.32326	122.07697	0.030	0.0	-0.03		5 Yr
62	18.32399	122.10898	0.060	0.0	-0.06		5 Yr
63	18.32467	122.07552	0.030	0.0	-0.03		5 Yr
64	18.32542	122.10898	0.030	0.0	-0.03		5 Yr
65	18.32609	122.07408	0.030	0.0	-0.03		5 Yr
66	18.32729	122.10895	0.610	0.0	-0.61		5 Yr
67	18.32837	122.10841	0.030	0.0	-0.03		5 Yr
68	18.32841	122.07185	0.280	1.0	0.72	every typhoon occurrence	5 Yr
69	18.32927	122.10748	0.030	0.0	-0.03		5 Yr
70	18.33073	122.10575	0.040	0.0	-0.04		5 Yr
71	18.33103	122.06973	0.030	1.0	0.97	every typhoon occurrence	5 Yr
72	18.33227	122.06614	0.560	0.0	-0.56		5 Yr
73	18.33276	122.06863	0.030	1.0	0.97	every typhoon occurrence	5 Yr
74	18.33301	122.10424	0.030	0.0	-0.03		5 Yr

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event/Date	Rain Return/ Scenario
	Lat	Long					
75	18.33340	122.06722	0.390	0.0	-0.39		5 Yr
76	18.33362	122.06813	2.070	0.8	-1.27	2000 Typhoon	5 Yr
77	18.33389	122.06394	0.050	0.0	-0.05		5 Yr
78	18.33393	122.06803	0.560	0.8	0.24	2000 Typhoon	5 Yr
79	18.33407	122.06364	0.100	0.8	0.70	TS Lawin/ October 2016	5 Yr
80	18.33590	122.10258	0.030	0.0	-0.03		5 Yr
81	18.33736	122.10154	0.110	0.0	-0.11		5 Yr
82	18.33925	122.10047	0.040	0.0	-0.04		5 Yr
83	18.34087	122.09932	0.090	0.0	-0.09		5 Yr
84	18.34088	122.09934	0.030	0.0	-0.03		5 Yr
85	18.34226	122.09828	0.030	0.0	-0.03		5 Yr
86	18.34374	122.09713	0.030	0.0	-0.03		5 Yr
87	18.34473	122.07990	0.390	0.0	-0.39		5 Yr
88	18.34498	122.08044	0.140	0.0	-0.14		5 Yr
89	18.34528	122.09614	0.030	0.0	-0.03		5 Yr
90	18.34608	122.08284	0.380	0.0	-0.38		5 Yr
91	18.34705	122.09512	0.210	0.0	-0.21		5 Yr
92	18.34711	122.08506	0.730	0.0	-0.73		5 Yr
93	18.34773	122.08639	0.030	0.0	-0.03		5 Yr
94	18.34841	122.08778	0.030	0.0	-0.03		5 Yr
95	18.34915	122.08701	0.030	0.3	0.27	TS Lawin/ October 2016	5 Yr
96	18.34925	122.08691	0.360	0.0	-0.36		5 Yr
97	18.34962	122.08590	0.100	0.0	-0.10		5 Yr
98	18.34971	122.09406	0.720	0.0	-0.72		5 Yr
99	18.34982	122.08516	0.030	0.3	0.27	TS Lawin/ October 2016	5 Yr
100	18.34985	122.08513	0.030	0.0	-0.03		5 Yr
101	18.34993	122.08260	0.030	0.3	0.27	TS Lawin/ October 2016	5 Yr
102	18.35003	122.08159	0.050	0.3	0.25	TS Lawin/ October 2016	5 Yr
103	18.35024	122.08407	0.030	0.0	-0.03		5 Yr
104	18.35057	122.09736	7.050	1.6	-5.45	TS Rubing/ October 5, 1989	5 Yr
105	18.35057	122.09737	7.050	1.6	-5.45	TS Rubing/ October 5, 1989	5 Yr
106	18.35066	122.09367	0.030	0.0	-0.03		5 Yr
107	18.35061	122.08289	0.030	0.3	0.27	TS Lawin/ October 2016	5 Yr
108	18.35071	122.09258	0.030	0.0	-0.03		5 Yr
109	18.35094	122.09567	2.240	1.6	-0.64	TS Rubing/ October 5, 1989	5 Yr

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event/Date	Rain Return/ Scenario
	Lat	Long					
110	18.35094	122.09580	2.270	1.6	-0.67	TS Rubing/ October 5, 1989	5 Yr
111	18.35091	122.08410	0.540	0.0	-0.54		5 Yr
112	18.35129	122.09407	3.540	0.0	-3.54		5 Yr
113	18.35140	122.08268	0.040	0.3	0.26	TS Lawin/ October 2016	5 Yr
114	18.35154	122.09468	4.430	1.6	-2.83	TS Rubing/ October 5, 1989	5 Yr
115	18.35159	122.09370	4.920	0.8	-4.12	TS Rubing/ October 5, 1989	5 Yr
116	18.35168	122.10937	0.060	0.0	-0.06		5 Yr
117	18.35164	122.09362	3.260	0.8	-2.46	TS Rubing/ October 5, 1989	5 Yr
118	18.35168	122.08411	0.040	0.3	0.26	TS Lawin/ October 2016	5 Yr
119	18.35180	122.09469	2.610	0.0	-2.61		5 Yr
120	18.35180	122.08311	0.590	0.0	-0.59		5 Yr
121	18.35183	122.08332	0.030	0.3	0.27		5 Yr
122	18.35184	122.08393	0.040	0.0	-0.04		5 Yr
123	18.35193	122.09555	0.030	1.6	1.57	TS Rubing/ October 5, 1989	5 Yr
124	18.35190	122.08281	0.030	0.0	-0.03		5 Yr
125	18.35211	122.09342	3.470	1.6	-1.87	TS Rubing/ October 5, 1989	5 Yr
126	18.35208	122.08288	0.030	0.0	-0.03		5 Yr
127	18.35225	122.09432	5.350	1.3	-4.05	TS Lawin/ October 2016	5 Yr
128	18.35259	122.09312	2.370	0.8	-1.57	TS Rubing/ October 5, 1989	5 Yr
129	18.35274	122.09293	0.870	0.8	-0.07	TS Rubing/ October 5, 1989	5 Yr
130	18.35296	122.09290	0.750	0.4	-0.35	TS Rubing/ October 5, 1989	5 Yr
131	18.35307	122.08323	0.290	0.0	-0.29		5 Yr
132	18.35308	122.08324	0.290	0.0	-0.29		5 Yr
133	18.35341	122.09264	1.300	0.4	-0.90	TS Rubing/ October 5, 1989	5 Yr
134	18.35357	122.10679	0.030	0.0	-0.03		5 Yr
135	18.35391	122.08317	0.030	0.0	-0.03		5 Yr
136	18.35441	122.08306	0.030	0.0	-0.03		5 Yr
137	18.35469	122.09340	0.670	1.6	0.93	TS Rubing/ October 5, 1989	5 Yr
138	18.35478	122.08311	0.340	0.0	-0.34	TS Rubing/ October 5, 1989	5 Yr
139	18.35515	122.10452	0.030	0.0	-0.03		5 Yr
140	18.35539	122.10032	0.510	0.0	-0.51		5 Yr

Point Number	Validation Coordinates		Model Var (m)	Validation Points (m)	Error	Event/Date	Rain Return/ Scenario
	Lat	Long					
141	18.35558	122.10304	0.150	0.0	-0.15		5 Yr
142	18.35572	122.09246	1.030	1.6	0.57	TS Rubing/ October 5, 1989	5 Yr
143	18.35608	122.11248	0.300	0.0	-0.30		5 Yr
144	18.35662	122.10876	0.060	0.4	0.34	every typhoon occurrence	5 Yr
145	18.35664	122.09160	0.390	1.6	1.21	TS Rubing/ October 5, 1989	5 Yr
146	18.35672	122.10253	0.030	0.0	-0.03		5 Yr
147	18.35759	122.10779	0.060	0.4	0.34	every typhoon occurrence	5 Yr
148	18.35809	122.10239	0.030	0.0	-0.03		5 Yr
149	18.35816	122.10388	0.080	0.0	-0.08		5 Yr
150	18.35933	122.10059	0.600	0.0	-0.60		5 Yr
151	18.35949	122.10694	1.580	0.0	-1.58		5 Yr
152	18.36160	122.10029	0.690	0.0	-0.69		5 Yr
153	18.36329	122.09863	1.040	0.0	-1.04		5 Yr
154	18.36507	122.09788	0.290	0.0	-0.29		5 Yr
155	18.36560	122.09819	0.110	0.0	-0.11		5 Yr
156	18.36663	122.09852	0.660	0.0	-0.66		5 Yr
157	18.36721	122.09827	0.030	5.0	4.97	1972	5 Yr
158	18.36722	122.09852	0.110	5.0	4.89	1973	5 Yr
159	18.36764	122.09897	0.110	0.4	0.29	TS Lawin/ October 2016	5 Yr
160	18.36770	122.09906	0.220	0.4	0.18	TS Lawin/ October 2016	5 Yr

Annex 12. Educational Institutions Affected in Baua Floodplain

Table A-12.1 Educational Institutions in Gonzaga, Cagayan affected by flooding in Baua Floodplain

Cagayan				
Gonzaga				
Building Name	Barangay	Rainfall Scenario		
		5-year	25-year	100-year
Baua Central School	Baua	Medium	Medium	High
Baua Day Care Center	Baua	Medium	High	High
Baua National High School	Baua	Medium	High	High
Cabiraoan Elemenetary School	Cabiraoan			
Baua National High School Extension	Cabiraoan			
Cabiraoan Day Care	Cabiraoan			
Cabiraoan Dela Cruz Elementary School	Cabiraoan			
Cabiraoan Elementary School	Cabiraoan			
Prince Aaron Christian School	San Jose	Low	Low	Low
San Jose Day Care Center	San Jose			
San Jose Elementary School	San Jose			
Sta Cruz Day Care Center	Santa Cruz	Low	Medium	Medium
Sta Cruz Elementary School	Santa Cruz			Low
Sta. Maria Day Care Center	Santa Maria			
Sta. Maria Elementary School	Santa Maria			

Annex 13. Health Institutions Affected in Baua Floodplain

No health institutions in Gonzaga, Cagayan are affected by flooding in Baua, Floodplain.